

# Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No.  
1907/2006 (REACH)



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Substance name:	<b>Fuels, diesel</b>
Code:	<b>817652</b>
Unique Formula Identifier (UFI):	<b>X4MS-CM5S-AK77-AVAX</b>
MARPOL Annex I Category:	Fuels, Including Ship's Bunkers
REACH Registration Number:	01-2119484664-27-0221
Issue date:	18-Nov-2020

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Fuel
Uses advised against:	Uses other than those covered by the exposure scenarios appended to this Safety Data Sheet are not supported.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier:	Phillips 66 CS Limited 7th Floor 200-202 Aldersgate Street London EC1A 4HD UK
------------------------	--

SDS Information:	URL: <a href="http://www.Phillips66.com/SDS">www.Phillips66.com/SDS</a> Email: <a href="mailto:ESDS@P66.com">ESDS@P66.com</a> CHEMTREC Global +1 703 527 3887 CHEMTREC Germany 0800-181-7059 CHEMTREC France +(33)-975181407 CHEMTREC Spain 900-868538 CHEMTREC UK +(44)-870-8200418 CHEMTREC Denmark +(45)-69918573 CHEMTREC Sweden (Stockholm) +(46)-852503403 CHEMTREC Netherlands +(31)-858880596
------------------	--

### 1.4. Emergency telephone number

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### CLP Classification (EC No 1272/2008)

H226 - Flammable liquids -- Category 3  
H304 -- Aspiration Hazard -- Category 1  
H315 -- Skin corrosion/irritation -- Category 2  
H332 -- Acute toxicity, Inhalation -- Category 4  
H351 -- Carcinogenicity -- Category 2  
H373 -- Specific target organ toxicity (repeated exposure) -- Category 2 (Immune system/Liver/bone)  
H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2

### 2.2. Label elements



**DANGER**

- H226 - Flammable liquid and vapour**
- H304 - May be fatal if swallowed and enters airways**
- H315 - Causes skin irritation**
- H332 - Harmful if inhaled**
- H351 - Suspected of causing cancer**
- H373 - May cause damage to organs through prolonged or repeated exposure**
- H411 - Toxic to aquatic life with long lasting effects**
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray
- P273 - Avoid release to the environment
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P331 - Do NOT induce vomiting

**2.3. Other hazards**

Electrostatic charge may be generated during pumping and other operations  
 Does not meet the criteria for persistent, bioaccumulative and toxic (PBT) or very persistent, very bioaccumulative (vPvB) substances.

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Chemical Name	CASRN	EINECS	REACH Registration No	Concentration <sup>1</sup>	Classification <sup>2</sup>
Fuels, diesel	68334-30-5	269-822-7	01-2119484664-27	0-100	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Acute Tox. 4, H332 Carc. 2, H351 STOT RE 2, H373 Aquatic Chronic 2, H411
Kerosine, petroleum	8008-20-6	232-366-4	01-2119485517-27	0-18	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Aromatic hydrocarbons, distillation residues, naphthalene-rich	98072-36-7	308-487-4	01-2119480164-41	<10	Acute Tox. 4, H302 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 Muta. 1B, H340 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Naphthalene, 1,2,3,4-tetrahydro-	119-64-2	204-340-2	Not applicable	<5	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
Naphthalene	91-20-3	202-049-5	-	<2.5	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

<sup>1</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.  
<sup>2</sup> Regulation EC 1272/2008.  
 See Section 11 for more information.

Total Sulphur: < 0.1 wt%

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Eye Contact:** If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

**Skin Contact:** Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician. (see Note to Physician)

**Inhalation:** If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If symptoms persist, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

**Ingestion:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

While significant vapour concentrations are not likely, high concentrations can cause minor respiratory irritation, headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Ingestion can cause irritation of the digestive tract, nausea, diarrhea, and vomiting. Prolonged or repeated contact may dry skin and cause irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician:** When using high-pressure equipment, injection of product under the skin can occur. In this case, the casualty should be sent immediately to the hospital. Do not wait for symptoms to develop. High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. These injuries often require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury. Early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Dry chemical, carbon dioxide, or foam is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters.

### 5.2. Special hazards arising from the substance or mixture

**Unusual Fire & Explosion Hazards:** Flammable. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe) Vapours may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapour/air explosion hazard indoors, in confined spaces, outdoors, or in sewers. This product will float and can be reignited on surface water. Vapours are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulphur may also be formed.

### 5.3. Special protective actions for fire-fighters

For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When

the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapours and to protect personnel. Avoid spreading burning liquid with water used for cooling purposes. Cool equipment exposed to fire with water, if it can be done safely.

**See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits**

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. The use of explosion-proof electrical equipment is recommended. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorised personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

### **6.2. Environmental precautions**

Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorised drainage systems, and natural waterways. Use foam on spills to minimise vapours Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard.

### **6.3. Methods and material for containment and cleaning up**

Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use non-sparking tools. Do not breathe vapour or mist. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8).

Flammable. May vaporize easily at ambient temperatures. The vapour is heavier than air and may create an explosive mixture of vapor and air. Beware of accumulation in confined spaces and low lying areas. Open container slowly to relieve any pressure. Electrostatic charge may accumulate and create a hazardous condition when handling or processing this material. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes for specific bonding/grounding requirements). Do not enter confined spaces such as tanks or pits without following proper entry procedures. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames.

High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing of high pressure hydraulic oil equipment.

For use as a motor fuel only. Do not use as a solvent due to its flammable and potentially toxic properties. Siphoning by mouth can result in lung aspiration which can be harmful or fatal.

The use of hydrocarbon fuel in an area without adequate ventilation may result in hazardous levels of incomplete combustion products (e.g. carbon monoxide, oxides of sulphur and nitrogen, benzene and other hydrocarbons) and/or dangerously low

oxygen levels.

Diesel engine exhaust contains hazardous combustion products and has been identified as a cancer hazard. Exposure should be minimized to reduce potential risk.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Post area "No Smoking or Open Flame." Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to appropriate guidance pertaining to cleaning, repairing, welding, or other contemplated operations. Outdoor or detached storage is preferred. Indoor storage should meet Country or Committee standards and appropriate fire codes.

**7.3. Specific end use(s)**

Refer to supplemental exposure scenarios if attached.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational Exposure Limits:**

Chemical Name	ACGIH	Ireland	United Kingdom	Phillips 66
Fuels, diesel	TWA-8hr: 100 mg/m <sup>3</sup> inhalable fraction and vapor Skin	TWA-8hr: 100 mg/m <sup>3</sup> STEL: 300 mg/m <sup>3</sup>	---	TWA-8hr: 100 mg/m <sup>3</sup> Skin
Kerosine, petroleum	TWA-8hr: 200 mg/m <sup>3</sup> total hydrocarbon vapor Kerosene/Jet fuels Skin	Skin	---	TWA-8hr: 200 mg/m <sup>3</sup> TWA-8hr: 28 ppm Skin
Naphthalene	TWA-8hr: 10 ppm Skin	TWA-8hr: 10 ppm TWA-8hr: 50 mg/m <sup>3</sup> STEL: 30 ppm STEL: 150 mg/m <sup>3</sup>	---	TWA-8hr: 10 ppm Skin

STEL = Short Term Exposure Limit (15 minutes); TWA = Time Weighted Average (8 hours); --- = No Occupational Exposure Limit. Local regulations may be more stringent than regional or national requirements.

**Biological Limit Values:**

Chemical Name	ACGIH	European Union	United Kingdom
Naphthalene	1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis in : , end of shift (nonquantitative, nonspecific)	---	---

--- = No Biological Limit Value. Local regulations may be more stringent than regional or national requirements

**Relevant DNEL and PNEC:**

**Worker Derived No-Effect Level (DNEL)**  
**Inhalation:** 68.3 mg/m<sup>3</sup>  
**Dermal:** 2.9 mg/kgbw/day

**Consumer Derived No-Effect Level (DNEL)**  
**Inhalation:** 20 mg/m<sup>3</sup>  
**Dermal:** 1.3 mg/kgbw/day  
**Ingestion:** Not applicable

Environmental Predicted No-Effect Concentration (PNEC): No information available

## 8.2. Exposure controls

**Engineering controls:** If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

**Eye/Face Protection:** The use of eye protection that meets or exceeds EN 166 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, close fitting eye protection and a face shield may be necessary.

**Skin/Hand Protection:** The use of gloves impervious to the specific material handled that comply with EN 374 is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical resistant boots, aprons, arm covers, hoods, coveralls, or encapsulated suits. Suggested protective materials: Nitrile rubber

**Respiratory Protection:** Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type A, organic gases and vapour filters (as specified by the manufacturer) may be used.

A respiratory protection programme that follows recommendations for the selection, use, care and maintenance of respiratory protective devices in EN 529:2005 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health.

**Other Protective Equipment:** Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before reuse.

**Environmental Exposure Controls:** Refer to Sections 6, 7, 12 and 13.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Data represent typical values and are not intended to be specifications. N/A = Not Applicable; N/D = Not Determined

<b>Appearance:</b>	Clear to amber
<b>Physical form of product:</b>	Liquid
<b>Odour:</b>	Diesel fuel
<b>Odour threshold:</b>	N/D
<b>pH:</b>	N/A
<b>Melting / freezing point:</b>	N/D
<b>Initial boiling point and boiling range:</b>	356 - 734 °F / 180 - 390 °C
<b>Flash point:</b>	> 131 °F / > 55 °C
<b>Method:</b>	CC (closed cup)
<b>Evaporation Rate (nBuAc=1):</b>	N/D
<b>Flammability (solid, gas):</b>	N/A
<b>Upper Explosive Limits (vol % in air):</b>	5.0
<b>Lower Explosive Limits (vol % in air):</b>	0.5
<b>Vapour pressure:</b>	<0.3 kPa @20°C
<b>Vapour density:</b>	>1 (air = 1)
<b>Relative density:</b>	0.85 @ 60°F (15.6°C) (water = 1)
<b>Solubility(ies):</b>	Negligible
<b>Partition coefficient n-octanol /water (log KOW):</b>	N/D
<b>Autoignition temperature:</b>	250 °C
<b>Decomposition temperature:</b>	N/D
<b>Viscosity:</b>	4.8 mm <sup>2</sup> /s @ 20°C; 1.5-5.5 mm <sup>2</sup> /s @ 40°C
<b>Explosive properties:</b>	N/D
<b>Oxidising properties:</b>	N/D

## 9.2. Other information

### Other information

Pour point: -11.2 °F / -24 °C  
Bulk Density:: N/D

## SECTION 10: Stability and reactivity

- 10.1. Reactivity** Not chemically reactive.
- 10.2. Chemical stability** Stable under normal ambient and anticipated conditions of use.
- 10.3. Possibility of hazardous reactions** Hazardous reactions not anticipated.
- 10.4. Conditions to avoid** Avoid high temperatures and all sources of ignition. Prevent vapour accumulation.
- 10.5. Incompatible materials** Avoid contact with strong oxidizing agents and strong reducing agents.
- 10.6. Hazardous decomposition products** Not anticipated under normal conditions of use.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Substance / Mixture

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Harmful if inhaled		> 4.1 mg/L (mist, estimated) (rat)
Dermal	Unlikely to be harmful		>2 g/kg (Estimated) (rabbit)
Oral	Unlikely to be harmful		>5 g/kg (Estimated) (rat)

**Likely Routes of Exposure:** Inhalation, eye contact, skin contact

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Skin Corrosion/Irritation:** Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

**Serious Eye Damage/Irritation:** Causes mild eye irritation.

**Skin Sensitisation:** Not expected to be a skin sensitizer.

**Respiratory Sensitisation:** No information available on the mixture, however none of the components have been classified for respiratory sensitisation (or are below the concentration threshold for classification).

**Specific Target Organ Toxicity (Single Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Carcinogenicity:** Suspected of causing cancer. Based on component information.

**Germ Cell Mutagenicity:** No information available on the mixture, however none of the components have been classified for germ cell mutagenicity (or are below the concentration threshold for classification). Based on component information.

**Reproductive Toxicity:** Not expected to cause reproductive toxicity.

**Other Comments:** Diesel engine exhaust has been classified by the International Agency for Research on Cancer (IARC) and National Toxicology Programme (NTP) as a carcinogen.

### 11.2 Information on Hazardous Components

Fuels, diesel

Carcinogenicity: Repeated application of residual aromatic extracts to mouse skin resulted in an increased incidence of skin tumours. They have been identified as a carcinogen by IARC.

Target Organ(s): Repeated dermal application of petroleum gas oils for 90 days resulted in decreased liver, thymus, and spleen weights, and altered bone marrow function. Microscopic alterations included liver hypertrophy and necrosis, decreased hematopoiesis and lymphocyte depletion.

Target organs, tissues and biological systems: Immune system, Liver, bone

#### **Kerosine, petroleum**

Target organs, tissues and biological systems: Central Nervous System (CNS)

Reproductive Toxicity: Hydrodesulphurized kerosene applied to the skin of female rats at 494, 330, or 165 mg/kg daily for 7 consecutive weeks (pre-mating, mating, and gestation), or for 8 consecutive weeks in males did not result in systemic, reproductive, or developmental toxicity.

#### **Naphthalene**

Carcinogenicity: Naphthalene has been evaluated in two year inhalation studies in both rats and mice. The US National Toxicology Programme (NTP) concluded that there is clear evidence of carcinogenicity in male and female rats based on increased incidences of respiratory epithelial adenomas and olfactory epithelial neuroblastomas of the nose. NTP found some evidence of carcinogenicity in female mice (alveolar adenomas) and no evidence of carcinogenicity in male mice.

Naphthalene has been identified as a carcinogen by IARC and NTP.

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Experimental studies of gas oils show that acute aquatic toxicity values are typically in the range 2-20 mg/L. These values are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions. They should be regarded as toxic to aquatic organisms, with the potential to cause long term adverse effects in the aquatic environment.

### **12.2. Persistence and degradability**

Gas oils are complex combinations of individual hydrocarbon species. Based on the known or expected properties of individual constituents, category members are not predicted to be readily biodegradable. Some hydrocarbon constituents of gas oils are predicted to meet the criteria for persistence; on the other hand, some components can be easily degraded by microorganisms under aerobic conditions.

**Persistence per IOPC Fund definition:** Non-Persistent

### **12.3. Bioaccumulative potential**

Gas oil components have measured or calculated Log Kow values in the range of 3.9 to 6 which indicates a high potential to bioaccumulate. Lower molecular weight compounds are readily metabolized and the actual bioaccumulation potential of higher molecular weight compounds is limited by the low water solubility and large molecular size.

### **12.4. Mobility in soil**

Releases to water will result in a hydrocarbon film floating and spreading on the surface. For the lighter components, volatilisation is an important loss process and reduces the hazard to aquatic organisms. In air, the hydrocarbon vapours react readily with hydroxyl radicals with half-lives of less than one day. Photooxidation on the water surface is also a significant loss process particularly for polycyclic aromatic compounds. In water, the majority of components will be adsorbed on sediment. Adsorption is the most predominant physical process on release to soil. Adsorbed hydrocarbons will slowly degrade in both water and soil.

### **12.5. Results of PBT and vPvB assessment**

Not a PBT or vPvB substance.

### **12.6. Other adverse effects**

None anticipated.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

**European Waste Code:** 13 07 01\* fuel oil and diesel

This material, if discarded as produced, would be considered as hazardous waste pursuant to Directive 2008/98/EC on



hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies. This code has been assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste generators/producers are responsible for assessing the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code.

Disposal must be in accordance with Directive 2008/98/EC and other applicable national or regional provisions, and based upon material characteristics at time of disposal. For incineration of waste, follow Directive 2000/76/EC. For landfill of waste, follow Directive 1999/31/EC. Product is suitable for burning in an enclosed controlled burner for fuel value if >5000 BTU, or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Follow Directive 2000/76/EC.

**Empty Containers:** Container contents should be completely used and containers emptied prior to discard. Empty drums should be properly sealed and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with applicable regulations.

## SECTION 14: Transport information

### 14.1. UN number

UN1202

### 14.2. UN proper shipping name

Diesel fuel

### 14.3. Transport hazard class(es)

3; (N2, F)

### 14.4. Packing group

III

### 14.5. Environmental hazards

Marine pollutant - Environmentally Hazardous

### 14.6. Special precautions for user

If transported in bulk by marine vessel in international waters, product is being carried under the scope of MARPOL Annex I.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EC 1272/2008 - Classification, labelling and packaging of substances and mixtures  
EN166:2002 Eye Protection  
EN 529:2005 Respiratory Protective devices  
BS EN 374-1:2003 Protective gloves against chemicals and micro-organisms  
Occupational Exposure Limits, Technical Rules for Dangerous Substances  
Occupational Exposure Limits, Health and Safety Authority  
Workplace Exposure Limits, EH40/2005, Control of Substances Hazardous to Health  
Federal Water Act on the Classification of Substances Hazardous to Waters  
Directive 2008/98/EC (Waste Framework Directive)  
Directive 2000/76/EC on incineration of waste  
Directive 1999/31/EC on landfill of waste

**Export Rating:** NLR (No Licence Required)

### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out for the substance/mixture.

## SECTION 16: Other information

Issue date 18-Nov-2020  
Status: FINAL  
Previous Issue Date: 19-Aug-2020  
Revised Sections or Basis for Revision: Unique Formula Identifier (UFI)  
Toxicological (Section 11)  
Format change  
Safety Data Sheet Number: 817652  
Language: BE

**List of Relevant Hazard Statements:**

- H226 - Flammable liquid and vapour
- H302 - Harmful if swallowed
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H336 - May cause drowsiness or dizziness
- H340 - May cause genetic defects
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects
- H411 - Toxic to aquatic life with long lasting effects

**Regulatory Basis of Classification**

	Regulatory Basis
CLP Classification (EC No 1272/2008)	Regulatory Basis
H226 - Flammable liquids -- Category 3	Based on component information.
H304 -- Aspiration Hazard -- Category 1	Based on component information.
H315 -- Skin corrosion/irritation -- Category 2	Based on component information.
H332 -- Acute toxicity, Inhalation -- Category 4	Based on component information.
H351 -- Carcinogenicity -- Category 2	Based on component information.
H373 -- Specific target organ toxicity (repeated exposure) -- Category 2 (Immune system/Liver/bone)	Based on component information.
H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2	Based on component information.

**Guide to Abbreviations:**

ACGIH = American Conference of Governmental Industrial Hygienists; ADR = Agreement on Dangerous Goods by Road; BMGV = Biological Monitoring Guidance Value; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA = [US] Environmental Protection Agency; Germany-TRGS = Technical Rules for Dangerous Substances; IARC = International Agency for Research on Cancer; ICAO/IATA = International Civil Aviation Organisation / International Air Transport Association; INSHT = National Institute for Health and Safety at Work; IMDG = International Maritime Dangerous Goods; Irland-HSA = Ireland's National Health and Safety Authority; LEL = Lower Explosive Limit; MARPOL = Marine Pollution; N/A = Not Applicable; N/D = Not Determined; NTP = [US] National Toxicology Programme; PBT = Persistent, Bioaccumulative and Toxic; RID = Regulations Concerning the International Transport of Dangerous Goods by Rail; STEL = Short Term Exposure Limit; TLV = Threshold Limit Value; TRGS 903 = Technical rules for hazardous substances; TWA = Time Weighted Average; UEL = Upper Explosive Limit; UK-EH40 = United Kingdom EH40/2005 OEL; vPvB = very Persistent, very Bioaccumulative

**Disclaimer of Expressed and implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorisation is given nor implied to practice any patented invention without a licence.



## 1. Manufacture of substance - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Manufacture of substance
<b>Use Descriptor</b>	
Sector(s) of use	3, 8, 9
Process category(ies)	1, 2, 3, 4, 8a, 8b, 15
Environmental release category(ies)	1, 4
Specific Environmental Release Category	ESVOC SpERC 1.1.v1
<b>Processes, tasks, activities covered</b>	
Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Operation is carried out at elevated temperature (>20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
<b>Specific Risk Management Measures &amp; Operating Conditions</b>	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
bulk closed loading and unloading	Handle substance within a closed system Wear suitable gloves tested to EN374.
bulk open loading and unloading	Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or

	maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Laboratory activities	No other specific measures identified
Bulk product storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
<b>2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Substance is complex UVCB. Predominantly hydrophobic.	
<b>Amounts used</b>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.8e7
Fraction of regional tonnage used locally	0.021
<b>Frequency and duration of use</b>	
Continuous release.	
Emission days (days/year)	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
Release fraction to air from process (initial release prior to RMM)	1.0e-2
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-5
Release fraction to soil from process (initial release prior to RMM)	0.0001
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	90.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	3.3e6
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	10000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>3.2 Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1 Health</b>
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.
<b>4.2 Environment</b>
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ). Scaled local assessments for EU refineries have been performed using site-specific data and are attached in PETRORISK file – “Site-Specific Production” worksheet.

## 2. Use of substance as an intermediate - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Use as an intermediate
<b>Use Descriptor</b>	
Sector(s) of use	3, 8, 9
Process category(ies)	1, 2, 3, 4, 8a, 8b, 15
Environmental release category(ies)	6a
Specific Environmental Release Category	ESVOC SpERC 6.1a.v1
<b>Processes, tasks, activities covered</b>	
Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Operation is carried out at elevated temperature (>20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to

	EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
bulk closed loading and unloading	Handle substance within a closed system Wear suitable gloves tested to EN374.
bulk open loading and unloading	Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	No other specific measures identified
Laboratory activities	No other specific measures identified
Bulk product storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
<b>2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Substance is complex UVCB. Predominantly hydrophobic.	
<b>Amounts used</b>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	3.5e5
Fraction of regional tonnage used locally	0.043
<b>Frequency and duration of use</b>	
Continuous release.	
Emission days (days/year)	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
Release fraction to air from process (initial release prior to RMM)	1.0e-3
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-5
Release fraction to soil from process (initial release prior to RMM)	0.001
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	51.7
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment)	94.1

plant) RMMs (%):	
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	4.1e5
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of the substance is generated.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>	
<b>4.1 Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
<b>4.2 Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHimpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHimpl-ES-CSA-CSR.pdf</a> ).	

### 3. Distribution of substance - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Distribution of substance
<b>Use Descriptor</b>	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 4, 8a, 8b, 9, 15
Environmental release category(ies)	1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7
Specific Environmental Release Category	ESVOC SpERC 1.1b.v1
<b>Processes, tasks, activities covered</b>	
Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
General measures applicable to all activities	<b>Specific Risk Management Measures &amp; Operating Conditions</b> Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to

	minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
Laboratory activities	No other specific measures identified
bulk closed loading and unloading	Handle substance within a closed system Wear suitable gloves tested to EN374.
bulk open loading and unloading	Wear suitable gloves tested to EN374.
Drum and small package filling	Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
<b>2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Substance is complex UVCB. Predominantly hydrophobic.	
<b>Amounts used</b>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.8e7
Fraction of regional tonnage used locally	0.002
<b>Frequency and duration of use</b>	
Continuous release.	
Emission days (days/year)	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
Release fraction to air from process (initial release prior to RMM)	1.0e-3
Release fraction to wastewater from process (initial release prior to RMM)	1.0e-6
Release fraction to soil from process (initial release prior to RMM)	0.00001
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	9.6



If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	4.1e5
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of the substance is generated.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>	
<b>4.1 Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
<b>4.2 Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).	

## 4. Formulation & (Re)packing of substance - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Formulation & (re)packing of substances and mixtures
<b>Use Descriptor</b>	
Sector(s) of use	3, 10
Process category(ies)	1, 2, 3, 4, 5, 8a, 8b, 9, 14, 15
Environmental release category(ies)	2
Specific Environmental Release Category	ESVOC SpERC 2.2.v1
<b>Processes, tasks, activities covered</b>	
Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios / Product Category	Specific Risk Management Measures & Operating Conditions
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
Drum/batch transfers	Use drum pumps or carefully pour from container Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Bulk transfers	Handle substance within a closed system Wear suitable gloves tested to EN374.
Mixing operations (open systems)	Provide extract ventilation to points where emissions occur Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Production or preparation of articles by tableting, compression, extrusion or pelletisation	Wear suitable gloves tested to EN374.
Drum/batch transfers	Wear suitable gloves tested to EN374.
Laboratory activities	No other specific measures identified
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance Wear suitable gloves tested to EN374.
Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
<p><b>2.2 Control of environmental exposure</b></p>	
<p><b>Product characteristics</b></p>	
<p>Substance is complex UVCB. Predominantly hydrophobic.</p>	
<p><b>Amounts used</b></p>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.8e7
Fraction of regional tonnage used locally	0.0011
<p><b>Frequency and duration of use</b></p>	

Continuous release.	
Emission days (days/year)	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
Release fraction to air from process (initial release prior to RMM)	1.0e-2
Release fraction to wastewater from process (initial release prior to RMM)	2.0e-5
Release fraction to soil from process (initial release prior to RMM)	0.0001
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	60.0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	91.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	6.8e5
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or national regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>	
<b>4.1 Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
<b>4.2 Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).	

## 5. Use of substance in Metal working fluids / rolling oils - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Metal working fluids / rolling oils
<b>Use Descriptor</b>	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 17

Environmental release category(ies)	4
Specific Environmental Release Category	ESVOC SpERC 4.7a.v1
<b>Processes, tasks, activities covered</b>	
Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
<b>Specific Risk Management Measures &amp; Operating Conditions</b>	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Provide extract ventilation to points where emissions occur
Bulk transfers	Handle substance within a closed system Wear suitable gloves tested to EN374.
Filling / preparation of equipment from drums or containers	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
Metal machining operations	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Treatment by dipping and pouring	Wear suitable gloves tested to EN374.
Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) Wear suitable gloves (tested to EN374), coverall and eye protection.
Manual Roller, spreader, flow application	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Automated metal rolling/forming	Handle substance within a predominantly closed system provided with extract ventilation
Semi-automated metal rolling/forming	Provide extract ventilation to points where emissions occur
Equipment cleaning and maintenance	Drain down and flush system prior to equipment break-in or maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system

Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.

**2.2 Control of environmental exposure**

**Product characteristics**  
 Substance is complex UVCB. Predominantly hydrophobic.

**Amounts used**

Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	1.0e4
Fraction of regional tonnage used locally	0.01

**Frequency and duration of use**

Continuous release.

Emission days (days/year)	20
---------------------------	----

**Environmental factors not influenced by risk management**

Local freshwater dilution factor	10
Local marine water dilution factor	100

**Other operational conditions of use affecting environmental exposure**

Release fraction to air from process (initial release prior to RMM)	0.02
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-6
Release fraction to soil from process (initial release prior to RMM)	0

**Technical conditions and measures at process level (source) to prevent release**  
 Common practices vary across sites thus conservative process release estimates used.

**Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil**  
 Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Treat air emission to provide a typical removal efficiency of (%):	70
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0

**Organisation measures to prevent/limit release from site**  
 Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

**Conditions and measures related to municipal sewage treatment plant**

Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	7.8e4
Assumed domestic sewage treatment plant flow (m³/d):	2000

**Conditions and measures related to external treatment of waste for disposal**  
 External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**  
 External recovery and recycling of waste should comply with applicable local and/or national regulations.

**Section 3 Exposure Estimation**

**3.1 Health**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**3.2 Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

**Section 4 Guidance to check compliance with the Exposure Scenario**

<b>4.1 Health</b>
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.
<b>4.2 Environment</b>
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).

## 6. Use of substance as Release agents or binders - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Use as binders and release agents
<b>Use Descriptor</b>	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 4, 6, 7, 8b, 10, 13, 14
Environmental release category(ies)	4
Specific Environmental Release Category	ESVOC SpERC 4.10a.v1
<b>Processes, tasks, activities covered</b>	
Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mold forming and casting, and handling of waste.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
<b>Specific Risk Management Measures &amp; Operating Conditions</b>	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are

	likely to lead to substantial aerosol release, e.g. spraying
Bulk transfers	Handle substance within a closed system
Drum/batch transfers	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Mixing operations (closed systems)	No other specific measures identified
Mixing operations (open systems)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Mould forming	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Casting operations (open systems)	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Wear suitable gloves tested to EN374.
Machine Spraying	Minimise exposure by extracted full enclosure for the operation or equipment. Wear suitable gloves tested to EN374.
Manual Spraying	Wear a full face respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable gloves (tested to EN374), coverall and eye protection. Ensure operatives are trained to minimise exposures.
Manual Roller, spreader, flow application	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system

Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.

**2.2 Control of environmental exposure**

**Product characteristics**

Substance is complex UVCB. Predominantly hydrophobic.

**Amounts used**

Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	1.4e4
Fraction of regional tonnage used locally	0.18

**Frequency and duration of use**

Continuous release.

Emission days (days/year)	100
---------------------------	-----

**Environmental factors not influenced by risk management**

Local freshwater dilution factor	10
Local marine water dilution factor	100

**Other operational conditions of use affecting environmental exposure**

Release fraction to air from process (initial release prior to RMM)	1.0
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-7
Release fraction to soil from process (initial release prior to RMM)	0

**Technical conditions and measures at process level (source) to prevent release**

Common practices vary across sites thus conservative process release estimates used.

**Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil**

Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Treat air emission to provide a typical removal efficiency of (%):	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal	59.2

efficiency >= (%):	
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	1.7e5
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or national regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>	
<b>4.1 Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
<b>4.2 Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).	

## 7. Use of substance as Release agents or binders - Professional

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Use as binders and release agents
<b>Use Descriptor</b>	
Sector(s) of use	22
Process category(ies)	1, 2, 3, 4, 6, 8a, 8b, 10, 11, 14
Environmental release category(ies)	8a, 8d
Specific Environmental Release Category	ESVOC SpERC 8.10b.v1
<b>Processes, tasks, activities covered</b>	
Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.



Contributing Scenarios / Product Category	Specific Risk Management Measures & Operating Conditions
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying
Material transfers (closed systems)	No other specific measures identified
Drum/batch transfers	Wear suitable gloves tested to EN374.
Mixing operations (closed systems)	No other specific measures identified
Mixing operations (open systems)	Wear suitable gloves tested to EN374.
Mould forming	Provide extract ventilation to points where emissions occur Wear suitable gloves tested to EN374.
Casting operations with local exhaust ventilation	Provide extract ventilation to points where emissions occur Wear suitable gloves tested to EN374.
Casting operations without local exhaust ventilation	Wear a respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable gloves (tested to EN374), coverall and eye protection.
Spraying Manual without local exhaust ventilation	Carry out in a vented booth or extracted enclosure Wear suitable gloves (tested to EN374), coverall and eye protection. Ensure operatives are trained to minimise exposures.
Spraying Manual without local exhaust ventilation	Wear a full face respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable gloves (tested to EN374), coverall and eye protection. Ensure operatives are trained to minimise exposures.
Manual Roller, spreader, flow application	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to</p>	

protect from these adverse effects.	
<b>2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Substance is complex UVCB. Predominantly hydrophobic.	
<b>Amounts used</b>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.9e3
Fraction of regional tonnage used locally	0.0005
<b>Frequency and duration of use</b>	
Continuous release.	
Emission days (days/year)	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
Release fraction to air from process (initial release prior to RMM)	0.95
Release fraction to wastewater from process (initial release prior to RMM)	0.025
Release fraction to soil from process (initial release prior to RMM)	0.025
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%):	N/A
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	6.2e1
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or national regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>	
<b>4.1 Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
<b>4.2 Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).	

## 8. Use of substance as a Fuel - Industrial

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Use as a fuel
<b>Use Descriptor</b>	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 8a, 8b, 16
Environmental release category(ies)	7
Specific Environmental Release Category	ESVOC SpERC 7.12a.v1
<b>Processes, tasks, activities covered</b>	
Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
<b>Specific Risk Management Measures &amp; Operating Conditions</b>	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up any contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Bulk transfers	Wear suitable gloves tested to EN374.
Drum/batch transfers	Wear suitable gloves tested to EN374.
Use as a fuel (closed systems)	No other specific measures identified
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system
Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived.	

Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.

**2.2 Control of environmental exposure**

**Product characteristics**

Substance is complex UVCB. Predominantly hydrophobic.

**Amounts used**

Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	4.5e6
Fraction of regional tonnage used locally	0.34

**Frequency and duration of use**

Continuous release.

Emission days (days/year)	300
---------------------------	-----

**Environmental factors not influenced by risk management**

Local freshwater dilution factor	10
Local marine water dilution factor	100

**Other operational conditions of use affecting environmental exposure**

Release fraction to air from process (initial release prior to RMM)	5.0e-3
Release fraction to wastewater from process (initial release prior to RMM)	0.00001
Release fraction to soil from process (initial release prior to RMM)	0

**Technical conditions and measures at process level (source) to prevent release**

Common practices vary across sites thus conservative process release estimates used.

**Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil**

Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Treat air emission to provide a typical removal efficiency of (%):	95
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	97.7
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	60.4

**Organisation measures to prevent/limit release from site**

Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

**Conditions and measures related to municipal sewage treatment plant**

Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	97.7
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	5.5e6
Assumed domestic sewage treatment plant flow (m³/d):	2000

**Conditions and measures related to external treatment of waste for disposal**

Combustion emissions considered in regional exposure assessment.

**Conditions and measures related to external recovery of waste**

External recovery and recycling of waste should comply with applicable local and/or national regulations.

**Section 3 Exposure Estimation**

**3.1 Health**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**3.2 Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

**Section 4 Guidance to check compliance with the Exposure Scenario**

**4.1 Health**

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.

**4.2 Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to

define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf>).

## 9. Use of substance as a Fuel - Professional

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Use as a fuel
<b>Use Descriptor</b>	
Sector(s) of use	22
Process category(ies)	1, 2, 3, 8a, 8b, 16
Environmental release category(ies)	9a, 9b
Specific Environmental Release Category	ESVOC SpERC 9.12b.v1
<b>Processes, tasks, activities covered</b>	
Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of worker exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
<b>Contributing Scenarios / Product Category</b>	
<b>Specific Risk Management Measures &amp; Operating Conditions</b>	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Bulk transfers	Wear suitable gloves tested to EN374.
Drum/batch transfers	Use drum pumps or carefully pour from container Wear suitable gloves tested to EN374.
Refuelling	Wear suitable gloves tested to EN374.
Use as a fuel (closed systems)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) or Ensure operation is undertaken outdoors
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
<b>2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Substance is complex UVCB. Predominantly hydrophobic.	
<b>Amounts used</b>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	6.7e6
Fraction of regional tonnage used locally	0.0005
<b>Frequency and duration of use</b>	
Continuous release.	
Emission days (days/year)	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
Release fraction to air from process (initial release prior to RMM)	1.0e-4
Release fraction to wastewater from process (initial release prior to RMM)	0.00001
Release fraction to soil from process (initial release prior to RMM)	0.00001
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%):	N/A
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
<b>Organisation measures to prevent/limit release from site</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	1.4e5
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1 Health</b>
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.
<b>4.2 Environment</b>
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).

## 10. Use of substance as a Fuel - Consumer

<b>Section 1 Exposure Scenario</b>	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
<b>Title</b>	Use as a fuel
<b>Use Descriptor</b>	
Sector(s) of use	21
Product category(ies)	13
Environmental release category(ies)	9a, 9b
Specific Environmental Release Category	ESVOC SpERC 9.12c.v1
<b>Processes, tasks, activities covered</b>	
Covers consumer uses in liquid fuels.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>2.1 Control of consumer exposure</b>	
<b>Product characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 Pa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	For each use event, covers use amounts up to (g): 37500 Covers skin contact area up to (cm <sup>2</sup> ): 420
Other operational conditions affecting exposure	Covers use up to (times/day of use): 0.143. Covers exposure up to (hours/event): 2 hours per event.
<b>Contributing Scenarios / Product Category</b>	
<b>Specific Risk Management Measures &amp; Operating Conditions</b>	
Liquid: Automotive Refuelling	Covers concentrations up to (%): 100%. Covers use up to (days/year): 52. Covers use up to (times/day of use): 1. Covers skin contact area up to (cm <sup>2</sup> ): 210.00. For each use event, covers use amounts up to (g): 37500. Covers use in room size of (m <sup>3</sup> ): 100. Covers exposure up to (hours/event): 0.05. Covers outdoor use No specific risk management measure identified beyond those operational conditions stated
Liquid Garden Equipment - Use	Covers concentrations up to (%): 100%. Covers use up to (days/year): 26. Covers use up to (times/day of use): 1. For each use event, covers use amounts up to (g): 750. Covers outdoor use Covers use in room size of (m <sup>3</sup> ): 100. Covers exposure up to (hours/event): 2.00. No specific risk management measure identified beyond those operational conditions stated
Liquid: garden equipment - refuelling	Covers concentrations up to (%): 100%. Covers use up to (days/year): 26. Covers use up to (times/day of use): 1. Covers skin contact area up to (cm <sup>2</sup> ): 420.00. For each use event, covers use amounts up to (g): 750. Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation. Covers use in room size of (m <sup>3</sup> ): 34. Covers exposure up to (hours/event): 0.03. No specific risk management measure identified beyond those operational conditions

stated	
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
<b>2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Substance is complex UVCB. Predominantly hydrophobic.	
<b>Amounts used</b>	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	1.6e7
Fraction of regional tonnage used locally	0.0005
<b>Frequency and duration of use</b>	
Continuous release.	
Emission days (days/year)	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor	10
Local marine water dilution factor	100
<b>Other operational conditions of use affecting environmental exposure</b>	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	3.5e5
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d):	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
<b>Section 3 Exposure Estimation</b>	
<b>3.1 Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures, consistent with the content of ECETOC report #107 and the Chapter R15 of the IR&CSA TGD. Where exposure determinants differ to these sources, then they are indicated.	
<b>3.2 Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>	
<b>4.1 Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
<b>4.2 Environment</b>	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf">https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf</a> ).	



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: **7750**  
Version: **2.0 en**  
Replaces version of: 2016-12-01  
Version: (1)

date of compilation: 2016-12-01  
Revision: 2020-10-06

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **Iron(III) chloride solution 40 %**  
Article number **7750**  
Registration number (REACH) **not relevant (mixture)**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** laboratory chemical  
laboratory and analytical use

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:** +49 (0) 721 - 56 06 0

**Telefax:** +49 (0) 721 - 56 06 149

**e-mail:** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

**Website:** [www.carlroth.de](http://www.carlroth.de)

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

**e-mail (competent person):** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

Emergency information service **+49/(0)89 19240**

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Classification acc. to GHS			
Section	Hazard class	Hazard class and category	Hazard statement
2.16	substance or mixture corrosive to metals	(Met. Corr. 1)	H290
3.10	acute toxicity (oral)	(Acute Tox. 4)	H302
3.2	skin corrosion/irritation	(Skin Irrit. 2)	H315
3.3	serious eye damage/eye irritation	(Eye Dam. 1)	H318

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

Classification acc. to GHS			
Section	Hazard class	Hazard class and category	Hazard statement
3.4S	skin sensitisation	(Skin Sens. 1)	H317

## 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP)

**Signal word**                      **Danger**

### Pictograms

GHS05, GHS07



### Hazard statements

H290                      May be corrosive to metals  
H302                      Harmful if swallowed  
H315                      Causes skin irritation  
H317                      May cause an allergic skin reaction  
H318                      Causes serious eye damage

### Precautionary statements

#### Precautionary statements - prevention

P280                      Wear protective gloves/eye protection.

#### Precautionary statements - response

P302+P352              IF ON SKIN: Wash with plenty of water.  
P305+P351+P338      IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310                      Immediately call a POISON CENTER/doctor.

**Hazardous ingredients for labelling:**                      Iron(III) chloride, Hydrochloric acid .... %

### Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



H317                      May cause an allergic skin reaction.  
H318                      Causes serious eye damage.  
P280                      Wear protective gloves/eye protection.  
P302+P352              IF ON SKIN: Wash with plenty of water.  
P305+P351+P338      IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310                      Immediately call a POISON CENTER/doctor.  
contains:              Iron(III) chloride, Hydrochloric acid .... %

## 2.3 Other hazards

There is no additional information.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Description of the mixture

Composition/information on ingredients.

Name of substance	Identifier	wt %	Classification acc. to 1272/2008/EC	Pictograms	Notes	Specific Conc. Limits
Iron(III) chloride	CAS No 7705-08-0  EC No 231-729-4  REACH Reg. No 01-2119497998- 05-xxxx	39 – 41	Met. Corr. 1 / H290 Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317			
Hydrochloric acid .... %	CAS No 7647-01-0  EC No 231-595-7  Index No 017-002-01-X  REACH Reg. No 01-2119484862- 27-xxxx	≤ 1	Met. Corr. 1 / H290 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335		B(a) GHS- HC IOELV	Met. Corr. 1; H290: C ≥ 0,1 % Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Dam. 1; H318: C ≥ 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 % STOT SE 3; H335: C ≥ 10 %

##### Notes

B(a): The classification refers to an aqueous solution  
GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)  
IOELV: Substance with a community indicative occupational exposure limit value

##### Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Take off immediately all contaminated clothing.

##### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following skin contact

Rinse skin with water/shower. In case of skin reactions, consult a physician. In case of skin irritation, consult a physician.

##### Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes hold-  
ing eyelids apart and consult an ophthalmologist. Protect uninjured eye.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

### Following ingestion

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritation, Corrosion, Allergic reactions, Nausea, Vomiting, Risk of serious damage to eyes

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings  
water spray, foam, dry extinguishing powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Non-combustible.

#### Hazardous combustion products

in case of fire and/or explosion do not breathe fumes

### 5.3 Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Do not breathe vapour/spray. Avoid contact with skin and eyes.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provide adequate ventilation. Avoid exposure. Handle and open container with care.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in the original container. Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice

##### • Ventilation requirements

Use local and general ventilation.

##### • Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C.

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Source
EU	hydrogen chloride	7647-01-0		IOELV	5	8	10	15			2000/39/EC
GB	hydrogen chloride	7647-01-0	ga	WEL	1	2	5	8			EH40/2005

#### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

ga As gases and aerosols

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

### Relevant DNELs/DMELs/PNECs and other threshold levels

#### • relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Iron(III) chloride	7705-08-0	DNEL	2,8 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrochloric acid .... %	7647-01-0	DNEL	8 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Hydrochloric acid .... %	7647-01-0	DNEL	15 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

NBR (Nitrile rubber)

#### • material thickness

≥0,3 mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

#### Respiratory protection



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

Respiratory protection necessary at: Aerosol or mist formation. Type: B-P2 (combined filters for acidic gases and particles, colour code: Grey/White).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (fluid)
Colour	dark brown
Odour	stinging
Odour threshold	no data available

#### Other physical and chemical parameters

pH (value)	<1
Melting point/freezing point	-12 °C
Initial boiling point and boiling range	this information is not available
Flash point	not determined
Evaporation rate	no data available
Flammability (solid, gas)	not relevant (fluid)

#### Explosive limits

• lower explosion limit (LEL)	this information is not available
• upper explosion limit (UEL)	this information is not available
Explosion limits of dust clouds	not relevant

Vapour pressure	this information is not available
Density	1,39 – 1,45 g/cm <sup>3</sup> at 20 °C
Vapour density	this information is not available
Bulk density	Not applicable
Relative density	this information is not available

#### Solubility(ies)

Water solubility	miscible in any proportion
------------------	----------------------------

#### Partition coefficient

n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	Information on this property is not available.
Decomposition temperature	no data available

#### Viscosity

• kinematic viscosity	6,897 mm <sup>2</sup> /s at 20 °C
• dynamic viscosity	10 mPa s at 20 °C

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

Explosive properties	Shall not be classified as explosive.
Oxidising properties	none

### 9.2 Other information

There is no additional information.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Substance or mixture corrosive to metals.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

Violent reaction with: Alkalis, Metals

### 10.4 Conditions to avoid

Keep away from heat.

### 10.5 Incompatible materials

different metals

#### Release of flammable materials with

metals (due to the release of hydrogen in an acid/alkaline medium)

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### • Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Iron(III) chloride	7705-08-0	oral	500 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

May cause an allergic skin reaction. May cause sensitization by skin contact.

#### Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant

##### • Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### • Specific target organ toxicity - repeated exposure



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

nausea, vomiting, Liver and kidney damage

#### • If in eyes

Causes serious eye damage, risk of blindness

#### • If inhaled

irritant effects

#### • If on skin

causes skin irritation, may cause an allergic skin reaction

### Other information

None

## SECTION 12: Ecological information

### 12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.

### 12.2 Process of degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Iron(III) chloride	7705-08-0		-4 (24 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

##### Sewage disposal-relevant information

Do not empty into drains.

##### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.


#### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

### SECTION 14: Transport information

14.1	UN number	2582
14.2	UN proper shipping name	<b>FERRIC CHLORIDE SOLUTION</b>
	Hazardous ingredients	Iron(III) chloride, Hydrochloric acid .... %
14.3	Transport hazard class(es)	
	Class	8 (corrosive substances)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	<b>Special precautions for user</b>	
		Provisions for dangerous goods (ADR) should be complied within the premises.
14.7	<b>Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	
		The cargo is not intended to be carried in bulk.
14.8	<b>Information for each of the UN Model Regulations</b>	
		• <b>Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)</b>
	UN number	2582
	Proper shipping name	FERRIC CHLORIDE SOLUTION
	Particulars in the transport document	UN2582, FERRIC CHLORIDE SOLUTION, 8, III, (E)
	Class	8
	Classification code	C1

# Safety data sheet



according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: **7750**

---

Packing group	III
Danger label(s)	8
	
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	E
Hazard identification No	80
<b>Emergency Action Code</b>	2X
<b>• International Maritime Dangerous Goods Code (IMDG)</b>	
UN number	2582
Proper shipping name	FERRIC CHLORIDE SOLUTION
Particulars in the shipper's declaration	UN2582, FERRIC CHLORIDE SOLUTION, 8, III
Class	8
Marine pollutant	-
Packing group	III
Danger label(s)	8
	
Special provisions (SP)	223
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	1 - Acids
<b>• International Civil Aviation Organization (ICAO-IATA/DGR)</b>	
UN number	2582
Proper shipping name	Ferric chloride solution
Particulars in the shipper's declaration	UN2582, Ferric chloride solution, 8, III
Class	8
Packing group	III
Danger label(s)	8

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Relevant provisions of the European Union (EU)

- **Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)**

None of the ingredients are listed.

- **Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)**

None of the ingredients are listed.

- **Regulation 850/2004/EC on persistent organic pollutants (POP)**

None of the ingredients are listed.

- **Restrictions according to REACH, Annex XVII**

Name of substance	Type of registration	Conditions of restriction	No
Iron(III) chloride solution	1907/2006/EC annex XVII	R3	3

##### Legend

R3

1. Shall not be used in:
  - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
  - tricks and jokes,
  - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
  - can be used as fuel in decorative oil lamps for supply to the general public, and,
  - present an aspiration hazard and are labelled with R65 or H304,
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
  - (a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
  - (b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
  - (c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.
7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.

Name acc. to inventory	CAS No	Wt%	Listed in	Remarks
Metals and their compounds		40	A)	

##### Legend

A) Indicative list of the main pollutants

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

- **Restrictions according to REACH, Title VIII**

None.

- **List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list**

none of the ingredients are listed

- **Seveso Directive**

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

- **Directive 75/324/EEC relating to aerosol dispensers**

### Filling batch

#### Deco-Paint Directive (2004/42/EC)

VOC content	0 % 0 g/l
-------------	--------------

#### Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content	0 %
VOC content Water content was discounted	0 g/l

#### Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

None of the ingredients are listed.

#### Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

#### Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

Name acc. to inventory	CAS No	Listed in	Remarks
Metals and their compounds		A)	

#### Legend

A) Indicative list of the main pollutants

#### Regulation 98/2013/EU on the marketing and use of explosives precursors

none of the ingredients are listed

#### Regulation 111/2005/EC laying down rules for the monitoring of trade between the Community and third countries in drug precursors

Name of substance	CAS No	Classification	CN Code	Threshold level
Hydrochloric acid .... %	7647-01-0	Category 3	2806 10 00	

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

### National inventories

Country	National inventories	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1	Remarks: For full text of Hazard- and EU Hazard-statements: see SECTION 16.		yes
2.2		Pictograms: change in the listing (table)	yes
2.2	Hazardous ingredients for labelling: Iron(III) chloride	Hazardous ingredients for labelling: Iron(III) chloride, Hydrochloric acid .... %	yes
2.2	contains: Iron(III) chloride	contains: Iron(III) chloride, Hydrochloric acid .... %	yes
3.2		Description of the mixture: change in the listing (table)	yes

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
8.1	Occupational exposure limit values (Workplace Exposure Limits): Data are not available.	Occupational exposure limit values (Workplace Exposure Limits)	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.1		• relevant DNELs of components of the mixture: change in the listing (table)	yes
14.2	Hazardous ingredients: Iron(III) chloride	Hazardous ingredients: Iron(III) chloride, Hydrochloric acid .... %	yes
14.3	Transport hazard class(es)	Transport hazard class(es): class 8 hazard - corrosive substances	yes
14.8		Marine pollutant: -	yes
14.8	Packing group: III8	Packing group: III	yes
14.8		Danger label(s): 8	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
Acute Tox.	acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
CN Code	Combined Nomenclature
COD	chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: 7750

Abbr.	Descriptions of used abbreviations
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	indicative occupational exposure limit value
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	substance or mixture corrosive to metals
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
Skin Sens.	skin sensitisation
STEL	short-term exposure limit
STOT SE	specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	time-weighted average
VOC	Volatile Organic Compounds
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

### Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- Dangerous Goods Regulations (DGR) for the air transport (IATA)
- International Maritime Dangerous Goods Code (IMDG)



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



## Iron(III) chloride solution 40 %

article number: **7750**

---

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	may be corrosive to metals
H302	harmful if swallowed
H314	causes severe skin burns and eye damage
H315	causes skin irritation
H317	may cause an allergic skin reaction
H318	causes serious eye damage
H335	may cause respiratory irritation

### Disclaimer

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Ref. 2.1/GB/EN

**SUPERFLOC C-498HMW**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier****Commercial Product Name**  
**SUPERFLOC C-498HMW****1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Use of the Substance/Mixture**

Water treatment chemical

**Recommended restrictions on use**

-

**1.3 Details of the supplier of the safety data sheet**Kemira Oyj  
P.O. Box 33000101 HELSINKI FINLAND  
Telephone+358108611, Telefax. +358108621124  
ProductSafety.FI.Helsinki@kemira.com**1.4 Emergency telephone number**

Carechem 24 International: +44 (0) 1235 239 670

**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification according to Regulation (EU) 1272/2008(CLP)**

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.;

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)****Hazard statements**

:

EUH210

Not a hazardous substance or mixture  
according to Regulation (EC) No.  
1272/2008.

Safety data sheet available on request.

### 2.3 Other hazards

**Advice;** Forms slippery/greasy layers with water.

**Potential environmental effects;** This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

Chemical nature of the mixture	Cationic polyacrylamide.		
CAS/EU number/REACH Registration Number	Chemical name of the substance	Concentration	Classification according to Regulation (EU) 1272/2008(CLP)
77-92-9 201-069-1 01-2119457026-42	Citric acid	0 - 9.9 %	Eye Irrit. Category 2,H319
124-04-9 204-673-3 01-2119457561-38	Adipic acid	0 - 5 %	Eye Irrit. Category 2,H319

The total combined concentration of Adipic acid and Citric acid does not exceed 9.9%.

### Further information

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice

Show this safety data sheet to the doctor in attendance.

#### Inhalation

Remove to fresh air. If symptoms persist, call a physician.

#### Skin contact

Wash off immediately with soap and plenty of water.

#### Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

#### Ingestion

Rinse mouth with water. Call a physician immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms : No information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment : Symptomatic treatment.

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media**

Extinguishing media : Water spray  
Dry chemical  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : none

**5.2 Special hazards arising from the substance or mixture**

Dust may form explosive mixture in air.

**5.3 Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

**5.4 Specific methods**

Avoid dust accumulation.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures**

For personal protection see section 8.

**6.2 Environmental precautions**

Try to prevent the material from entering drains or water courses.

**6.3 Methods and materials for containment and cleaning up**

Product becomes slippery when it is wet. Sweep up and shovel into suitable containers for disposal.  
Flush with water. Prevent product from entering drains.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

Ref. 2.1/GB/EN

**SUPERFLOC C-498HMW**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

The product is hygroscopic. Protect from moisture. Avoid dust formation.

**7.2 Conditions for safe storage, including any incompatibilities**

Store at room temperature in the original container.

**Materials for packaging**

Unsuitable material: To avoid product degradation and equipment corrosion, do not use iron, copper or aluminium containers or equipment.

**Materials to avoid:**

Strong oxidizing agents

**Storage stability:**

Storage temperature 4 - 27 °C

Other data Stable under recommended storage conditions.

**7.3 Specific end use(s)**

Not listed

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

Contains no substances with occupational exposure limit values.

PNEC : No data available

**8.2 Exposure controls****8.2.1 Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes and clothing. Do not breathe dust. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation.

**8.2.2 Individual protection measures, such as personal protective equipment****Hand protection**

Glove material: Nitrile rubber, Protective gloves complying with EN 374. Permeability tests are not available for this product. Please observe the instructions regarding permeability and breakthrough time

Ref. 2.1/GB/EN

**SUPERFLOC C-498HMW**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

### Eye protection

Safety glasses with side-shields conforming to EN166

### Skin and body protection

Protective clothing.

### Respiratory protection

Dust safety masks are recommended when the dust concentration is more than 10 mg/m<sup>3</sup>. Half mask with a particle filter P2 (EN 143)

### 8.2.3 Environmental exposure controls

No data available

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

#### General Information (appearance, odour)

Physical state	solid, crystalline, powder
Colour	off-white
Odour	odourless
Odour Threshold	Not relevant

#### Important health safety and environmental information

pH	3 - 5 ( 0.5 %) (as aqueous solution)
Melting point/range	No data available
Boiling point/boiling range	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability (solid, gas) :	No data available
<b>Explosive properties:</b>	
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapour pressure	Not applicable

### SUPERFLOC C-498HMW

Ref. 2.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

<b>Relative vapour density</b>	Not applicable
<b>Bulk density</b>	750 kg/m <sup>3</sup>
<b>Solubility(ies):</b>	
<b>Water solubility</b>	Limited by viscosity.
<b>Partition coefficient: n-octanol/water</b>	Not applicable
<b>Auto-ignition temperature</b>	> 150 °C
<b>Thermal decomposition</b>	> 150 °C
<b>Viscosity:</b>	
<b>Viscosity, dynamic</b>	Not applicable
<b>Oxidizing</b>	The substance or mixture is not classified as oxidizing.
<b>Saturation in air (% vol.)</b>	Not applicable

#### 9.2 Other data

<b>Surface tension</b>	Not applicable
------------------------	----------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid contact with alkaline materials which will degrade the polymer.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Ammonia  
Carbon oxides (CO<sub>x</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
hydrogen chloride (HCl)

Ref. 2.1/GB/EN

**SUPERFLOC C-498HMW**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

---

Thermal decomposition : > 150 °C

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects****Acute toxicity**

The acute toxicological results displayed may not be the results of actual testing of this material but based on a similar tested material.

LD50/Oral/Rat: > 5,000 mg/kg

Remarks: estimated

LC50/Inhalation/4 h/Rat: 20 mg/l

Remarks: estimated

LD50/Dermal/Rabbit: > 2,000 mg/kg

Remarks: estimated

**Irritation and corrosion**

Skin:

No skin irritation

Eyes:

No eye irritation

**Sensitisation**

Not sensitizing.

**Long term toxicity**

Repeated dose toxicity

Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.



Ref. 2.1/GB/EN

**SUPERFLOC C-498HMW**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT - single exposure**

The substance or mixture is not classified as specific target organ toxicant, single exposure.

**STOT - repeated exposure**

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

**Aspiration toxicity**

No aspiration toxicity classification

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Aquatic toxicity**

Ecotoxicological information provided is based on a structurally or compositionally similar product. This material is not classified as dangerous for the environment. The effects on aquatic organisms are due to an external (non-systemic) mode of action and are significantly reduced (by a factor of 7-20) within 30 minutes due to the binding of the product to dissolved organic carbon and inorganic sorbents such as clays and silts.

LC50/96 h/Branchydanio rerio (zebra fish)/Acute toxicity/OECD Test Guideline 203: > 1 - 10 mg/l  
EC50/48 h/Daphnia magna (Water flea)/Immobilization/OECD Test Guideline 202: > 10 - 100 mg/l  
IC50/algae/Growth inhibition/OECD Test Guideline 201:  
Due to the cationicity of the polymer, test is not appropriate.

**Toxicity to other organisms**

No data available

**12.2 Persistence and degradability**

Biological degradability:  
CO2 Evolution Test/OECD Test Guideline 301B/28 d:

The polymeric ingredient is not readily biodegradable, but degradable by hydrolysis.

### SUPERFLOC C-498HMW

Ref. 2.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date: 22.03.2019

#### 12.3 Bioaccumulative potential

Bioaccumulation is unlikely. Because of the high molecular weight of the polymer diffusion through biological membranes is very small.

Partition coefficient: n-octanol/water: Not applicable

#### 12.4. Mobility in soil

##### Mobility

Water solubility: Limited by viscosity.

Surface tension: Not applicable

#### 12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

No information available.

## SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

##### Product

Recycling, recovery and reuse of materials is recommended if permitted by regulations. If recycling is not practicable, dispose of in compliance with local regulations.

##### Contaminated packaging

Dirty package must be disposed of in the same way as the product itself.

## SECTION 14: TRANSPORT INFORMATION

#### 14.1 UN number

##### Land transport

Not classified as dangerous in the meaning of transport regulations.

##### Sea transport

Not classified as dangerous in the meaning of transport regulations.

##### Air transport

Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not classified as dangerous in the meaning of transport regulations.

## SUPERFLOC C-498HMW

Ref. 2.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

### 14.8 Special precautions for user

None known.

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

#### Notification status

TSCA : All components of this product are included in the United States TSCA Chemical Inventory or are not required to be listed on the United States TSCA Chemical Inventory.

DSL : All components of this product are included in the Canada Domestic Substance List (DSL) or are not required to be listed on the Canada Domestic Substance List (DSL).

EINECS : All components of this product are included in the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.

AICS : All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on the Australian Inventory of Chemical Substances (AICS).

IECSC : All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

ENCS : All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese (ENCS) inventory.

KECI : All components of this product are included in the Korean (ECL) inventory or are not required to be listed on the Korean (ECL) inventory.

PICCS : All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine (PICCS) inventory.

NZIoC : All components of this product are included in the New Zealand inventory (NZIoC) or are not required to be listed on the New Zealand inventory(NZIoC).

TCSI : All components of this product are included on the Taiwan Toxic Chemical Substances Control Act Inventory.

---

**15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this mixture.

**SECTION 16: OTHER INFORMATION****Full text of H-Statements referred to under section 3.**

H319 Causes serious eye irritation.

H319 Causes serious eye irritation.

**Training advice**

Read the safety data sheet before using the product.

**Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Sources of key data used to compile the Safety Data Sheet**

Regulations, databases, literature, own tests.

**Additions, Deletions, Revisions**

Relevant changes have been marked with vertical lines.

Ref. 1.1/GB/EN

**SUPERFLOC C-6598**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier****Commercial Product Name**  
**SUPERFLOC C-6598****1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Use of the Substance/Mixture**

Water treatment: treatment of waste waters and WWTP sludge

**Recommended restrictions on use**

-

**1.3 Details of the supplier of the safety data sheet**Kemira Oyj  
P.O. Box 33000101 HELSINKI FINLAND  
Telephone+358108611, Telefax. +358108621124  
ProductSafety.FI.Helsinki@kemira.com**1.4 Emergency telephone number**

Carechem 24 International: +44 (0) 1235 239 670

**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification according to Regulation (EU) 1272/2008(CLP)**

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.;

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)****Hazard statements**

:

EUH210

Not a hazardous substance or mixture  
according to Regulation (EC) No.  
1272/2008.

Safety data sheet available on request.

### 2.3 Other hazards

**Advice;** Contaminated surfaces will be extremely slippery.

**Potential environmental effects;** This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

Chemical nature of the mixture	Cationic Polyacrylamide, emulsion.		
CAS/EU number/REACH Registration Number	Chemical name of the substance	Concentration	Classification according to Regulation (EU) 1272/2008(CLP)
01-2119453414-43	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	0 - 25 %	Asp. Tox. Category 1,H304
01-2119485032-45	Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	0 - 25 %	Asp. Tox. Category 1,H304
01-2119826592-36	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	0 - 25 %	Asp. Tox. Category 1,H304
77-92-9 201-069-1 01-2119457026-42	Citric acid	1 - 3 %	Eye Irrit. Category 2,H319

Components listed above that have a zero minimum and a common maximum range are interchangeably used components based on availability. Only one of these components is contained in the product up to the maximum amount noted.

### Further information

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice

Show this safety data sheet to the doctor in attendance.

#### Inhalation

Remove to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

#### Skin contact

Take off contaminated clothing and shoes immediately. Wash off immediately with plenty of water. Wash

### SUPERFLOC C-6598

Ref. 1.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

contaminated clothing before reuse. Get medical attention if irritation develops and persists.

#### Eye contact

Rinse immediately with plenty of water for at least 15 minutes. If symptoms persist, call a physician.

#### Ingestion

If swallowed : Call a physician immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Symptomatic treatment.

## SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Extinguishing media : Water spray  
 Dry chemical  
 Carbon dioxide (CO<sub>2</sub>)  
 Unsuitable : Water spray jet  
 extinguishing media

#### 5.2 Special hazards arising from the substance or mixture

Contaminated surfaces will be extremely slippery.

#### 5.3 Advice for firefighters

Wear full protective clothing and self-contained breathing apparatus. For personal protection see section 8.

#### 5.4 Specific methods

Cool containers/tanks with water spray. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Where the exposure level is not known, wear approved, positive pressure, self-contained respirator.  
 Where the exposure level is known, wear approved respirator suitable for the level of exposure.  
 Chemical resistant boots.

#### 6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

#### 6.3 Methods and materials for containment and cleaning up

Ref. 1.1/GB/EN

**SUPERFLOC C-6598**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

Soak up with inert absorbent material. Shovel or sweep up. Flush away traces with water. Contaminated surfaces will be extremely slippery. Spill area should be re-cleaned in case slipperiness remains.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

For personal protection see section 8.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep container tightly closed in a dry and well-ventilated place. Keep away from food and drink.  
Store in original container.

**Materials for packaging**

Unsuitable material: To avoid product degradation and equipment corrosion, do not use iron, copper or aluminium containers or equipment.

**Materials to avoid:**

Strong oxidizing agents, Avoid contact with alkaline materials which will degrade the polymer.

**Storage stability:**

Storage temperature 4 - 27 °C

Other data Stable under recommended storage conditions.

**7.3 Specific end use(s)**

Not listed

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

Contains no substances with occupational exposure limit values.

PNEC : No data available

**8.2 Exposure controls**



### SUPERFLOC C-6598

Ref. 1.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

#### 8.2.1 Appropriate engineering controls

Wash hands and face before breaks and immediately after handling the product. Keep away from food and drink.

Ensure adequate ventilation.

#### 8.2.2 Individual protection measures, such as personal protective equipment

##### Hand protection

Glove material: Impervious gloves, Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. The information on suitable gloves is derived from literature, manufacture information or from data on the use of similar substances.

##### Eye protection

Ensure that eyewash stations and safety showers are close to the workstation location. Tightly fitting safety goggles or face-shield.

##### Skin and body protection

Avoid contact with skin. Wear suitable protective clothing.

##### Respiratory protection

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Recommended Filter type: (filter A2-P2) (EN 14387)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

#### General Information (appearance, odour)

Physical state	liquid ( 20 °C ), viscous, dispersion
Colour	opaque, greenish, to, milky, white
Odour	slight, hydrocarbon-like

#### Important health safety and environmental information

pH	2.3 - 4.0 (0,5 % solution)
Melting point/range	not determined
Boiling point/boiling range	approximately 100 °C
Flash point	> 100 °C (closed cup)
Evaporation rate	not determined

#### Explosive properties:

### SUPERFLOC C-6598

Ref. 1.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

<b>Lower explosion limit</b>	No data available
<b>Upper explosion limit</b>	No data available
<b>Vapour pressure</b>	similar to water
<b>Relative vapour density</b>	not determined
<b>Density</b>	approximately 1.015 - 1.045 g/cm <sup>3</sup>
<b>Solubility(ies):</b>	
<b>Water solubility</b>	Limited by viscosity.
<b>Partition coefficient: n-octanol/water</b>	Not applicable
<b>Auto-ignition temperature</b>	> 150 °C
<b>Thermal decomposition</b>	> 200 °C
<b>Viscosity:</b>	
<b>Viscosity, kinematic</b>	> 20.5 mm <sup>2</sup> /s ( 40 °C)
<b>Oxidizing</b>	The substance or mixture is not classified as oxidizing.
<b>Saturation in air (% vol.)</b>	No data available

### 9.2 Other data

<b>Surface tension</b>	not determined
------------------------	----------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Stable under normal conditions.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Conditions to avoid : Keep away from open flames, hot surfaces and sources of ignition.  
Do not freeze.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents  
Avoid contact with alkaline materials which will degrade the polymer.

Ref. 1.1/GB/EN

**SUPERFLOC C-6598**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

**10.6 Hazardous decomposition products**

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.  
Ammonia

Thermal decomposition : > 200 °C

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects****Acute toxicity**

Acute toxicity estimate/Oral: > 5,000 mg/kg

Remarks: estimated

Acute toxicity estimate/Inhalation: > 20 mg/l

Remarks: estimated

Acute toxicity estimate/Dermal: > 5,000 mg/kg

Remarks: estimated

**Irritation and corrosion**

Skin: No skin irritation

Remarks: Based on available data, the classification criteria are not met.

Eyes: No eye irritation

Remarks: Based on available data, the classification criteria are not met.

**Sensitisation**

Not sensitizing.

**Long term toxicity**

Repeated dose toxicity

Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Ref. 1.1/GB/EN

**SUPERFLOC C-6598**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT - single exposure**

The substance or mixture is not classified as specific target organ toxicant, single exposure.

**STOT - repeated exposure**

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

**Aspiration toxicity**

No aspiration toxicity classification

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Aquatic toxicity**

Ecotoxicological information provided is based on a structurally or compositionally similar product. This material is not classified as dangerous for the environment. The effects on aquatic organisms are due to an external (non-systemic) mode of action and are significantly reduced (by a factor of 7-20) within 30 minutes due to the binding of the product to dissolved organic carbon and inorganic sorbents such as clays and silts.

LC50/96 h/Branchydanio rerio (zebra fish)/Acute toxicity/OECD Test Guideline 203: > 1 - 10 mg/l

Remarks: fresh water

EC50/48 h/Daphnia magna (Water flea)/Immobilization/OECD Test Guideline 202: > 10 - 100 mg/l

ErC50/72 h/algae/Growth inhibition:

Remarks: Due to the cationicity of the polymer, test is not appropriate.

**Toxicity to other organisms**

No data available

**12.2 Persistence and degradability**

### SUPERFLOC C-6598

Ref. 1.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

Biological degradability:  
CO2 Evolution Test/OECD Test Guideline 301B:

Not readily biodegradable. The polymeric ingredient is not readily biodegradable, but degradable by hydrolysis.

#### 12.3 Bioaccumulative potential

Bioaccumulation is unlikely. Because of the high molecular weight of the polymer diffusion through biological membranes is very small.

Partition coefficient: n-octanol/water: Not applicable

#### 12.4. Mobility in soil

##### Mobility

Water solubility: Limited by viscosity.

Surface tension: not determined

#### 12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Additional ecological information: Ecotoxicological information provided is based on a structurally or compositionally similar product.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

##### Product

Recycling, recovery and reuse of materials is recommended if permitted by regulations. If recycling is not practicable, dispose of in compliance with local regulations. Incineration is recommended.

##### Contaminated packaging

Dirty package must be disposed of in the same way as the product itself.

### SECTION 14: TRANSPORT INFORMATION

#### 14.1 UN number

##### Land transport

Not classified as dangerous in the meaning of transport regulations.

##### Sea transport

Not classified as dangerous in the meaning of transport regulations.

Ref. 1.1/GB/EN

**SUPERFLOC C-6598**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

**Air transport**

Not classified as dangerous in the meaning of transport regulations.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**14.8 Special precautions for user**

None known.

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Other regulations : This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

**Notification status**

TSCA : All components of this product are included in the United States TSCA Chemical Inventory or are not required to be listed on the United States TSCA Chemical Inventory.

DSL : All components of this product are included in the Canada Domestic Substance List (DSL) or are not required to be listed on the Canada Domestic Substance List (DSL).

EINECS : All components of this product are included in the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.

AICS : All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on the Australian Inventory of Chemical Substances (AICS).

IECSC : All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

ENCS : All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese (ENCS) inventory.

KECI : All components of this product are included in the Korean (ECL) inventory or are not required to be listed on the Korean (ECL) inventory.

Ref. 1.1/GB/EN

**SUPERFLOC C-6598**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 14.11.2018

Previous date: 09.02.2017

Print Date:04.07.2019

---

PICCS	:	All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine (PICCS) inventory.
NZIoC	:	All components of this product are included in the New Zealand inventory (NZIoC) or are not required to be listed on the New Zealand inventory(NZIoC).
TCSI	:	All components of this product are included on the Taiwan Toxic Chemical Substances Control Act Inventory.

### 15.2 Chemical safety assessment

not required

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under section 3.

H304	May be fatal if swallowed and enters airways.
H304	May be fatal if swallowed and enters airways.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.

### Training advice

Read the safety data sheet before using the product.

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### Sources of key data used to compile the Safety Data Sheet

Regulations, databases, literature, own tests.

### Additions, Deletions, Revisions

Relevant changes have been marked with vertical lines.

Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier****Commercial Product Name**  
KemFoamX 2500**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Use of the Substance/Mixture**

Defoamer, Process aid for industrial applications.

**Recommended restrictions on use**

There are no uses advised against.

**1.3 Details of the supplier of the safety data sheet**Kemira Oyj  
P.O. Box 33000101 HELSINKI FINLAND  
Telephone+358108611, Telefax. +358108621124  
ProductSafety.FI.Helsinki@kemira.com**1.4 Emergency telephone number**

Carechem 24 International (Europe): +44 (0) 1235 239 670

**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification according to Regulation (EU) 1272/2008(CLP)**

Chronic aquatic toxicity; Category 4; May cause long lasting harmful effects to aquatic life.

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)****Hazard statements** : H413 May cause long lasting harmful effects to aquatic life.



Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

**Precautionary statements** : P273 Avoid release to the environment.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

- 68002-96-0 (C16 - C18) Alkyl alcohol ethoxylate propoxylate

### 2.3 Other hazards

**Advice;** Contaminated surfaces will be extremely slippery.

**Remarks;** This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Chemical name	CAS-No. EINECS-No. / ELINCS No.	Concentration [%]
(C16 - C18) Alkyl alcohol ethoxylate propoxylate	68002-96-0	>= 99

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice

Show this safety data sheet to the doctor in attendance.

#### Inhalation

Move to fresh air. Call a physician if symptoms occur.

#### Skin contact

Wash off with plenty of water. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

#### Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician if symptoms occur.

Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

### Ingestion

Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No hazards to be specially mentioned.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Symptomatic treatment., There is no specific antidote available.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Extinguishing media : Water mist  
Carbon dioxide (CO<sub>2</sub>)  
Foam  
Dry powder  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of: Fumes harmful gases and vapours

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### 5.4 Specific methods

Contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Contaminated surfaces will be extremely slippery.

Wear personal protective equipment. For personal protection see section 8.

### 6.2 Environmental precautions

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Do not allow contact with soil, surface or ground water.

### 6.3 Methods and materials for containment and cleaning up

### KemFoamX 2500

Ref. 2.3/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

See Sections 7 and 8 for proper handling and protective measures and Section 13 for proper waste disposal measures.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. For personal protection see section 8.

Handle in accordance with good industrial hygiene and safety practice.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Protect from frost, heat and sunlight.

Avoid temperatures above 60°C, direct sunlight and contact with sources of heat.

#### Incompatible products

Keep away from oxidizing agents and strongly acid or alkaline materials.

#### Materials for packaging

Suitable material: Stainless steel

Suitable material: Carbon steel

Suitable material: polyethylene containers

#### Materials to avoid:

Strong acids and oxidizing agents

### 7.3 Specific end use(s)

Defoamer

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before breaks and immediately after handling the product. Wear suitable protective equipment.

### 8.2.2 Individual protection measures, such as personal protective equipment

#### Hand protection

Glove material: butyl-rubber, Break through time: 480 min, Glove thickness: 0.7 mm  
Glove material: Nitrile rubber, Break through time: 30 min, Glove thickness: 0.4 mm  
Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

#### Eye protection

Safety glasses with side-shields conforming to EN166

#### Skin and body protection

Protective suit

#### Respiratory protection

No special protective equipment required. Ensure adequate ventilation. In the case of vapour formation use a respirator with an approved filter. Type A (filter A-P2) (filter ABEK-P2)

### 8.2.3 Environmental exposure controls

Should not be released into the environment.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

#### General Information (appearance, odour)

<b>Physical state</b>	liquid,
<b>Colour</b>	colourless, Yellowish
<b>Odour</b>	odourless

### KemFoamX 2500

Ref. 2.3/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

### Important health safety and environmental information

<b>pH</b>	5 - 7 in water, 5,0%.
<b>Melting point/freezing point</b>	ca. -7 °C
<b>Boiling point/boiling range</b>	> 200 °C
<b>Flash point</b>	> 125 °C (DIN 51758)
<b>Explosive properties:</b>	
<b>Lower explosion limit</b>	Not applicable
<b>Upper explosion limit</b>	Not explosive, Not applicable
<b>Vapour pressure</b>	< 0.0015 hPa ( 20 °C)
<b>Relative vapour density</b>	not determined
<b>Density</b>	approximately 0.98 g/cm <sup>3</sup> ( 20 °C) (DIN 51757)
<b>Relative density</b>	ca. 0.98(25 °C, )
<b>Bulk density</b>	No data available, liquid
<b>Solubility(ies):</b>	
<b>Water solubility</b>	practically insoluble, dispersible
<b>Solubility in other solvents</b>	solvent-like: mineral oil
	soluble solvent-like: Hydrocarbons
	soluble solvent-like: Alcohols
	soluble
<b>Partition coefficient: n-octanol/water</b>	Not applicable
<b>Auto-ignition temperature</b>	> 200 °C (DIN 51794)
<b>Thermal decomposition</b>	> 200 °C
<b>Viscosity:</b>	
<b>Viscosity, dynamic</b>	250 - 500 mPa.s ( 20 °C) (Brookfield )
<b>Viscosity, kinematic</b>	not determined

### 9.2 Other data

<b>Surface tension</b>	not determined
------------------------	----------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

(c) Kemira Oyj. All rights reserved. Reproduction and distribution is not permitted, unless used for the sole purpose of REACH 1907/2006 by customers of Kemira products only.

Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

The product is chemically stable.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : None reasonably foreseeable.

**10.4 Conditions to avoid**

Conditions to avoid : Hazardous polymerisation does not occur.  
Direct heating, dirt, chemical contamination, sunlight, UV or ionising radiation.

**10.5 Incompatible materials**

Materials to avoid : Strong acids and oxidizing agents

**10.6 Hazardous decomposition products**

Hazardous decomposition products : Carbon oxides (CO<sub>x</sub>)  
: No decomposition if stored normally.

Thermal decomposition : > 200 °C

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects****Acute toxicity**

LD50/Oral/Rat/Calculation method: > 2,000 mg/kg  
Based on available data, the classification criteria are not met.  
LC50/Inhalation:  
No data available

LD50 Dermal/Dermal:  
No data available

**Irritation and corrosion**

Skin: Rabbit:  
Remarks: Literary reference  
Based on available data, the classification criteria are not met.

Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

Eyes: Rabbit:  
Remarks: Literary reference  
Based on available data, the classification criteria are not met.

**Sensitisation**

Based on available data, the classification criteria are not met.

**Long term toxicity**

Repeated dose toxicity

Remarks: No information available.

Carcinogenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Teratogenicity

Based on available data, the classification criteria are not met.

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Aquatic toxicity**

EC50/48 h/Daphnia magna (Water flea)/static test/Directive 84/449/EEC, C.2: > 100 mg/l

**Toxicity to other organisms**

### KemFoamX 2500

Ref. 2.3/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

EC10/bacteria of activated sludge/DEV-L2: > 2,000 mg/l  
The inhibition of the degradation activity of activated sludge is not anticipated when introduced in appropriate low concentrations.

#### 12.2 Persistence and degradability

Biological degradability:  
CO2 Evolution Test/OECD Test Guideline 301B/28 d: < 60 %

Not readily biodegradable. Due to the low solubility in water, the product is easily separated through mechanical route e.g. in waste water treatment plant.

Chemical Oxygen Demand (COD): 2,150 mg/g

#### 12.3 Bioaccumulative potential

No data is available on the product itself.  
Partition coefficient: n-octanol/water: Not applicable

#### 12.4. Mobility in soil

##### Mobility

Vapour pressure: < 0.0015 hPa ( 20 °C)  
Water solubility: practically insoluble  
Surface tension: not determined

#### 12.5. Results of PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### 12.6 Other adverse effects

Adsorbed organic bound halogens (AOX):  
Product does not contain any organic halogens.  
None known.  
Additional ecological information: Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

##### Product

Must be disposed of in accordance with local and national regulations.



Ref. 2.3/GB/EN

**KemFoamX 2500**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

### SECTION 14: TRANSPORT INFORMATION

#### 14.1 UN number

##### Land transport

Not classified as dangerous in the meaning of transport regulations.

##### Sea transport

Not classified as dangerous in the meaning of transport regulations.

##### Air transport

Not classified as dangerous in the meaning of transport regulations.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not classified as marine pollutant

**14.8 Special precautions for user**  
None known.

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : None known.

: None

#### Notification status

- :
- : All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on the Australian Inventory of Chemical Substances (AICS).
- : All components of this product are included in the Canada

### KemFoamX 2500

Ref. 2.3/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 02.02.2018

Previous date: 02.03.2015

Print Date:21.11.2018

- Domestic Substance List (DSL) or are not required to be listed on the Canada Domestic Substance List (DSL).
- : All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.
  - : All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese (ENCS) inventory.
  - : All components of this product are included in the Korean (ECL) inventory or are not required to be listed on the Korean (ECL) inventory.
  - : All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine (PICCS) inventory.
  - : All components of this product are included in the United States TSCA Chemical Inventory or are not required to be listed on the United States TSCA Chemical Inventory.
  - : All components of this product are included in the New Zealand inventory (NZIoC) or are not required to be listed on the New Zealand inventory(NZIoC).
  - : All components of this product are included in the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.

### 15.2 Chemical safety assessment

## SECTION 16: OTHER INFORMATION

### Training advice

Read the safety data sheet before using the product.

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### Sources of key data used to compile the Safety Data Sheet

Regulations, databases, literature, own tests.

### Additions, Deletions, Revisions

Relevant changes have been marked with vertical lines.

Revision Date 24/05/13  
 Revision 9  
 Supersedes date March 2011



## SAFETY DATA SHEET

### Sodium hydroxide solution, 5 - 51%

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

<b>Product name</b>	Sodium hydroxide solution, 5 - 51%
<b>REACH Registration number</b>	01-2119457892-27
<b>CAS-No.</b>	1310-73-2
<b>EC No.</b>	215-185-5

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	Treatment of drinking water, has received approval by the European Committee for Standardisation. Treatment of waste water. Raw material. Neutralising agent. pH regulating agent Manufacture of substances. Absorbant for gases and liquids Manufacturing soaps Washing and cleaning products
------------------------	---

##### 1.3. Details of the supplier of the safety data sheet

<b>Supplier</b>	Industrial Chemicals Limited Hogg Lane Grays Essex RM17 5DU United Kingdom T:+44 (0)1375 389000 F:+44 (0)1375 389110 sds@icgl.co.uk
-----------------	---

##### 1.4. Emergency telephone number

+44 (0)1865 407333 (24-hour)

#### SECTION 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

###### **Classification (EC 1272/2008)**

Physical and Chemical Hazards	Met. Corr. 1 - H290
Human health	Skin Corr. 1A - H314; Eye Dam. 1 - H318
Environment	Not classified.

###### **Classification (1999/45/EEC)**

C;R35.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

###### **Human health**

Corrosive. Prolonged contact causes serious eye and tissue damage.

###### **Environment**

Substantial amounts of the product may lead to a local change in acidity in small water systems which may have adverse effects on aquatic organisms.

##### 2.2. Label elements

<b>EC No.</b>	215-185-5
<b>Contains</b>	SODIUM HYDROXIDE
<b>Label In Accordance With (EC) No. 1272/2008</b>	

## Sodium hydroxide solution, 5 - 51%



**Signal Word** Danger

### Hazard Statements

H290 May be corrosive to metals.  
 H314 Causes severe skin burns and eye damage.  
 H318 Causes serious eye damage.

### Supplementary Precautionary Statements

P234 Keep only in original container.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P260 Do not breathe vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P321 Specific treatment (see medical advice on this label).  
 P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.  
 P310 Wash contaminated clothing before reuse.  
 P363 Absorb spillage to prevent material damage.  
 P390 Store locked up.  
 P405 Store in corrosive resistant/... container with a resistant inner liner.  
 P501 Dispose of contents/container to ...

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

<b>SODIUM HYDROXIDE</b>		<b>40-60%</b>
<b>CAS-No.:</b> 1310-73-2	<b>EC No.:</b> 215-185-5	
Classification (EC 1272/2008) Met. Corr. 1 - H290 Skin Corr. 1A - H314 Eye Dam. 1 - H318	Classification (67/548/EEC) C;R35	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**REACH Registration number** 01-2119457892-27  
**CAS-No.** 1310-73-2  
**EC No.** 215-185-5

#### Composition Comments

Mercury (Rayon) grade contains a low level of mercury, typically less than 0.1 ppm. Diaphragm grade contains up to 1.3% sodium chloride, which increases the density of the solution.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General information

Get medical attention immediately! CAUTION! First aid personnel must be aware of own risk during rescue!

# Sodium hydroxide solution, 5 - 51%

## **Inhalation**

Rinse nose, mouth, and throat with running water.

## **Ingestion**

Do not induce vomiting. If confined to the mouth, rinse mouth thoroughly and ensure water is not swallowed. If swallowed, drink plenty of water. If substance has been swallowed, give water or milk to drink immediately. Get medical attention immediately!

## **Skin contact**

Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention immediately!

## **Eye contact**

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes.

## **4.2. Most important symptoms and effects, both acute and delayed**

### **General information**

Strong corrosive action on all body tissue, causing burns and frequently deep ulceration, and ultimately scarring.

### **Inhalation**

Mist/droplets are irritating to the respiratory tract, and will cause a burning sensation in the throat, coughing, and breathing difficulties. Pulmonary oedema (excessive liquid in the lungs) can occur after inhalation of higher amounts.

### **Ingestion**

Causes severe damage to gastrointestinal tract. Can cause perforation and scarring.

### **Skin contact**

Burning pain and severe corrosive skin damage. Causes burns, deep ulceration, and scarring. Frequent contact with lower concentrations may cause eczema.

### **Eye contact**

Corrosive to eyes. May cause severe corneal damage, reduced vision, or even blindness.

## **4.3. Indication of any immediate medical attention and special treatment needed**

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

#### **Extinguishing media**

The product is non-combustible. Use fire-extinguishing media appropriate for surrounding materials.

### **5.2. Special hazards arising from the substance or mixture**

#### **Hazardous combustion products**

Contact with some metals can liberate flammable hydrogen gas.

### **5.3. Advice for firefighters**

#### **Protective equipment for fire-fighters**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

### **6.2. Environmental precautions**

Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material. Release to rivers will cause a strong increase in pH, resulting in death to aquatic organisms. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### **6.3. Methods and material for containment and cleaning up**

Small Spillages: Neutralise with weak acid and wash away with water. Alternately, drench spill with water and wash away. Large Spillages: Isolate and pump into a tank. Dispose of via a licensed hazardous waste contractor. Keep people and animals away from contaminated areas.

### **6.4. Reference to other sections**

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

## Sodium hydroxide solution, 5 - 51%

Following prolonged storage in metal tanks, a black sludge will collect at the bottom of the tank. This will contain iron, sodium carbonate, and when Mercury (Rayon) grade is stored, mercury. Test the atmosphere in the tank for oxygen and mercury vapour before entering. Appropriate care must be taken when removing and handling this sludge, including control of atmospheric levels. Handle with care as an alkaline material. Take care when diluting with water (heat generation). Avoid contact with skin and eyes. Avoid generation of sprays or mists.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in vessels of mild steel. Keep away from acids and other chemicals that react with this product. Build-up of white metal carbonate crystals may occur if tank is open to air.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
SODIUM HYDROXIDE	WEL				2 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

#### Protective equipment



#### Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

#### Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

#### Hand protection

Wear protective gloves. Rubber or plastic.

#### Eye protection

Goggles/face shield are recommended.

#### Other Protection

Chemical suit and boots if handling large quantities.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Colourless liquid.
Odour	Odourless.
Solubility	Miscible with water
Initial boiling point and boiling range (°C)	142
Melting point (°C)	For 50% Membrane grade 12
Relative density	For 50% Membrane grade 1525 20
Viscosity	For 50% Membrane grade 78 cP 20
	For 50% Membrane grade

### 9.2. Other information

## Sodium hydroxide solution, 5 - 51%

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

#### 10.2. Chemical stability

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Vessels should not be open to air; substance absorbs water and carbon dioxide. In extreme cases, the carbonate can form white floating crystals. Do not store adjacent to incompatible materials, such as acids and amphoteric metals eg aluminium, magnesium, zinc, tin and bronze - may release hydrogen gas.

#### 10.5. Incompatible materials

##### Materials To Avoid

Reaction with ammonium compounds releases ammonia. May react violently with acrolein, acrylnitrile, and allyl alcohol. Heating with trichloroethylene will form explosive mixtures of dichloroacetylene. Some plastics, leather and textiles are destroyed on contact. Mixture with water or acids will release large quantities of heat.

#### 10.6. Hazardous decomposition products

Thermally stable to boiling point; does not decompose. Precipitation of metal hydroxide crystals can occur below 12C.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

##### General information

Strong corrosive action on all body tissue, causing burns and frequently deep ulceration, with ultimate scarring.

##### Inhalation

Mist/droplets are corrosive to the respiratory tract, and will cause a burning sensation in the throat, coughing and breathing difficulties. Pulmonary oedema (excessive liquid in lungs) can occur after inhalation of higher amounts.

##### Ingestion

If ingested will cause severe damage to gastrointestinal tract. Can cause perforation and scarring.

##### Skin contact

Corrosive to body tissue, causing burns, deep ulceration, and scarring. Frequent contact with lower concentrations may cause eczema.

##### Eye contact

Vapour or spray may cause eye damage, impaired sight or blindness.

### SECTION 12: ECOLOGICAL INFORMATION

##### Ecotoxicity

Spillage will cause localised damage to animals and plants on the ground. Do not allow release into controlled waters; resulting high pH will affect aquatic life forms. If allowed to enter drains will damage effluent treatment organisms. Neutralisation and dilution will greatly reduce these effects. Product is chemically degradable into sodium carbonate.

#### 12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l                      45.4

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

## Sodium hydroxide solution, 5 - 51%

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Neutralise with dilute acid and wash away with large amounts of water. Confirm disposal procedures with environmental engineer and local regulations.

### SECTION 14: TRANSPORT INFORMATION

#### 14.1. UN number

UN No. (ADR/RID/ADN) 1824

#### 14.2. UN proper shipping name

Proper Shipping Name SODIUM HYDROXIDE SOLUTION

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class Class 8: Corrosive substances.

#### Transport Labels



#### 14.4. Packing group

ADR/RID/ADN Packing group II

IMDG Packing group II

ICAO Packing group II

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

Hazard No. (ADR) 80

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

### SECTION 16: OTHER INFORMATION

#### General information

The material must only be loaded and unloaded from tankers by trained personnel, such as those with a Hazchem certificate.

Sodium hydroxide solution is used as a chemical for the treatment of drinking water, as approved by the European Committee for Standardisation under EN 896:2005.

This data sheet was prepared in accordance with EC 1907/2006 concerning REACH.

Issued By D.Kelly  
 Revision Date 24/05/13  
 Revision 9



## Sodium hydroxide solution, 5 - 51%

**Supersedes date**

March 2011

**Risk Phrases In Full**

R35 Causes severe burns.

**Hazard Statements In Full**

H318 Causes serious eye damage.

H314 Causes severe skin burns and eye damage.

H290 May be corrosive to metals.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006****Sodium hypochlorite 10-15% (All grades)**Version 7.1  
Revision Date 2011/01/20Print Date 2011/01/20  
MSDS code: MSHY100**1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : Sodium hypochlorite 10-15% (All grades)  
Substance name : sodium hypochlorite, solution 10-15 % Cl active  
Index-No. : 017-011-00-1  
CAS-No. : 7681-52-9  
EC-No. : 231-668-3

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the Substance/Mixture : At this time we do not yet have information on identified uses. They will be included in this safety data sheet when available.

Recommended restrictions on use : At that time we do not yet have information on use restrictions. They will be included in this safety data sheet when available.

**1.3. Details of the supplier of the safety data sheet**

Company : Brenntag UK & Ireland  
Albion House, Rawdon Park  
GB LS19 7XX Leeds Yeadon  
Telephone : 0113 3879 200  
Telefax : 0113 3879 280  
E-mail address : msds@brenntag.co.uk

**1.4. Emergency telephone number**

Emergency telephone number : Emergency only telephone number (open 24 hours):  
01865 407333 (N.C.E.C. Culham)

**2. Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008****REGULATION (EC) No 1272/2008**

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

Hazard class	Hazard category	Target Organs	Hazard statements
Skin corrosion	Category 1B		H314
Acute aquatic toxicity	Category 1		H400

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Classification according to EU Directives 67/548/EEC or 1999/45/EC**

Directive 67/548/EEC or 1999/45/EC	
Hazard symbol / Category of danger	Risk phrases
Corrosive (C)	R34
	R31
Dangerous for the environment (N)	R50

For the full text of the R-phrases mentioned in this Section, see Section 16.

**Most important adverse effects**

- Human Health : See section 11 for toxicological information.  
No further information available.
- Physical and chemical hazards : See section 9 for physicochemical information., No further information available.
- Potential environmental effects : See section 12 for environmental information.

**2.2. Label elements****Labelling according to Regulation (EC) No 1272/2008**

Hazard symbols : 

Signal word : Danger

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

Hazard statements	: H314 H400	Causes severe skin burns and eye damage. Very toxic to aquatic life.
Precautionary statements		
Prevention	: P260 P273 P280	Do not breathe vapours. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response	: P301 + P330 + P331 P303 + P361 + P353 P305 + P351 + P338	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Additional Labelling:**

EUH031 Contact with acids liberates toxic gas.

**Hazardous components which must be listed on the label:**

|| • sodium hypochlorite, solution

**2.3. Other hazards**

No other information is available.

**3. Composition/information on ingredients****3.1. Substances**

|| Chemical nature : sodium hypochlorite  
Aqueous solution

Chemical Name	Identification Number	Amount [%]
---------------	-----------------------	------------

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**Version 7.1  
Revision Date 2011/01/20Print Date 2011/01/20  
MSDS code: MSHY100

<b>sodium hypochlorite, solution</b>	Index-No.	: 017-011-00-1	
	CAS-No.	: 7681-52-9	
	EC-No.	: 231-668-3	>= 10 - <= 15
	Registration number	: 01-2119488154-34-xxxx	
<b>sodium hydroxide</b>	Index-No.	: 011-002-00-6	
	CAS-No.	: 1310-73-2	
	EC-No.	: 215-185-5	>= 0 - < 5

**4. First aid measures****4.1 Description of first aid measures**

<b>General advice</b>	: Take off all contaminated clothing immediately.
<b>If inhaled</b>	: In case of accident by inhalation: remove casualty to fresh air and keep at rest. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
<b>In case of skin contact</b>	: Wash off immediately with soap and plenty of water. If irritation appears or if the contamination is important, seek medical advice.
<b>In case of eye contact</b>	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist immediately. Go to an ophthalmic hospital if possible.
<b>If swallowed</b>	: Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. If swallowed, do not induce vomiting - seek medical advice. If a person vomits when lying on his back, place him in the recovery position.

**4.2 Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	: Inhalation may provoke the following symptoms: Cough Headache Lung oedema
<b>Effects</b>	: Risk of serious damage to the lungs (by aspiration).

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment : Treat symptomatically.  
Later control for pneumonia and lung oedema.

**5. Fire-fighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. The product itself does not burn.

Unsuitable extinguishing media : Exempt

**5.2. Special hazards arising from the substance or mixture**

Specific hazards during fire fighting : Fire may cause evolution of:  
Chlorine  
Hydrogen chloride gas  
chlorine oxides

**5.3. Advice for firefighters**

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Wear appropriate body protection (full protective suit)

Further information : Cool closed containers exposed to fire with water spray. Heating will cause a pressure rise - with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

**6. Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment. Wear respiratory

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100



protection. Keep people away from and upwind of spill/leak. Provide adequate ventilation. Danger of slipping if spilled. Avoid contact with skin and eyes. Do not breathe vapour.

**6.2 Environmental precautions**



Environmental precautions : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities. If material reaches soil inform authorities responsible for such cases.

**6.3 Methods and materials for containment and cleaning up**



Methods and materials for containment and cleaning up : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Keep in suitable, closed containers for disposal.



Further information : Treat recovered material as described in the section "Disposal considerations".

**6.4 Reference to other sections**

For personal protection see section 8.

**7. Handling and storage**

**7.1 Precautions for safe handling**



Advice on safe handling : Do not keep the container sealed. Handle and open container with care. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist. Use respirator with appropriate filter if vapours or aerosol are released. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity.

Hygiene measures : Keep away from food, drink and animal feedingstuffs. Smoking,

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100



eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday. Take off all contaminated clothing immediately. Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist.

**7.2 Conditions for safe storage, including any incompatibilities**



Requirements for storage areas and containers : Keep in an area equipped with alkali resistant flooring. Keep only in the original container. Store in a receptacle equipped with a vent.



Advice on protection against fire and explosion : The product is not flammable. Normal measures for preventive fire protection.



Further information on storage conditions : Keep in a well-ventilated place. Protect against light. Store in cool place. Do not keep the container sealed.



Advice on common storage : Keep away from food, drink and animal feedingstuffs. Do not store together with acids and ammonium salts.



German storage class : 8B: Non-combustible substances, corrosive

**7.3 Specific end uses**

Specific use(s) : No information available.

**8. Exposure controls/personal protection**

**8.1. Control parameters**

Component: sodium hydroxide

CAS-No.  
1310-73-2



## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

**Other OELs**

Regulatory Basis : UK. EH40 Workplace Exposure Limits (WELs)  
Regulatory List : EH40 WEL  
Value type : Short Term Exposure Limit (STEL):  
Value : 2 mg/m<sup>3</sup>

**Component: chlorine**

**CAS-No.**  
**7782-50-5**

**Other OELs**

Regulatory Basis : EU. Indicative Exposure and Directives relating to the protection of risks related to work exposure to chemical, physical, and biological agents.  
Regulatory List : EU ELV  
Value type : Short Term Exposure Limit (STEL):  
Value : 0.5 ppm  
Value : 1.5 mg/m<sup>3</sup>  
Remarks : Indicative

Regulatory Basis : UK. EH40 Workplace Exposure Limits (WELs)  
Regulatory List : EH40 WEL  
Value type : Short Term Exposure Limit (STEL):  
Value : 0.5 ppm  
Value : 1.5 mg/m<sup>3</sup>

**8.2. Exposure controls****Engineering measures**

Refer to protective measures listed in sections 7 and 8.

**Personal protective equipment***Respiratory protection*

Advice : Use respirator with appropriate filter if vapours or aerosol are released.  
Recommended Filter type:  
Combination filter:B-P2  
Combination filter:B-P3

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**Version 7.1  
Revision Date 2011/01/20Print Date 2011/01/20  
MSDS code: MSHY100**II***Hand protection*

**II** Advice : The glove material has to be impermeable and resistant to the product / the substance / the preparation.  
Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
Protective gloves should be replaced at first signs of wear.

**II** Material : butyl-rubber

**II** Gloves : 8 h

**II** Glove thickness : 0.5 mm

**II** Material : Polyvinylchloride

**II** Gloves : 8 h

**II** Glove thickness : 0.5 mm

**II** Material : polychloroprene

**II** Gloves : 8 h

**II** Glove thickness : 0.5 mm

*Eye protection*

**II** Advice : Tightly fitting safety goggles

*Skin and body protection*

**II** Advice : alkali resistant protective clothing

**Environmental exposure controls**

**II** General advice : Do not flush into surface water or sanitary sewer system.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100



If material reaches soil inform authorities responsible for such cases.

**9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Form	: liquid
Colour	: yellowish green
Odour	: slight chlorine
Odour Threshold	: Currently we do not have any Information from our supplier about this.
pH	: > 11
Melting point/range	: -17 °C
Boiling point/boiling range	: 110 °C
Flash point	: not applicable
Evaporation rate	: Currently we do not have any Information from our supplier about this.
Flammability (solid, gas)	: does not ignite
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Vapour pressure	: Currently we do not have any Information from our supplier about this.
Relative vapour density	: > 1.0 (Air = 1.0)
Density	: 1.2 - 1.3 g/cm <sup>3</sup>
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: Currently we do not have any Information from our supplier about this.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

Ignition temperature	: not applicable
Thermal decomposition	: Currently we do not have any Information from our supplier about this.
Viscosity, dynamic	: 3.45 mPa.s 20 °C (Aqueous, solution, 15 %)
Explosive properties	: Not explosive
Oxidizing properties	: Currently we do not have any Information from our supplier about this.

**9.2 Other information**

No further information available.

**10. Stability and reactivity**

**10.1. Reactivity**

Advice : This product is a very reactive substance that can react with many inorganic and organic compounds.

**10.2. Chemical stability**

Advice : Decomposes on heating.  
Decomposes on exposure to light.

**10.3. Possibility of hazardous reactions**

**H** Hazardous reactions : May develop chlorine if mixed with acidic solutions.

**10.4. Conditions to avoid**

Conditions to avoid : Heat.

**10.5. Incompatible materials**

**I** Materials to avoid : Acids  
ammonium compounds  
Acetic anhydride  
Organic materials  
Hydrogen peroxide

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100



metal salts  
Copper  
Nickel  
Iron

**10.6. Hazardous decomposition products**

Hazardous decomposition products : Hydrogen chloride gas  
Chlorine  
chlorine oxides

**11. Toxicological information****11.1. Information on toxicological effects**

Product: sodium hypochlorite, solution 10-15 % Cl active	CAS-No. 7681-52-9
<b>Acute toxicity</b>	
<b>Oral</b>	
Value type	: LD50
Value	: 2,900 - 3,400 mg/kg
Species	: mouse
Remarks	: Cause serious burns with severe pains, vomiting, pains in the stomach, possibly chock and damaged kidneys. The burn may occur even if only small amounts have been swallowed.
<b>Inhalation</b>	
Value type	: LC50
Value	: > 10.5 mg/l
Species	: rat
<b>Dermal</b>	
Value type	: LD50

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

Value : > 2,000 mg/kg  
Species : rabbit

**Irritation****Skin**

Species : rabbit  
Result : Severe skin irritation  
Method : OECD Test Guideline 404

Species : human.  
Result : corrosive effects

**Eyes**

Species : rabbit  
Result : corrosive effects  
Remarks : Risk of serious damage to eyes.

**Sensitisation**

Species : guinea pig  
Result : not sensitizing

**Further information**

Other relevant toxicity information : All numerical values for acute toxicity are calculated on the pure substances.  
If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.  
Handle in accordance with good industrial hygiene and safety practice.

**12. Ecological information****12.1. Toxicity**

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

**Product: sodium hypochlorite, solution 10-15 %  
Cl active**

**CAS-No.  
7681-52-9**

**Acute toxicity****Fish**

Species	: Pimephales promelas
Exposure Time	: 96 h
Value type	: LC50
Value	: 0.22 - 0.62 mg/l

**Toxicity to daphnia and other aquatic invertebrates.**

Species	: Daphnia magna
Exposure time	: 96 h
Value type	: EC50
Value	: 2.1 mg/l

**algae**

Species	: Desmodesmus subspicatus (green algae)
Exposure time	: 24 h
Value type	: EC50
Value	: 28 mg/l

**12.2. Persistence and degradability**

**Product: sodium hypochlorite, solution 10-15 %  
Cl active**

**CAS-No.  
7681-52-9**

**Persistence and degradability****Persistence**

Remarks : no data available

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

### Sodium hypochlorite 10-15% (All grades)

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

#### Biodegradability

Remarks : The methods for determining the biological degradability are not applicable to inorganic substances.

#### 12.3. Bioaccumulative potential

<b>Product:</b> sodium hypochlorite, solution 10-15 % Cl active	<b>CAS-No.</b> 7681-52-9
--	-----------------------------

#### Bioaccumulation

Remarks : Bioaccumulation is not expected.

#### 12.4. Mobility in soil

<b>Product:</b> sodium hypochlorite, solution 10-15 % Cl active	<b>CAS-No.</b> 7681-52-9
--	-----------------------------

#### Mobility

Remarks : The product is mobile in water environment.

#### 12.5. Results of PBT and vPvB assessment

<b>Product:</b> sodium hypochlorite, solution 10-15 % Cl active	<b>CAS-No.</b> 7681-52-9
--	-----------------------------

#### Results of PBT and vPvB assessment

Remarks : No information available.

#### 12.6. Other adverse effects



## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

**Product: sodium hypochlorite, solution 10-15 %  
Cl active**

**CAS-No.  
7681-52-9**

**Additional ecological information**

Remarks : All numerical values for ecotoxicity effects are calculated on the pure substances.  
Do not flush into surface water or sanitary sewer system.

**13. Disposal considerations****13.1. Waste treatment methods**

Product : Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services.

Contaminated packaging : Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

European Waste Catalogue Number : No waste code according to the European Waste Catalogue can be assigned for this product, as the intended use dictates the assignment. The waste code is established in consultation with the regional waste disposer.

**14. Transport information****14.1. UN number**

1791

**14.2. UN proper shipping name**

ADR : HYPOCHLORITE SOLUTION  
RID : HYPOCHLORITE SOLUTION  
IMDG : HYPOCHLORITE SOLUTION

**14.3. Transport hazard class(es)**

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

ADR-Class (Labels; Classification Code; Hazard identification No; Tunnel restriction code)	:	8  8; C9; 80; (E)
RID-Class (Labels; Classification Code; Hazard identification No)	:	8  8; C9; 80
IMDG-Class (Labels; EmS)	:	8  8; F-A, S-B

**14.4. Packaging group**

ADR	:	III
RID	:	III
IMDG	:	III

**14.5. Environmental hazards**

Labeling according to 5.2.1.8 ADR	:	Fish and tree
Labeling according to 5.2.1.8 RID	:	Fish and tree
Labeling according to 5.2.1.6.3 IMDG	:	Fish and tree
Classification as environmentally hazardous according to 2.9.3 IMDG	:	yes

**14.6. Special precautions for user**

Note : not applicable

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

IMDG : Not applicable.

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006***Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
MSDS code: MSHY100

**15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2. Chemical Safety Assessment**

Currently we do not have any Information from our supplier about this.

**16. Other information****Full text of R-phrases referred to under sections 2 and 3.**

R31 Contact with acids liberates toxic gas.  
R34 Causes burns.  
R50 Very toxic to aquatic organisms.

**Full text of H-Statements referred to under sections 2 and 3.**

H314 Causes severe skin burns and eye damage.  
H400 Very toxic to aquatic life.

**Further information**

Other information : Restricted to professional users. Attention - Avoid exposure - obtain special instructions before use.  
The information provided in this Safety Data Sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship.  
The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Sodium hypochlorite 10-15% (All grades)**

Version 7.1  
Revision Date 2011/01/20

Print Date 2011/01/20  
**MSDS code: MSHY100**

|| Indicates updated section.



Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Expert Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

## 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

### 1.1 Product identifier

Substance name: Hydrated lime, Calcium dihydroxide  
Synonyms: Slaked lime, Air slaked lime, Building lime, Fat lime, Chemical lime, Finishing lime, Mason's lime, Calcium dihydroxide, Calcium hydroxide, Calcium hydrate, Lime, Lime water  
Chemical name and formula: Calcium dihydroxide -  $\text{Ca}(\text{OH})_2$   
Trade name: Ultralime® Hydrated Lime  
CAS: 1305-62-0  
EINECS: 215-137-3  
Molecular Weight: 74.09 g/mol  
REACH Registration number: 01-2119475151-45-0019

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Please check the identified uses in table 1 of the Appendix of this SDS.

Uses advise against: There are no uses advised against.

### 1.3 Details of the supplier of the safety data sheet

Name: Singleton Birch Limited  
Address: Melton Ross Quarries, Barnetby,  
North Lincolnshire DN38 6AE  
Phone N°: +44(0)1652 686000  
Fax N°: +44(0)1652 686081  
E-mail of competent person responsible for SDS in the MS or in the EU: kb@singletonbirch.co.uk; jt@singletonbirch.co.uk

### 1.4 Emergency telephone number

European Emergency N°: 112  
National centre for Prevention & Treatment of Intoxications N°: National Chemicals Emergency Centre (NCEC) +44 (0) 870 190 6621  
Emergency telephone at the company: +44(0)1652 686000 (24 hours)  
Available outside office hours: Yes

## 2 HAZARDS IDENTIFICATION

### 2.1 Classification of the substance

#### 2.1.1 Classification according to Regulation (EC) 1272/2008

STOT Single Exp. 3, Route of exposure: Inhalation

Skin Irritation 2

Eye Damage 1



**2.1.2 Classification according to Directive 67/548/EEC**

Xi – irritant

**2.2 Label elements**

**2.2.1 Labelling according to Regulation (EC) 1272/2008**

**Signal word:**

Danger

**Hazard pictogram:**



**Hazard statements:**

H315:

Causes skin irritation

H318:

Causes serious eye damage

H335:

May cause respiratory irritation

**Precautionary statements:**

P102:

Keep out of reach of children

P280:

Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P310:

IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTRE or doctor/physician

P302+P352:

IF ON SKIN: Wash with plenty of water

P261:

Avoid breathing dust/spray

P304+P340:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P501:

Dispose of contents/container in accordance with local, regional, national and international regulation – use a registered hazardous waste carrier/licence holder, and/or contact the manufacturer

**2.2.2 Labelling according to Directive 67/548/EEC**

**Indication of danger:**

Xi irritant

**Hazard pictogram:**



**Risk phrases:**

R37: Irritating to respiratory system

R38: Irritating to skin

R41: Risk of serious damage to eyes



Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Export Capabilities



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

**Safety phrases:**

- S2: Keep out of the reach of children
- S25: Avoid contact with eyes
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- S37: Wear suitable gloves
- S39: Wear eye/face protection

### 2.3 Other hazards

The substance does not meet the criteria for PBT or vPvB substance.  
No other hazards identified.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

#### Main constituent

Name: Calcium dihydroxide  
CAS: 1305-62-0  
EINECS: 215-137-3

#### Impurities

No impurities relevant for classification and labelling.

## 4 FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice

No known delayed effects. Consult a physician for all exposures except for minor instances.

#### Following inhalation

Move source of dust or move person to fresh air. Obtain medical attention immediately.

#### Following skin contact

Carefully and gently brush the contaminated body surfaces in order to remove all traces of product. Wash affected area immediately with plenty of water. Remove contaminated clothing. If necessary seek medical advice.

#### Following eye contact

Rinse eyes immediately with plenty of water and seek medical advice.

#### Following ingestion

Clean mouth with water and drink afterwards plenty of water. Do **NOT** induce vomiting. Obtain medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

Calcium dihydroxide is not acutely toxic via the oral, dermal, or inhalation route. The substance is classified as irritating to skin and the respiratory tract, and entails a risk of serious damage to the eye. There is no concern for adverse systemic effects because local effects (pH-effect) are the major health hazard.





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Expanded Features



Change

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Follow the advises given in section 4.1

### **5 FIREFIGHTING MEASURES**

#### **5.1 Extinguishing media**

##### **5.1.1 Suitable extinguishing media**

Suitable extinguishing media: The product is not combustible. Use a dry powder, foam or CO<sub>2</sub> fire extinguisher to extinguish the surrounding fire. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

##### **5.1.2 Unsuitable extinguishing media**

Do not use water

#### **5.2 Special hazards arising from the substance or mixture**

None

#### **5.3 Advice for fire fighters**

Avoid generation of dust. Use breathing apparatus. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **6 ACCIDENTAL RELEASE MEASURES**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

##### **6.1.1 For non-emergency personnel**

Ensure adequate ventilation.

Keep dust levels to a minimum.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8)

##### **6.1.2 For emergency responders**

Keep dust levels to a minimum.

Ensure adequate ventilation.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8)

#### **6.2 Environmental precautions**

Contain the spillage. Keep the material dry if possible. Cover area if possible to avoid unnecessary dust hazard. Avoid uncontrolled spills to watercourses and drains (pH increase). Any large spillage into watercourses must be alerted to the Environment Agency or other regulatory body.







Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Expanded Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

### 6.3 Methods and material for containment and cleaning up

In all cases avoid dust formation.

Keep the material dry if possible.

Pick up the product mechanically in a dry way.

Use vacuum suction unit, or shovel into bags.

### 6.4 Reference to other sections

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13 and the Annex of this safety data sheet.

## 7 HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### 7.1.1 Protective measures

Avoid contact with skin and eyes. Wear protective equipment (refer to section 8 of this safety data sheet). Do not wear contact lenses when handling this product. It is also advisable to have individual pocket eyewash. Keep dust levels to a minimum. Minimize dust generation. Enclose dust sources, use exhaust ventilation (dust collector at handling points). Handling systems should preferably be enclosed. When handling bags usual precautions should be paid to the risks outlined in the Council Directive 90/269/EEC.

#### 7.1.2 Advice on general occupational hygiene

Avoid inhalation or ingestion and contact with skin and eyes. General occupational hygiene measures are required to ensure safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no drinking, eating and smoking at the workplace. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home.

### 7.2 Conditions for safe storage, including any incompatibilities

The substance should be stored under dry conditions. Any contact with air and moisture should be avoided. Bulk storage should be in purpose – designed silos. Keep away from acids, significant quantities of paper, straw, and nitro compounds. Keep out of reach of children. Do not use aluminium for transport or storage if there is a risk of contact with water.

### 7.3 Specific end use(s)

Please check the identified uses in table 1 of the Appendix of this SDS.

For more information please see the relevant exposure scenario, available via your supplier/given in the Appendix, and check section 2.1: Control of worker exposure.





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Expanded Features



Change

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

SCOEL recommendation (SCOEL/SUM/137 February 2008; see Section 16.6):

**Workplace Exposure Limit (WEL), 8 h TWA:** 5 mg/m<sup>3</sup>

**Occupational Exposure Limit (OEL), 8h TWA:** 1 mg/m<sup>3</sup> respirable dust of calcium oxide

**Short-term exposure limit (STEL), 15 min:** 4 mg/m<sup>3</sup> respirable dust of calcium oxide

**PNEC aqua** = 490 µg/l

**PNEC soil/groundwater** = 1080 mg/l

### 8.2 Exposure controls

To control potential exposures, generation of dust should be avoided. Further, appropriate protective equipment is recommended. Eye protection equipment (e.g. goggles or visors) must be worn, unless potential contact with the eye can be excluded by the nature and type of application (i.e. closed process). Additionally, face protection, protective clothing and safety shoes are required to be worn as appropriate.

Please check the relevant exposure scenario, given in the Appendix/available via your supplier.

#### 8.2.1 Appropriate engineering controls

If user operations generate dust, use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne dust levels below recommended exposure limits.

#### 8.2.2 Individual protection measures, such as personal protective equipment

##### 8.2.2.1 Eye/face protection

Do not wear contact lenses. For powders, tight fitting goggles with side shields, or wide vision full goggles. It is also advisable to have individual pocket eyewash.

##### 8.2.2.2 Skin protection

Since calcium dihydroxide is classified as irritating to skin, dermal exposure has to be minimised as far as technically feasible. The use of protective gloves (nitrile), protective standard working clothes fully covering skin, full length trousers, long sleeved overalls, with close fittings at openings and shoes resistant to caustics and avoiding dust penetration are required to be worn.

##### 8.2.2.3 Respiratory protection

Local ventilation to keep levels below established threshold values is recommended. A suitable particle filter mask is recommended, depending on the expected exposure levels - please check the relevant exposure scenario, given in the Appendix/available via your supplier.

##### 8.2.2.4 Thermal hazards

The substance does not represent a thermal hazard, thus special consideration is not required.





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Expanded Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

### 8.2.3 Environmental exposure controls

All ventilation systems should be filtered before discharge to atmosphere.

Avoid releasing to the environment.

Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority responsible for environmental protection or other regulatory body.

For detailed explanations of the risk management measures that adequately control exposure of the environment to the substance please check the relevant exposure scenario, available via your supplier.

For further detailed information, please check the Appendix of this SDS.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance:	White or off white (beige) fine powder
Odour:	odourless
Odour threshold:	not applicable
pH:	12.4 (saturated solution at 20 °C)
Melting point:	> 450 °C (study result, EU A.1 method)
Boiling point:	not applicable (solid with a melting point > 450 °C)
Flash point:	not applicable (solid with a melting point > 450 °C)
Evaporation rate:	not applicable (solid with a melting point > 450 °C)
Flammability:	non flammable (study result, EU A.10 method)
Explosive limits:	non explosive (void of any chemical structures commonly associated with explosive properties)
Vapour pressure:	not applicable (solid with a melting point > 450 °C)
Vapour density:	not applicable
Relative density:	2.24 (study result, EU A.3 method)
Solubility in water:	1844.9 mg/L (study results, EU A.6 method)
Partition coefficient:	not applicable (inorganic substance)
Auto ignition temperature:	no relative self-ignition temperature below 400 °C (study result, EU A.16 method)
Decomposition temperature:	When heated above 580°C, calcium dihydroxide decomposes to produce calcium oxide (CaO) and water (H <sub>2</sub> O)
Viscosity:	not applicable (solid with a melting point > 450 °C)
Oxidising properties:	no oxidising properties (Based on the chemical structure, the substance does not contain a surplus of oxygen or any structural groups known to be correlated with a tendency to react exothermally with combustible material)

### 9.2 Other information

Not available





Your complimentary use period has ended.  
Thank you for using PDF Complete.



Click Here to upgrade to  
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

## 10 STABILITY AND REACTIVITY

### 10.1 Reactivity

In aqueous media  $\text{Ca}(\text{OH})_2$  dissociates resulting in the formation of calcium cations and hydroxyl anions (when below the limit of water solubility).

### 10.2 Chemical stability

Under normal conditions of use and storage, calcium dihydroxide is stable.

### 10.3 Possibility of hazardous reactions

Calcium dihydroxide reacts exothermically with acids. When heated above 580 °C, calcium dihydroxide decomposes to produce calcium oxide (CaO) and water (H<sub>2</sub>O):  $\text{Ca}(\text{OH})_2 \rightarrow \text{CaO} + \text{H}_2\text{O}$ . Calcium oxide reacts with water and generates heat. This may cause risk to flammable material.

### 10.4 Conditions to avoid

Minimise exposure to air and moisture to avoid degradation.

### 10.5 Incompatible materials

Calcium dihydroxide reacts exothermically with acids to form salts. Calcium dihydroxide reacts with aluminium and brass in the presence of moisture leading to the production of hydrogen.



### 10.6 Hazardous decomposition products

None

Further information: calcium dihydroxide reacts with carbon dioxide to form calcium carbonate, which is a common material in nature.

## 11 TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Calcium dihydroxide is classified as irritating to skin and the respiratory tract and it entails a risk of serious damage to the eye. The occupational exposure limit for the prevention of local sensory irritation and decrease of lung function parameters as critical effects is OEL (8 h) = 1 mg/m<sup>3</sup> respirable dust.

Toxicity endpoints	Outcome of the effects assessment
Absorption	The primary health effect of calcium dihydroxide is local irritation due to a pH shift. Therefore, absorption is not a relevant parameter for the effects assessment.





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.



Click Here to upgrade to  
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

Toxicity endpoints	Outcome of the effects assessment
<b>Acute toxicity</b>	<p>Calcium dihydroxide is not acutely toxic.</p> <p>Oral LD<sub>50</sub> &gt; 2000 mg/kg bw (OECD 425, rat)</p> <p>Dermal LD<sub>50</sub> &gt; 2500 mg/kg bw (calcium dihydroxide, OECD 402, rabbit)</p> <p>Inhalation no data available</p> <p>Classification for acute toxicity is not warranted.</p> <p>For irritating effects to the respiratory tract see below.</p>
<b>Irritation / corrosion</b>	<p>Eye Irritation: Calcium dihydroxide entails a risk of serious damage to the eye (eye irritation studies (<i>in vivo</i>, rabbit).</p> <p>Skin Irritation: Calcium dihydroxide is irritating to skin (<i>in vivo</i>, rabbit).</p> <p>Respiratory Irritation: From human data it is concluded that Ca(OH)<sub>2</sub> is irritating to the respiratory tract.</p> <p>Based on experimental results, calcium dihydroxide requires classification as irritating to skin [R38, irritating to skin; Skin Irrit 2 (H315 - Causes skin irritation)] and as severely irritating to the eye [R41, Risk of serious damage to eye; Eye Damage 1 (H318 - Causes serious eye damage)].</p> <p>As summarised and evaluated in the SCOEL recommendation (Anonymous, 2008), based on human data calcium dihydroxide is classified as irritating to the respiratory system [R37, Irritating to respiratory system; STOT SE 3 (H335 - May cause respiratory irritation)].</p>
<b>Sensitisation</b>	<p>No data available. Calcium dihydroxide is considered not to be a skin sensitiser, based on the nature of the effect (pH shift) and the essential requirement of calcium for human nutrition.</p> <p>Classification for sensitisation is not warranted.</p>
<b>Repeated dose toxicity</b>	<p>Toxicity of calcium via the oral route is addressed by upper intake levels (UL) for adults determined by the Scientific Committee on Food (SCF), being UL = 2500 mg/d, corresponding to 36 mg/kg bw/d (70 kg person) for calcium.</p> <p>Toxicity of Ca(OH)<sub>2</sub> via the dermal route is not considered as relevant in view of the anticipated insignificant absorption through skin and due to local irritation as the primary health effect (pH shift).</p> <p>Toxicity of Ca(OH)<sub>2</sub> via inhalation (local effect, irritation of mucous membranes) is addressed by an 8-h TWA determined by the Scientific Committee on Occupational Exposure Limits (SCOEL) of 1 mg/m<sup>3</sup> respirable dust (see Section 8.1).</p> <p>Therefore, classification of Ca(OH)<sub>2</sub> for toxicity upon prolonged exposure is not required.</p>
<b>Mutagenicity</b>	<p>Bacterial reverse mutation assay (Ames test, OECD 471): Negative</p> <p>In view of the omnipresence and essentiality of Ca and of the physiological non-relevance of any pH shift induced by lime in aqueous media, lime is obviously void of any genotoxic potential.</p> <p>Classification for genotoxicity is not warranted.</p>





Your complimentary use period has ended.  
Thank you for using PDF Complete.



Click Here to upgrade to Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

Toxicity endpoints	Outcome of the effects assessment
<b>Carcinogenicity</b>	Calcium (administered as Ca-lactate) is not carcinogenic (experimental result, rat). The pH effect of calcium oxide does not give rise to a carcinogenic risk. Human epidemiological data support lack of any carcinogenic potential of calcium oxide. Classification for carcinogenicity is not warranted.
<b>Toxicity for reproduction</b>	Calcium (administered as Ca-carbonate) is not toxic to reproduction (experimental result, mouse). The pH effect does not give rise to a reproductive risk. Human epidemiological data support lack of any potential for reproductive toxicity of calcium dihydroxide. Both in animal studies and human clinical studies on various calcium salts no reproductive or developmental effects were detected. Also see the Scientific Committee on Food (Section 16.6). Thus, calcium dihydroxide is not toxic for reproduction and/or development. Classification for reproductive toxicity according to regulation (EC) 1272/2008 is not required.

## 12 ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### 12.1.1 Acute/Prolonged toxicity to fish

LC<sub>50</sub> (96h) for freshwater fish: 50.6 mg/l

LC<sub>50</sub> (96h) for marine water fish: 457 mg/l

#### 12.1.2 Acute/Prolonged toxicity to aquatic invertebrates

EC<sub>50</sub> (48h) for freshwater invertebrates: 49.1 mg/l

LC<sub>50</sub> (96h) for marine water invertebrates: 158 mg/l

#### 12.1.3 Acute/Prolonged toxicity to aquatic plants

EC<sub>50</sub> (72h) for freshwater algae: 184.57 mg/l

NOEC (72h) for freshwater algae: 48 mg/l

#### 12.1.4 Toxicity to micro-organisms e.g. bacteria

At high concentration, through the rise of temperature and pH, calcium dihydroxide is used for disinfection of sewage sludges

#### 12.1.5 Chronic toxicity to aquatic organisms

NOEC (14d) for marine water invertebrates: 32 mg/l





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.



Click Here to upgrade to  
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

#### **12.1.6 Toxicity to soil dwelling organisms**

EC<sub>10</sub>/LC<sub>10</sub> or NOEC for soil macro organisms: 2000 mg/kg soil dw

EC<sub>10</sub>/LC<sub>10</sub> or NOEC for soil micro organisms: 12000 mg/kg soil dw

#### **12.1.7 Toxicity to terrestrial plants**

NOEC (21d) for terrestrial plants: 1080 mg/kg

#### **12.1.8 General effect**

Acute pH-effect. Although this product is useful to correct water acidity, an excess of more than 1 g/l may be harmful to aquatic life. pH-value of > 12 will rapidly decrease as result of dilution and carbonation

#### **12.2 Persistence and degradability**

Not relevant for inorganic substances

#### **12.3 Bioaccumulative potential**

Not relevant for inorganic substances

#### **12.4 Mobility in soil**

Calcium dihydroxide which is sparingly soluble, and present a low mobility in most soils

#### **12.5 Results of PBT and vPvB assessment**

Not relevant for inorganic substances

#### **12.6 Other adverse effects**

No other adverse effects are identified

### **13 DISPOSAL CONSIDERATIONS**

#### **13.1 Waste treatment methods**

Disposal of calcium dihydroxide should be in accordance with local and national legislation.

Processing, use or contamination of this product may change the waste management options.

Dispose of container and unused contents in accordance with applicable member state and local requirements.

The used packing is only meant for packing this product; it should not be reused for other purposes.

After usage, empty the packing completely.

### **14 TRANSPORT INFORMATION**

Calcium dihydroxide is not classified as hazardous for transport (ADR (Road), RID (Rail), IMDG / GGVSea (Sea)).

#### **14.1 UN-Number**

Not regulated





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

[Click Here to upgrade to  
Unlimited Pages and Export Capabilities](#)



Change

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

#### 14.2 UN proper shipping name

Not regulated

#### 14.3 Transport hazard class

Not regulated

#### 14.4 Packing group

Not regulated

#### 14.5 Environmental hazards

None

#### 14.6 Special precautions for user

Avoid any release of dust during transportation, by using air-tight tanks

#### 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not regulated.

### 15 REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance

Authorisations: Not required

Restrictions on use: None

Other EU regulations: Calcium dihydroxide is not a SEVESO substance, not an ozone depleting substance and not a persistent organic pollutant.

National regulations: Water endangering class 1 (Germany)

#### 15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.

### 16 OTHER INFORMATION

Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.

#### 16.1 Hazard Statements

H315: Causes skin irritation

H318: Causes serious eye damage

H335: May cause respiratory irritation

#### 16.2 Precautionary Statements

P102: Keep out of reach of children

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+P351: IF IN EYES: Rinse cautiously with water for several minutes

P310: Immediately call a POISON CENTRE or doctor/physician







Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

Click Here to upgrade to  
Unlimited Pages and Expanded Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

- P302+P352: **IF ON SKIN:** Wash with plenty of soap and water  
P261: Avoid breathing dust/fume/gas/mist/vapours/spray  
P304+P340: **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P501: Dispose of contents/container in accordance with local/regional/national/international regulation - use a registered hazardous waste carrier/licence holder, and/or contact the manufacturer

### 16.3 Risk Phrases

- R37: Irritating to respiratory system  
R38: Irritating to skin  
R41: Risk of serious damage to eyes

### 16.4 Safety Phrases

- S2: Keep out of the reach of children  
S25: Avoid contact with eyes  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
S37: Wear suitable gloves  
S39: Wear eye/face protection

### 16.5 Abbreviations

- EC<sub>50</sub>: median effective concentration  
LC<sub>50</sub>: median lethal concentration  
LD<sub>50</sub>: median lethal dose  
NOEC: no observable effect concentration  
WEL: workplace exposure limit  
OEL: occupational exposure limit  
PBT: persistent, bioaccumulative, toxic chemical  
PNEC: predicted no-effect concentration  
STEL: short-term exposure limit  
TWA: time weighted average  
vPvB: very persistent, very bioaccumulative chemical  
EULA: European Lime Association

### 16.6 Key literature references

- Anonymous, 2006: Tolerable upper intake levels for vitamins and minerals Scientific Committee on Food, European Food Safety Authority, ISBN: 92-9199-014-0 [SCF document]  
Anonymous, 2008: Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL) for calcium oxide (CaO) and calcium dihydroxide (Ca(OH)<sub>2</sub>), European Commission, DG Employment, Social Affairs and Equal Opportunities, SCOEL/SUM/137 February 2008





Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.

[Click Here to upgrade to  
Unlimited Pages and Expanded Features](#)



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

### **16.7 Revision**

SDS revised in accordance with EULA SDS format

#### Disclaimer

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.

#### **ANNEX**

Addition of exposure Scenarios as applicable - Please see Appendix SD30A SDS - Hydrate Lime Range.

