

Schedule 1- Environmental Permitting Regulations		Limits of specified activity and waste types
Section 5.4 A1 (b) (iii) non-hazardous waste installation – treatment of slags and ashes.	R4: Recycling/reclamation of metals and metal compounds R5: Recycling/reclamation of other inorganic materials.	From receipt of permitted waste through to treatment and recovery of by-products (incinerator bottom ash aggregate). Treatment of incinerator bottom ash consisting of crushing, separation and screening shall be carried out in an enclosed building and on an impermeable surface with a sealed drainage.
Section 5.4 A1 (a) ii Disposal of non-hazardous waste with a capacity exceeding 50 tonnes per day involving physico-chemical treatment	D9 - Physico-chemical treatment not specified elsewhere which results in final compounds or mixtures which are discarded by means of any of the operations numbered D1 to D12	Disposal of non-hazardous waste with a capacity exceeding 50 tonnes per day involving physico-chemical treatment Treatment of leachate on site prior to discharge to local foul water system under a trade effluent consent.
Waste Operation		
Blending of IBA and materials to produce an aggregate.	R5: Recycling/reclamation of other inorganic materials. R3 Recycling/reclamation of organic substances which are not used as solvents (including composting and other biological transformation processes)	IBAA, Blended with non waste aggregate imported to site to be used under RPS 247 Using unbound incinerator bottom ash aggregate (IBAA) in construction activities.
Raw material storage	Storage of raw materials.	Non waste aggregate stored on site in discreet piles in main storage areas.
Directly Associated Activity		
Storage and handling of waste	R13: Storage of waste pending the operations numbered R5 (excluding temporary storage, pending collection, on the site where it is produced).	From receipt of waste to dispatch off-site for recovery. Temporary storage of waste. Storage of incinerator bottom ash on impermeable surface with sealed drainage system prior to treatment in enclosed building and externally. Storage of processed incinerator bottom ash aggregate on impermeable surface with sealed drainage system. Storage of ferrous/non-ferrous metals arising from the treatment of incinerator bottom ash, on impermeable surface with sealed drainage system.

Storage of residual waste	<p>R13: Storage of waste pending the operations numbered R5 (excluding temporary storage, pending collection, on the site where it is produced).</p> <p>D15: Storage pending any of the operations numbered D1 to D14 (excluding temporary storage, pending collection, on the site where it is produced).</p>	Residual waste to be removed from site.
Fuel Storage/chemical Storage	<p>Diesel</p> <p>Hydraulic Oils</p> <p>Lubricating Oils</p>	<p>5000 litres</p> <p>10 drums up to 205 litre per drum.</p> <p>10 drums 205 litre per drum.</p>
Raw material storage	Storage of raw materials.	Non waste aggregate stored on site in discreet piles in main storage areas.