



TD_0229_L64_1519_50_250_EN_SI_V2

Voltage / Frequency
 Heating water temperature (in / out)
 NOx emissions (dry, 5 % O₂)
 Mixture cooler 1st stage water temperature (in)
 Mixture cooler 2nd stage water temperature (in)
 Exhaust gas temperature
 Catalytic converter
 Special equipment
 Elevation above sea level
 Combustion air temperature
 Relative combustion air humidity
 Standard specifications and regulations

GG12V4000D1M

V / Hz	11000	/	50
°C		70 / 85.0	
mg/m ³ i.N.		< 250	
°C		45	
°C		422	
		not included	
m / mbar	100	/	1000
°C		25	
%		30	
		VDE-AR-N 4110	

Energy balance	%	100	75	50
Electrical Power ²⁾³⁾	kW	1519	1140	760
Energy input ⁴⁾⁵⁾	kW	3560	2731	1924
Thermal output total ⁶⁾	kW	1608	1262	940
Thermal output engine (block, lube oil, 1st stage mixture cooler) ⁶⁾	kW	828	603	417
Thermal output mixture cooler 1st stage ⁶⁾	kW			
Thermal output mixture cooler 2nd stage ⁶⁾	kW	116	79	50
Exhaust heat optional (120 °C) ⁶⁾	kW	(780)	(659)	(523)
Engine power ISO 3046-1 ²⁾	kW	1560	1172	786
Generator efficiency at power factor = 1	%	97.4	97.3	96.7
Electrical efficiency ⁴⁾	%	42.7	41.7	39.5
Total efficiency	%	87.8	88.0	88.4
Power consumption ⁷⁾	kW			

Combustion air / Exhaust gas

Combustion air volume flow ¹⁾	m ³ i.N./h	6100	4578	3076
Combustion air mass flow	kg/h	7880	5914	3974
Exhaust gas volume flow, wet ¹⁾	m ³ i.N./h	6404	4811	3241
Exhaust gas volume flow, dry ¹⁾	m ³ i.N./h	5748	4306	2885
Exhaust gas mass flow, wet	kg/h	8148	6118	4118
Exhaust temperature after turbocharger	°C	422	458	516

Reference fuel⁸⁾

Natural gas		CH ₄ >95 Vol.%
Sewage gas		not applicable
Biogas		not applicable
Landfill gas		not applicable

Fuel requirements⁹⁾

Nominal rated methane number	MN	70
Range of heating value: design / operation range without power derating	kWh/m ³ i.N.	10.0 - 10.1 / 8.0 - 11.0

Exhaust gas emissions⁵⁾⁸⁾ Compliance with emissions standards only for ≥ 760 kWel

NOx, stated as NO ₂ (dry, 5 % O ₂)	mg/m ³ i.N.	< 250
CO (dry, 5 % O ₂)	mg/m ³ i.N.	< 1300
HCHO (dry, 5 % O ₂)	mg/m ³ i.N.	< 130
VOC (dry, 5 % O ₂)	mg/m ³ i.N.	

Otto-gas engine, lean burn operation with turbocharging

Number of cylinders / configuration	12	/	v
Engine type		12V4000L64FNER EU	
Engine speed	1/min	1500	
Bore	mm	170.0	
Stroke	mm	210.0	
Displacement	dm ³	57.2	
Mean piston speed	m/s	10.5	
Compression ratio		12.5	
BMEP at nominal engine speed min-1	bar	21.8	
Lube oil consumption ¹⁰⁾	dm ³ /h	0.27	
Exhaust back pressure min. - max. after module	mbar - mbar	30 - 60	

Generator

Rating power (temperature rise class F) ¹¹⁾	kVA	2314
Insulation class / temperature rise class		H / F
Winding pitch		5/6
Protection		IP 23
Max. allowable p.f. inductive (overexcited) / capacitive (underexcited) ¹²⁾		0.8 / 0.95
Voltage tolerance / frequency tolerance	%	± 10 / ± 5

Engine cooling water system

Coolant temperature (in / out), design	°C	78 / 92
Coolant flow rate, constant ¹³⁾¹⁴⁾	m ³ /h	54.79
Pressure drop, design ¹⁴⁾	Cv value ¹³⁾¹⁵⁾	bar / m ³ /h
Max. operation pressure (coolant before engine)	bar	6

Exhaust gas heat exchanger (EGHE)

Exhaust gas temperature (out)	°C	
Coolant temperature (in / out), design	°C	
Coolant volumetric flow, constant ¹³⁾¹⁴⁾	m ³ /h	
Pressure drop, design ¹⁴⁾	Cv value ¹³⁾¹⁵⁾	kPa / m ³ /h
Min. coolant flow rate / min. operation gauge pressure	m ³ /h / bar	/
Max. operation pressure (coolant water)	bar	



TD_0229_L64_1519_50_250_EN_SI_V2

GG12V4000D1M

Mixture cooler 1st stage, external				
Coolant temperature (in / out), design	°C			
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h			
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h	/	
Min. coolant flow rate / min. operation gauge pressure	m³/h / bar		/	
Max. operation pressure before mixture cooler	bar			
Mixture cooling 2nd stage, external				
Coolant temperature (in / out), design	°C	45 / 48.4		
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h	32.0		
Permissible pressure drop outside the heat recovery system	Cv value ^{13) 15)}	bar / m³/h	0.8	/
Max. operation pressure before mixture cooler	bar			6
Heating circuit interface				
Engine coolant temperature (in / out), design	°C	92 / 78		
Heating water temperature (in / out), design	°C	70 / 85.0		
Heating water flow rate, design ^{14) 16)}	m³/h	48.2		
Pressure drop, design ¹⁴⁾	Cv value ^{15) 16)}	bar / m³/h	0.3	/ 93.9
Max. operation gauge pressure (heating water)	bar			
Room ventilation				
Genset ventilation heat ¹⁷⁾	kW		90	
Inlet air temperature: (min./design/max.)	°C		20 / 25 / 30	
Min. engine room temperature ¹⁸⁾	°C		15	
Max. temperature difference ventilation air (in / out)	°C		20	
Min. supply air volume flow rate (combustion + ventilation) ¹⁹⁾	m³ i.N./h		19000	
Gearbox	%	100	75	50
Efficiency	%			
Starter battery				
Nominal voltage / power / capacity required	V / kW / Ah		24 / 9 / --	
Filling quantities				
First filling quantity lube oil / refilling amount lube oil	dm³		320 / 280	
Coolant in engine circuit	dm³		290	
Coolant in mixture cooler	dm³		85	
Heating water for plate heat exchanger ²⁰⁾	dm³		30	
Lube oil for gearbox	dm³			
Gas regulation line				
Nominal size / gas pressure min. - max. (at gas regulation line inlet)	DN / mbar - mbar	80	/	144 - 250
Engine sound level²¹⁾ (1 meter distance, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level				
Frequency	Hz	63	125	250 500
Sound pressure level	dB	83.3	87.4	88.6 91.3
Frequency	Hz	1000	2000	4000 8000
Sound pressure level	dB	90.1	87.3	92.9 103.9
Linear total sound pressure level	Lin dB	104.9		
A-weighted total sound pressure level	dB(A)	104.5		
A-weighted total sound power level	dB(A)	123.9		
Undampened exhaust noise²¹⁾ (1 meter distance to outlet within 90°, free field) +3 dB(A) for total A-weighted level tolerance; + 5 dB for single octave level				
Frequency	Hz	63	125	250 500
Sound pressure level	dB	118.5	120.3	110.8 102.2
Frequency	Hz	1000	2000	4000 8000
Sound pressure level	dB	92.9	92.3	92.1 82.5
Linear total sound pressure level	Lin dB	122.8		
A-weighted total sound pressure level	dB(A)	108.4		
A-weighted total sound power level	dB(A)	121.3		
Dimensions (aggregate / heat recovery system)				
Length	mm		~ 4800	
Width	mm		~ 1900	
Height	mm		~ 2300	
Gross weight (dry weight)	kg		~ 15000 (~ 14000) / ~ 0.0 (~ 0.0)	
Power derating				
Maximum ambient air dew point on site	°C		19.0	
Combustion air temperature			specific to the project	
Mixture cooler coolant temperature (in)			specific to the project	
Methane number			specific to the project	

Boundary conditions and consumables
 Systems and consumables have to conform to the following actual company standards: A001072

- 1) Normal cubic meter at 1013 mbar and T = 273 K
- 2) Prime power operation will be designed specific to the project
- 3) Generator gross power at nominal voltage, power factor = 1 and nominal frequency
- 4) According to ISO 3046 (+ 5 % tolerance), using reference fuel used at nominal voltage, power factor = 1 and nominal frequency
- 5) Emission values during grid parallel operation
- 6) Thermal output at layout temperature; tolerance +/- 8 %
- 7) Power consumption of all electrical consumers which are mounted at the module / genset
- 8) Deviations from the layout parameters respectively the reference fuel can have influence on the obtained efficiency and exhaust emissions
- 9) Functional capability
- 10) Reference value at nominal load (without amount of oil exchange) oil density set to 860g/l
- 11) Generator (at nominal power) max. 1000 m height of location and max. 40 °C intake air temperature; else power derating
- 12) Max. allowable cos phi at nominal power (view of producer)
- 13) Stated values for cooling fluid composition 65% water and 35% glycol, adaption for use of other cooling fluid composition necessary
 The system design must consider the tolerance.
- 14) Pressure loss at reference flow rate
- 15) The Cv value declares the volumetric flow in m³/h at a pressure drop of 1 bar. Min. and max. flow rate limits are defined.
- 16) Stated values for pure water, adaption for other cooling fluid composition necessary
- 17) Only generator- and surface losses
- 18) Frost-free conditions must be guaranteed
- 19) Amount of ventilation air must be adapted to the gas safety concept
- 20) Assemblies including pipe work
- 21) All sound pressure levels at nominal load, according to ISO 8528-10 and ISO 6798.
- 22) Max. admissible cos phi depending on voltage in accordance with the requirements of the valid 'Standard specifications and regulations'