









Specification Date Sheet | Model: EBD5000-EU(W)



ENVIROBULKA Deluxe 22300 litres

A static bunded fuel storage tank built to a standard of BS799 Part 5. The Envirobulka is fully bunded (steel tank enclosed in steel outer bund) to comply with PPG2 (Pollution Prevention Guidelines) requirements for fuel storage.

-  Robust steel in steel construction ensures security, whilst 110% weatherproof bund complies with environmental requirements for fuel storage.
-  Pump, nozzle, hoses and generator feed & return connections are all housed within secure, lockable bund compartment. Feed and return hoses can be fed through openings enabling generator to be run whilst connections are kept secure in compartment – helps to prevent theft and vandalism
-  Manhole providing quick and easy access to inner tank for maintenance and inspection
-  Fitted with lifting eyes and forklift pockets for ease of handling and relocation of inner tank.
-  X2 heavy duty mesh shelves for other equipment storage.
-  All outlets are top mounted above fuel level helping prevent weepage of fuel. Suction pipe to help remove any fluid in the bund.
-  Optional anti-siphon valve available for extra environmental protection. Part No. V090
-  Bund sensor to detect fluid in bund.

SPECIFICATION

Standard Tank Fittings : Offset 2" hard connect fill point complete with locking valve : 2" tank and bund vent : tank and bund sight glass: tank and bund contents gauge : 1" and 1.5" pump feed : 2 x ½" generator feed and return ports : Spare Ports – 4 x 1.5" Socket : 1 x ½" bund and tank socket.

Capacity Litres:	22300	Bund Material:	S235
Capacity Gallons:	5000	Weight Empty (Approx kg):	4831
Dimensions Length (mm):	5400	Weight Full (Approx kg):	22671
Dimensions Width (mm):	2300	Tank Material:	S235- 5mm outer, 5mm inner
Dimensions Height (mm):	2560		

Notes

Revision Date: 20/02/2015

