



Monitoring and Reporting of Emissions (Air, Water, Sewer, and Waste)

The installation carries out the following emissions monitoring:

- Annual flue gas analysis on the gas fired boiler stacks
- Monthly utility provider sampling of the trade effluent (sewer)

Records of all waste and by-product removals from site are also retained. The table below demonstrates compliance with BAT requirements for the Red Meat Processing (Cattle, Sheep and Pigs) Sector:

Ref	Requirement	Comment
1.	Identify process variables that may affect the environment and monitor as appropriate.	Compliant
2.	<ul style="list-style-type: none">• Salt	n/a
3.	<ul style="list-style-type: none">• Refrigerant – Quantity of refrigerant and oil added to or removed from the system	Each charge or drain
4.	<ul style="list-style-type: none">• Detergent and disinfectant – You should monitor the consumption of detergent and disinfectant to check that correct dilutions and application procedures are being followed	Weekly
5.	<ul style="list-style-type: none">• Bleeding times – Blood has a very high BOD. By monitoring bleeding times, you can check that the maximum quantity of blood has been collected for sale or separate disposal and will not overload the effluent treatment plant	Regular monitoring checks, however, line speed and thus bleeding time is fixed. Sheep – line speed 130/h with 35 in trough hence 16 minutes draining time



ABP Kingswinford

6.	<ul style="list-style-type: none">• Efficiency of blood collection – At single species abattoirs, the efficiency of the blood collection procedures can be assessed by monitoring the quantity of blood collected per animal processed	Quarterly calculation done on numbers of kill in throughput
7.	<ul style="list-style-type: none">• Energy consumption – Energy consumption across the abattoir and at individual points of use in accordance with the energy plan	Electricity – continuous Gas – by utility bill
8.	<ul style="list-style-type: none">• Water use – Fresh water use across the activities and at individual points of use should be monitored as part of the water efficiency plan	Meter reading
9.	<ul style="list-style-type: none">• Levels in the blood collection tank – The risk of accidents can be reduced by installing a high-level alarm on the blood tank linked to an automatic cut-off for the blood trough pumps	Maintenance team to ensure high-level alarm is operational.
10.	<ul style="list-style-type: none">• Effluent quality	By routine utility provider sampling. Consent No, 009330V



Emission Monitoring

Schedule 3 Table S3.1 lists the point sources of emissions to air for ABP Kingswinford.

Table S3.1 Point source emissions to air – emission limits and monitoring requirements						
Emission point ref. & location	Source	Parameter	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
A1 [Point A1 on site plan in Schedule 7]	Gas boiler stack	Products of combustion	No limit set	--	--	--
A2 [Point A2 on site plan in schedule 7]	Pressure washer boiler stacks	Products of combustion	No limit set	--	--	--
A3 [Point A3 on site plan in schedule 7]						
A4 [Point A4 on site plan in schedule 7]						
A5 [Point A5 on site plan in schedule 7]						
A6 [Point A6 on site plan in schedule 7]						
A7 [Point A7 on site plan in schedule 7]						
A8 [Point A8 on site plan in schedule 7]						
A9 [Point A9 on site plan in schedule 7]						
A10 [Point A10 on site plan in schedule 7]	Gas boiler stack	Products of combustion	No limit set	--	--	--
A11 [Point A11 on site plan in schedule 7]	Gas boiler stack	Products of combustion	No limit set	--	--	--

Schedule 3 Table S3.1 of the facility's permit states that there are no specific controls imposed upon emissions to air at the facility. ABP Kingswinford proposes to remove 7 Point Source Emissions to air (A2, A3, A4, A5, A6, & A7) and install a 450kwh hot water boiler (LAT 52.510966, LONG -2.1605904) to lowering the sites emissions to air while also ensuring energy efficiency for the processing of meat processing.



Schedule 3 table S3.2 lists point source to sewer for ABP Kingswinford as:

Table S3.2 Point source emissions to sewer, effluent treatment plant or other transfers off-site- emission limits and monitoring requirements						
Emission point ref. & location	Source	Parameter	Limit (incl. Unit)	Reference period	Monitoring frequency	Monitoring standard or method
E1 (Point E1 on site plan in Schedule 7; emission to Severn Trent Water Sewage Treatment Works)	Process effluent discharge from the production factory and ancillary production activities	No parameters Set	No limit set	--	--	--
E2 ^{Note 1} (Point E2 on site plan in Schedule 7; emission to Severn Trent Water Sewage Treatment Works)	Process effluent discharge from the production factory and ancillary production activities	No parameters Set	No limit set	--	--	--

Note 1: Trade effluent consent for the discharge of process effluent from Building B is in the process of being obtained from Severn Trent water.

ABP Kingswinford is permitted to process emission to sewer at E1 and E2. Both these emission points are sent to Severn Trent Water Limited. The company proposes to change the emission point labels from E1 and E2 to S1 and S2.

S1 – Consent No. 009330V

S2 – Consent No. 009331V

Schedule 3, Table S3.2 of the facility's permit states that there are no specific controls imposed upon emission to sewer at the facility. ABP Kingswinford complies with the high standards outlined in Appendix I of the specific Consent for both locations.