

**Waste Acceptance Criteria Testing BS EN 12457
Part 3, 2 Stage Process
Issue 1**



Sample Details		Test Values	
Sample Number	12339470	Mass of Raw Test Portion (MW) kg	0.177
Job Number	771818	Mass of Dried Test Portion (MD) kg	0.175
Sample ID	TP1	Moisture Content Ratio (MC) %	0.99
Site	Chadwich Lane Quarry	Dry Matter Content Ratio (DR) %	99.02
Job Description	WAC Analysis	Moisture Content @ 105c	0.98
Date Sampled		Leachant Volume (1) (L2) Litre	0.348
Date Received	15/04/2011	Leachant Volume (2) (L8) Litre	1.4
Particle Size (<4mm)	<=95%	Eluate Volume (1) (VE1) Litre	0.272
Method of size reduction	jaw crusher	Eluate Volume (2) (VE2) Litre	1.402
Non-crushable matter	N/A		

Eluate Analysis	Concentration in Eluate		Amount Leached		Landfill Waste Acceptance Criteria		
	2:1	8:1	2:1	10:1	BS EN 12457-3 Limit Values (mg/Kg) at L:S 10:1		
Liquid:Waste Ratio							
Sample Number	12339471	12339472			Inert Waste	Stable Non- Reactive hazardous waste in non- hazardous	Hazardous Waste
pH	9.13	9.46					
Temperature °C	22	21					
Conductivity uS/cm	1083	166.3					
	mg/l	mg/l	mg/Kg	mg/Kg			
Arsenic as As	<0.0050	<0.0050	<0.010	<0.050	0.5	2	25
Barium as Ba	0.036	<0.010	0.072	0.056	20	100	300
Cadmium as Cd	<0.00010	<0.00010	<0.00020	<0.0010	0.04	1	5
Chromium as Cr	0.012	0.004	0.024	0.052	0.5	10	70
Copper as Cu	0.029	0.013	0.058	0.15	2	50	100
Mercury as Hg	<0.00050	<0.00050	<0.0010	<0.0050	0.01	0.2	2
Molybdenum as Mo	0.049	0.01	0.098	0.16	0.5	10	30
Nickel as Ni	<0.020	<0.020	<0.040	<0.20	0.4	10	40
Lead as Pb	0.016	<0.010	0.032	0.025	0.5	10	50
Antimony as Sb	0.015	0.01	0.03	0.11	0.06	0.7	5
Selenium as Se	<0.010	<0.010	<0.020	<0.100	0.1	0.5	7
Zinc as Zn	<0.025	<0.025	<0.050	<0.25	4	50	200
Chloride as Cl	47.6	2	95	91	800	15000	25000
Fluoride as F	1.1	0.6	2.2	6.8	10	150	500
Sulphate as SO4	441	33.5	880	970	1000	20000	50000
Total Dissolved Solids (TDS)	847	110	1700	2200	4000	60000	100000
Phenol Index	<0.15	<0.15	<0.30	<1.5	1		
Dissolved Organic Carbon (DOC)	13.5	4.84	27	62	500	800	1000
Waste Analysis							
Total Organic Carbon w/w %				2.2	3%	5%	6%
Loss on Ignition %							10%
BTEX mg/Kg					6		
PCBs (7 congeners) mg/Kg				0.015	1		
Mineral Oil (C10-C40) mg/Kg				<50	500		
PAHs mg/Kg				84	100		
pH				8.4		>6	
Acid Neutralisation Capacity (pH4) mol/Kg						To be evaluated	To be evaluated
Acid Neutralisation Capacity (pH7) mol/Kg						To be evaluated	To be evaluated

Disclaimer: Eluate concentrations below the detection limit are assumed to be negligible when calculating mg/kg values. The limits quoted for Waste Acceptance are derived from the Landfill (England and Wales) Regulations 2002 (as amended) and are provided as guidance only. STS does not take responsibility for any errors or omissions with regard to these limits.

Additional Eluate Analysis	Concentration in Eluate		Amount Leached	
	2:1	8:1	2:1	10:1
	mg/l	mg/l	mg/Kg	mg/Kg

Additional Waste Analysis	Units	Result
Conductivity @ 20 C	uS/cm	880
Benzene	mg/kg	<0.10
Toluene	mg/kg	<0.10
Ethylbenzene	mg/kg	<0.10
m&p-Xylene	mg/kg	<0.20
o-Xylene	mg/kg	<0.10

Sample Comments	
12339470	stainless steel sieve
12339470	
12339471	
12339472	

Severn Trent Services Analytical Services is a trading name of Severn Trent Laboratories Limited.
This communication has been sent to you by Severn Trent Laboratories Limited. Registered in England and Wales. Registered No.2148934.
Registered Office: Severn Trent Centre, 2 St. John's Street, Coventry, CV1 2LZ.