

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
1/86

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Ammonia, anhydrous

Trade name: Ammonia Heat Treatment Grade N3.8, Ammonia Micrographic Grade N3.8, Ammonia Premium Grade N3.8, Ammonia Refrigerant Grade N3.8

Additional identification

Chemical name: ammonia, anhydrous
Chemical formula: NH₃
INDEX No. 007-001-00-5
CAS-No. 7664-41-7
EC No. 231-635-3
REACH Registration No. 01-2119488876-14

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use. Casting operations Explosives manufacture & use Freezing, chilling, and packaging of foodstuffs. Manufacturing of fertilisers and nitric acid. Production of plastics. Refrigerant. Use for electronic component manufacture. Use of gas to manufacture pharmaceutical products. Using gas alone or in mixtures for the calibration of analysis equipment. Using gas as feedstock in chemical processes. Using gas for metal treatment. Washing of textiles or metal parts Water treatment. Use in laboratories Formulation of mixtures with gas in pressure receptacles.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier
BOC
Priestley Road, Worsley
M28 2UT Manchester

Telephone: 0800 111 333

E-mail: ReachSDS@boc.com

1.4 Emergency telephone number: 0800 111 333

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas

Category 2

H221: Flammable gas.

SAFETY DATA SHEET

Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
2/86

Gases under pressure

Liquefied gas

H280: Contains gas under pressure; may explode if heated.

Health Hazards

Acute toxicity (Inhalation - gas)

Category 3

H331: Toxic if inhaled.

Skin corrosion

Category 1B

H314: Causes severe skin burns and eye damage.

Serious eye damage

Category 1

H318: Causes serious eye damage.

Environmental Hazards

Acute hazards to the aquatic environment

Category 1

H400: Very toxic to aquatic life.

Chronic hazards to the aquatic environment

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label Elements

Contains:

ammonia, anhydrous



Signal Word:

Danger

Hazard Statement(s):

H221: Flammable gas.
H280: Contains gas under pressure; may explode if heated.
H331: Toxic if inhaled.
H314: Causes severe skin burns and eye damage.
H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements

General

None.

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260: Do not breathe gas/vapours.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

SAFETY DATA SHEET
Ammonia, anhydrousIssue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
3/86

Response: P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.
P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well-ventilated place.
P405: Store locked up.

Disposal None.

Supplemental information

EUH071: Corrosive to the respiratory tract.

2.3 Other hazards Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Chemical name ammonia, anhydrous
INDEX No.: 007-001-00-5
CAS-No.: 7664-41-7
EC No.: 231-635-3
REACH Registration No.: 01-2119488876-14
Purity: 100%
The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.

Trade name: Ammonia Heat Treatment Grade N3.8, Ammonia Micrographic Grade N3.8, Ammonia Premium Grade N3.8, Ammonia Refrigerant Grade N3.8

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
ammonia, anhydrous	NH ₃	100%	7664-41-7	01-2119488876-14	Aquatic Toxicity (Acute): 1	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
4/86

SECTION 4: First Aid Measures

General: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting Measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapours or divert vapour cloud drift. Water Spray or Fog Dry powder. Foam.

Unsuitable extinguishing media: Carbon dioxide. Do not use water jet, as this may cause corrosive liquid to splash.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
5/86

Hazardous Combustion Products: If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Nitrogen monoxide ; nitrogen dioxide

5.3 Advice for firefighters

Special fire fighting procedures:

In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dyke for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for firefighters:

Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dyke for water control.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections:

Refer to sections 8 and 13.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
6/86

SECTION 7: Handling and Storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

**7.2 Conditions for safe storage,
including any incompatibilities:**

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Keep away from food, drink and animal feeding stuffs. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
7/86

7.3 Specific end use(s): None.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
ammonia, anhydrous	TWA	25 ppm 18 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
	STEL	35 ppm 25 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
	TWA	20 ppm 14 mg/m ³	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	STEL	50 ppm 36 mg/m ³	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)

DNEL-Values

Critical component	Type	Value	Remarks
ammonia, anhydrous	Workers - Inhalation, Local, short-term	36 mg/m ³	respiratory tract irritation
	Workers - Inhalation, Local, long-term	14 mg/m ³	respiratory tract irritation
	Workers - Inhalation, Systemic, short-term	47.6 mg/m ³	Repeated dose toxicity
	Workers - Inhalation, Systemic, long-term	47.6 mg/m ³	Repeated dose toxicity
	Workers - Dermal, Systemic, long-term	6.8 mg/kg bw/day	Repeated dose toxicity
	Workers - Eyes, Local effect		High hazard (no threshold derived)
	Workers - Dermal, Systemic, short-term	6.8 mg/kg bw/day	Repeated dose toxicity

PNEC-Values

Critical component	Type	Value	Remarks
ammonia, anhydrous	Aquatic (freshwater)	0.001 mg/l	-
ammonia, anhydrous	Aquatic (marine water)	0.001 mg/l	-

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
8/86

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of flammable gases or vapours may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Use only permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges. Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment

General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Eye/face protection:

Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection:

Guideline: EN 388 Protective gloves against mechanical risks.
Additional Information: Wear working gloves while handling containers
Material: Chloroprene rubber.
Break-through time: 30 min
Glove thickness: 0.5 mm
Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Material: Butyl rubber.
Break-through time: 480 min
Glove thickness: 0.7 mm
Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
9/86

Body protection:	Wear fire resistant or flame retardant clothing. Keep suitable chemically resistant protective clothing readily available for emergency use. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Material: Filter K Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking. Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13.

SECTION 9: Physical And Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Colour:	Colorless
Odour:	Pungent suffocating odor
Odour Threshold:	Odour threshold is subjective and is inadequate to warn of over exposure.
pH:	If dissolved in water pH-value will be affected.
Melting Point:	-77.7 °C Experimental result, Key study
Boiling Point:	-33 °C
Sublimation Point:	Not applicable.
Critical Temp. (°C):	132.0 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
10/86

Flammability (solid, gas):	Flammable Gas
Flammability limit - upper (%):	33.6 %(V) Experimental result, Key study
Flammability limit - lower(%):	15.4 %(V)
Vapour pressure:	8.5737 bar (20 °C) Experimental result, Key study
Vapour density (air=1):	0.59 AIR=1
Relative density:	0.8
Solubility(ies)	
Solubility in Water:	531 g/l (20 °C)
Partition coefficient (n-octanol/water):	< 1
Autoignition Temperature:	651 °C Experimental result, Key study
Decomposition Temperature:	> 450 °C
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)
Explosive properties:	Not applicable.
Oxidising Properties:	Not applicable.

9.2 Other information: None.

Molecular weight: 17.03 g/mol (NH₃)

SECTION 10: Stability and Reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of Hazardous Reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to Avoid:	Avoid moisture in the installation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible Materials:	Air and oxidisers. Moisture. For material compatibility see latest version of ISO-11114. Reacts with water to form corrosive alkalis. May react violently with acids.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: The following decomposition products may be produced: Nitrogen monoxide ; nitrogen dioxide

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
11/86

SECTION 11: Toxicological Information
--

General information: Inhalation of large amounts leads to bronchospasm, laryngeal oedema and pseudomembrane formation.

11.1 Information on toxicological effects

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

ammonia, anhydrous LD 50 (Rat): 350 mg/kg Remarks: Experimental result, Key study

Acute toxicity - Dermal Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation Product Toxic if inhaled.

ammonia, anhydrous LC 50 (Rat, 4 h): 2000 ppm

Repeated dose toxicity
ammonia, anhydrous NOAEL (Rat(Female, Male), Oral, 28 - 53 d): 250 mg/kg Oral Read-across from supporting substance (structural analogue or surrogate), Key study
LOAEL (Rat, Inhalation, 35 - 75 d): 175 mg/m³ Inhalation Experimental result, Weight of Evidence study

Skin Corrosion/Irritation Product Causes severe burns.

Serious Eye Damage/Eye Irritation Product Causes serious eye damage.

Respiratory or Skin Sensitisation Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity Product Based on available data, the classification criteria are not met.

Carcinogenicity Product Based on available data, the classification criteria are not met.

Reproductive toxicity Product Based on available data, the classification criteria are not met.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
12/86

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

SECTION 12: Ecological Information

General information: Avoid release to the environment. Product is not allowed to be discharged into ground water or the aquatic environment.

12.1 Toxicity

Acute toxicity

Product Very toxic to aquatic life with long lasting effects.

Acute toxicity - Fish

ammonia, anhydrous LC 50 (Pimephales promelas, 96 h): 0.75 - 3.4 mg/l (flow-through) Remarks: Read-across from supporting substance (structural analogue or surrogate), Key study

Acute toxicity - Aquatic Invertebrates

ammonia, anhydrous LC 50 (48 h): 101 mg/l Remarks: Experimental result, Key study

Toxicity to microorganisms

ammonia, anhydrous Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

Toxicity to terrestrial organisms

ammonia, anhydrous Study not necessary due to exposure considerations.

Chronic toxicity - Fish

ammonia, anhydrous LOEC (Fish, 73 Days): 0.022 mg/l

Chronic toxicity - Aquatic Invertebrates

ammonia, anhydrous LC 50 (Daphnia magna, 96 h): 4.07 mg/l (flow-through) Read-across from supporting substance (structural analogue or surrogate), Key study

Toxicity to aquatic plants

ammonia, anhydrous LC 50 (Algae, algal mat (Algae), 18 Days): 2,700 mg/l

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
13/86

12.2 Persistence and Degradability
Product

Not applicable to gases and gas mixtures..

Biodegradation

Inorganic The product is not readily biodegradable.

12.3 Bioaccumulative Potential
Product

The substance has no potential for bioaccumulation.

12.4 Mobility in Soil
Product

The substance has low mobility in soil.

12.5 Results of PBT and vPvB
assessment
Product

Not classified as PBT or vPvB.

12.6 Other Adverse Effects:

Other Ecological Information

May cause pH changes in aqueous ecological systems. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

SECTION 13: Disposal Considerations
--

13.1 Waste treatment methods

General information:

Must not be discharged to atmosphere. Consult supplier for specific recommendations.

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws. Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere. Gas may be scrubbed in water. Gas may be scrubbed in sulphuric acid solution.

European Waste Codes

Container:

16 05 04*: gases in pressure containers (including halons) containing dangerous substances

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
14/86

SECTION 14: Transport Information

ADR

14.1 UN Number: UN 1005
14.2 UN Proper Shipping Name: AMMONIA, ANHYDROUS
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.3, 8
Hazard No. (ADR): 268
Tunnel restriction code: (C/D)
Emergency Action Code: 2RE
14.4 Packing Group: -
14.5 Environmental hazards: Environmentally Hazardous
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1005
14.2 UN Proper Shipping Name: AMMONIA, ANHYDROUS
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.3, 8
14.4 Packing Group: -
14.5 Environmental hazards: Environmentally Hazardous
14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 1005
14.2 UN Proper Shipping Name: AMMONIA, ANHYDROUS
14.3 Transport Hazard Class(es)
Class: 2.3
Label(s): 2.3, 8
EmS No.: F-C, S-U
14.4 Packing Group: -
14.5 Environmental hazards: P
14.6 Special precautions for user: -

IATA

14.1 UN Number: UN 1005
14.2 Proper Shipping Name: Ammonia, anhydrous
14.3 Transport Hazard Class(es)
Class: 2.3
Label(s): -
14.4 Packing Group: -
14.5 Environmental hazards: Environmentally Hazardous
14.6 Special precautions for user: -
Other information

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
15/86

Passenger and cargo aircraft: Forbidden.
Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Chemical	CAS-No.	Lower-tier Requirements	Upper-tier Requirements
ammonia, anhydrous	7664-41-7	50 t	200 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
ammonia, anhydrous	7664-41-7	100%

National Regulations

Dangerous Substances and Explosive Atmospheres Regulations (DSEAR 2002 No. 2776). Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations (EPS, 1996 No. 192). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
16/86

15.2 Chemical safety assessment: CSA has been carried out.

SECTION 16: Other Information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

EH40 (as amended) Workplace exposure limits.

Wording of the H-statements in sections 2 and 3

H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
17/86

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 2, H221
Press. Gas Liq. Gas, H280
Acute Tox. 3, H331
Skin Corr. 1B, H314
Eye Dam. 1, H318
Aquatic Acute 1, H400
Aquatic Chronic 2, H411

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Note: When the Product Name appears in the SDS header the decimal sign and its position comply with rules for the structure and drafting of international standards, and is a comma on the line. As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

Last revised date:

27.04.2020

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
18/86

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1.	Industrial use, Formulation & (re)packing of substances and mixtures
Exposure Scenario 2.	Industrial use, Manufacture of fine chemicals
Exposure Scenario 3.	Industrial use, Metal surface treatment products
Exposure Scenario 4.	Industrial use, Manufacture of computer, electronic and optical products, electrical equipment
Exposure Scenario 5.	Industrial use, Exhaust gas DeNOx applications
Exposure Scenario 6.	Industrial use, Non-metal-surface treatment products
Exposure Scenario 7.	Industrial use, Non-metal-surface treatment products
Exposure Scenario 8.	Professional use, Laboratory activities
Exposure Scenario 9.	Professional use, Refilling of refrigeration equipment
Exposure Scenario 10.	Professional use, Water treatment chemicals

Exposure Scenario 1.

Exposure Scenario worker

1. Industrial use, Formulation & (re)packing of substances and mixtures

List of use descriptors

Sector(s) of use

Product categories [PC]:

Name of contributing environmental scenario and corresponding ERC

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:
ERC2: Formulation into mixture

Contributing Scenarios

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:
PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

2.1. Contributing exposure scenario controlling environmental exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Product characteristics

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
19/86

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

Amounts used

Annual amount per site	1,000,000 t
Regional use tonnage (tons/year):	3,800,000 t

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
20/86

Remarks:	not relevant
----------	--------------

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
21/86

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Transfer of substance or mixture (charging and discharging) at dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
22/86

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Handle product within a closed system				Transfer of substance or mixture (charging and discharging) at dedicated facilities
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
---------------------	-----------------	--------------	---------------	---------

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
23/86

				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at dedicated facilities

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

ERC2:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000049 7 mg/l	0.045	EUSES	none
marine water				0.000012 mg/l

Health:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

PROC1:

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
24/86

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use., without local exhaust ventilation	0 mg/m ³	< 0.01	ECETOC TRA worker v2.0	none

PROC1:

inhalative, long-term, local	Indoor/Outdoor use., without local exhaust ventilation
------------------------------	--

PROC1:

inhalative, short-term, systemic, (acute)	Indoor/Outdoor use., with local exhaust ventilation
---	---

PROC1:

inhalative, long-term, systemic	Indoor/Outdoor use., with local exhaust ventilation
---------------------------------	---

PROC1:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
---------------------------------------	--

PROC1:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
-----------------------------	--

PROC8b:

inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection
--	-------------------------------------

PROC8b:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	--

PROC8b:

inhalative, long-term, local	Outdoor use, Respiratory Protection
------------------------------	-------------------------------------

PROC8b:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	--

PROC8b:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
---	-------------------------------------

PROC8b:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	--

PROC8b:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection
---------------------------------	-------------------------------------

PROC8b:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
---------------------------------	--

PROC8b:

SAFETY DATA SHEET

Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
25/86

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
PROC8b:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
PROC8b:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
PROC8b:	
dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 2.

Exposure Scenario worker

1. Industrial use, Manufacture of fine chemicals

List of use descriptors	
Sector(s) of use	SU9: Manufacture of fine chemicals
Product categories [PC]:	PC21: Laboratory chemicals
Name of contributing environmental scenario and corresponding ERC	<u>Using gas as feedstock in chemical processes.:</u> ERC6a: Use of intermediate
Contributing Scenarios	<u>Using gas as feedstock in chemical processes.:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
26/86

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:

Kinematic viscosity:	No data available.
----------------------	--------------------

Dynamic viscosity:	0.7 mPa.s (48.9 °C)
--------------------	---------------------

Amounts used

Annual amount per site	800,000 t
------------------------	-----------

Regional use tonnage (tons/year):	3,800,000 t
-----------------------------------	-------------

Frequency and duration of use

Batch process:	330 Emission days
----------------	-------------------

Continuous process:	not relevant
---------------------	--------------

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
27/86

	to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
28/86

Process Categories:	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p>
----------------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
------------------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC2, PROC3

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
29/86

				conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
--	--	--	--	--

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet
--

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Handle product within a closed system				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
30/86

Handle product within a closed system				Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
31/86

				occasional controlled exposure or processes with equivalent containment condition
	Wear suitable gloves tested to EN374: 90 %			Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
	Wear suitable face shield.			Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
	Wear suitable coveralls to prevent exposure to the skin.			Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
		Use suitable eye protection.		Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
32/86

				in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
--	--	--	--	---

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.:

ERC6a:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000083 7 mg/l	0.076	EUSES	none
marine water	0.0000205 mg/l			

Health:

Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use., without local exhaust ventilation	0 mg/m ³	< 0.01	ECETOC TRA worker v2.0	none

PROC1:

inhalative, long-term, local	Indoor/Outdoor use., without local exhaust ventilation
------------------------------	--

PROC1:

inhalative, short-term, systemic, (acute)	Indoor/Outdoor use., with local exhaust ventilation
---	---

PROC1:

inhalative, long-term, systemic	Indoor/Outdoor use., with local exhaust ventilation
---------------------------------	---

PROC1:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local
---------------------------------------	------------------------------------

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
33/86

	exhaust ventilation, No gloves worn
PROC1:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC2:	
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection
PROC2:	
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC2:	
inhalative, long-term, local	Outdoor use, Respiratory Protection
PROC2:	
inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
PROC2:	
inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
PROC2:	
inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC2:	
inhalative, long-term, systemic	Outdoor use, Respiratory Protection
PROC2:	
inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
PROC2:	
dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC2:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
PROC2:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC2:	
dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
PROC3:	
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection
PROC3:	
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC3:	

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
34/86

inhalative, long-term, local	Outdoor use, Respiratory Protection
PROC3:	
inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
PROC3:	
inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
PROC3:	
inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC3:	
inhalative, long-term, systemic	Outdoor use, Respiratory Protection
PROC3:	
inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
PROC3:	
dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC3:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
PROC3:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC3:	
dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 3.

Exposure Scenario worker

1. Industrial use, Metal surface treatment products

List of use descriptors	
Sector(s) of use	SU14: Manufacture of basic metals, including alloys SU15: Manufacture of fabricated metal products, except machinery and equipment
Product categories [PC]:	PC14: Metal surface treatment products

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
35/86

Name of contributing environmental scenario and corresponding ERC	<u>Using gas for metal treatment.:</u> ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
---	--

Contributing Scenarios	<u>Using gas for metal treatment.:</u> PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
------------------------	--

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas for metal treatment., Aluminium casting

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.

Viscosity:

Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

Amounts used

Annual amount per site	25,000 t
Regional use tonnage (tons/year):	354,000 t

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
36/86

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
-------------------------------	-------------------------	---------

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
37/86

See section 13 of the SDS	External recovery and recycling of waste should comply with applicable local and/or national regulations.
---------------------------	---

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas for metal treatment., Aluminium casting

Process Categories:	PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC22

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Manufacturing and processing of minerals and/or metals at substantially elevated temperature

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
38/86

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release
--

See section 8 of the safety data sheet
--

Technical conditions and measures to control dispersion from source towards the worker
--

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Manufacturing and processing of minerals and/or metals at substantially elevated temperature
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Manufacturing and processing of minerals and/or metals at substantially elevated temperature

Organisational measures to prevent/limit releases, dispersion and exposure
--

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
39/86

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Manufacturing and processing of minerals and/or metals at substantially elevated temperature
	Wear suitable gloves tested to EN374: 90 %			Manufacturing and processing of minerals and/or metals at substantially elevated temperature
	Wear suitable face shield.			Manufacturing and processing of minerals and/or metals at substantially elevated temperature
	Wear suitable coveralls to prevent exposure to the skin.			Manufacturing and processing of minerals and/or metals at substantially elevated temperature
		Use suitable eye protection.		Manufacturing and processing of minerals and/or metals at substantially elevated temperature

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas for metal treatment., Aluminium casting:

ERC6b:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000001 7 mg/l	0.002	EUSES	none
marine water				0.0000002 mg/l

Health:

Using gas for metal treatment., Aluminium casting:

PROC22:

SDS_GB - 000010021772

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
40/86

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection	mg/m ³			No data available.

PROC22:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	--

PROC22:

inhalative, long-term, local	Outdoor use, Respiratory Protection
------------------------------	-------------------------------------

PROC22:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	--

PROC22:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
---	-------------------------------------

PROC22:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	--

PROC22:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection
---------------------------------	-------------------------------------

PROC22:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
---------------------------------	--

PROC22:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
---------------------------------------	---

PROC22:

dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
---------------------------------------	--

PROC22:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
-----------------------------	---

PROC22:

dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
-----------------------------	--

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 4.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
41/86

Exposure Scenario worker

1. Industrial use, Manufacture of computer, electronic and optical products, electrical equipment

List of use descriptors

Sector(s) of use	SU16: Manufacture of computer, electronic and optical products, electrical equipment
Product categories [PC]:	PC33: Semiconductors

Name of contributing environmental scenario and corresponding ERC	<u>Use for electronic component manufacture.:</u> ERC6a: Use of intermediate
---	---

Contributing Scenarios	<u>Use for electronic component manufacture.:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
------------------------	--

2.1. Contributing exposure scenario controlling environmental exposure for: Use for electronic component manufacture.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

Amounts used

Annual amount per site	800,000 t
Regional use tonnage (tons/year):	3,800,000 t

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
--------------------------------------	----------------------------------	------------------------------------	----------------	----------

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
42/86

(m ³ /d):				
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
43/86

		national regulations.
--	--	-----------------------

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Use for electronic component manufacture.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1

Human factors not influenced by risk management

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
44/86

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
45/86

				correctly and that the OCs are being followed
--	--	--	--	---

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Use for electronic component manufacture.:

ERC6a:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000083 7 mg/l	0.076	EUSES	none
marine water	0.0000205 mg/l			

Health:

Use for electronic component manufacture.:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use., without local exhaust ventilation	0 mg/m ³	< 0.01	ECETOC TRA worker v2.0	none

PROC1:

inhalative, long-term, local	Indoor/Outdoor use., without local exhaust ventilation
------------------------------	--

PROC1:

inhalative, short-term, systemic, (acute)	Indoor/Outdoor use., with local exhaust ventilation
---	---

PROC1:

inhalative, long-term, systemic	Indoor/Outdoor use., with local exhaust ventilation
---------------------------------	---

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
46/86

PROC1:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
---------------------------------------	--

PROC1:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
-----------------------------	--

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 5.

Exposure Scenario worker

1. Industrial use, Exhaust gas DeNOx applications

List of use descriptors	
Sector(s) of use	SU23: Electricity, steam, gas water supply and sewage treatment
Product categories [PC]:	PC20: Processing aids such as pH-regulators, flocculants, precipitants, neutralization agents

Name of contributing environmental scenario and corresponding ERC	<u>Exhaust gas DeNOx applications:</u> ERC6a: Use of intermediate
---	--

Contributing Scenarios	<u>Exhaust gas DeNOx applications:</u> PROC23: Open processing and transfer operations at substantially elevated temperature
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Exhaust gas DeNOx applications

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
47/86

Amounts used

Annual amount per site	800,000 t
Regional use tonnage (tons/year):	3,800,000 t

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
48/86

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Exhaust gas DeNOx applications

Process Categories:	PROC23: Open processing and transfer operations at substantially elevated temperature
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
49/86

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC23

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Open processing and transfer operations at substantially elevated temperature

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Open processing and transfer operations at substantially elevated temperature
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Open processing and transfer operations at substantially elevated temperature

Organisational measures to prevent/limit releases, dispersion and exposure

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
50/86

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Open processing and transfer operations at substantially elevated temperature
	Wear suitable gloves tested to EN374: 90 %			Open processing and transfer operations at substantially elevated temperature
	Wear suitable face shield.			Open processing and transfer operations at substantially elevated temperature
	Wear suitable coveralls to prevent exposure to the skin.			Open processing and transfer operations at substantially elevated temperature
		Use suitable eye protection.		Open processing and transfer operations at substantially elevated temperature

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
51/86

in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Exhaust gas DeNOx applications:

ERC6a:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000083 7 mg/l	0.076	EUSES	none
marine water	0.0000205 mg/l			

Health:

Exhaust gas DeNOx applications:

PROC23:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection	mg/m ³			No data available.

PROC23:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE				
--	--	--	--	--	--

PROC23:

inhalative, long-term, local	Outdoor use, Respiratory Protection				
------------------------------	-------------------------------------	--	--	--	--

PROC23:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE				
------------------------------	--	--	--	--	--

PROC23:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection				
---	-------------------------------------	--	--	--	--

PROC23:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE				
---	--	--	--	--	--

PROC23:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection				
---------------------------------	-------------------------------------	--	--	--	--

PROC23:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE				
---------------------------------	--	--	--	--	--

PROC23:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn				
---------------------------------------	---	--	--	--	--

PROC23:

SAFETY DATA SHEET

Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
52/86

dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
---------------------------------------	---

PROC23:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
-----------------------------	--

PROC23:

dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
-----------------------------	---

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 6.

Exposure Scenario worker

1. Industrial use, Non-metal-surface treatment products

List of use descriptors	
Sector(s) of use	SU12: Manufacture of plastics products, including compounding and conversion
Product categories [PC]:	PC15: Non-metal surface treatment products
Name of contributing environmental scenario and corresponding ERC	<u>Treatment of plastics:</u> ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)

Contributing Scenarios	<u>Treatment of plastics:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Treatment of plastics

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
53/86

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

Amounts used

Annual amount per site	25,000 t
Regional use tonnage (tons/year):	354,000 t

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

SAFETY DATA SHEET
Ammonia, anhydrousIssue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
54/86

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Treatment of plastics

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
55/86

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	$\geq 20^{\circ}\text{C}$
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	$\leq 8\text{ h}$	5 days per week	PROC1, PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Transfer of substance or mixture (charging and discharging) at dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product				Chemical production or

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
56/86

within a closed system				refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Handle product within a closed system				Transfer of substance or mixture (charging and discharging) at dedicated facilities
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
57/86

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at dedicated facilities

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Treatment of plastics:

ERC6b:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000001 7 mg/l	0.002	EUSES	none
marine water	0.0000002 mg/l			

Health:

Treatment of plastics:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term,	Indoor/Outd	0 mg/m ³	< 0.01	ECETOC TRA	none

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
58/86

local, (acute)	oor use., without local exhaust ventilation			worker v2.0	
----------------	--	--	--	-------------	--

PROC1:

inhalative, long-term, local	Indoor/Outdoor use., without local exhaust ventilation
------------------------------	---

PROC1:

inhalative, short-term, systemic, (acute)	Indoor/Outdoor use., with local exhaust ventilation
---	--

PROC1:

inhalative, long-term, systemic	Indoor/Outdoor use., with local exhaust ventilation
---------------------------------	--

PROC1:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
---------------------------------------	---

PROC1:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
-----------------------------	---

PROC8b:

inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection
--	-------------------------------------

PROC8b:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	---

PROC8b:

inhalative, long-term, local	Outdoor use, Respiratory Protection
------------------------------	-------------------------------------

PROC8b:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	---

PROC8b:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
---	-------------------------------------

PROC8b:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	---

PROC8b:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection
---------------------------------	-------------------------------------

PROC8b:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
---------------------------------	---

PROC8b:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
---------------------------------------	--

PROC8b:

SAFETY DATA SHEET

Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
59/86

dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
---------------------------------------	---

PROC8b:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
-----------------------------	--

PROC8b:

dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
-----------------------------	---

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 7.

Exposure Scenario worker

1.Industrial use, Non-metal-surface treatment products

List of use descriptors	
Sector(s) of use	SU5: Manufacture of textiles, leather, fur
Product categories [PC]:	PC34: Textile dyes and impregnating products

Name of contributing environmental scenario and corresponding ERC	<u>Non-metal-surface treatment products:</u> ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
---	--

Contributing Scenarios	<u>Non-metal-surface treatment products:</u> PROC4: Chemical production where opportunity for exposure arises PROC6: Calendering operations
------------------------	---

2.1.Contributing exposure scenario controlling environmental exposure for: Non-metal-surface treatment products

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
60/86

Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

Amounts used

Annual amount per site	25,000 t
Regional use tonnage (tons/year):	354,000 t

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
61/86

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Non-metal-surface treatment products

Process Categories:	PROC4: Chemical production where opportunity for exposure arises PROC6: Calendering operations
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
62/86

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC4
No data available.			PROC6

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Chemical production where opportunity for exposure arises
No data available.				Calendering operations

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Chemical production where opportunity for exposure arises
During indoor processes or in cases where natural ventilation is not sufficient, LEV				Chemical production where opportunity for exposure arises

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
63/86

should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				
No data available.				Calendering operations

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Chemical production where opportunity for exposure arises
	Wear suitable gloves tested to EN374: 90 %			Chemical production where opportunity for exposure arises
	Wear suitable face shield.			Chemical production where opportunity for exposure arises
	Wear suitable coveralls to prevent exposure to the skin.			Chemical production where opportunity for exposure arises
		Use suitable eye protection.		Chemical production where opportunity for exposure

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
64/86

				arises
No data available.	No data available.	No data available.		Calendering operations

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Non-metal-surface treatment products:

ERC6b:

Compartment	PEC	RCR	Method	Remarks
freshwater	0.000001 7 mg/l	0.002	EUSES	none
marine water	0.0000002 mg/l			

Health:

Non-metal-surface treatment products:

PROC4:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection	2.48 mg/m ³	0.069	ECETOC TRA worker v2.0	none

PROC4:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	--

PROC4:

inhalative, long-term, local	Outdoor use, Respiratory Protection
------------------------------	-------------------------------------

PROC4:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	--

PROC4:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
---	-------------------------------------

PROC4:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	--

PROC4:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection
---------------------------------	-------------------------------------

PROC4:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation,
---------------------------------	---

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
 Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
 65/86

	No RPE
PROC4:	
dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC4:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
PROC4:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC4:	
dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
PROC6:	
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection
PROC6:	
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC6:	
inhalative, long-term, local	Outdoor use, Respiratory Protection
PROC6:	
inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
PROC6:	
inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
PROC6:	
inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC6:	
inhalative, long-term, systemic	Outdoor use, Respiratory Protection
PROC6:	
inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
PROC6:	
dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC6:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
PROC6:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn

PROC6:

SDS_GB - 000010021772

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
66/86

dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
-----------------------------	---

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 8.

Exposure Scenario worker

1. Professional use, Laboratory activities

List of use descriptors	
Sector(s) of use	SU24: Scientific research and development
Product categories [PC]:	PC21: Laboratory chemicals

Name of contributing environmental scenario and corresponding ERC	<u>Using gas alone or in mixtures for the calibration of analysis equipment.:</u> ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
---	---

Contributing Scenarios	<u>Using gas alone or in mixtures for the calibration of analysis equipment.:</u> PROC15: Use as laboratory reagent
------------------------	--

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)

Amounts used

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
67/86

Annual amount per site	No data available.
Regional use tonnage (tons/year):	No data available.

Frequency and duration of use

Batch process:	not relevant
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
68/86

Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Process Categories:	PROC15: Use as laboratory reagent
---------------------	-----------------------------------

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of
-----------------------	---

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
69/86

	containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
--	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC15

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor use				Use as laboratory reagent

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet
--

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Use as laboratory reagent
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Use as laboratory reagent
Local exhaust ventilation				Use as laboratory reagent

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
70/86

				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Use as laboratory reagent
	Wear suitable gloves tested to EN374: 90 %			Use as laboratory reagent
	Wear suitable face shield.			Use as laboratory reagent
	Wear suitable coveralls to prevent exposure to the skin.			Use as laboratory reagent
		Use suitable eye protection.		Use as laboratory reagent

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas alone or in mixtures for the calibration of analysis equipment.:

ERC8b:

Compartment	PEC	RCR	Method	Remarks
-------------	-----	-----	--------	---------

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
71/86

freshwater	mg/l	< 1		No data available.
marine water	mg/l			

Health:

Using gas alone or in mixtures for the calibration of analysis equipment.:

PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation, No RPE	35.42 mg/m ³	0.98	ECETOC TRA worker v2.0	none

PROC15:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	--

PROC15:

inhalative, long-term, local	Indoor use, without local exhaust ventilation, No RPE
------------------------------	---

PROC15:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	--

PROC15:

inhalative, short-term, systemic, (acute)	Indoor use, without local exhaust ventilation, No RPE
---	---

PROC15:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	--

PROC15:

inhalative, long-term, systemic	Indoor use, without local exhaust ventilation, No RPE
---------------------------------	---

PROC15:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
---------------------------------	--

PROC15:

inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation, Respiratory Protection
--	---

PROC15:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, Respiratory Protection
--	--

PROC15:

inhalative, long-term, local	Indoor use, without local exhaust ventilation, Respiratory Protection
------------------------------	---

PROC15:

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
72/86

inhalative, long-term, local	Indoor use, with local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, short-term, systemic, (acute)	Indoor use, without local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, long-term, systemic	Indoor use, without local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation, No RPE
PROC15:	
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC15:	
inhalative, long-term, local	Indoor use, without local exhaust ventilation, No RPE
PROC15:	
inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
PROC15:	
inhalative, short-term, systemic, (acute)	Indoor use, without local exhaust ventilation, No RPE
PROC15:	
inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
PROC15:	
inhalative, long-term, systemic	Indoor use, without local exhaust ventilation, No RPE
PROC15:	
inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
PROC15:	
inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation,

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
73/86

	Respiratory Protection
PROC15:	
inhalative, long-term, local	Indoor use, without local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, long-term, local	Indoor use, with local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, short-term, systemic, (acute)	Indoor use, without local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, long-term, systemic	Indoor use, without local exhaust ventilation, Respiratory Protection
PROC15:	
inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, Respiratory Protection
PROC15:	
dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC15:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
PROC15:	
dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
PROC15:	
dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, Gloves worn
PROC15:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, No gloves worn
PROC15:	
dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
PROC15:	
dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
PROC15:	
dermal, long-term, systemic	Indoor use, with local exhaust ventilation, Gloves worn

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
74/86

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 9.

Exposure Scenario worker

1. Professional use, Refilling of refrigeration equipment

List of use descriptors	
Sector(s) of use	
Product categories [PC]:	PC16: Heat transfer fluids
Name of contributing environmental scenario and corresponding ERC	<u>Refilling of refrigeration equipment:</u> ERC9a: Widespread use of functional fluid (indoor) ERC9b: Widespread use of functional fluid (outdoor)
Contributing Scenarios	<u>Refilling of refrigeration equipment:</u> PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

2.1. Contributing exposure scenario controlling environmental exposure for: Refilling of refrigeration equipment

Product characteristics	
Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)
Amounts used	
Annual amount per site	No data available.
Regional use tonnage (tons/year):	No data available.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
75/86

Frequency and duration of use

Batch process:	not relevant
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
76/86

Remarks:	Direct emissions to the municipal STP should not be made.
----------	---

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Refilling of refrigeration equipment

Process Categories:	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
77/86

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC22

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
78/86

				exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

SDS_GB - 000010021772

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
79/86

Refilling of refrigeration equipment:

ERC9a, ERC9b:

Compartment	PEC	RCR	Method	Remarks
freshwater	mg/l	< 1		No data available.
marine water				mg/l

Health:

Refilling of refrigeration equipment:

PROC8a:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection	mg/m ³			No data available.

PROC8a:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	--

PROC8a:

inhalative, long-term, local	Outdoor use, Respiratory Protection
------------------------------	-------------------------------------

PROC8a:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	--

PROC8a:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
---	-------------------------------------

PROC8a:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	--

PROC8a:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection
---------------------------------	-------------------------------------

PROC8a:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
---------------------------------	--

PROC8a:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
---------------------------------------	---

PROC8a:

dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
---------------------------------------	--

PROC8a:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
-----------------------------	---

PROC8a:

dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
-----------------------------	--

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
80/86

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 10.

Exposure Scenario worker

1. Professional use, Water treatment chemicals

List of use descriptors	
Sector(s) of use	SU23: Electricity, steam, gas water supply and sewage treatment
Product categories [PC]:	PC37: Water treatment chemicals
Name of contributing environmental scenario and corresponding ERC	<u>Water treatment:</u> ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
Contributing Scenarios	<u>Water treatment:</u> PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

2.1. Contributing exposure scenario controlling environmental exposure for: Water treatment.

Product characteristics	
Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.7 mPa.s (48.9 °C)
Amounts used	
Annual amount per site	No data available.
Regional use tonnage (tons/year):	No data available.
Frequency and duration of use	

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
81/86

Batch process:	not relevant
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18,000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Closed systems are used in order to prevent unintended emissions
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Closed systems are used in order to prevent unintended emissions
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
82/86

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Water treatment.

Process Categories:	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

SDS_GB - 000010021772

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
83/86

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor/Outdoor use.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system				Transfer of substance or mixture (charging and discharging) at dedicated facilities
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
84/86

				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	Dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at dedicated facilities

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
85/86

Environment:

Water treatment.:

ERC8b:

Compartment	PEC	RCR	Method	Remarks
freshwater	mg/l	< 1		No data available.
marine water				mg/l

Health:

Water treatment.:

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Outdoor use, Respiratory Protection	3.72 mg/m ³	0.103	ECETOC TRA worker v2.0	none

PROC8b:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation, No RPE
--	--

PROC8b:

inhalative, long-term, local	Outdoor use, Respiratory Protection
------------------------------	-------------------------------------

PROC8b:

inhalative, long-term, local	Indoor use, with local exhaust ventilation, No RPE
------------------------------	--

PROC8b:

inhalative, short-term, systemic, (acute)	Outdoor use, Respiratory Protection
---	-------------------------------------

PROC8b:

inhalative, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No RPE
---	--

PROC8b:

inhalative, long-term, systemic	Outdoor use, Respiratory Protection
---------------------------------	-------------------------------------

PROC8b:

inhalative, long-term, systemic	Indoor use, with local exhaust ventilation, No RPE
---------------------------------	--

PROC8b:

dermal, short-term, systemic, (acute)	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
---------------------------------------	---

PROC8b:

dermal, short-term, systemic, (acute)	Indoor use, with local exhaust ventilation, No gloves worn
---------------------------------------	--

PROC8b:

dermal, long-term, systemic	Indoor/Outdoor use., without local exhaust ventilation, Gloves worn
-----------------------------	---

PROC8b:

SAFETY DATA SHEET
Ammonia, anhydrous

Issue Date: 16.01.2013
Last revised date: 27.04.2020

Version: 3.0

SDS No.: 000010021772
86/86

dermal, long-term, systemic	Indoor use, with local exhaust ventilation, No gloves worn
-----------------------------	---

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>