

Direction to vary conditions of consent to the discharge of trade effluent to the public foul water sewer

To: The Company Secretary
Pukka Pies Ltd
The Halfcroft
Syston
Leicester
LE7 8LD

WHEREAS

Trade effluent is now discharged from the premises known as **Pukka Pies Ltd** and situated at **The Halfcroft, Syston, Leicester, LE7 8LD** under a consent dated 1 December 1983 issued by Severn Trent Water Authority

NOW THEREFORE Severn Trent Water Limited (hereinafter called "The Sewerage Undertaker") HEREBY Direct under the powers conferred on them by Section 124 of the Water Industry Act 1991, that subject as hereinafter specified as from 29 March 2009 the Consent dated 1 December 1983 be varied and the following conditions substituted for the conditions previously attached thereto.

- | | |
|------------------------------|---|
| Sewer Affected | 1. The public sewer into which the trade effluent may be discharged is the foul water sewer situated in The Halfcroft . |
| Nature or Composition | 2. The trade effluent to be discharged shall consist solely of waste waters specified in the trade effluent notice served in respect of the premises and derived from utensil and floor wash . |
| Maximum volume | 3. The maximum volume of trade effluent to be discharged in any continuous period of 24 hours shall not exceed 100 cubic metres. |
| Maximum rate | 4. The highest rate at which the trade effluent may be discharged shall not exceed 15 litres per second. |
| Period of discharge | 5. The trade effluent shall only be discharged into the public sewer between 00:00 and 23:59 hours. |
| Quality Conditions | 6. a. The trade effluent to be discharged shall not contain any of the substances or properties listed in Appendix I in amounts or proportions other than those which comply with the limits there stated and shall not contain any substances or properties not listed in Appendix I except with the prior written permission of the Sewerage Undertaker and on such terms and conditions as are set out therein.

b. The trade effluent to be discharged shall not contain any special category effluent (as defined in Section 138 of the Water Industry Act 1991) in a concentration greater than background concentration (as defined in the Trade Effluents (Prescribed Processes and Substances) Regulations 1989).


c. Where the trade effluent derives from a prescribed process mentioned in Schedule 2 to the Trade Effluents (Prescribed Processes and Substances) Regulations 1989, it shall not contain asbestos (as defined in the said Regulations) and chloroform in a concentration greater than the background concentration (as defined in the said Regulations); |

- Inspection chamber** 7. An inspection chamber or manhole shall be provided and maintained in connection with each pipe through which the trade effluent is to be discharged into the public sewer, and such inspection chamber or manhole shall be so constructed and maintained as to enable a person to readily obtain samples at any time, of the trade effluent so discharged.
- Quality and volume measurement** 8. a. Apparatus adequate for measuring and automatically recording the volume, rate and composition of trade effluent so discharged shall be provided with every such pipe and such measurement apparatus shall be maintained and tested to the satisfaction of the Sewerage Undertaker.
- b. If the measuring and recording apparatus ceases to record or is suspected of not measuring correctly, then the Sewerage Undertaker shall have the right to make estimates of the volume and composition of the trade effluent until such time as the said apparatus is again operating to the satisfaction of the Sewerage Undertaker.
- c. The foregoing provisions of this condition shall be of no effect so long as there is provided and maintained to the satisfaction of the Sewerage Undertaker some other method approved by the Sewerage Undertaker of sampling the trade effluent or determining, measuring and recording the volume and composition of the trade effluent so discharged.
- d. Records of the volume and composition of the trade effluent discharged into the sewer shall be kept available at all times for inspection by any authorised representative of the Sewerage Undertaker and copies of such records shall be sent to the Sewerage Undertaker on demand.
- Payment** 9. Payment shall be made to the Sewerage Undertaker for the reception, treatment and disposal of the trade effluent discharged into the public foul water sewer in accordance with the Sewerage Undertaker's Charging Scheme in force from time to time.

All sums payable to the Sewerage Undertaker under this condition shall become due and payable on demand.

Dated the twenty second day of January 2009

For and on behalf of the Sewerage Undertaker



J. Lingard
General Manager – Commercial Services

Address of the Sewerage Undertaker

Severn Trent Water Limited
2297 Coventry Road
Birmingham
B26 3PU

NOTE: Your attention is drawn to the right of appeal to the Director General of Water Services conferred by Section 126 of the Water Industry Act 1991.

APPENDIX I

Consent No **001704V**

Direction No **0003**

QUALITY CONDITIONS

1. The pH value of the trade effluent shall not be less than 6 nor greater than 10 in the recognised scale.
2. The total of Suspended Solids in the trade effluent shall not exceed 4500 milligrams per litre.
3. The Chemical Oxygen Demand from acidified dichromate (C.O.D.) of the Effluent shall not exceed 6500 milligrams per litre expressed as O.
4. The maximum Chemical Oxygen Demand load in the Effluent to be discharged during any period of 24 hours shall not exceed 450 kilograms, the load being the product of the volume and the Chemical Oxygen Demand from acidified dichromate of the trade effluent discharged during that 24 hour period, determined on the basis of a settled sample.
5. The temperature of the Effluent shall not exceed 43 degrees Centigrade.
6. The trade effluent shall be free from physically separable, dispersed or emulsified oil and soluble oil.
7. The trade effluent shall not contain any substance or substances which either alone, or in combination with any matter in any sewers or receiving sewage treatment works vested in and/or under the control of Severn Trent Water Limited, would give rise to obnoxious, poisonous or inflammable gases, or otherwise a statutory nuisance as defined by the Environmental Protection Act 1990 in such sewers or works, would be deleterious to such sewers or to the processes in use at such works or to the disposal of effluents and sludges produced by such works.

A shaken sample is to be used except for C.O.D., where the sample shall be supernatant after 1 hour settlement

PUKKA PIES LIMITED
THE HALFCROFT
SYSTON
LEICESTER
LE7 1LD

AGREED TRADE EFFLUENT SAMPLING POINT

PUKKA PIES LIMITED
(10 102 443 00)
(94200235)
(003704V)

HIGH STREET

THE HALFCROFT

THE HALFCROFT

ROSSE WAY

I, the undersigned am authorised to confirm that the point shown on the attached Plan and Marked as: "Agreed Trade Effluent Sampling Point" is the point from which representative trade effluent samples discharging to the foul sewer can be obtained

Signed.....
Print Name..... **AT STOREY**
Designation..... **M.D**
Date..... **6/11/08**

The material contained in this drawing has been based upon the Ordnance Survey Map by Severn Trent Water Limited by permission of Ordnance Survey on behalf of the controller of Her Majesty's Stationary Office.
© Crown copyright - Severn Trent Water Ltd - WU298522
Document users, other than Severn Trent Water Business users, are advised that this document is provided for reference purpose only and no further copies should be made from it.

QUALITY AND VOLUME MEASUREMENT

1. Quality measurement

1.1. Sampling point

To enable a representative sample of trade effluent to be taken a suitable sampling point shall be provided to the satisfaction of the Sewerage Undertaker at a point marked SAMPLING POINT as shown on the Plan No. 001704v/03/09 attached hereto.

The Sampling Point is located at the right hand side of the building, when viewed from the front looking at reception, externally towards the rear of the factory, close to some cooling towers, close to the site fence line. Permanent sample tubing and Company Composite sampling machine has been installed on the V Notch flow measuring flume installed at this point.

Safe access to and exit from this point for inspection and monitoring purposes by authorised representatives of the Sewerage Undertaker shall be provided.

2. Volume measurement

There shall be provided a continuous integrating flow recorder which shall record in litres per second and integrate in cubic metres. The volume measured shall be that of the trade effluent excluding domestic sewage, rainwater and uncontaminated surface water. The instrument must be fitted with a recording chart or other data logging device acceptable to the Sewerage Undertaker and the data so recorded must be kept readily available for on site examination by authorised representatives of the Sewerage Undertaker.

TRADE EFFLUENT CHARGE CALCULATION

The payment to be made by the occupier of the premises from which the trade effluent is discharged for the whole or any part of any period of twelve calendar months commencing on 1 April in any year shall be calculated as follows:

1. The volume of trade effluent discharged in cubic metres multiplied by C, where

$$C = R + V + \frac{Ot}{Os} \times B + \frac{St}{Ss} \times S$$

C = Total charge per cubic metre of trade effluent.

R = One third of the amount determined by the Sewerage Undertaker as the average cost to the Sewerage Undertaker for the year of charge of receiving into its sewers (other than those used solely for surface water) and conveying one cubic metre of sewage to the Sewerage Undertaker's sewage treatment works.

V = The amount determined by the Sewerage Undertaker as the average cost for the year of charge of primary treatment and other volumetric treatment costs in the treatment of one cubic metre of sewage at the Sewerage Undertaker's sewage treatment works.

Ot = The Chemical Oxygen Demand (COD) of the trade effluent in milligrams per litre (mg/l) after one hour quiescent settlement.

Os = The estimated average Chemical Oxygen Demand (COD) of settled sewage in milligrams per litre (mg/l) at the Sewerage Undertaker's works as determined by the Sewerage Undertaker for the purposes of the year of charge.

B = The amount determined by the Sewerage Undertaker as the average cost to the Sewerage Undertaker for the year of charge of biological treatment of one cubic metre of sewage at the Sewerage Undertaker's sewage treatment works.

St = The total suspended solids in the trade effluent in milligrams per litre (mg/l) at the pH of the trade effluent.

Ss = The estimated average amount of suspended solids in milligrams per litre (mg/l) determined on a shaken sample, in sewage received for treatment at the Sewerage Undertaker's works as determined by the Sewerage Undertaker for the purposes of the year of charge.

S = The amount determined by the Sewerage Undertaker as the average cost to the Sewerage Undertaker for the year of charge, of primary sludge treatment and disposal of one cubic metre of sewage at the Sewerage Undertaker's sewage treatment works.

2. Minimum charge for small volumes:

Where the product of the volume of trade effluent in cubic metres and the unit charge calculated from the above formula is less than the minimum charge determined by the Sewerage Undertaker for the year of charge, then that minimum charge shall be paid.

- 3 The Sewerage Undertaker will notify the occupier of the premises from which trade effluent is discharged of the factors in the above formula, on which the Sewerage Undertaker's trade effluent charges will be based for each year of charge, prior to 1 April in any year.

OFFENCES

Water Industry Act 1991

Your attention is drawn to the provisions of the following Sections:-

Section 121 of the Water Industry Act 1991, which provides inter alia that the occupier of the premises from which trade effluent is discharged in contravention of any condition imposed on a consent shall be guilty of an offence and be liable on summary conviction to a fine not exceeding the statutory maximum or on conviction on indictment, to a fine.

Section 111 of the Water Industry Act 1991, the effect of which is given here below, in relation to a discharge of trade effluent which may not comply with either the description stated by the occupier in the trade effluent notice or with any condition in a consent or direction issued under the Act:-

1. No person shall throw, empty or turn, or suffer or permit to be thrown or emptied or to pass, into any public sewer, or into any drain or sewer communicating with a public sewer:
 - (a) Any matter likely to injure the sewer or drain, or to interfere with the free flow of its contents, or to affect prejudicially the treatment and disposal of its contents; or
 - (b) Any chemical refuse or waste steam, or any liquid of a temperature higher than one hundred and ten degrees Fahrenheit, being refuse or steam which, or a liquid which when so heated, is, either alone or in combination with the contents of the sewer or drain, dangerous, or the cause of a nuisance, or prejudicial to health; or
 - (c) Any petroleum spirit, or carbide of calcium.
2. A person who contravenes any of the provisions of this Section shall be liable:
 - (a) On summary conviction to a fine not exceeding the Statutory maximum and to a further fine not exceeding £50 for each day on which the offence continues after conviction;
 - (b) On conviction on indictment, to imprisonment for a term not exceeding two years or a fine or both.
3. In respect of the imposition of a daily penalty:
 - (a) the Court may fix a reasonable date from the date of conviction for compliance with any directions given by the Court; and
 - (b) where a Court has fixed such a period, the daily penalty shall not be imposed in respect of any day before the end of that period.
4. In this section the expression "petroleum spirit" means any such:
 - (a) Crude petroleum
 - (b) Oil made from petroleum, or from coal, shale, peat or other bituminous substances; or
 - (c) Product of petroleum or mixture containing petroleum, as, when tested in the manner prescribed by or under the Petroleum (Consolidation) Act, 1928, gives off an inflammable vapour at a temperature of less than seventy three degrees Fahrenheit.

Direction to vary conditions of consent to the discharge of trade effluent to the public foul water sewer

To: The Company Secretary
Pukka Pies Ltd
The Halfcroft
Syston
Leicester
LE7 8LD

WHEREAS

Trade effluent is now discharged from the premises known as **Pukka Pies Ltd** and situated at **The Halfcroft, Syston, Leicester, LE7 1LD** under a consent dated 1 August 2003 issued by Severn Trent Water Limited

NOW THEREFORE Severn Trent Water Limited (hereinafter called "The Sewerage Undertaker") HEREBY Direct under the powers conferred on them by Section 124 of the Water Industry Act 1991, that subject as hereinafter specified as from 29 March 2009 the Consent dated 1 August 2003 be varied and the following conditions substituted for the conditions previously attached thereto.

- | | |
|------------------------------|---|
| Sewer Affected | 1. The public sewer into which the trade effluent may be discharged is the foul water sewer situated in The Halfcroft . |
| Nature or Composition | 2. The trade effluent to be discharged shall consist solely of waste waters specified in the trade effluent notice served in respect of the premises and derived from waste from cleaning down / cooking . |
| Maximum volume | 3. The maximum volume of trade effluent to be discharged in any continuous period of 24 hours shall not exceed 50 cubic metres. |
| Maximum rate | 4. The highest rate at which the trade effluent may be discharged shall not exceed 5 litres per second. |
| Period of discharge | 5. The trade effluent shall only be discharged into the public sewer between 00:00 and 23:59 hours. |
| Quality Conditions | 6. a. The trade effluent to be discharged shall not contain any of the substances or properties listed in Appendix I in amounts or proportions other than those which comply with the limits there stated and shall not contain any substances or properties not listed in Appendix I except with the prior written permission of the Sewerage Undertaker and on such terms and conditions as are set out therein.

b. The trade effluent to be discharged shall not contain any special category effluent (as defined in Section 138 of the Water Industry Act 1991) in a concentration greater than background concentration (as defined in the Trade Effluents (Prescribed Processes and Substances) Regulations 1989).

c. Where the trade effluent derives from a prescribed process mentioned in Schedule 2 to the Trade Effluents (Prescribed Processes and Substances) Regulations 1989, it shall not contain asbestos (as defined in the said Regulations) and chloroform in a concentration greater than the background concentration (as defined in the said Regulations); |

- Inspection chamber** 7. An inspection chamber or manhole shall be provided and maintained in connection with each pipe through which the trade effluent is to be discharged into the public sewer, and such inspection chamber or manhole shall be so constructed and maintained as to enable a person to readily obtain samples at any time, of the trade effluent so discharged.
- Quality and volume measurement** 8. a. Apparatus adequate for measuring and automatically recording the volume, rate and composition of trade effluent so discharged shall be provided with every such pipe and such measurement apparatus shall be maintained and tested to the satisfaction of the Sewerage Undertaker.
- b. If the measuring and recording apparatus ceases to record or is suspected of not measuring correctly, then the Sewerage Undertaker shall have the right to make estimates of the volume and composition of the trade effluent until such time as the said apparatus is again operating to the satisfaction of the Sewerage Undertaker.
- c. The foregoing provisions of this condition shall be of no effect so long as there is provided and maintained to the satisfaction of the Sewerage Undertaker some other method approved by the Sewerage Undertaker of sampling the trade effluent or determining, measuring and recording the volume and composition of the trade effluent so discharged.
- d. Records of the volume and composition of the trade effluent discharged into the sewer shall be kept available at all times for inspection by any authorised representative of the Sewerage Undertaker and copies of such records shall be sent to the Sewerage Undertaker on demand.
- Payment** 9. Payment shall be made to the Sewerage Undertaker for the reception, treatment and disposal of the trade effluent discharged into the public (and) water sewer in accordance with the Sewerage Undertaker's Charging Scheme in force from time to time.

All sums payable to the Sewerage Undertaker under this condition shall become due and payable on demand.

Dated the twenty second day of January 2000

For and on behalf of the Sewerage Undertaker

J. Lingard
General Manager - Commercial Services

Address of the Sewerage Undertaker

Severn Trent Water Limited
2297 Coventry Road
Birmingham
B26 3PU

NOTE: Your attention is drawn to the right of appeal to the Director General of Water Services conferred by Section 126 of the Water Industry Act 1991.

APPENDIX I

Consent No **005626V**

Direction No **0001**

QUALITY CONDITIONS

1. The pH value of the Effluent shall not be less than 6 nor greater than 10 in the recognised scale.
2. The total of Suspended Solids in the Effluent shall not exceed 1000 milligrams per litre.
3. The Chemical Oxygen Demand from acidified dichromate (C.O.D.) of the Effluent shall not exceed 2000 milligrams per litre expressed as O.
4. The maximum Chemical Oxygen Demand load in the Effluent to be discharged during any period of 24 hours shall not exceed 50 kilograms, the load being the product of the volume and the Chemical Oxygen Demand from acidified dichromate of the trade effluent discharged during that 24 hour period, determined on the basis of a settled sample.
5. The temperature of the Effluent shall not exceed 43 degrees Centigrade.
6. The trade effluent shall be free from physically separable, dispersed or emulsified oil and soluble oil.
7. The trade effluent shall not contain any substance or substances which either alone, or in combination with any matter in any sewers or receiving sewage treatment works vested in and/or under the control of Severn Trent Water Limited, would give rise to obnoxious, poisonous or inflammable gases, or otherwise a statutory nuisance as defined by the Environmental Protection Act 1990 in such sewers or works, would be deleterious to such sewers or to the processes in use at such works or to the disposal of effluents and sludges produced by such works.

A shaken sample is to be used except for C.O.D., where the sample shall be supernatant after 1 hour settlement

FOSSE WAY

PUKKA PIES LIMITED
THE HALFCROFT
SYSTEM
LEICESTER
LE7 1LD

THE HALFCROFT


AGREED TRADE EFFLUENT SAMPLING POINT →

PUKKA PIES LIMITED
(10 102 0443 01)
(095 23017)
(0153626V)

HIGH STREET

THE HALFCROFT

I, the undersigned am authorised to confirm that the point shown on the attached Plan and Marked as: "Agreed Trade Effluent Sampling Point" is the point from which representative trade effluent samples discharging to the foul sewer can be obtained

Signed..... 

Print Name..... **M.D. STOREK**

Designation..... **M.D.**

Date..... **6/11/08**

The material contained in this drawing has been based upon the Guidance Survey Map by Severn Trent Water Limited by permission of Ordnance Survey on behalf of the controller of Her Majesty's Stationary Office.
© Crown copyright - Severn Trent Water Ltd. WU298522

Document users, other than Severn Trent Water Business users, are advised that this document is provided for reference purpose only and no further copies should be made from it.

QUALITY AND VOLUME MEASUREMENT

1. Quality measurement

1.1. Sampling point

To enable a representative sample of trade effluent to be taken a suitable sampling point shall be provided to the satisfaction of the Sewerage Undertaker at a point marked SAMPLING POINT as shown on the Plan No. 005626v/03/09 attached hereto.

The Sampling Point is located at the drain access chamber situated on the left hand end of the building, when viewed facing the Reception area, out side of the plant room access door.

Safe access to and exit from this point for inspection and monitoring purposes by authorised representatives of the Sewerage Undertaker shall be provided.

2. Volume measurement

There shall be provided a water meter which will measure only the volume used by the process producing the effluent and not the water used for domestic purposes. This meter shall record in cubic metres.

TRADE EFFLUENT CHARGE CALCULATION

The payment to be made by the occupier of the premises from which the trade effluent is discharged for the whole or any part of any period of twelve calendar months commencing on 1 April in any year shall be calculated as follows:

1. The volume of trade effluent discharged in cubic metres multiplied by C, where

$$C = R + V + \frac{O_t}{O_s} \times B + \frac{S_t}{S_s} \times S$$

C = Total charge per cubic metre of trade effluent.

R = One third of the amount determined by the Sewerage Undertaker as the average cost to the Sewerage Undertaker for the year of charge of receiving into its sewers (other than those used solely for surface water) and conveying one cubic metre of sewage to the Sewerage Undertaker's sewage treatment works.

V = The amount determined by the Sewerage Undertaker as the average cost for the year of charge of primary treatment and other volumetric treatment costs in the treatment of one cubic metre of sewage at the Sewerage Undertaker's sewage treatment works.

O_t = The Chemical Oxygen Demand (COD) of the trade effluent in milligrams per litre (mg/l) after one hour quiescent settlement.

O_s = The estimated average Chemical Oxygen Demand (COD) of settled sewage in milligrams per litre (mg/l) at the Sewerage Undertaker's works as determined by the Sewerage Undertaker for the purposes of the year of charge.

B = The amount determined by the Sewerage Undertaker as the average cost to the Sewerage Undertaker for the year of charge of biological treatment of one cubic metre of sewage at the Sewerage Undertaker's sewage treatment works.

S_t = The total suspended solids in the trade effluent in milligrams per litre (mg/l) at the pH of the trade effluent.

S_s = The estimated average amount of suspended solids in milligrams per litre (mg/l) determined on a shaken sample, in sewage received for treatment at the Sewerage Undertaker's works as determined by the Sewerage Undertaker for the purposes of the year of charge.

S = The amount determined by the Sewerage Undertaker as the average cost to the Sewerage Undertaker for the year of charge, of primary sludge treatment and disposal of one cubic metre of sewage at the Sewerage Undertaker's sewage treatment works.

2. Minimum charge for small volumes:

Where the product of the volume of trade effluent in cubic metres and the unit charge calculated from the above formula is less than the minimum charge determined by the Sewerage Undertaker for the year of charge, then that minimum charge shall be paid.

- 3 The Sewerage Undertaker will notify the occupier of the premises from which trade effluent is discharged of the factors in the above formula, on which the Sewerage Undertaker's trade effluent charges will be based for each year of charge, prior to 1 April in any year.

OFFENCES

Water Industry Act 1991

Your attention is drawn to the provisions of the following Sections:-

Section 121 of the Water Industry Act 1991, which provides inter alia that the occupier of the premises from which trade effluent is discharged in contravention of any condition imposed on a consent shall be guilty of an offence and be liable on summary conviction to a fine not exceeding the statutory maximum or on conviction on indictment, to a fine.

Section 111 of the Water Industry Act 1991, the effect of which is given here below, in relation to a discharge of trade effluent which may not comply with either the description stated by the occupier in the trade effluent notice or with any condition in a consent or direction issued under the Act:-

1. No person shall throw, empty or turn, or suffer or permit to be thrown or emptied or to pass, into any public sewer, or into any drain or sewer communicating with a public sewer:
 - (a) Any matter likely to injure the sewer or drain, or to interfere with the free flow of its contents, or to affect prejudicially the treatment and disposal of its contents; or
 - (b) Any chemical refuse or waste steam, or any liquid of a temperature higher than one hundred and ten degrees Fahrenheit, being refuse or steam which, or a liquid which when so heated, is, either alone or in combination with the contents of the sewer or drain, dangerous, or the cause of a nuisance, or prejudicial to health; or
 - (c) Any petroleum spirit, or carbide of calcium.
2. A person who contravenes any of the provisions of this Section shall be liable:
 - (a) On summary conviction to a fine not exceeding the Statutory maximum and to a further fine not exceeding £50 for each day on which the offence continues after conviction;
 - (b) On conviction on indictment, to imprisonment for a term not exceeding two years or a fine or both.
3. In respect of the imposition of a daily penalty:
 - (a) the Court may fix a reasonable date from the date of conviction for compliance with any directions given by the Court; and
 - (b) where a Court has fixed such a period, the daily penalty shall not be imposed in respect of any day before the end of that period.
4. In this section the expression "petroleum spirit" means any such:
 - (a) Crude petroleum
 - (b) Oil made from petroleum, or from coal, shale, peat or other bituminous substances; or
 - (c) Product of petroleum or mixture containing petroleum, as, when tested in the manner prescribed by or under the Petroleum (Consolidation) Act, 1928, gives off an inflammable vapour at a temperature of less than seventy three degrees Fahrenheit.