Dust Management Plan

Harriet's Poultry Farm

Overview

In the planning of the construction of the site layout consideration has been given siting main operational activities away from the nearest receptor to the Northwest of the site. Prevailing wind is from the southwest.

The following plan has been prepared as part of the EPR permit application.

The following tables highlight the likely sources of dust arising from broiler production at Harriet's Poultry Farm.

Actions and measures are listed that will prevent where possible or minimise dust emissions at Harriet's Poultry Farm.

Site plan shows all material storage areas and potential dust emission sources.

Plan to be reviewed every year from permit issue date, prior to any major changes to operations (to ensure effectiveness) or following any complaint, any changes to DMP or other management plans to be documented dated and signed and Area Officer notified.

Actions and preventative measures in DMP referenced from Bioaerosol Assessment Document and Fugitive Emissions Assessment in line with the H1 Risk Assessment, to be implemented in conjunction with the following key documents;

Emergency Plan

Technical Standards

Routine Maintenance Schedule

Key responsibility for the DMP and the referenced plans are the Operator or deputies who have been briefed on the requirements.

The table below lists receptors within 100m of the boundary

Receptor	Description	Distance	Orientation	National Grid
Name				Reference
Poolham	Commercial	5m	Northwest	521570 , 369351
Storage	Commercial	3	1401tilwest	321370,303331
Storage				

Dust Related Issue	Potential Risks and Problems	Actions taken to minimise dust risks at Harriet's Poultry Farm	Completion date
Feed delivery and storage	Release of dust when filling silos	Silo vents fitted with dust cyclones preventing dust release to atmosphere	In place
•		Any spillage of feed around the bin is immediately swept up.	In place
		The condition of feed bins is checked frequently so that any damage or leaks can be identified. Feed deliveries are monitored to avoid dust and spills.	In place
Manufacture and selection of feed	Milling and mixing of compound feeds.	No on-site milling and mixing. Sealed system. Feed drops minimised and hoppers covered	In place
		Feed specifications are prepared by the feed compounder's nutrition specialist. Feed is supplied only from UKAS accredited feed	In place
		mills, so that only approved raw materials are used.	In place

Bedding selection/material	Potential dust release	Use of dust extracted shavings spread inside each house, not blown in.	In place
Ventilation and heating Systems	Extraction fans located close to sensitive receptors.	Use of high velocity extraction fans to aid dispersion checked prior to cycle commencement by qualified electrician who will provide 24hr breakdown cover Poultry houses screened by extensive hedges. The ventilation and heating system is regularly adjusted to match the age and requirements of the flock. Humidity recorded daily and maintained in the range of 55 – 65% keeping a balance of dry litter and avoiding dust production. Stock inspections carried out by trained staff to avoid panicking birds creating dust. Ventilation outlets cleaned between cycles using low pressure washing minimising dust release	In place In place In place In place In place

Litter management	Dust arising from litter (see above).	Controls on feed and ventilation (see above) help to maintain litter quality. Stocking levels at optimum to prevent overcrowding. Use of veterinarian bespoke health plan. Use of dust extracted shavings.	In place
Carcase disposal	Inadequate storage of carcasses on site	Carcasses placed into plastic sealed bags, stored in sealed, shaded and vermin proof containers away from sensitive receptors.	In place
House clean out	Creation of dust associated with litter removal from houses	Houses sealed immediately following depletion of birds. Minimum ventilation employed during delittering, houses sealed immediately following delittering awaiting washing. Litter carefully placed into trailers positioned close to doors. Trailers sheeted before leaving fill position. Litter out carried out within 24 hours following destocking.	In place In place In place
Used litter	Transport of litter to third party.	All trailers sheeted before leaving fill position. Avoidance of double handling.	In place
Fugitive emissions	Leaks to doors, bin pipes, feed bins	Checks to feed storage and fill pipes as per routine maintenance schedule.	In place

Plan completed June 2025 Plan to be reviewed every year or following a substantiated complaint, or any changes to operations, with Area officer being notified of any changes for approval. Version 1 June 2025