



# **Landfill Gas Risk Assessment**

Meridian Water Waste Recovery Permit Application

March 2024

**Waterman Infrastructure & Environment Ltd** 

Pickford's Wharf, Clink Street, London SE1 9DG www.watermangroup.com



Client Name: Taylor Woodrow Construction

Document Reference: WIE16279-300-R-31-3-1-LGRA

Project Number: WIE16279

Project Document No: SIW-WAT-XX-XX-RP-W-000005

# Quality Assurance – Approval Status

This document has been prepared and checked in accordance with Waterman Group's IMS (BS EN ISO 9001: 2015, BS EN ISO 14001: 2015 and BS EN ISO 45001:2018)

IssueDatePrepared byChecked byApproved by31-3-1March 2024Robbie J Moore<br/>Senior ConsultantFreddie Alcock<br/>Technical DirectorFreddie Alcock<br/>Technical Director

£ 1/2

Comments



#### Disclaimer

This report has been prepared by Waterman Infrastructure & Environment Limited, with all reasonable skill, care and diligence within the terms of the Contract with the client, incorporation of our General Terms and Condition of Business and taking account of the resources devoted to us by agreement with the client.

We disclaim any responsibility to the client and others in respect of any matters outside the scope of the above.

This report is confidential to the client and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at its own risk.



# **Contents**

### **Glossary**

1.	Introd	uction	.1
	1.1	The Brief	.1
	1.2	Context	.1
	1.3	Report Structure and Scope	.2
	1.4	Limitations and Constraints	.3
2.	Conce	ptual Site Model - Landfill Gas	.4
	2.1	Ground Gas Risk	.4
	2.2	Sources	.4
	2.3	Pathways	.8
	Recept	tors	.9
3.	Landfi	II Gas Risk Assessment1	10
	3.1	The Nature of the Landfill Gas Risk Assessment	10
	3.2	The Proposed Assessment Scenarios	10
	3.3	Accidents and their Consequences	10
	3.4	Generated Gases to be Modelled	11
	3.5	Numerical Modelling	11
	3.6	Risks to the Environment and Human Health	11
	3.7	Landfill Gas Completion Criteria	12
4.	Landfi	II Gas Management1	13
	4.1	Control Measures	13
	4.2	Chemical Sampling Ahead of Emplacement	13
	4.3	Gas Monitoring	13
5.	Concl	usions1	14
	5.1	Compliance with the Landfill Directive 1999	14
Figu	ıres		
_	ıre 1:	Typical Landfilled Waste	.5

# **Appendices**

- A. Site Plans
- B. Exploratory Hole Logs for Source of Waste Area
- C. Collated Ground Gas Results for Source of Waste and Permitted Site Areas
- D. Ground Gas Generic Assessment Criteria



# **Glossary**

- The permitted site this refers to the proposed permitted area as defined in Plan D-ESSD1C.
- Meridian Water Strategic Infrastructure Works (SIW) the enabling works required in advance of the
  construction of Phase 2 of the Meridian Water Development. The works will occur across two
  adjacent areas termed Phase 1 SIW and Phase 2 SIW collectively 'the SIW site' for the purposes of
  the EP application documents.
- Development Zones (DZ) specific areas in Phase 2 Meridian Water Development referred to in
  planning documents. As shown on Plan D-ESSD1D. Edmonton Marshes flood relief storage basins –
  to be excavated at the eastern end of the site as part of the SIW in DZLV1. The waste the subject of
  this EP application will arise from excavation into the former Lee Valley Trading Estate landfill to
  create part of the flood relief storage basins.



## 1. Introduction

#### 1.1 The Brief

Waterman Infrastructure & Environment Limited ("Waterman") is instructed by Taylor Woodrow Construction, the civil engineering arm of Vinci Construction UK Limited ("the applicant" and "the operator") to prepare an application for an Environmental Permit (EP). The EP application is to authorise the permanent deposit of waste on land as a recovery activity. The waste recovery is for previously deposited (waste) soil and stones to be used in the Strategic Infrastructure Works at Meridian Water, Enfield, London (the "Permitted Site").

To support this EP application, a landfill gas risk assessment (LGRA) has been prepared detailing the potential for recovery of the waste to create a potential source for ground gas with risks to future site users and visitors at the completed area.

#### 1.2 Context

The Meridian Water scheme is a regeneration project led by the London Borough of Enfield (LBE). The permitted site is one small part of the wider Meridian Water scheme. The permitted site is centred at approximate National Grid Reference 535601 191831.

Overall, the Meridian Water scheme will deliver:

- 10,000 new homes;
- 6,000 high quality jobs, a further 10,000 construction jobs;
- new train station;
- schools, healthcare provisions and other local services; and
- naturalisation of the Pymmes Brook and improved waterside public green spaces.

The first phase of the scheme ("Meridian One") was granted full planning permission and is underway. The new Meridian Water station opened in 2019, the first new school in 2017 and the first 950 homes are scheduled for completion in 2026 at Willoughby Lane.

LBE is now bringing forward Phase 2 of the Meridian Water scheme. Phase 2 is a residential led mixed use scheme including up to 2,300 new homes, various non- residential uses including workspace and a new school. To enable Phase 2, the SIW are required to prepare the development area including the implementation of flood mitigation measures.

Earthworks material will be excavated from various locations across the SIW site where the level needs to be lowered to provide flood storage basins or to create a suitable development platform level. Some material will be suitable for reuse in earthworks without treatment, other material will require remediation (regulated by separate mobile treatment plant permit). Material confirmed to be suitable for reuse will be moved to various locations in the SIW site where levels need to be raised. The cut and fill locations are shown on plan D-ESSD4.

Most of the material to be excavated and / or treated will be reused in accordance with the Definition of Waste: Development Industry Code of Practice (DoWCoP). However, some excavation will be necessary in an area that is considered by the Environment Agency (EA) to be an historic landfill site (Lee Valley Trading Estate Landfill located at the eastern end of the SIW site and shown on plan D-ESSD2E).

The waste recovery green line boundary is shown on plan D-ESSD1C, with the SIW site boundary on plan D-ESSD1A. The actual locations where waste will be deposited will depend on the detailed sequencing of the works (so dependent on factors including progress of remediation works) and the time taken by the EA to determine the EP application. The balance of fill placed in the waste recovery areas will be placed in accordance with the DoWCoP.



Treatment of waste will be limited to sorting at the point of excavation to separately remove any gross contamination or large lumps of hard materials. Waste suitable for recovery will be stored in stockpiles, until required for use in earthworks in the permitted site. Waste may also be treated with lime or cement for moisture control and / or creation of capping material. Both applications will be for geotechnical improvement so should not require waste regulatory controls. However, should the EA disagree, the treatment will be carried out under mobile treatment plant permit and the relevant List of Waste codes included for in the waste recovery EP application.

### 1.3 Report Structure and Scope

The EP application requires a LGRA. This has been developed using relevant EA guidance,<sup>1</sup> and the template provided<sup>2</sup>. Any sections that are not applicable to the activity have been included for completeness with an explanation of why they are not relevant.

The conceptual model in its entirety is included in the Conceptual Site Model, Environmental Setting and Site Design (ESSD) report completed separately to this report and should be read in conjunction and referred to in addition to this document. A summary of the conceptual site model with a focus on ground gas is included within this document.

Technical information prepared for the Meridian Water Development Area has been utilised where appropriate, including but not limited to that prepared for:

- · the planning applications for the scheme;
- documents required to fulfil planning conditions (e.g. Construction Environmental Management Plan (CEMP);
- data and analysis from ground investigation;
- waste classification analysis of samples collected from the former landfill area;
- specification for materials suitable for reuse in the earthworks; and
- · detailed design (highways, drainage, landscaping).

Taylor Woodrow's general and environmental management policies and procedures are in place for the SIW construction site, and will be applied as appropriate to the permitted activities. Taylor Woodrow documents referred to are included elsewhere in the application bundle.

The LGRA will form part of the environmental management system (EMS) to be operated by the applicant for the lifetime of the EP. A copy of the LGRA and EMS will be kept in Taylor Woodrow's site office at Phase 1 SIW.

Where EA templates have been used to structure the report, any sections that are not applicable to the activity have been included for completeness. With an explanation of why they are not relevant.

Plans and drawings referred to in this report are to be found in the "ESSD drawings and information bundle" submitted as part of the EP application. In the text of this report the plans may be referred to in full or by abbreviated reference e.g. D-ESSD1A.

This report should be read alongside the "Conceptual Site Model, Environmental Setting and Site Design Report" (ESSD report) prepared by Waterman and included in the EP application.

<sup>&</sup>lt;sup>1</sup> https://www.gov.uk/government/publications/management-of-landfill-gas-lftgn-03 (accessed 30/05/2022).

<sup>&</sup>lt;sup>2</sup> https://www.gov.uk/government/publications/landfill-gas-risk-assessment-report-template (accessed 30/05/2022).



# 1.4 Limitations and Constraints

Waterman has endeavoured to assess all information provided to them during the preparation of this document. But makes no guarantees or warranties as to the accuracy or completeness of this information.

The conclusions resulting from this report are not necessarily indicative of future conditions or operating practices at or adjacent to the Permitted Site.



# 2. Conceptual Site Model - Landfill Gas

#### 2.1 Ground Gas Risk

As identified throughout available guidance including the CL:AIRE RB17 A Pragmatic Approach to Ground Gas Risk Assessment 2012 guidance document and CIRIA C665 document "Assessing Risks Posed by Hazardous Ground Gases to Buildings", ground gases only pose a risk when the following can be satisfied:

- an accumulation of a large volume of gas in the ground in or near the receptor (source).
- a pathway that allows gas to migrate through and/or out of the ground into a building or other structure sufficiently quickly to allow it to build up inside (pathway).
- a confined space within the building or structure where gas can build up to unacceptable levels (receptor).

In order for a risk from ground gases a source – pathway – receptor linkage needs to be present. This requires a sufficient quantity of gas to pose a hazard and one or more pathways by which it may cause significant harm to people and vegetation. For sustained gas migration to occur gas must be replenished at the source to negate the effects of attenuating factors such as oxidation of the methane to carbon dioxide in the aerobic zone or low permeability soils decreasing the migration potential. Therefore, sustained high levels of gas generation is required for ground gas to migrate via advective or diffusive flow and cause high ground gas concentrations at the surface/within built structures.

Critically it is the volume of ground gas which is the principal factor which should be considered rather than the ground gas concentration (or monitoring well concentration), which is commonly mistaken as posing a risk to future site users. The assessment of ground gas volume is based on a review of both ground gas flow data and ground gas concentration data. A risk will only be existent where sufficient flow is present in addition to high gas concentrations. Assessment of the risk based solely on gas concentrations is an outdated and incorrect methodology in determining whether a possible ground gas source poses a risk. A high gas concentration present without the ability to be emitted at the surface/receptor would not pose a risk.

#### 2.2 Sources

#### 2.2.1 Ground Gas Characteristics of Waste to be Recovered

For the purposes of this LGRA, excavation arisings from construction of the Edmonton Marshes flood relief storage basins in DZLV1, in the area to be agreed by the project remediation contractor with the EA to be historic landfill, will be the waste the subject of this waste recovery EP application. The maximum of extent is the area of historic landfill shown on plan D-ESSD2E. Data arising from the area shown on plan D-ESSD2E is discussed in its entirety.

Further detail on the historical development of the former "Lee Valley Trading Estate Landfill", and assessment of ground investigation data from DZLV1 is set out in the ESSD. No new sources of contamination are being introduced to the Permitted Site given that the former landfill is within the SIW boundary.

The area comprises material deposited during the land raising undertaken between the 1930s and 1950s. The waste encountered during previous ground investigations can be described as:

- in-situ natural soils including alluvium, sands and gravels but excluding highly compressible and degradable soils such as peat;
- previously placed reworked natural soils comprising principally natural soils and stones; and
- soils described as Made Ground but comprising principally natural soils.



An exploratory hole location plan for the source of waste area is included at Appendix A. Exploratory hole logs from previous ground investigation works across the source of waste area are included in Appendix B.

Chemically, the waste contains lower levels of contamination relative to land elsewhere in Phase 2 Meridian Water. Slightly elevated levels of some contaminants (lead, zinc, TPH and PAH) were recorded in the waste, however levels were not unusual for an urban setting. A summary of the laboratory data gathered during previous investigations is included in the Waste Acceptance Procedures (WAP) document included in the EP application bundle. Figure 1 shows typical ground conditions encountered by Arup during ground investigations of the historic landfill area<sup>3</sup>.





Left: Natural alluvium at the base of the trial pit. Right: layers of Made Ground within the mound including yellow brown sandy gravel and brown sand with grey sandy clay.

Ground gas monitoring was undertaken in two wells (DZLV1\_BH2073 and DZLV1\_BH2076) installed in undisturbed waste (Arup SIW ground investigation (2020) <sup>4</sup>. Ground gas monitoring wells are shown on Arup drawing No. 260636 Rev F1 (drawing 6) in the Arup SIW ground investigation report and Appendix A. DZLV1\_BH2073 was installed in the Made Ground with a response zone between 0.50 and 1.80m bgl. Made Ground at this location was described as including high proportion of masonry material including concrete and brick gravels and cobbles as well as gravelly clay with brick, concrete and flint. Evidence of a landfill was not encountered. Six monitoring rounds were completed.

DZLV1\_BH2076 was installed in the Alluvium with a response zone between 2.00 and 3.50m bgl. Two monitoring rounds were completed.

<sup>&</sup>lt;sup>3</sup> Arup (2021), Meridian Water SIW, Lee Valley Trading Estate Landfill - Technical Note (001).

<sup>&</sup>lt;sup>4</sup> Arup (2020), Strategic Infrastructure Work, Meridian Water - Ground Contamination Risk Assessment (REP/260637/CL/001).



Ground gas monitoring concentrations recorded from DZLV1\_BH2073 did not identify a significant ground gas regime (Characteristic Situation 1). Flow rate and methane concentrations were below instrument detection limits and carbon dioxide concentrations were low (below 4.3%). DZLV1\_BH2076 recorded a peak methane concentration of 23.5% and low oxygen concentrations (0.5%). Carbon dioxide concentrations of 3.7% and 8.3% were recorded. The flow rates (0.7l/hour) and high methane concentration equate to a Characteristic Situation 2 ground gas regime.

Ground gas baseline measurements collected during previous investigation works at the source of waste area are collated in Appendix C. Generic Assessment Criteria (GAC) used to assess the ground gas regime are included in Appendix D.

The absence of measurable sustained gas flow rates is typical of material in which only a low volume of organic content is present. Generally, where waste material with the potential to generate methane and other ground gases has been emplaced and remained undisturbed in place for a significant period of time (i.e. more than 20 years), aerobic digestion of organic material present (such as plant matter) occurs. This process produces methane and carbon dioxide which outflows to the surface until all oxygen within the waste is depleted. Following this, the remaining organic material is degraded anaerobically to produce carbon dioxide. However, once the anaerobic digestion commences, production of methane is significantly reduced and gas volumes outflowing to surface levels decrease. After the anaerobic digestion phase commences, gas outflows to surface generally occur at such low rates that they are not emitted at quantities sufficient to pose a risk to receptors, with the ground gas effectively entrained in the soil matrix and oxidising prior to being emitted at surface level.

The waste to be used primarily comprises clayey and sandy natural soils excavated to facilitate realignment of nearby waterways and construction of reservoirs. As such, the organic content of this material is lower than that of conventional 'landfill' material, which will contain organic matter such as plant and food waste, paper and waste wood. Testing for total organic carbon (TOC) on soil samples from the undisturbed waste recorded mean TOC concentrations of 1.75%. This indicates the material does not have a high organic carbon content which is consistent with the low ground gas generation potential of the waste.

The ground gas monitoring provides a body of quantitative evidence that the waste has a negligible ground gas generation potential, owing to the low quantity of readily degradable organic material present in the soil matrix. During the excavation and stockpiling of the waste prior to final placement, the residual low quantities of stabilised organic material will be exposed to aerobic conditions. The aerobic conditions will temporarily increase the biodegradation of the organic material further decreasing the quantum of organic material present post placement, further decreasing the wastes ground gas generation potential.

## 2.2.2 Ground Gas Characteristics of Existing Soils at Meridian Water

#### Phase 1

Ground gas monitoring within the SIW Phase 1 area was completed in 2020 as part of the Arup Detailed Quantitative Risk Assessment (SIW Phase 1)<sup>5</sup>, and by BWB<sup>6</sup> at plots DZ6 and DZ7.

As part of the SIW investigation, six monitoring wells were included in the ground gas monitoring network within DZ6, DZ7 and DZLV1. A maximum GSV of 21.6l/hr was calculated based on a maximum methane concentration of 81% and a flow rate of 26.7l/hr in DZLV1\_BH2076 (which screens the Alluvium). The PID reading on this monitoring round was 1.8ppm suggesting these methane concentrations cannot be attributed to high vapour concentrations. On the following monitoring visit (9th March 2021) a methane concentration of 44%v/v and flow rate of 9.9l/hr were recorded resulting in a GSV of 4.40l/hr.

<sup>&</sup>lt;sup>5</sup> Arup (2022) Strategic Infrastructure Works, Meridian Water - Detailed Quantitative Risk Assessment – SIW - Phase 1 (260637/REP/CL/003)

<sup>6</sup> BWB (March 2020) Phase 2 Geo-Environmental Risk Assessment (MWD-BWB-ZZ-XX-YE-RP-0001\_Ph2)



It should be noted this location screens the Alluvium which is logged as 1.9m thickness of gravelley clay underlain by 0.7m of dark brown peat which may be acting as a localised ground gas source. Outside of this location, the maximum gas Characteristic Situation is CS2 recorded in DZ7\_BH2059a with a maximum flow rate of 11.2l/hr and maximum carbon dioxide concentration of 0.9%.

The BWB investigation recorded the DZ6 and DZ7 areas as a CS1 due to only slightly elevated gas levels and negligible flows.

#### Phase 2

Ground gas monitoring in wells outside the landfill area and in the SIW Phase 2 area (DZ4 and DZ5) was undertaken as part of the Arup SIW ground investigation (2020). Twenty-three boreholes were installed with six rounds of monitoring completed in nine locations, and between five and three rounds in the remaining fourteen locations. The majority of monitoring standpipes were installed in Made Ground and Alluvium. These results, along with results of previous monitoring completed by the SLR Meridian Water ground investigation (2019)<sup>7</sup> recorded the following.

- Concentrations of carbon dioxide were above 5% at multiple locations over several rounds. Carbon dioxide concentrations ranged typically between 0.2% and 20.6%. A peak value of 71% v/v was recorded in DZ4\_WS1007 (SLR, 2019), however, the steady state value for this monitoring round was 0.4% v/v and maximum peak level on previous rounds was 13.9% v/v.
- Methane recorded predominantly at low concentrations or below the equipment's limit of detection during Arup ground gas monitoring. Concentrations above 1% were recorded in two locations: DZ4\_BH2042 (1.1% v/v and 1.3% v/v on two occasions) and DZ5\_BH2018 (3.1% v/v and 24.5% v/v). However, DZ5\_BH2018 targeted the Kempton Park Gravels and the screened section was entirely submerged, therefore the data was considered not to be reflective of potential gas risk at the proposed development. During SLR ground gas monitoring, methane concentrations above 1% were recorded in fourteen out of nineteen boreholes and a maximum concentration of 18.5% v/v was recorded in DZ4\_BH1005.
- Flow rates were generally below the equipment's detection limit (0.1l/hr). Flow readings greater than 0.1l/hr were recorded in nine locations and ranged between 0.71l/hr and 6.6l/hr, recorded in DZ4\_BH2018. However, as discussed above, the data was considered not to be reflective of potential gas risk at the proposed development.

All investigation locations including ground gas monitoring wells are presented on plan in Appendix A. The gas monitoring dataset considered is included in Appendix C.

The background ground gas concentrations identify the Made Ground and natural soils at the Phase 2 SIW area outside the former landfill as having a low risk from ground gas that requires only low levels of protection (CS2). The SLR (2019) assessment identified slightly higher risks (CS3) in the south of DZ4, however, this was based on a very conservative interpretation of the data. The background ground gas concentrations provide further evidence that significant volumes of ground gas are not being generated by the undisturbed waste.

The Made Ground across the wider Phase 2 Meridian Water site has a low concentration of organic matter and given its age since deposition (at least 70 years) it is expected to have a negligible ground gas generation potential. Previous ground gas monitoring (as detailed in Section 2.2.2) does not identify any significant ground gas concentrations including the lateral migration of ground gas from deposits outside the waste.

<sup>&</sup>lt;sup>7</sup> SLR (2019), Meridian Water, IKEA Clear Site - Ground Investigation Interpretative Report (409.05569.00004).



#### 2.2.3 Odour

Previous ground investigations<sup>8</sup> recorded the following information with regards to odour in the waste:

- In localised pockets the waste identified as Made Ground was recorded as having a distinct hydrocarbon odour (GTS-9-250 between 0.35m and 0.60m, DZLV1\_TT2006 at 0.40m).
- Soil headspace analysis of soil samples recorded low concentrations with a peak concentration of 4ppm.
- Soil laboratory analysis of sixty-nine samples from twenty-three exploratory locations was undertaken
  in the former landfill. Samples were predominantly from the Made Ground (70%) and generally
  recorded low volatile contaminant concentrations.

Aliphatic C5-C6: <0.01mg/kg - 0.0181mg/kg; Aliphatic C6-C8: <0.01mg/kg - 0.0952mg/kg; Aliphatic C8-C10: <0.01mg/kg - 0.108mg/kg;

Aliphatic C10-C12: <1mg/kg except for one sample (DZLV1\_TP2038) where concentration of 1.83mg/kg was recorded;

Aromatic C6-C7: <0.01mg/kg Aromatic C7-C8: <0.01mg/kg

Aromatic C8-C10: <0.01mg/kg - 0.0869mg/kg;

Aromatic C10-C12: <1mg/kg except for two samples: DZLV1\_TP2038 (2.78mg/kg) and

DZLV1\_TP2047 (11.9mg/kg);

Aromatic C12-C16: <1mg/kg - 6.54mg/kg excluding one sample (DZLV1\_TP2047) where concentration of 47.5mg/kg was recorded;

Naphthalene: <0.009mg/kg - 0.504mg/kg; and

Chlorinated Solvents and BTEX: <0.4mg/kg - <0.8mg/kg.

- Ground gas monitoring in boreholes installed within the undisturbed former landfill recorded hydrogen sulphide below the equipment's limit of detection on all occasions.
- The above confirms the waste has a negligible odour component. In addition, as part of the
  excavation process material in which gross visual or olfactory evidence for contamination will be
  excluded from being used at the Permitted Site and will require disposal off-site.

#### 2.3 Pathways

As discussed previously for a risk from ground gas risk there must be sufficient flow from the ground gas in the sub-surface environment into an enclosed space or vegetation root zone. The permeability of soil should therefore be considered when determining the potential for ground gas to reach the surface and migrate into a building.

The waste will be used below roads, footpaths and development plots in the completed development. Soils derived from the waste will be used under soft and hard landscaping at the Brooks Park naturalisation scheme and at Edmonton Marshes. Potential pathways to human health receptors in the completed development and emissions to atmosphere include:

- vertical migration into confined spaces (i.e. manhole chambers, service channels or small temporary structures above ground) where placed below building plots and public squares;
- lateral migration through preferential pathways such as service/utility ducts or through the surrounding soil matrix; and

<sup>&</sup>lt;sup>8</sup> Arup (2021), Meridian Water SIW, Lee Valley Trading Estate Landfill - Technical Note (001).



 vertical migration through cracks in the overlying hardstanding, or through soft landscaping for direct emission to the atmosphere.

Ground conditions outside the Permitted Site will comprise material placed under the DoWCoP regime during the proposed developments enabling works. This material will be rolled to compact it and provide a suitable development platform. The compacted Made Ground will have a low total porosity and effective porosity substantially restricting lateral migration of ground gases through it. The migration potential and emission risk of ground gases will be further restricted by the absence of a significant volume of ground gas.

There will be drainage runs within the deposited waste which could act as a preferential pathway for the migration of ground gases. However, given the expected low volume of ground gases (given the wastes low ground gas generation potential) and restricted migration potential within the waste due to its compaction, a significant volume of ground gas is not expected to accumulate within the drainage runs and migrate off-site.

Ground investigations undertaken by Arup<sup>9</sup> have classified the ground gas regime as CS2, with basic ground gas protection measures to be installed in the completed development to restrict ground gas migration. The ground gas protection measures will include ground gas membrane and suspended reinforced concrete slab to create a physical barrier. Services will be sealed where they gain entry to built structures in line with the requirements of CS2 classification. These protection measures will work to further break the pathway for ground gases to migrate through and accumulate in confined spaces in the completed development.

# Receptors

Potential receptors identified in the Meridian Water Development Area include:

#### During the Works:

- construction workers encountering ground gas while excavating service trenches on-site;
- migration of greenhouse gas to atmosphere contributing to global warming;
- exposure of nearby workers and the public neighbouring the site to odour.

#### At Completed Development:

- damage to vegetation and ecosystems from ground gas emissions; and
- future site users including maintenance workers, future residential occupants and commercial users and users of public open space from ground gas accumulation in confined spaces within structures;
- future buildings and structures from ingress of potentially explosive gases.

Human health receptors including construction workers and future residents / workers have an acute risk and therefore highest sensitivity to ground gas, whereas the global climate is a long-term risk and has a lower sensitivity than the risk to people posed by ground gas.

<sup>&</sup>lt;sup>9</sup> Arup (2020), Strategic Infrastructure Work, Meridian Water - Ground Contamination Risk Assessment (REP/260637/CL/001).



## 3. Landfill Gas Risk Assessment

#### 3.1 The Nature of the Landfill Gas Risk Assessment

The recovery of waste will involve the excavation of material already present at the SIW area in which the Permitted Site is located, and its use on the Permitted Site. A new potential ground gas generating source will not be introduced to the Meridian Water site. As evidenced by the qualitative and quantitative assessment of the waste prior to excavation and use, it has a low ground gas generation potential and is unlikely to pose a significant risk to identified receptors. This includes both from a bulk ground gas or odour perspective once in-situ.

The sensitivity of potential receptors is predominantly low on account of being predominantly roadways, footpaths and landscaped areas, however, areas of high sensitivity (new structures on development plots) are included within the proposed development to be constructed on the Permitted Site. Whilst the sensitivity of potential receptors is considered high, the low ground gas generation potential of the waste, absence of new ground gas source, and restriction of pathways means a detailed quantitative risk assessment would not be required and a qualitative assessment will instead be undertaken.

Given the low expected low ground gas generation potential of the material, significant quantities of ground gas will not be produced, and ground gas extraction and utilisation will not be required. Similarly, containment, collection and / or treatment systems would not be required.

# 3.2 The Proposed Assessment Scenarios

#### 3.2.1 Lifecycle Phases

The deposition of the waste will occur in phases as development progresses. Backfill will comprise placement of the material in layers with which will be compacted to the required density. Waste may also be treated with lime or cement for moisture control and / or creation of capping material. Waste with visual and / or olfactory signs of gross contamination will not be used in the earthworks.

A tracking system will be used to record the location and depth of placed material including confirmation it has passed chemical and geotechnical re-use criteria and is non-hazardous waste. Details of the tracking system used are set out in the WAP included in the EP application.

As identified in Section 2.2, the waste in situ has been demonstrated to have low organic matter content and therefore a low ground gas generation potential. During its excavation and stockpiling the creation of aerobic conditions will catalyse the degradation of residual organic matter resulting in a lower organic matter and ground gas generation potential upon its deposition in the Permitted Site. The volume of ground gas created following placement already considered to be negligible will therefore be even lower and steadily decrease over time as residual organic matter degrades or becomes unavailable for degradation (trapped in soil pores) (referred to as stabilised organic matter).

The presence of high methane/carbon dioxide concentrations is not uncommon from recently placed engineered material, and that this effect is pronounced should the material be saturated with groundwater and/or an anaerobic zone exists. Gas is generated in these occasions from small residual quantities of organic material that would be present even in natural soils / inert fill. The volume of gas generated is low. Therefore, a risk of being emitted at the surface also low.

Post placement ground gas monitoring is not a requirement of the planning process for this site.

# 3.3 Accidents and their Consequences

Earthworks across the SIW site will be undertaken using waste within the Permitted Site and non-waste elsewhere placed in accordance with the DoWCoP. Whilst tracking systems will be in place, the potential exists for the accidental placing of non-waste in the Permitted Site. Given the ground gas data available for the SIW site more generally (see Section 2.2.2) the accidental introduction of non-waste soils is unlikely to introduce a new ground gas generation source.



Visually or olfactorily grossly contaminated material will not be used. This will primarily be controlled through visual screening at excavation, a second check will be carried out during placement of the waste. If undetected pockets of household waste or asbestos containing materials for example are present within the former landfill, it will be easily identifiable in comparison to the typical waste, therefore the likelihood of a roque load of waste being used is low.

Owing to the low ground gas generation potential and incomplete pollutant linkages to controlled waters receptors as set out in the Hydrogeological Risk Assessment included in the EP application, neither a landfill gas management system nor a leachate containment / management system will be required. The degradation of such systems has therefore not been considered.

#### 3.4 Generated Gases to be Modelled

This section is not applicable. No modelling is proposed given the low potential for ground gas generation.

## 3.5 Numerical Modelling

#### 3.5.1 Justification for Modelling Approach and Software

This section is not applicable. No modelling is proposed given the low potential for ground gas generation.

#### 3.5.2 Model Parameterisation

This section is not applicable. No modelling is proposed given the low potential for ground gas generation.

#### 3.5.3 Sensitivity Analysis

This section is not applicable. No modelling is proposed given the low potential for ground gas generation.

#### 3.5.4 Model Validation

This section is not applicable. No modelling is proposed given the low potential for ground gas generation.

#### 3.6 Risks to the Environment and Human Health

#### 3.6.1 Landfill Gas Emissions

As identified in Section 2.2, the waste has a low ground gas generation potential which will be further reduced during excavation and stockpiling. Ground gas emissions from the waste in situ have been found to be negligible, and following use and emplacement is anticipated to further decrease over time as residual organic matter degrades or becomes unavailable for degradation (for example through gas capture within soil pores, referred to as stabilised organic matter). At no point following its deposition will significant ground gas emissions occur, with an overall decline following deposition anticipated.

## 3.6.2 Sub-Surface Migration and Vegetation Stress

For sustained ground gas migration to occur and a risk to receptors be present, a significant volume of ground gas is required to sustain the ground gas migration and replace the gas that has migrated. As evidenced in Section 2.2, the waste has a low ground gas generation potential which will decrease following deposition. A negligible volume of ground gas will therefore exist in the soil pore space following deposition which will not support sustained migration and a risk to on and off-site receptors.



The sub-surface migration (lateral and vertical) of ground gas will also be inhibited by the following aspects:

The waste material following deposition will be emplaced above cohesive Made Ground. The deposited waste material is anticipated to have a lower ground gas generation potential than the undisturbed Made Ground and would not therefore increase the ground gas risk.

New built structures in the completed development will incorporate CS2 protection measures which are to be determined by the plot developer. Potential measures include a ground gas membrane or suspended reinforced concrete slab to create a physical barrier.

New service ducts at the proposed development will be appropriately sealed where they gain entry to built structures in line with the requirements of CS2 classification to prevent them acting as preferential pathways for the migration of ground gases.

Given the above a negligible risk of ground gas migration and impact to receptors will exist.

### 3.6.3 Atmospheric Dispersion and Odour

Significant ground gas emissions including odour are not expected given the materials low ground gas generation potential and observations on the potential for odour as set out in Section 2.2.3. A landfill gas management plan will therefore not be required, and this section is not applicable.

#### 3.6.4 Exposure

Significant ground gas emissions (including odour) are not expected given the low ground gas generation potential of the waste, in conjunction with the migration pathway inhibitors. A low level of exposure to receptors from ground gases generated from the waste will exist.

#### 3.6.5 Global Atmospheric Impact

Significant ground gas emissions from the waste will not occur due to the low ground gas generation potential of the waste.

Where residual methane is present, monitoring of the waste in situ indicates the gas generation rates are at levels where methane will oxidise to oxygen and water vapour in the aerobic sub-surface environment prior to emission at surface level. This will further restrict the likely global atmospheric impact.

#### 3.7 Landfill Gas Completion Criteria

As identified in Section 2.2 the waste has a low ground gas generation potential. During excavation and stockpiling, oxygen will be introduced into the waste and residual organic matter catalysing its breakdown and further reducing the ground gas generation potential. The volume of ground gas created following placement will therefore be even lower and steadily decrease over time as residual organic matter degrades or becomes unavailable for degradation (trapped in soil pores) referred to as stabilised organic matter. The waste will therefore not pose a ground gas risk (pressure driven or diffusive flow) to the environment or human health receptors at any point in the waste life cycle and would therefore be considered as being 'completed' immediately after its deposition.



# 4. Landfill Gas Management

#### 4.1 Control Measures

The waste has low ground gas generation potential, and therefore landfill gas control measures are not required.

# 4.2 Chemical Sampling Ahead of Emplacement

As part of the Waste Acceptance Procedures (WAP), chemical quality sampling of the waste will be undertaken including TOC testing. The results of this TOC testing will represent an initial indicator for the potential for the used waste to generate ground gas after emplacement. Waste which exceeds the acceptability criteria for TOC will not be used.

# 4.3 Gas Monitoring

Ground gas monitoring is not required to satisfy the planning process.

Environment Agency guidance for waste recovery details that gas monitoring is required where a risk of gas is identified, and where waste is to be deposited more than two metres below the surrounding ground surface. Due to the nature of the waste with low potential to generate ground gas, and TOC screening measures to prevent potential gas-generating waste from being used, monitoring of the waste postemplacement is not proposed.



## 5. Conclusions

The EP will only allow the use of waste excavated from historic landfill present in DZVL1 within the Meridian Water Development Area, as shown on plans in the ESSD drawings bundle. Therefore, there will be no change to the ground gas regime and risk to off-site receptors.

The waste has been demonstrated during previous ground investigations through ground gas monitoring and assessment of its TOC concentration as having a negligible ground gas generation potential. This ground gas generation potential will decrease further during excavation and temporary stockpiling, in which the residual organic matter will be exposed to aerobic conditions catalysing its degradation. During and post completion of the waste deposition significant volumes of ground gas will not be produced and a risk to human health receptors on the wider Meridian Water Development Area and off-site will not occur.

Given the negligible ground gas generation of the waste significant surface emissions will also not occur which could impact the global atmosphere. Given the negligible risk to human health receptors and the global atmosphere, specific ground gas control measures to control the accumulation of ground gases would not be required.

Confirmatory TOC sampling will be undertaken for the waste pre-emplacement as part of Waste Acceptance Procedures. Should sampling identify elevated TOC concentrations above the acceptance criteria within sections of the waste, this material will be separated out and will not be used. This will ensure that material with the potential to generate ground gas is not used, and therefore gas monitoring will not be necessary.

Furthermore, Condition 16 for the Meridian Water Phase 2 planning application (MWP2 19-02718-RE3) requires that "prior to each phase of development approved by this planning permission no development shall commence until a remediation strategy to deal with the risks associated with contamination of the site in respect to the development hereby permitted, has been submitted to, and approved in writing by, the local planning authority". Development on each plot will be subject to ground gas protection measures dependant on the gas regime identified. Previous ground investigations classified the ground gas regime on the wider Meridian Water Development Area as being CS2 where basic ground gas protection measures will be required in the completed development. These protection measures will work to further break the pathway for ground gases to migrate through and accumulate in confined spaces in the completed development.

#### 5.1 Compliance with the Landfill Directive 1999

The waste will be used under a recovery activity EP, compliance with the 1999 Landfill Directive would therefore not be applicable.




# **APPENDICES**



# A. Site Plans

- Previous Ground Investigation Locations Relevant to the SIW
- Exploratory Hole Location Plan for the Source of Waste Area





SIW Boundary

Wider SIte Boundary

## Previous Ground Investigation

- Chalk Installation
- **SWB KPGR & Lambeth Group Installation**
- KPGR Installation
- KPGR & Lambeth Group Installation
- SLR Borehole
- Existing Borehole
- Surface Water Monitoring Location
- Trial Pit
- Trial Trench





Project Details

WIE16279-300: Meridian Water SIW

WIE116279-300\_GIS\_LGRA\_1A

Figure Title

Figure A1: Previous Ground Investigation Locations relevant to SIW


Figure Ref
Date

March 2024

File Location

N:\Projects\WIE16279-300\9\_GIS\WIE16279-300\_GIS\_LQD

www.watermangroup.com





SIW Boundary

Environmental Permit Boundary

#### **Previous Ground Investigation**

- Chalk Installation
- KPGR Installation
- Trial Pit
- Trial Trench





Project Details

WIE16279-300: Meridian Water SIW

Figure Title

Date

Figure B1: Previous investigation locations with soil chemical quality data completed within the historical landfill area

Figure Ref

Ma

File Location

March 2024

N:Projects\WIE16279-300\9\_GIS\WIE16279-300\_GIS\_LQD


www.watermangroup.com

WIE116279-300\_GIS\_HRA\_2B

© WATERMAN INFRASTRUCTURE & ENVIRONMENT
Reproduced from the Ordnance Survey maps with the permission of the Controller of Her Majesty's Stationery Office,© Crown copyright, Waterman Infrastructure & Environment, Pickfords Wharf, Clink Street, London SE1 9DG. Licence number 100023262.



B. Exploratory Hole Logs for Source of Waste Area



#### Shallow Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 27/02/2020 - 02/03/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536050.11 N192230.19 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: AE Drilling Equipment: Hand tools | Dando 2000 Borehole Number Hole Type Level Logged By Scale Page Number GI\_DZLV1\_BH2073 CP 10.69m AOD AW | JJ 1:50 Sheet 1 of 1 Sample and In Situ Testing Water Depth Leve Stratum Description Well Legend Strikes (m) (m) Depth (m) Results Type 0.00 - 0.10 Vegetation over dark brown slightly clayey slightly 0.00 - 0.50 sandy SILT with occasional gravel and occasional rootlets. Sand is fine and medium. Gravel is 0.50 - 0.60ES subangular to subrounded fine to coarse concrete and flint. 0.80 D 0.80 10.69 [MADE GROUND] 0.80 - 0.90ES Greyish brown slightly sandy slightly gravelly CLAY. 0.80 - 1.20 В Sand is fine to coarse. Gravel is angular to 1.20 - 1.65 UT Ublow = 10subrounded fine to coarse concrete and flint. Rec. = 100% [MADE GROUND] 1.65 - 1.70 1.70 - 2.15UT Ublow = 13 1.80 9.89 Soft orangish brown sandy CLAY with rootlets. Sand is Rec. = 100% fine and medium. D [ALLUVIUM] 2.20 1.80 - 1.90 2.15 - 2.20 ES Very soft grey mottled brownish grey slightly sandy CLAY with occasional rootlets. Sand is fine and D 2.20 medium. 2.20 - 2.65 UT Ublow = 15 2.70 8.49 [ALLUVIUM] Rec. = 100% Medium dense greyish brown multicoloured very 2.65 - 2.70 D sandy GRAVEL. Sand is fine to coarse. Gravel is 2.70 - 3.00 В subangular to subrounded fine to coarse flint. D 3.00 - 3.45 [KEMPTON PARK GRAVEL FORMATION] 3.00 - 3.50 В 3.00 SPT N=10 (2,2/2,2,3,3) 3.75 EW 3.75 EW 3.75 EW EW 3.75 4.00 - 4.45 D 4.00 - 4.50 В 4.00 SPT N=19 (3,4/4,4,5,6) 4.80 7.99 4.80 D Stiff dark grey slightly sandy silty CLAY. Sand is fine UT 4.80 - 5.25 Ublow = 485 and medium. Rec. = 100% [LONDON CLAY FORMATION] 5.25 - 5.30 5.30 - 5.75 D UT Ublow = 45Rec. = 100% 5.75 - 5.80 D 5.80 - 6.25 6 5.80 SPT N=16 (2,3/3,4,4,5) 6.25 5.89 End of Borehole at 6.25m 8 9

#### Remarks

Depth Base

Hole Diameter

Diameter

Casing Diameter

Diameter

250 200

Depth Base

2.50 5.30

1. Position CAT scanned prior to digging, 2. Position hand dug to 1.20 m bgl - clear of services, 3. Position cored using 300 mm bit. 4. Water encountered at 2.70 m bgl. 5. Environmental seal installed at 1.30 m to 2.30 m. 6. Borehole terminated at 6.25 m bgl. 7. Dual 50 mm standpipe installation - response zone from 0.5 m to 1.80 mbgl and 3.00 m to 4.50 m with gravel filter pack, 8. Borehole back filled with bentonite.

Depth Top Depth Base Duration

Chiselling

Tool

10

Orientation

Inclination and Orientation

Depth Top Depth Base Inclination

		: Meridiar Ground I			Clier	nt: Lon	don B	oroug	h of Enfiel	ld		Date: 1	3/02/20	20 - 25/	02/2020	0	
-		idian Wat	- 23		Cont		: Grou	nd Te	chnology (	Services	1	Co-ord	s: E5359	994.44 [	N19214	5.22	
ojec	t No. : (	GTS-19-2	50			v Nam	e: AE							ent: Bei	retta T4	1   Dand	o 400
Borehole Number Hole Type				Level Logged By								age Num					
SI_D	_DZLV1_BH2074 RC Water Sample and In Situ Testing				15.91m AOD			AW   JJ			1:25 Sheet 1			heet 1 of	10		
/ell	Water Strikes	Depth (		*	-	TCR	Coring	RQD	Legend	Depth (Level)			Stratum	Descrip	tion		
		0.50 - 0. 0.50 - 0. 0.50 - 0. 0.50	00 B		ppm						GRA plast is an cond	WEL with	subangu I flint.	nal fragn d is fine	nents of to coars	metal e. Gravel	
		1.50 - 1. 1.50 - 1. 1.50 - 1. 1.50	60 ES		opm						1.00 i pocke		50 m occ	 casional _	soft cla	ay	N II
		2.00 - 2.	.10 D														
		2.50 2.50 - 2. 2.50 - 2. 2.50 - 3. 2.50	60 ES		opm					2.50 (15.91)	coar	se. Grav	ly sandy rel is angu oncrete a UND]	ular to su	bangula	ne to ir fine to	
		3.00 - 3. 3.00 - 3. 3.00		Γ N=4 (1,1/1,	1,1,1)												
		3.60 3.60 - 3. 3.60 - 3. 3.60 - 4. 3.60 4.00 - 4. 4.00 - 4.	70 ES 00 B PII 45 D	PID = 0 ;						3.60 (13.41)	wood fine	d fibres.	d brown g Gravel is lium flint. UND]	angular			4
		4.50 4.50 - 4. 4.50 - 4. 4.50 4.50	95 U1	Ublow = Rec. = 10	00%						£						
	Hole Diam			ng Diameter					selling		4				g Flush		
pth I	Base I	Diameter	Depth Bas	e Diameter	Dept	th Top	Depth	Base	Duration	Too	ol	Depth Top (m)	Depth Base (m)	Flush Type	Flush Colou	ır Min (%)	Max

# Remarks

<sup>1.</sup> Position CAT scanned prior to digging. 2. Position hand dug to 1.20 m bgl - clear of services. 3. Position cored using 300 mm bit. 4. Water encountered at 8.30 m bgl. 5. Environmental seal installed at 6.20 m to 7.20 m and 10.20 m to 11.20 m. 6. Borehole terminated at 49.45 m bgl. 7. Single 50 mm standpipe installation - response zone from 44.00 m to 49.00 m bgl with gravel filter pack. 8. Borehole back filled with cement grout and bentonite. 9. Cable percussion drilling to 12.20 with Rotary drilling to base of the borehole.

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E535994.44 N192145.22 Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2074 15.91m AOD AW | JJ 1:25 Sheet 2 of 10 RC Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) Depth (m) SCR RQD TCR Type Results 5.00 - 5.45 Ublow = 26 Dark grey and brown gravelly CLAY with rare Rec. = 100% wood fibres. Gravel is angular to subangular fine and medium flint. [MADE GROUND] 5.45 - 5.50 D 5.50 - 5.60 ES 5.50 - 5.60 ES 5.50 - 5.95 UT Ublow = 28 Rec. = 100% 5.50 PID PID = 0 ppm5.95 - 6.00 D 6.00 - 6.45 UT Ublow = 10 Rec. = 100% 6.45 - 6.50 D 6.50 - 6.60 ES 6.50 - 6.60 ES Ublow = 16 6.50 - 6.95 UT 6.70 Rec. = 100% Soft brownish grey mottled greenish grey silty (12.31)PID PID = 0 ppm CLAY. [ALLUVIUM] 6.95 D 7.00 - 7.45 UT Ublow = 25Rec. = 100% 7.45 - 7.50D 7.50 - 7.60 FS 7.50 - 7.60 7.50 - 7.95 ES UT Ublow = 32Rec. = 100% 7.80 PID PID = 0 ppm 7 50 Soft to firm brown very sandy CLAY. Sand is (9.21)fine to coarse. 7.95 - 8.00 [ALLUVIUM] 8.00 8.00 - 8.45 D Loose multicoloured very clayey very sandy (8.11)8.00 - 8.50 В GRAVEL. Sand is fine to coarse. Gravel is 8.00 SPT N=8 (1,1/2,2,2,2) subrounded to subangular fine and medium [KEMPTON PARK GRAVEL FORMATION] 9 9.50 - 10.00 9.50 - 9.95 D 9.50 SPT N=11 (1,2/2,2,3,4) 10 Drilling Flush Hole Diameter Casing Diameter Chiselling Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

#### Remarks

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E535994.44 N192145.22 Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2074 15.91m AOD AW | JJ 1:25 Sheet 3 of 10 RC Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) SCR Depth (m) TCR RQD Type Results Loose multicoloured very clayey very sandy GRAVEL. Sand is fine to coarse. Gravel is subrounded to subangular fine and medium [KEMPTON PARK GRAVEL FORMATION] 10.70 D 10.70 Very stiff brown fissured slightly sandy 10.70 - 11.15 UT Ublow = 25(7.91)micaceous CLAY. Sand is fine and medium. Rec. = 100% Fissures are randomly orientated extremely closely spaced predominantly undulating rough with occasional planar smooth. [LONDON CLAY FORMATION] 11.15 - 11.20 D 11.20 - 11.65 UT Ublow = 30 Rec. = 100% 11.65 - 11.70 D 11.70 - 12.15 D 11.70 - 12.20 В 11.70 SPT N=19 (2,3/4,4,5,6) 12 12.20 - 13.00 PP PP = 1.9 kg/cm<sup>2</sup> 12.20 12.50 - 12.60 ES PP 12.50 $PP = 1.6 \text{ kg/cm}^2$ 100 12 50 PID PID = 0 ppm12.80 PP $PP = 1.5 \text{ kg/cm}^2$ 13.00 - 13.50 13 13.00 - 14.50 13.10 PP $PP = 1.8 \text{ kg/cm}^2$ 13.40 PP $PP = 0.9 \text{ kg/cm}^2$ PP 13.70 $PP = 1.1 \text{ kg/cm}^2$ 100 14.00 - 14.50 14 14.00 PP $PP = 1.2 \text{ kg/cm}^2$ 14.30 PP PP = 1.2 kg/cm<sup>2</sup> 14.50 - 14.95 14.50 - 16.00 C SPT 14 50 N=18 (2,3/3,4,5,6) PP 14.60 $PP = 1.1 \text{ kg/cm}^2$ PP 14.90 PP = 1.2 kg/cm<sup>2</sup> 15 -Drilling Flush Hole Diameter Casing Diameter Chiselling Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

#### Remarks

<sup>1.</sup> Position CAT scanned prior to digging. 2. Position hand dug to 1.20 m bgl - clear of services. 3. Position cored using 300 mm bit. 4. Water encountered at 8.30 m bgl. 5. Environmental seal installed at 6.20 m to 7.20 m and 10.20 m to 11.20 m. 6. Borehole terminated at 49.45 m bgl. 7. Single 50 mm standpipe installation - response zone from 44.00 m to 49.00 m bgl with gravel filter pack. 8. Borehole back filled with cement grout and bentonite. 9. Cable percussion drilling to 12.20 with Rotary drilling to base of the borehole.

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E535994.44 N192145.22 Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2074 15.91m AOD AW | JJ 1:25 Sheet 4 of 10 RC Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) SCR RQD Depth (m) TCR Type Results Very stiff brown fissured slightly sandy micaceous CLAY. Sand is fine and medium. Fissures are randomly orientated extremely 15 20 PP $PP = 2.6 \text{ kg/cm}^2$ closely spaced predominantly undulating rough with occasional planar smooth. [LONDON CLAY FORMATION] 15.50 PP $PP = 2.4 \text{ kg/cm}^2$ 100 15.80 PP $PP = 2.6 \text{ kg/cm}^2$ 16.00 - 16.10 16.00 - 16.45 16.00 - 17.50 16.00 SPT N=19 (1,3/3,5,5,6) 16.10 PP $PP = 2.4 \text{ kg/cm}^2$ PP 16.40 $PP = 2.4 \text{ kg/cm}^2$ 16.70 PP $PP = 2.4 \text{ kg/cm}^2$ 100 17.00 - 17.50 В 17 PP $PP = 2.5 \text{ kg/cm}^2$ 17.00 PP 17.30 $PP = 2.5 \text{ kg/cm}^2$ 17.50 - 17.95 17.50 - 19.00 C SPT 17 50 N = 46(4,7/11,13,11,11) PP 17.60 $PP = 2.6 \text{ kg/cm}^2$ PP 17.90 $PP = 2.5 \text{ kg/cm}^2$ 18 18.20 PP $PP = 2.5 \text{ kg/cm}^2$ 87 18.50 PP $PP = 2.6 \text{ kg/cm}^2$ PP 18.80 $PP = 2.7 \text{ kg/cm}^2$ 18.90 - 19.00 D 19.00 - 19.35 D 19 19.00 - 20.50 PP $PP = 0.4 \text{ kg/cm}^2$ 19.00 19.00 SPT 50 (5,13/50 for 195mm) 19.30 PP = 1.2 kg/cm<sup>2</sup> 19.40 Very stiff to hard brownish blue mottled red (5.21)100 slightly sandy CLAY. Sand is fine and medium. [LAMBETH GROUP] PP 19.60 $PP = 2.8 \text{ kg/cm}^2$ 19.70 - 19.80 FS 19.70 PID PID = 0 ppmPP 19 90 $PP = 3.0 \text{ kg/cm}^2$

#### Remarks

Depth Base

Hole Diameter

20.00 - 20.10

Diameter

D

Depth Base

Casing Diameter

Diameter

1. Position CAT scanned prior to digging. 2. Position hand dug to 1.20 m bgl - clear of services. 3. Position cored using 300 mm bit. 4. Water encountered at 8.30 m bgl. 5. Environmental seal installed at 6.20 m to 7.20 m and 10.20 m to 11.20 m. 6. Borehole terminated at 49.45 m bgl. 7. Single 50 mm standpipe installation - response zone from 44.00 m to 49.00 m bgl with gravel filter pack. 8. Borehole back filled with cement grout and bentonite. 9. Cable percussion drilling to 12.20 with Rotary drilling to base of the borehole.

Depth Top Depth Base Duration

Chiselling

Tool

20

Drilling Flush

Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Co-ords: E535994.44 N192145.22 Location: Meridian Water, Enfield Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2074 RC 15.91m AOD AW | JJ 1:25 Sheet 5 of 10 Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) SCR RQD Depth (m) TCR Type Results Very stiff to hard brownish blue mottled red 20.10 - 20.50 В slightly sandy CLAY. Sand is fine and medium. [LAMBETH GROUP] PP 20 20 $PP = 3.1 \text{ kg/cm}^2$ 20.50 - 20.95 20.50 - 22.00 C PP 20.50 $PP = 2.8 \text{ kg/cm}^2$ 20.50 SPT N=31 (3,5/6,8,8,9) 20.80 PP $PP = 2.7 \text{ kg/cm}^2$ 21.00 - 21.10 D 21 21.10 PP PP = 2.6 kg/cm<sup>2</sup> 21.20 - 22.00 В 100 PP 21.40 $PP = 2.1 \text{ kg/cm}^2$ $PP = 2.1 \text{ kg/cm}^2$ 21.70 PP 22.00 - 22.27 D 22 22.00 - 23.50 C PP $PP = 2.0 \text{ kg/cm}^2$ 22.00 50 (3,8/50 for SPT 22.00 122mm) $PP = 2.1 \text{ kg/cm}^2$ 22.30 22.50 m to 23.35 m becoming very sandy. 22.60 PP $PP = 2.3 \text{ kg/cm}^2$ Sand is fine and medium 100 22.90 - 23.00 PP 22.90 $PP = 2.0 \text{ kg/cm}^2$ 23 23.20 PP $PP = 2.6 \text{ kg/cm}^2$ 23.35 Very dense bluish light green silty SAND. Sand (-3.49)is fine and medium. 23.50 - 23.67 [LAMBETH GROUP] 23.50 - 25.00 23.50 SPT 50 (8,17/50 for 24.00 - 25.00 В 24 100 25.00 - 25.38 25.00 25 Hole Diameter Chiselling Drilling Flush Casing Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

#### Remarks

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Co-ords: E535994.44 N192145.22 Location: Meridian Water, Enfield Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2074 RC 15.91m AOD AW | JJ 1:25 Sheet 6 of 10 Sample and In Situ Testing Corina Water Depth Well Legend Stratum Description Strikes (Level) SCR RQD Depth (m) Results TCR Type 25.00 - 26.50 (-7.44)Very dense dark grey slightly silty SAND. Sand 25.00 SPT 50 (4,11/50 for is fine and medium. [THANET SAND FORMATION] 230mm) 25.30 - 25.40 FS 25.30 PID PID = 0 ppm33 26.00 - 27.00 В 26.50 - 26.74 26.50 - 28.00 D С 26.50 SPT 50 (6,18/50 for 86mm) 60 27.00 - 27.10 D 27 100 100 28.00 - 28.31 28 28.00 - 29.00 В 28.00 - 29.50 50 (2,10/50 for 28.00 SPT 156mm) 100 29 29.50 - 29.95 D 29.50 - 31.00 C SPT 29 50 N = 50(3,5/8,11,13,18)30.00 - 30.10 D 30 Hole Diameter Chiselling Drilling Flush Casing Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

<b>G</b> F			L	Je	ep	RO	ren	Ole	e L	og				
Project Name: Meridi	an Water HI	F and	Client: Lor	ndon B	orough	of Enfiel	d		Date: 1	3/02/20:	20 - 25/	02/2020	)	
Infrastructure Ground Location: Meridian W		711	Contractor						Co-ords	- F5350	994.44 N	J19214	5 22	
	2883		Limited										1   Dand	o 4000
Project No. : GTS-19-			Crew Nam			3	1.5		Hand	tools				
Borehole Number GI_DZLV1_BH2074	0	e Type RC		evel Im AOI	D		gged By W   JJ			Scale 1:25			ige Num neet 7 of	
Well Water Strikes Depth		Situ Testing Results	TCR	Coring	RQD	Legend	Depth (Level)			Stratum	Descript	ion		
31.00 - 31.00 - 31.1	31.45 D 32.50 C		100	SCR	RQD			is fine	e and me	edium.	slightly s		D. Sand	31 —
32.50 - 32.50 - 32.5 33.00 -	34.00 C 50 SPT	N=50 (3,5/50 255mm)	0 0											33 —
34.00 -	34.24 D		100											34
34.00 - 34.00 - 34.00 - 34.0	35.00 B 35.50 C	50 (4,7/50 fi 90mm)	100 100											34 —
														35 —
Hole Diameter  Depth Base Diameter	Casing Depth Base	Diameter Diameter	Depth Top	Depth	Chise Base	elling Duration	Tool		Depth Top (m)	Depth Base (m)	Drillin Flush Type	g Flush Flush Colou	Min (%)	Max (%)
Remarks	.,		p 22 1 2 p	- , , , , ,			.30				.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		100	

rastructure	e: Meridian e Ground In	Water HIF	and	5.4		1.70	h of Enfiel		Date: 13/02/2020 - 2	25/02/2020		
7.0	ridian Wate		•	Contract Limited	or: Gro	und Te	chnology S	Services	C0-0108. E333994.4			
oject No. :	GTS-19-25	0		Crew Na	me: AE	c K			Drilling Equipment:   Hand tools	Beretta T41   Dan	do 400	
Borehole			Type RC	Level 15.91m AOD				gged By	Scale 1:25	Page Number Sheet 8 of 10		
GI_DZLV1_ Water	T		Situ Testing	15.8	Coring			W   JJ Depth	ill.		10	
ell Strikes		P	Results	TCF	-1	RQD	Legend	(Level)	Stratum Desc			
35.50 - 35 35.50 - 37 35.50			50 (4,12/50	100					Very dense dark grey slight is fine and medium. [THANET SAND FORMATI			
	36.00 - 36.	10 D	82mm)	100	ī						36	
	37.00 - 37. 37.00 - 37. 37.00 - 38. 37.00	50 B	50 (4,11/50 95mm)	for			× × × × × × × × × × × × × × × × × × ×				37	
	38.00 - 38.	10 D		100							38	
	38.50 - 38. 38.50 - 40. 38.50	00 C SPT	50 (4 10/50 151mm)								38	
Hole Diai			Diameter Diameter	Depth Top	Depth	Chis	selling  Duration	Тоо		rilling Flush Type Flush Colour Min (%	40 ) Max	

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Co-ords: E535994.44 N192145.22 Location: Meridian Water, Enfield Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2074 RC 15.91m AOD AW | JJ 1:25 Sheet 9 of 10 Sample and In Situ Testing Corina Water Depth Well Stratum Description Legend Strikes (Level) SCR RQD Depth (m) Results TCR Type 40.00 - 41.50 Very dense dark grey slightly silty SAND. Sand 40.00 SPT 50 (2,6/50 for is fine and medium. [THANET SAND FORMATION] 135mm) 100 41.00 - 41.10 D 41.50 - 41.85 41.50 - 43.00 D С 41.50 SPT 48 (3,10/48 for 202mm) 42.00 - 42.50 В 42 100 43.00 - 43.38 43.00 - 44.50 43.00 Weak, medium density, off white CHALK. C (-9.09)Fractures are medium spaced, sub horizontal to 50 (4,10/50 for 43.00 SPT vertical tight planar rough clean. (CIRIA Grade 230mm) 43.30 - 43.40 **IWHITE CHALK GROUP -**43.30 PID PID = 0 ppmUNDIFFERENTIATED] 100 87 44.00 - 44.50 В 44 44.50 - 44.95 D 44.50 - 46.00 44.50 SPT N=31 (3,5/6,8,8,9) 45.00 - 45.10 45 Hole Diameter Chiselling **Casing Diameter Drilling Flush** Depth Base Diameter Depth Base Depth Top Depth Base Duration Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%) 43.00

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 13/02/2020 - 25/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Co-ords: E535994.44 N192145.22 Location: Meridian Water, Enfield Limited Drilling Equipment: Beretta T41 | Dando 4000 Project No.: GTS-19-250 Crew Name: AE | Hand tools Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2074 RC 15.91m AOD AW | JJ 1:25 Sheet 10 of 10 Sample and In Situ Testing Corina Water Depth Well Legend Stratum Description Strikes (Level) SCR RQD Depth (m) Type Results TCR Weak, medium density, off white CHALK. Fractures are medium spaced, sub horizontal to vertical tight planar rough clean. (CIRIA Grade [WHITE CHALK GROUP -UNDIFFERENTIATED] 100 96 96 46.00 **EW** 46.00 - 46.45 46.00 - 47.50 D C 46.00 SPT N=33 (4,6/6,8,8,11)EW 46.50 100 73 73 47 47.50 - 47.89 47.50 - 49.00 D C SPT 50 (5,7/50 for 47.50 235mm) 48 100 53 53 49.00 - 49.45 49 49.00 N=40 (5,8/8,10,10,12)End of Borehole at 49.45m (-27.09)) 50 Hole Diameter Chiselling Drilling Flush Casing Diameter Depth Base Diameter Depth Base Depth Top Depth Base Tool Flush Colour Max (%) epth Base (m) Flush Type Min (%) 43.00 47.50 30 47.50 49.00 Water White

# Remarks

#### Shallow Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 28/01/2020 - 04/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536068.97 N192015.95 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: MS Drilling Equipment: Hand Tools | Dando 2000 Borehole Number Hole Type Level Logged By Scale Page Number GI\_DZLV1\_BH2076 WS 11.80m AOD 1:25 Sheet 1 of 2 JJ Sample and In Situ Testing Water Depth Leve Well Legend Stratum Description Strikes (m) (m) Depth (m) Results Type Strong light grey CONCRETE. 10-20 % aggregate of subrounded to subrounded fine to medium flint gravel. 0.15 - 0.330.18 11.80 10-20 % small voids. 0.20 D [MADE GROUND] 0.20 - 0.30FS 0.33 11.62 Yellowish brown sandy clayey GRAVEL with some 0.20 PID PID = 0 ppmcobble content. Sand is fine to coarse. Gravel is 0.30 - 0.80 В angular to subrounded fine to coarse of concrete brick 0.40 - 0.50FS and flint. Cobble is angular and subangular of PID PID = 0 ppm0.40 concrete. 0.50 D [MADE GROUND] Soft dark grey slightly sandy gravelly silty CLAY with 0.80 - 1.20В low cobble content. Sand is medium. Gravel is angular 0.90 - 1.00 FS to subrounded medium to coarse of concrete brick 0.90 PID PID = 0 ppmand flint. Cobble is angular to subangular of concrete 1.00 D [MADE GROUND] 1.20 cSPT N=3 (1,0/1,1,0,1) 1 65 D 1.90 11.47 Soft silty slightly gravelly CLAY with bands of soft light 2.00 - 2.45 UT Ublow = 19 grey sandy clay with shell fragments. Sand is fine to Rec. = 100% medium. Gravel is subrounded to rounded fine to medium of flint. [ALLUVIUM] 2 45 D 2.70 - 3.00В 300 - 345UT Ublow = 18Rec. = 100% 3.45 D 3.70 - 3.803.70 - 3.80 В 3.80 9.90 Soft dark brown and black silty pseudo-fibrous PEAT. 3.80 - 4.00 [ALLUVIUM] ale ale ale UT 4.00 - 4.45 Ublow = 19 e alle alle alle alle alle Rec. = 100% sile sile ale ale ale ale ale alte alte alte alte alte

Hole Diameter Casing Diameter Chiselling Inclination and Orientation

Depth Base Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top Depth Base Inclination Orientation

5.00 250 5.00 250

8.00

ale ale ale

Medium dense grey sandy GRAVEL. Sand is fine to coarse. Gravel is subangular to subrounded fine to

5

[KEMPTON PARK GRAVEL FORMATION]

# Remarks

4.45

5 00

D

cSPT N=19 (2,4/4,5,5,5)

1. Position cored and inspection pit dug to 1.20 m using hand tools - position clear of services. 2. Hole advanced to 8.00 m using cable percussive drilling techniques 3, Environmental seal installed from 4.00 m to 5.00 m. 4. Dual install with 50 mm pipe. Response zones from 2.00 m to 3.50 m and 5.00 m to 17.70 m.

4.50

### Shallow Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 28/01/2020 - 04/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536068.97 N192015.95 Limited Project No.: GTS-19-250 Crew Name: MS Drilling Equipment: Hand Tools | Dando 2000 Borehole Number Hole Type Level Logged By Scale Page Number 11.80m AOD GI\_DZLV1\_BH2076 WS 1:25 Sheet 2 of 2 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Medium dense grey sandy GRAVEL. Sand is fine to coarse. Gravel is subangular to subrounded fine to [KEMPTON PARK GRAVEL FORMATION] 5.45 D 5.60 - 6.00 В 6.00 cSPT N=22 (5,6/5,6,6,5) 6.35 EW 6.45 D 7.00 cSPT N=23 (6,5/5,6,6,6) D 7.45 7.70 7.70 EW 7.30 Firm to stiff brownish grey fissured CLAY. Fissures are 7.70 - 8.00В randomly orientated extremely closely spaced predominantly undulating rough with occasional planar 8 00 - 8 45 UT Ublow = 28[LONDON CLAY FORMATION] Rec. = 100% 8.45 D 8.50 - 8.95 UT Ublow = 29 Rec. = 100% 8.95 - 9.40 N=21 (4,5/5,5,5,6) 9.40 4.10 End of Borehole at 9.40m 10 Hole Diameter Chiselling Inclination and Orientation Casing Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Tool Depth Top Depth Base Inclination Orientation

# Remarks

1. Position cored and inspection pit dug to 1.20 m using hand tools - position clear of services. 2. Hole advanced to 8.00 m using cable percussive drilling techniques 3. Environmental seal installed from 4.00 m to 5.00 m. 4. Dual install with 50 mm pipe. Response zones from 2.00 m to 3.50 m and 5.00 m to 7.70 m.

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 10/02/2020 - 05/03/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536079.63 N191985.60 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS Dando 2000 Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2077 11.90m AOD AW | JJ 1:25 RC Sheet 1 of 8 Sample and In Situ Testing Coring Depth Well Stratum Description Legend Strikes (Level) SCR Depth (m) Results TCR RQD Type Strong light grey CONCRETE. 45-55 % aggregate subangular to subrounded fine and medium flint gravel. 10 % small voids. [MADE GROUND] 0.31 - 0.85 В 0.31 Brown sandy GRAVEL. Sand is fine to coarse. (11.90)0.40 - 0.50ES Gravel is angular to subangular fine to coarse 0.50 D concrete brick and flint. [MADE GROUND] 0.50 ES 0.50 PID PID = 0 ppm0.85 - 1.20 В 0.85 Grey silty slightly sandy slightly gravelly CLAY. Sand is fine to coarse. Gravel is subrounded to 0.90 - 1.00 ES (11.59)0.90 PID PID = 0 ppmrounded fine to coarse flint brick and concrete. [MADE GROUND] 1.20 - 1.65 1.20 cSPT N=2 (1,0/1,0,1,0) 1.50 - 1.60ES 1.50 PID PID = 2 ppm1.60 1.60 D Low strength, stiff slightly sandy slightly gravelly (11.05)1.60 - 2.00 CLAY with occasional organic debris. Sand is fine and medium. Gravel is subrounded to rounded fine and medium flint. [ALLUVIUM] 2.00 - 2.45 UT Ublow = 12Rec. = 100% D 2.45 EW 2.75 3.00 - 3.45UT Ublow = 15Rec. = 100% 3.45 D UT 4.00 - 4.45 Ublow = 9Rec. = 100% 4.40 - 4.60 В

Hole Diameter Casing Diameter Chiselling Drilling Flush

Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

2.00 250 250 250

4.90

(10.30)

Medium dense multicoloured sandy GRAVEL.

5

# Remarks

4.45

4.60 - 5.00

5.00

D

В

N=13 (2,3/3,3,3,4)

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 10/02/2020 - 05/03/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536079.63 N191985.60 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS Dando 2000 Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2077 11.90m AOD AW | JJ 1:25 Sheet 2 of 8 RC Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) SCR RQD Depth (m) Results TCR Type Medium dense multicoloured sandy GRAVEL. Sand is fine to coarse. Gravel is subangular to subrounded fine to coarse flint. [KEMPTON PARK GRAVEL FORMATION] 5.45 D 5.75 EW 6.00 SPT N=14 (3,4/3,4,4,3) 6.20 - 6.50 В High strength, very stiff brown fissured slightly (7.00)gravelly slightly sandy micaceous CLAY. Sand is fine to coarse. Gravel is subangular to 6.45 D subrounded fine and medium flint. Fissures are 6.50 - 6.95 Ublow = 24 UT randomly orientated extremely closely spaced Rec. = 100% predominantly undulating rough with occasional 6.50 - 8.00 planar smooth. 6.50 - 8.00 C [LONDON CLAY FORMATION] 6.80 ES 6.80 PID PID = 0 ppm6.95 D 7.00 - 7.45 UT Ublow = 26 Rec. = 100% PP = 2.6 kg/cm<sup>2</sup> 7.10 77 PP = 2.6 kg/cm<sup>2</sup> 7.10 PP 7.45 D SPT N=16 (3,3/4,4,4,4) 7.45 PP 7.60 $PP = 2.6 \text{ kg/cm}^2$ PP $PP = 2.6 \text{ kg/cm}^2$ 7.60 7.90 $PP = 2.4 \text{ kg/cm}^2$ PP 7.90 $PP = 2.4 \text{ kg/cm}^2$ 8.00 - 8.50 D 8.00 - 9.50 C 8.00 SPT N=7 (1,2/1,2,2,2) PP 8.20 $PP = 2.6 \text{ kg/cm}^2$ PP PP = 2.6 kg/cm<sup>2</sup> 8.20 8.50 - 8.60 D 8.60 $PP = 2.7 \text{ kg/cm}^2$ 8.60 PP $PP = 2.7 \text{ kg/cm}^2$ 100 9.00 PP = 2.6 kg/cm<sup>2</sup> 9 PP $PP = 2.6 \text{ kg/cm}^2$ 9.00 9.50 - 10.02 D 9.50 m rare subrounded gravel. Gravel is 9.50 - 11.00 В fine and medium 9.50 - 11.00 C 9.50 PP $PP = 2.6 \text{ kg/cm}^2$ 9.50 PP $PP = 2.6 \text{ kg/cm}^2$ 9.50 SPT N=10 (1,2/2,2,2,4) 10

# Remarks

Depth Base

Hole Diameter

Diameter

Casing Diameter

Diameter

Depth Base

1. Position CAT scanned prior to digging. 2. Position hand dug to 1.20 m bgl - clear of services. 3. Position cored using 300 mm bit. 4. Water encountered at 2.80 m bgl. 5. Environmental seal installed at 1.10 m to 2.10 m and 5.70 m to 6.70 m. 6. Borehole terminated at 35.27 m bgl. 7. Dual 50 mm standpipe installation - response zone from 1.50 m to 4.00 m, and 5.00 m to 6.50 m bgl with gravel filter pack. 9. Borehole back filled with cement grout and bentonite. 10. Cable percussion drilling to 7.45 with Rotary drilling to base of the borehole.

Depth Top Depth Base Duration

Chiselling

Tool

Drilling Flush

Min (%) Max (%)

Depth Top (m) Depth Base (m) Flush Type Flush Colour

#### Deep Borehole Log Project Name: Meridian Water HIF and Date: 10/02/2020 - 05/03/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536079.63 N191985.60 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS Dando 2000 Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2077 11.90m AOD AW | JJ 1:25 Sheet 3 of 8 RC Sample and In Situ Testing Coring Water Depth Well Legend Stratum Description Strikes (Level) SCR RQD Depth (m) Results TCR Type High strength, very stiff brown fissured slightly gravelly slightly sandy micaceous CLAY. Sand is fine to coarse. Gravel is subangular to subrounded fine and medium flint. Fissures are randomly orientated extremely closely spaced predominantly undulating rough with occasional planar smooth. 93 [LONDON CLAY FORMATION] 11.00 - 11.52 D 11.00 - 12.50 11.00 SPT N=13 (2,2/2,3,4,4) 100 12 12.50 - 12.95 12.50 - 14.00 C PP PP = 1.6 kg/cm<sup>2</sup> 12.50 SPT 12 50 N=14 (2,2/3,3,4,4) PP 12.80 $PP = 1.5 \text{ kg/cm}^2$ 13.00 - 13.50 В 13 13.10 PP $PP = 1.8 \text{ kg/cm}^2$ 100 13.40 PP $PP = 0.9 \text{ kg/cm}^2$ PP 13.70 $PP = 1.1 \text{ kg/cm}^2$ 14.00 - 14.52 14 14.00 - 15.50 14.00 PP $PP = 1.2 \text{ kg/cm}^2$ SPT N=22 (3,5/5,5,6,6) 14.00 14.30 PP PP = 1.2 kg/cm<sup>2</sup> 100 PP 14.60 $PP = 1.1 \text{ kg/cm}^2$ PP $PP = 1.2 \text{ kg/cm}^2$ 14.90 15.00 - 15.10 D 15 Hole Diameter Chiselling Casing Diameter **Drilling Flush** Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%) 14.00

# Remarks

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 10/02/2020 - 05/03/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536079.63 N191985.60 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS Dando 2000 Borehole Number Hole Type Page Number Level Logged By Scale GI\_DZLV1\_BH2077 11.90m AOD AW | JJ 1:25 RC Sheet 4 of 8 Sample and In Situ Testing Water Corina Depth Well Stratum Description Legend Strikes (Level) Depth (m) TCR SCR RQD Type Results High strength, very stiff brown fissured slightly PP 15 10 PP = 2.6 kg/cm<sup>2</sup> gravelly slightly sandy micaceous CLAY. Sand is fine to coarse. Gravel is subangular to subrounded fine and medium flint. Fissures are randomly orientated extremely closely spaced PP = 2.4 kg/cm<sup>2</sup> 15.40 PP predominantly undulating rough with occasional planar smooth. 15.50 - 15.95 [LONDON CLAY FORMATION] 15.50 - 17.00 15.50 SPT N=22 (2,3/3,5,7,7) 15.70 PP PP = 2.6 kg/cm<sup>2</sup> 16.00 - 16.50 16 PP $PP = 2.4 \text{ kg/cm}^2$ 16.00 100 PP 16.30 PP = 2.4 kg/cm<sup>2</sup> PP 16.60 PP = 2.4 kg/cm<sup>2</sup> PP 16.90 $PP = 2.5 \text{ kg/cm}^2$ 17.00 - 17.42 D 17 17.00 - 18.50 SPT N=52 (7,8/52 for 17.00 250mm) PP $PP = 2.5 \text{ kg/cm}^2$ 17.10 PP PP = 2.6 kg/cm<sup>2</sup> 17.40 17.50 - 17.60 D 17.50 Very high strength, very stiff brown fissured (5.70)slightly sandy CLAY. Sand is fine. [LONDON CLAY FORMATION] PP 17.70 $PP = 2.5 \text{ kg/cm}^2$ 100 18.00 - 18.10 18 18.00 PP $PP = 2.5 \text{ kg/cm}^2$ 18.30 - 18.50 18.30 PP $PP = 2.6 \text{ kg/cm}^2$ 18.50 - 18.95 Very stiff bluish light grey mottled orangish red 18.50 - 20.00 (-5.60)slightly sandy silty CLAY. Sand is fine and 18.50 PP $PP = 1.0 \text{ kg/cm}^2$ medium 18.50 SPT N=26 (3,4/5,6,8,7) [LAMBETH GROUP] 18.80 - 18.90 ES PP 18.80 $PP = 1.1 \text{ kg/cm}^2$ PID 18.80 PID = 0 ppm19 19.00 - 19.50 19.10 PP $PP = 1.5 \text{ kg/cm}^2$

Hole Diameter Casing Diameter Chiselling Diameter Chiselling Double Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

14.00 17.00 Water Grey 70 70

20

# Remarks

19.40

19.70

20.00 - 20.45

PP

PP

D

 $PP = 2.2 \text{ kg/cm}^2$ 

 $PP = 1.4 \text{ kg/cm}^2$ 

1. Position CAT scanned prior to digging, 2. Position hand dug to 1.20 m bgl - clear of services, 3. Position cored using 300 mm bit. 4. Water encountered at 2.80 m bgl. 5. Environmental seal installed at 1.10 m to 2.10 m and 5.70 m to 6.70 m. 6. Borehole terminated at 35.27 m bgl. 7. Dual 50 mm standpipe installation - response zone from 1.50 m to 4.00 m, and 5.00 m to 6.50 m bgl with gravel filter pack. 9. Borehole back filled with cement grout and bentonite, 10. Cable percussion drilling to 7.45 with Rotary drilling to base of the borehole.

100



# Deen Rorehole Log

	긔						L	)e	ер	Bo	reh	Ol	e L	og				
Project N Infrastruc	lame cture	: Meridian Ground In	Water	r HIF	1					n of Enfiel			Date: 1	0/02/20	20 - 05/0	03/2020	)	
Location:						Contra Limite		Grou	nd Ted	chnology S	Services	3	Co-ord:	s: E5360	079.63 N	V19198	5.60	
Project N	lo. : (	GTS-19-2	50					e: AR-	-MS				Drilling Dando		ent: Fra	ste PLC	Hand	tools
Boreho GI_DZL		E-80-67 million 12 million 1	]1		Type RC	1		vel m AOI	ס		ged By W   <mark>J</mark> J		Darido	Scale 1:25		100	ge Numb heet 5 of	
	ater	Sam Depth (r	F"		Situ Testing Results		TCR	Coring	RQD	Legend	Depth (Level)			Stratum	Descript	tion		
		20.00 - 2° 20.00 20.00 20.30	1.50 F S	C PP SPT PP	PP = 1.1 kg/ci N=24 (4,5/5,6,6 PP = 1.8 kg/ci	m² 6,7)	TOX	SON	KGD			sligh med		silty CL	rey mottle AY. Sand			
		20.60		PP PP	PP = 0.9 kg/cl		100											-
		21.00 - 21	1.10	D PP	PP = 1.2 kg/c													21 -
		21.50 - 2 <sup>3</sup> 21.50 - 23 21.50 21.50	3.00 F	D C PP SPT	PP = 1.2 kg/ci 50 (6,8/50 fc													-
		21.80 22.00 - 22	2.10 F	PP D	205mm) PP = 1.1 kg/c	m²												22 -
		22.10 22.40		PP PP	PP = 1.2 kg/cl	24	100											
		22.70		PP	PP = 2.4 kg/cl													-
		23.00 - 23 23.00 - 24 23.00 23.00	1.50 F S	D C PP SPT	PP = 2.6 kg/ci 50 (5,5/50 fc 280mm)					× × × × × × × × × × × × × × × × × × ×	23.00 (-6.60)	med	lium.		ty SAND.		fine and	- 23 -
		23.30 - 23 23.30 23.30 23.60	F	ES PP PID PP	PP = 2.4 kg/ci PID = 0 ppn PP = 2.4 kg/ci	m :m²	67			X								-
		23.90 24.00 - 24	1.50	PP B	PP = 2.6 kg/c	-1				X X X X X X X X X X X X X X X X X X X								24 -
		24.20 24.50 - 24		PP D	PP = 2.4 kg/c	em²				X X X X X X X X X X X X X X X X X X X								
		24.50 - 26 24.50 - 26 24.50 24.50	5.00 F S	C PP SPT	PP = 2.6 kg/cr 50 (4,7/50 fo 200mm) PP = 2.4 kg/cr	or												
		25.00 - 25		D	7.1 - 2.4 kg/C	-				×××× ××××	1	-						25 -
	e Diam				Diameter					elling		4			-	g Flush		
Depth Base	e [	Diameter	Depth B	Base	Diameter	Depth	Тор	Depth	Base	Duration	Too	ol	17.00	21.50	Flush Type Water	Flush Colour Grey	80	Max (%) 80
													21.50 23.00	24.00 24.50	Water Water	Grey Grey	70 85	70 85

# Remarks

1. Position CAT scanned prior to digging. 2. Position hand dug to 1.20 m bgl - clear of services. 3. Position cored using 300 mm bit. 4. Water encountered at 2.80 m bgl. 5. Environmental seal installed at 1.10 m to 2.10 m and 5.70 m to 6.70 m. 6. Borehole terminated at 35.27 m bgl. 7. Dual 50 mm standpipe installation - response zone from 1.50 m to 4.00 m, and 5.00 m to 6.50 m bgl with gravel filter pack. 9. Borehole back filled with cement grout and bentonite. 10. Cable percussion drilling to 7.45 with Rotary drilling to base of the borehole.

#### Deep Borehole Log Project Name: Meridian Water HIF and Date: 10/02/2020 - 05/03/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536079.63 N191985.60 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS Dando 2000 Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2077 RC 11.90m AOD AW | JJ 1:25 Sheet 6 of 8 Sample and In Situ Testing Corina Water Depth Well Legend Stratum Description Strikes (Level) SCR RQD Depth (m) TCR Type Results Very dense slightly silty SAND. Sand is fine and 25 10 PP $PP = 2.4 \text{ kg/cm}^2$ [THANET SAND FORMATION] 25.40 PP $PP = 2.4 \text{ kg/cm}^2$ 40 25.70 PP $PP = 2.5 \text{ kg/cm}^2$ 26.00 - 26.45 D 26 26.00 - 27.50 C 26.00 SPT N=36 (5,6/5,9,10,12) 100 27.00 - 27.10 D 27 100 27.50 - 27.95 27.50 - 29.00 C SPT N=32 (4,5/6,8,9,9) 27 50 28 00 - 28 10 D 28 53 29.00 - 29.45 29 29.00 - 29.50 В 29.00 - 30.50 C 29.00 SPT N=44 (5,6/6,8,15,15)80 30 Hole Diameter Chiselling Drilling Flush Casing Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%) 24.50 27.50

# Remarks

# Deep Borehole Log Project Name: Meridian Water HIF and Date: 10/02/2020 - 05/03/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536079.63 N191985.60 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS Dando 2000 Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2077 RC 11.90m AOD AW | JJ 1:25 Sheet 7 of 8 Sample and In Situ Testing Corina Water Depth Well Legend Stratum Description Strikes (Level) SCR RQD Depth (m) Results TCR Type Very dense slightly silty SAND. Sand is fine and [THANET SAND FORMATION] 30.50 - 30.86 30.50 - 32.00 DC SPT 50 (6,13/50 for 30.50 210mm) 31.00 - 31.10 D 31 73 32.00 - 32.30 32.00 - 33.50 D 32 C SPT N=50 (6,14/50 for 32.00 150mm) 0 33 33.50 - 33.82 33.50 - 34.25 33.50 SPT N=50 (6,18/50 for 34.00 - 34.10 D 34.25 - 35.00 C 93 35.00 - 35.27 35 Hole Diameter Chiselling Drilling Flush Casing Diameter

#### Depth Base Diameter Depth Base Diameter Depth Top Depth Base Tool Max (%) pth Base (m) Flush Type Min (%) 27.50 30.50 30.50 33.50 20 20 Water Grey 34.25

# Remarks

	G	_				De	ep	Во	reh	ole	e Lo	og				
			l n Water HII nvestigatio		Client:	ondon	Boroug	h of Enfie	ld	E	) ate: 10	/02/20	20 - 05/	(03/2020	 )	
			er, Enfield	n	Contrac	tor: Gro	1.00	chnology		, ,	o-ords:	E536	079.63	N19198	5.60	
		GTS-19-2	2005		Limited Crew N	ame: Al	R+MS				Drilling E	quipm			G   Hand	tools
	ehole N			е Туре	E.T.W.	Level		Lo	gged By		Dando 2	Scale		Pa	age Num	ber
GI_E	ZLV1_	BH2077	12	RC		.90m A0	DD	Α	W   JJ			1:25		S	sheet 8 o	f 8
Well	Water Strikes	San Depth (		Situ Testing Results		Corir	7	Legend	Depth (Level)			Stratum	Descrip	tion		
		35.00		50 (7,18/50 120mm)	for			× × ×		Very d mediu		ghtly sil	ty SAND	. Sand is	fine and	3/2
				12011111	"			× × × × × ×	25.27		NET SAN	ID FOR	MATION	1]		
									35.27 - (-11.10)		Enc	d of Bore	ehole at 3	35.27m		36
																38
																39 -
							+									40 -
	Hole Diam		_	Diameter				selling			-		-	ng Flush	1	
Depth I	Base	Diameter	Depth Base	Diameter	Depth T	op   Dept	h Base	Duration	Too	DI D	epth Top (m) D	epth Base (m	Flush Typ	e Flush Colou	Min (%)	Max (%)
2.80 m installat	ion CAT s bgl. 5. En ion - resp	vironmental onse zone f	seal installed rom 1.50 m to	Position hand of at 1.10 m to 2.10 4.00 m, and 5.0 .45 with Rotary	0 m and 5.	70 m to 6. 0 m bal w	70 m. 6. E ith gravel	Borehole terr filter pack, 9	ninated at 3	35.27 m b	gl. 7. Dua	1 50 mm	standpip			

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 04/02/2020 - 26/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536090.69 N191921.12 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS+BS Dando 2000 Borehole Number Hole Type Page Number Level Logged By Scale GI\_DZLV1\_BH2080 10.57m AOD AW | JJ RC 1:25 Sheet 1 of 7 Sample and In Situ Testing Coring Depth Well Stratum Description Legend Strikes (Level) Depth (m) TCR SCR RQD Type Results Strong grey CONCRETE. 50-60 % aggregate subangular to subrounded fine to coarse flint 0.18 - 0.42 0.18 gravel. 20 % small voids. 0.20 - 0.30ES (10.57)[MADE GROUND] 0.20 PID PID = 0 ppmBlack and grey sandy gravelly CLAY with 0.30 D medium cobble content. Sand is medium and 0.42 0.42 - 1.20 0.45 - 0.60 coarse. Gravel is angular to subangular fine to (10.39)ES coarse concrete brick and flint. Cobbles are 0.45 PID PID = 0 ppmangular to subangular red brick and concrete. [MADE GROUND] Grey dark grey and black silty sandy slightly gravelly CLAY with burnt wood fragments. Sand is fine and medium. Gravel is subangular to 1.00 D subrounded fine and medium flint and brick [MADE GROUND] 1.20 - 1.65 1.20 N=8 (2 for 2mm/1,2,3,2) 1.60 В 1.60 Soft to firm grey slightly sandy slightly gravelly (10.15)CLAY. Sand is fine to coarse. Gravel is subangular to subrounded fine to coarse flint. [ALLUVIUM] 2.00 - 2.45 UT Ublow = 16 2.00 Loose to medium dense multicoloured clayey Rec. = 100% (8.97)very sandy GRAVEL. Sand is fine to coarse. 2.00 - 2.60 В Gravel is subangular to subrounded fine to [KEMPTON PARK GRAVEL FORMATION] D 2 45 2.60 - 3.00 В 3.00 cSPT N=7 (1,0/1,2,2,2) 3.45 D 4.00 4.00 cSPT N=14 (2,2/3,3,4,4) 4.45 D 4.50 EW 4.50 EW

# Depth Base Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

Chiselling

5

Drilling Flush

# Remarks

Hole Diameter

4.87

5.00

EW

Casing Diameter

cSPT N=17 (3,4/4,4,4,5)

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 04/02/2020 - 26/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536090.69 N191921.12 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS+BS Dando 2000 Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2080 10.57m AOD AW | JJ 1:25 Sheet 2 of 7 RC Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) SCR RQD Depth (m) Results TCR Type Loose to medium dense multicoloured clayey very sandy GRAVEL. Sand is fine to coarse. Gravel is subangular to subrounded fine to [KEMPTON PARK GRAVEL FORMATION] 5.45 D 6.00 cSPT N=19 (4,4/5,4,5,5) 6.45 D 6.60 - 7.00 В 7.00 - 7.45 UT 7.00 Ublow = 27High strength, very stiff brown fissured slightly Rec. = 100% (8.57)micaceous CLAY. Sand is fine and medium. Fissures are randomly orientated extremely closely spaced predominantly undulating rough with occasional planar smooth [LONDON CLAY FORMATION] 7.45 UT 7.50 - 7.95Ublow = 29Rec. = 100% 7.60 C 7.60 - 9.10 В PP $PP = 3.0 \text{ kg/cm}^2$ 7.60 ES 7.90 - 8.00 PP 7.90 $PP = 3.0 \text{ kg/cm}^2$ 7.90 PID PID = 0 ppm7.95 D 7.95 SPT N=18 (3,4/4,4,5,5) PP 8.20 $PP = 3.0 \text{ kg/cm}^2$ 100 8.50 PP $PP = 3.0 \text{ kg/cm}^2$ PP 8.80 $PP = 3.0 \text{ kg/cm}^2$ 9 9.10 - 10.60 D 9.10 - 9.55 PP PP = 2.9 kg/cm<sup>2</sup> 9.10 SPT N=20 (3,3/20 for 9.10 0mm) PP $PP = 3.0 \text{ kg/cm}^2$ 9.40 100 PP PP = 2.9 kg/cm<sup>2</sup> 9.70 10.00 $PP = 2.9 \text{ kg/cm}^2$ 10 Chiselling Drilling Flush Hole Diameter Casing Diameter Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)

# Remarks

<sup>1.</sup> Position CAT scanned prior to digging. 2. Position hand dug to 1.20 m bgl - clear of services. 3. Position cored using 300 mm bit. 4. Water encountered at 2.10 m bgl. 5. Environmental seal installed at 1.10 m to 2.10 m and 6.10 m to 7.10 m. 6. Borehole terminated at 31.82 m bgl. 7. Dual 50 mm standpipe installation - response zone from 3.00 m to 5.00 m, and 17.60 m to 19.60 m bgl with gravel filter pack. 8. Borehole back filled with cement grout and bentonite. 9. Cable percussion drilling to 8.40 with Rotary drilling to base of the borehole.

#### Deep Borehole Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 04/02/2020 - 26/02/2020 Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536090.69 N191921.12 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS+BS Dando 2000 Borehole Number Hole Type Logged By Page Number Level Scale GI\_DZLV1\_BH2080 10.57m AOD AW | JJ 1:25 Sheet 3 of 7 RC Sample and In Situ Testing Coring Water Depth Well Stratum Description Legend Strikes (Level) SCR Depth (m) TCR RQD Type Results High strength, very stiff brown fissured slightly micaceous CLAY. Sand is fine and medium. Fissures are randomly orientated extremely closely spaced predominantly undulating rough 10.30 PP $PP = 3.1 \text{ kg/cm}^2$ with occasional planar smooth. [LONDON CLAY FORMATION] 10.42 - 10.52 D 10.60 - 11.05 C PP 10.60 - 12.10 10.60 PP = 3.1 kg/cm<sup>2</sup> 10.60 SPT N=22 (2,3/22 for 0mm) 97 12 12.10 - 12.65 D 12.10 - 12.60 12.10 - 13.60 В C N=29 (4.5/29 for 12 10 SPT 0mm) 100 13 13.60 - 14.05 13.60 - 15.10 13.60 PP PP = 2.6 kg/cm<sup>2</sup> 13.60 SPT N=31 (5,5/31 for 0mm) 13.90 PP $PP = 2.5 \text{ kg/cm}^2$ 14 14.20 PP $PP = 3.0 \text{ kg/cm}^2$ 100 14.50 PP $PP = 2.9 \text{ kg/cm}^2$ 14.70 - 14.80 D 15 Chiselling Hole Diameter Casing Diameter **Drilling Flush** Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%) Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool 13.60

# Remarks



# Deep Borehole Log

	P						L	Je	ep	BO	ren	Ol	е∟	og				
		: Meridian Ground Ir				Clien	nt: Lon	don B	oroug	h of Enfiel	d		Date: 0	4/02/20	20 - 26/	02/2020	)	
	1 10.50	idian Wat		-5				: Grou	nd Te	chnology (	Services	i	Co-ord:	s: E536	090.69 1	V19192	1.12	
		GTS-19-2	200			<u>Limit</u> Crev		e: AR-	+MS+	BS					nent: Fra	ste PLC	3   Hand	tools
	ehole N	2 2		Hole	Туре	E WEN	7	evel	21.150		ged By		Dando	2000 Scale		Pa	ige Numi	ber
		BH2080			RC		10.57	m AOI	D		W   JJ		0.	1:25			heet 4 of	
Well	Water Strikes		-		Situ Testing			Coring	r	Legend	Depth (Level)			Stratum	n Descript	tion		
	Ourkes	Depth (r	m)	Туре	Results	-	TCR	SCR	RQD		(LCVCI)	High	strenath	very st	iff brown	fissured	slightly	-
		15.10 - 15 15.10 - 16 15.10 - 16 15.10 15.10 15.40	5.60 5.60	D B C PP SPT PP PP	PP = 3.1 kg/c N=41 (4,5/8,10,10,10,10,10,10,10,10,10,10,10,10,10,	13) cm²	100					mica Fissi close with	aceous C ures are ely space occasior	LAY. Sar randomly ed predom nal plana	nd is fine y orientat minantly r smooth RMATION	and med ed extrei undulatir	lium. mely	
		16.00 16.30		PP PP	PP = 3.0 kg/c													16
		16.60 - 16 16.60 - 18 16.60 16.60 16.60 16.90 17.10	3.10	D C PP SPT PP EW PP	PP = 3.2 kg/c 50 (6.10/50 f 85mm) PP = 3.1 kg/c	for cm²	3											17 —
* • • • • • • • • • • • • • • • • • • •		17.50		PP	PP = 2.8 kg/c	cm²	93											- - - - - - -
		17.80 18.10		PP EW	PP = 3.1 kg/c	cm²					18.10	Voru	etiff to b	ard light	blue mot	tlad rad s	slightly	18 —
		18.10 - 18 18.10 - 19 18.10 - 19 18.10 18.10	9.60 9.60	D B C PP SPT	PP = 3.0 kg/c N=36 (4,5/6,9,10,1						(3.57)	sand		Sand is	fine and i			
		18.40 - 18 18.40 18.40 18.60 18.60 18.70	0.00	ES PP PID EW PP PP	PP = 2.5 kg/c PID = 0 ppr PP = 2.7 kg/c PP = 2.7 kg/c	cm² m cm²	100											19
		19.50 19.60 - 19	9.98	PP.	PP = 2.9 kg/c	cm²					19.60	Very	/ dense o	rev sligh	tly silty S	AND Sa	and is	
		19.60 - 21 19.60 - 21 19.60 19.90 - 20 19.90	0.00	B C SPT ES PID	N=50 (4,7/50 230mm) PID = 0 ppr						(-7.53)	fine	to coarse	e.	RMATION			20 -
	Hole Diam	eter		Casing	Diameter					elling					_	g Flush		
Depth	Base	Diameter	Depth	Base	Diameter	Dept	th Top	Depth	Base	Duration	Too	ol	Depth Top (m) 13.60	Depth Base (m	Flush Type Water	Flush Colour Grey	Min (%)	Max (%)
													15.10 18.10	18.10 19.60	Water Water	Grey Grey	80 90	80 90

# Remarks

### Deep Borehole Log Project Name: Meridian Water HIF and Date: 04/02/2020 - 26/02/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Contractor: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536090.69 N191921.12 Limited Drilling Equipment: Fraste PLG | Hand tools | Project No.: GTS-19-250 Crew Name: AR+MS+BS Dando 2000 Borehole Number Hole Type Level Logged By Page Number Scale GI\_DZLV1\_BH2080 RC 10.57m AOD AW | JJ 1:25 Sheet 5 of 7 Sample and In Situ Testing Corina Water Depth Well Legend Stratum Description Strikes (Level) SCR RQD Depth (m) Type Results TCR Very dense grey slightly silty SAND. Sand is fine to coarse [THANET SAND FORMATION] 21 21.10 - 21.29 21.10 - 22.60 С SPT 21.10 50 (25 for 90mm/50 for 100mm) 7 21.90 - 22.00 D 22 22.60 - 23.05 22.60 - 24.10 22.60 - 24.10 В SPT N=50 (6,13/50 for 22.60 295mm) 80 23 85 24 24.10 - 24.50 D 24.10 - 25.60 SPT N=50 (5,8/50 for 24.10 250mm) 100 25.00 - 25.10 25 Hole Diameter Chiselling Casing Diameter **Drilling Flush** Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%) Depth Base Diameter Depth Base Diameter Depth Top Depth Base Duration Tool 22.60

# Remarks

4					D	eep	Bo	reh	ole Log			
ject Name			on l			1.00	h of Enfiel		Date: 04/02/2020	0 - 26/02/	2020	
cation: Me	at 15 streets		1		or: Gr	ound Te	chnology :	Services	Co-ords: E53609	0.69 N19	1921.12	
ject No. :	GTS-19-2	50		Limited Crew Na	me: A	R+MS+	BS		Drilling Equipme	nt: Fraste	PLG   Hand	tools
Borehole N	171.5		le Type	BTANNA A	Level	A.D. LITTLEY 1		gged By	Dando 2000 Scale		Page Num	ber
I_DZLV1_	BH2080		RC	10.	57m A	OD	Α	W   JJ	1:25		Sheet 6 o	of 7
ell Water Strikes	Sam Depth (r	A STATE OF THE STA	n Situ Testing Results	тс	Cori	- T	Legend	Depth (Level)	Stratum D	escription		
	Dopu. (	, .,,,,,	Trocure						Very dense grey slightly fine to coarse.	silty SANI	D. Sand is	+
	25.60 - 25 25.60 - 27 25.60	7.10 C	50 (7,10/50 t 190mm)	for					THANET SAND FORM	ATION]		
				90								26
	27.10 - 27 27.10 - 28 27.10	3.60 C	50 (8,10/50 t 185mm)	for								27
				78	3							2
	28.60 - 29 28.60 - 30 28.60 - 30 28.60	0.10 B 0.10 C	N=50 (5,7/50 255mm)	for 67								2
Hole Dian			g Diameter				elling	_		Drilling Flu		3
th Base	Diameter	Depth Base	Diameter	Depth To	p Dep	oth Base	Duration	Tool	Depth Top (m) Depth Base (m) F	ush Type Flusi	h Colour Min (%)	Max
) m bgl. 5. En allation - resi	vironmental s	seal installed om 3.00 m t	at 1.10 m to 2.10	m and 6.1	0 m to 7 60 m bo	1.10 m. 6. E	Borehole tern	ninated at 3	using 300 mm bit. 4. Water e 11.82 m bgl. 7. Dual 50 mm st e back filled with cement gro	tandpipe	at	

9					L	<i>y</i> e	ep	RO	ren	noie Log
Project Name Infrastructure	: Meridian	Water HIF	and a	Client: L	ond	don B	orough	n of Enfiel	d	Date: 04/02/2020 - 26/02/2020
Intrastructure Location: Mer	-1 11 415-11-			Contrac				chnology S		A -
		28.0		<u>Limited</u>		. AD	MOID	20		Drilling Equipment: Fraste PLG   Hand tools
Project No. : (				Crew N			FIVIO+E	3.5	need D	Dando 2000
Borehole N GI_DZLV1_I	BH2080	F	e Type RC	10		n AOI			gged By W   JJ	1:25 Sheet 7 of 7
Well Water Strikes	Sam Depth (r	The second of the second	Situ Testing Results	тс		SCR SCR	RQD	Legend	Depth (Level)	
	Depth (n 30.10 - 30 30.10 - 31 30.10	D.29 D C SPT	50 (25 for 130mm/50 f 60mm)	r for		SCR	RQD		31.82 (-9.03)	Very dense grey slightly silty SAND. Sand is fine to coarse. [THANET SAND FORMATION]  31
Hale Dis-	enter	Castro	Diameter				Chic	alling		<u></u>
Depth Base 1	Diameter 146	Casing Depth Base	Diameter Diameter	Depth To	p I	Depth I		elling Duration	Тос	Tool Depth Top (m) Depth Base (m) Flush Type Flush Colour Min (%) Max (%)  22.60 31.60 Water Grey 90 90

### Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 25/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536036.51 N192241.08 Limited Project No.: GTS-19-250 Crew Name: DP Equipment: 140LC-7 Logged By Location Number Location Type Level Scale Page Number GI\_DZLV1\_TP2034 TP 14.49m AOD JT 1:25 Sheet 1 of 1 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Brown slightly gravelly sandy CLAY. Gravel is angular to subrounded fine to coarse flint red brick macadam and concrete. Sand is fine to coarse. [MADE GROUND] ES PID 0.50 - 0.600.50 PID=0.10 0.60 - 1.00 1.40 - 1.60 ES PID PID=0.00 1.40 1.60 - 2.00 В 2.00 14.49 Brown slightly gravelly sandy CLAY with low cobble content. Sand is fine to coarse. Gravel is angular to 2.20 - 2.40 2.20 - 2.70 subrounded fine to coarse flint red brick concrete and ES macadam. Cobbles are subrounded to subangular flint B PID PID=0.00 brick and concrete. 2 20 [MADE GROUND] 3.00 12.49 Dark grey slightly sandy slightly gravelly CLAY. Sand is fine and medium. Gravel is angular to subrounded fine to coarse flint ceramic brick and concrete. [MADE GROUND] 3.40 - 3.60 ES 3.40 - 3.90 В 3.40 PID PID=0.00 4.00 11.49 End of Trial Pit at 4.00m

Orientation Trench Support and Comment Pumping Data Dimensions Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Rate Remarks 45 Stable Not required 4.00 1.00 Weather: Fair and dry

5

# Remarks

1. Position CAT scanned prior to digging. 2. Water encountered at 2.50 m bgl. 3. Trial pit terminated at 4.00 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



# **Photographic Report**

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2034

Project ID:

GTS-19-250





TP2034\_4.00 m\_Side\_A

TP2034\_4.00 m\_Side\_C





TP2034\_4.00 m\_Side\_D

TP2034\_4.00 m\_stockpile



Photographic Report	Project:	Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2034


Project ID:

GTS-19-250



TT2034\_4.00 m\_Side\_B





Width (m) 1.00	Remarks:
Length (m) 4.00	1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.
Depth (m) 4.00	
Orientation (°) 045	

# Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 24/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536007.55 N192204.76 Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number 14.57m AOD GI\_DZLV1\_TP2035 TP AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Brown slightly sandy gravelly CLAY with occasional fragments of wire and rubber. Sand is fine to coarse. Gravel is angular to subrounded fine to coarse red brick concrete and macadam. [MADE GROUND] 0.40 - 0.50 ES 0.40 PID PID=0.00 0.50 - 1.00 1.30 - 1.40 ES 1.30 PID PID=0.00 1.40 - 2.00 2.40 - 2.60 ES 2.40 PID PID=0.10 2.60 - 3.00 В 14.57 3.00 End of Trial Pit at 3.00m

Trench Support and Comment Pumping Data Orientation Dimensions Pit Stability Shoring Used Date Pit Length (m) Pit Width (m) Orientation (deg Remarks Rate Remarks Stable Not required 3.00 1.00 330 Weather: Dry and sunny

5 -

# Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 3.00 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



# **Photographic Report**

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2035

Project ID:

GTS-19-250





TP2035\_3.00 m\_Side\_A





TP2035\_3.00 m\_Stockpile

TP2035\_3.00 m\_Side\_C



<b>Photographic</b>	Report
---------------------	--------

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2035


Project ID:

GTS-19-250



TP2036\_3.00 m\_Side\_D






vviatn (m)	
1.00	
Length (m)	
3.00	
Depth (m)	ĺ
3.00	
Orientation (°)	

330


Remarks:

1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.



# Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3.Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



# Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3.Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



# **Photographic Report**

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2035A

Project ID:

GTS-19-250



TP2035A\_3.00-5.60 m\_Side\_C



TP2035A\_3.0-5.60 m\_Side\_A\_and\_D



TP2035A\_3.00-5.60\_side\_C



TP2035A\_Marker



# **Photographic Report**


Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2035A

Project ID:

GTS-19-250






TP2035A3.00-5.60 m\_Side\_B2

TP3025A\_3.00-5.60 m\_Side\_B





Т	Width (m)	
	0.60	
	Length (m) 3.00	Î
	Depth (m) 5.60	ĺ
	Orientation (°) 330	ĺ

Remarks:

1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.

# Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 24/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536044.48 N192200.29 Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number 14.45m AOD GI\_DZLV1\_TP2036 TP AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Brown slightly sandy gravelly CLAY with occasional fragments of wire plastic rubber and ceramic. Sand is fine to coarse. Gravel is angular to subrounded fine to coarse brick and concrete. [MADE GROUND] ES PID 0.50 - 0.600.50 PID=0.00 0.60 - 1.00 1.20 - 1.30 1.20 PID PID=0.00 1.30 - 2.00 2.00 14.45 Dark grey slightly gravelly laminated CLAY. Gravel is subangular to subrounded, fine to coarse flint. 2.00 m to 3.00 m occasional thin grey laminations 2.30 - 2.80 В 2.40 - 2.60 ES 2.40 PID PID=0.10 3.00 12.45 End of Trial Pit at 3.00m

Orientation Trench Support and Comment Pumping Data Dimensions Shoring Used Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Remarks Rate Remarks Stable Not required 3.00 1.00 60 Weather: Dry and sunny

5 -

# Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 3.00 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



# **Photographic Report**

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2036

Project ID:


GTS-19-250













Photographic Report	Project:	Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2036


Project ID:

GTS-19-250



TP2036\_3.00 m\_Stockpile






Width (m) 1.00	Remarks:
Length (m) 3.00	1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.
Depth (m) 3.00	
Orientation (°) 060	

# Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 02/03/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536044.48 N192200.29 Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number 14.45m AOD GI\_DZLV1\_TP2036A TP WL 1:25 Sheet 1 of 2 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Brown slightly sandy gravelly CLAY with occasional fragments of wire plastic rubber and ceramic. Sand is fine to coarse. Gravel is angular to subrounded fine to coarse brick and concrete. [MADE GROUND] 2.00 14.45 Dark grey slightly gravelly laminated CLAY. Gravel is subangular to subrounded fine to coarse flint. [MADE GROUND] 3.00 12.45 Light to dark grey gravelly sandy CLAY. Sand is fine to coarse. Gravel is angular to rounded fine to coarse flint brick and concrete. [MADE GROUND] 3.50 - 3.60 ES 3.50 - 5.00 4.50 - 4.60 ES 4.50 - 5.00 В 5.00 - 6.00 5.00 5 11.45 Pumping Data Trench Support and Comment Dimensions Orientation Shoring Used Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Remarks Rate Remarks Stable Not required 3.00 0.60 60 Weather: Overcast

# Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2036A

Project ID:

GTS-19-250



TP2035A\_3.0-5.60 m\_Side\_B\_and\_C



TP2035A\_3.0-5.60 m\_Side\_D




TP2035A\_3.0-5.60 m\_Side\_C\_and D



TP2036A\_Stockpile





	Width (m)	
1	0.60	
	Length (m)	
L	3.00	
	Depth (m)	
	5.60	
	Orientation (°)	
	060	

Remarks:

1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.




# Trial Pit Log

transtructure Ground Investigation pocation: Meridian Water, Enfield  Engineer: Ground Technology Services Limited  Co-ords: E535978.44 N192189.85  Equipment: 140LC-7  Location Number Location Type Location Type Level Logged By Scale Page Number GI_DZLV1_TP2038  TP 12.19m AOD JT 1:25 Sheet 1 of 1	Engineer Ground Technology Services	Project Name	: Meridiar			Client	·London	Borough	of Enfield		Date: 05/03/20	120		
Content No. : GTS-19-250	Control Number   Cont			- 25		Engin	eer: Grou	1200		vices	No a market	evesev is used	102180 8	5
	Location Number   Location Type   Level   Logged By   Scale   Page Number   12.19m AOD   JT   125   Sheet 1 of 1   125   Sheet 1 of 1		200	200	u .			D.					192 109.0	
Vertex   V	Well   Water   Sample and in Situ Testing   Depth   Sirikes   Depth (m)   Type   Results   Depth (m)   Uppe   Results   Depth (m)   Depth (m)   Uppe   Results   Depth (m)   Uppe   Results   Depth (m)   Uppe   Results   Depth (m)   Uppe   Results   Depth (m)   Dep	1-37-70 71-71	V2. 0 2		ation Type	Crew		P	Logo	ad Rv			Page	Number
Strikes   Depth (m)   Type   Results   Type	Strikes			Loca	The state of the s	1		DC		556	2 40 C 25 27		-	
0.00 - 0.30   B   0.00 - 0.30   ES   0.30   12.19   0.35   11.60   0.35   11.60   0.35   11.60   0.35   11.60   0.60   11.79   0.60   0.60   11.79   0.60	0.00 - 0.30		100000000						Legend		Stratum De	escription	Ü	
1.00   ES	1.00 ES  1.10 11.59  1.50 - 1.60 B 1.50 - 1.60 B 1.50 - 1.60 B ES  1.80		0.00 - 0. 0.00 - 0. 0.30 0.60 - 1. 0.60 - 1.	.00 B D	5 5 5		0.35 0.40	11.89 11.84		medium. coarse flir [MADE G Weak blar medium a medium v [MADE G Greyish b coarse. G flint. [MADE G MADE G M	Gravel is angular to  t.  ROUND]  ck MACADAM. 75-  ind coarse granite  oids. (BINDER CC  ROUND]  rown SAND and G  ravel is angular to  ROUND]	subangul 85 % aggr and flint. 5 URSE). RAVEL. Sa subangula	egate angu % small ar and is fine t	o arse
2.50 - 2.80   ES   ES	2.50 - 2.60		1.50 - 1. 1.50 - 1. 1.50 - 1.	60 B 60 D 60 ES			1.10	11.59		aggregate and granit voids. [MADE G Yellowish to coarse flir [MADE G Grey sand gravel is a	e subangular to ang te gravel. 10 % sm ROUND] grey slightly silty g grey slightly silty g tt. ROUND] dy gravelly CLAY. Sangular to subround	gular fine to all voids ar ravelly SA to subangu	o coarse flir nd 5 % med ND. Sand is ular fine to	nt 1 lium s fine
3.20 - 3.50 B 3.20 - 3.50 ES  4.00 - 4.60 B 4.00 - 4.60 D 4.00 - 4.60 ES 4.00 - 4.60 ES 4.60 - 4.90 D 4.60 - 4.90 D 4.60 - 4.90 ES 4.90 T.59  Dimensions Orientation   Trench Support and Comment   Su	3.20 - 3.50 B 3.20 - 3.50 ES  4.00 - 4.60 B 4.00 - 4.60 D 4.00 - 4.60 ES  4.60 - 4.90 B 4.60 - 4.90 B 4.60 - 4.90 ES 4.90 ES 4.90 FS 5oft to firm grey cLAY.  [ALLUVIUM]  Greenish grey slightly gravelly calcareous SAND with numerous shell fragments. Sand is medium and coarse. Gravel is subangular to subrounded fine to coarse flint [ALLUVIUM]  Brownish grey gravelly SAND. Sand is fine and medium. Gravel is angular to subrounded, fine to coarse of flint. [KEMPTON PARK GRAVEL FORMATION] End of Trial Pit at 4.90m		2.50 - 2 2.50 - 2	.60 D	3		3 00	11.09						
4.00 - 4.60	4.00 - 4.60 ES  4.60 ES  4.60 - 4.90 B A A A A A A A A A A A A A A A A A A		3.20 - 3.	.50 D										
4.60 - 4.90	4.60 - 4.90 4.60 - 4.90 4.60 - 4.90 4.90 ES B D 4.90 ES A.90 FS A.90 A.90 Brownish grey gravelly SAND. Sand is fine and medium. Gravel is angular to subrounded, fine to coarse of flint.  [KEMPTON PARK GRAVEL FORMATION] End of Trial Pit at 4.90m		4.00 - 4.	.60 D			4.00	9.19		numerous coarse. G coarse flir	s shell fragments. S ravel is subangula nt	Sand is me	dium and	With
Length (m) Pit Width (m) Orientation (deg) Pit Stability Shoring Used Remarks Date Rate Remarks		•	4.60 - 4 4.60 - 4 4.60 - 4	.90 B .90 D .90 ES	s					medium.	Gravel is angular to flint. DN PARK GRAVEL	subround	led, fine to ON]	5
	Dimensions Orientation Trench Support and Comment Pumping Data				Pit Stability	Shor	Trench	Support	and Comme			Date		
										rtemarks		Date	Rate	Remarks

#### Remarks

1. Position CAT scanned prior to digging. 2. Water encountered at 4.60 m bgl. 3. Trial pit terminated at 4.90 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.





Width (m) 1.00	Remarks:
Length (m) 3.00	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 4.90	
Orientation (°) 240	

#### Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 27/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536001.12 N192172.08 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: DP Equipment: 140LC-7 Location Number Location Type Level Logged By Scale Page Number 14.60m AOD GI\_DZLV1\_TP2039 TP WL 1:25 Sheet 1 of 2 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Results Depth (m) Type Reddish brown sandy gravelly CLAY with localised lenses of orange fine and medium sand. Sand is fine to coarse. Gravel is angular to rounded fine to coarse flint red brick concrete plastic and glass. [MADE GROUND] 0.50 - 0.60ES 1.00 14.60 Grey to dark grey slightly sandy slightly gravelly CLAY. Sand is fine to coarse. Gravel is angular to rounded fine to coarse flint red brick and concrete. [MADE GROUND] 1.50 - 1.60ES 2.00 13.60 Dark grey slightly sandy slightly gravelly CLAY. Sand is fine to coarse. Gravel is angular to rounded fine and medium flint red brick and concrete. [MADE GROUND] 2.50 - 2.60 ES 3.50 - 3.60 ES 4.50 - 4.60 ES 5

# Pit Length (m) Pit Width (m) Orientation (deg) Pit Stability Shoring Used Remarks 3.00 0.60 120 Stable Not required Weather: Dry and supply

Trench Support and Comment


Pumping Data

#### Remarks

Dimensions

Orientation

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2039

Project ID:

GTS-19-250











GROUND TECHNOLOGY Victory Park, Attleborough Norfolk, NR17 1ZA Tel: 01953 459462

# **Photographic Report**

GI\_DZLV1\_TP2039

Project:

Meridian Water HIF and Infrastructure Ground Investigation

Project ID:

GTS-19-250






BH2039\_5.60 m\_side\_D3









1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.

Width (m) 0.60 Length (m) 3.00

Depth (m) 5.60 Orientation (°) 120

#### Trial Pit Log Project Name: Meridian Water HIF and Date: 06/03/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E535952.55 N192150.23 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number GI\_DZLV1\_TP2040 TP 11.36m AOD JT 1:25 Sheet 1 of 1 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description (m) Strikes (m) Results Depth (m) Type Dark brown silty slightly gravelly SAND. Sand is fine 0.10 - 0.40 0.10 11.36 and medium. Gravel is angular to subangular fine to 0.10 - 0.40 0.10 - 0.40 D ES [MADE GROUND] Brownish grey clayey gravelly SAND with low cobble content. Sand is fine to coarse. Gravel is angular to rounded fine to coarse flint and brick. Cobbles are angular concrete [MADE GROUND] 0.75 11.26 Strong light grey CONCRETE. 40-60 % aggregate angular to subangular fine and medium flint gravel. 10 % small voids. 0.95 10.61 [MADE GROUND] Yellowish grey silty very gravelly SAND with medium 1.10 - 1.20 В cobble content and low boulder content. Sand is fine 1.10 - 1.20 1.20 10.41 to coarse. Gravel is angular to subangular fine to 1.10 - 1.20 ES coarse flint brick and concrete. Cobbles and boulders are subrounded to subangular. [MADE GROUND] 1.50 - 1.70 B Light grey silty gravelly SAND. Sand is medium and 1.50 - 1.70 D coarse. Gravel is angular to subrounded fine and 1.50 - 1.70 ES medium concrete and brick. [MADE GROUND] 1.80 m to 2.30 m brick cobbles 2 PP 2.30 2.30 83.33 10.16 Very stiff brownish grey with brown staining silty CLAY. 2.40 - 2.50 В With very few very fine roots. 2.40 - 2.50 D [ALLUVIUM] 2.40 - 2.50ES 2.70 2.70 - 3.20В 9.06 Stiff grey and light grey silty gravelly SAND. Sand is 2.70 - 3.20 D medium and coarse. Gravel is angular to subrounded 2.70 - 3.20ES fine and medium chalk. PP 33 33 2.70 [ALLUVIUM] 3.50 8.66 End of Trial Pit at 3.50m

Trench Support and Comment Pumping Data Dimensions Orientation Pit Length (m) Pit Width (m) Orientation (deg Pit Stability Shoring Used Remarks Date Rate Remarks Stable Not required 1.30 315 3.30 Weather: Dry and sunny

5

#### Remarks

1.. Position CAT scanned prior to digging. 2. Water encountered at 3.30 m bgl. 3. Trial pit terminated at 3.50 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2040

Project ID:

GTS-19-250







TP2040\_3.50 m\_Side\_B\_2



TP2040\_3.50 m\_Side\_C\_1



GI\_DZLV1\_TP2040

Project:

Meridian Water HIF and Infrastructure Ground Investigation

Project ID: GTS-19-250





TP2040\_3.50 m\_Side\_D\_2







Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2040

Project ID:

GTS-19-250






TP2040\_3.50\_m \_Side\_B\_1

TP2040\_3,50 m\_stockpile\_2






Width (m) 1.30	Remarks:
Length (m) 3.30	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 3.50	
Orientation (°) 315	

#### Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 26/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536036.26 N192161.33 Limited Project No.: GTS-19-250 Crew Name: DP Equipment: 140LC-7 Location Number Location Type Level Logged By Scale Page Number 14.70m AOD GI\_DZLV1\_TP2041 TP WL 1:25 Sheet 1 of 2 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Reddish brown gravelly CLAY with frequent fragments of wire plastic metal pipes and sheet ACM. Gravel is angular to subrounded fine to coarse flint red brick concrete and macadam. [MADE GROUND] 0.50 - 0.70ES 1.50 - 1.70 ES 2.50 - 2.70 ES 14.70 3.00 Light grey to grey slightly gravelly CLAY. Gravel is subangular to rounded fine to coarse flint with rare brick and concrete. 3.20 - 3.40ES [MADE GROUND] 4.50 - 4.70 ES 5.00 11.70 5 Trench Support and Comment Pumping Data Orientation Dimensions Pit Stability Shoring Used Date Pit Length (m) Pit Width (m) Orientation (deg Remarks Rate Remarks Stable Not required 4.00 0.60 90 Weather: Overcast

#### Remarks

1. Position CAT scanned prior to digging. 2. Water encountered at 4.60 m bgl. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.





Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2041


Project ID:

GTS-19-250






TP2041\_5.60 m\_side\_B





TP2041\_5.60\_side\_C





1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.

Width (m) 0.60 Length (m) 4.00

Depth (m) 5.60 Orientation (°) 090




# Trial Pit Log

Project Name: Meridian Water HIF and Date: 27/02/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536029.81 N192139.55 Location: Meridian Water, Enfield Limited Equipment: 140LC-7 Project No.: GTS-19-250 Crew Name: DP Location Number Location Type Level Logged By Scale Page Number GI DZLV1 TP2046 TP 14.55m AOD WL 1:25 Sheet 1 of 2 Sample and In Situ Testing Water Depth Level Well Stratum Description Legend Strikes (m) (m) Results Depth (m) Type Greyish brown clayey gravelly SAND with medium 0.10 - 0.40 cobble and low boulder content and frequent 0.10 - 0.40D fragments of wood. Sand is fine to coarse. Gravel is 0.10 - 0.40FS angular to subrounded fine to coarse flint brick and concrete and rare glass and pottery. Cobbles and boulders are angular concrete and brick. [MADE GROUND] 0.50 - 0.60ES 1.00 - 1.40 В 1.00 14.55 Light reddish brown gravelly sandy CLAY with frequent 1.00 - 1.40 D fragments of wire and glass. Sand is fine and medium. 1.00 - 1.40 ES Gravel is angular to subrounded fine to coarse flint red brick cement [MADE GROUND] 1.50 - 1.60ES 2.00 - 2.40 В 2.00 13.55 Yellowish grey and greyish brown gravelly SAND with 2.00 - 2.40 D medium cobble content and occasional fragments of 2.00 - 2.40 ES wood metal plastic and sheet ACM. Sand is fine to coarse. Gravel is angular to subangular fine to coarse flint brick and concrete. Cobbles are angular brick and [MADE GROUND] 2.50 - 2.60 ES 3.00 - 3.10 В 3.00 - 3.10 D 3.10 m to 3.60 m frequent pockets of dark grey silty 3.00 - 3.10 ES gravelly sand with a moderate organic odour 3.50 - 3.60 ES PP 3.60 3.60 45.00 12.55 Firm greenish grey slightly sandy slightly gravelly CLAY and dark brown plant debris. Sand is fine and medium. Gravel is angular to subangular fine to coarse flint. 3.90 - 4.40 В [MADE GROUND] 3.90 - 4.40 D 4.00 10.95 Dark grey silty SAND and GRAVEL. Sand is fine to 3.90 - 4.40 ES 4.00 - 4.40 coarse. Gravel is angular to subrounded fine to coarse В 4.00 - 4.40 D flint. [ALLUVIUM] 4.00 - 4.40 ES 4.40 PP 50.00 4.40 10.55 Firm grey and greenish grey CLAY with a very few fine 4.50 - 4.60 ES semi decayed roots and root channels. Slight organic 4.50 - 4.90 B odour 4.50 - 4.90 D [ALLUVIUM] 5 Trench Support and Comment Pumping Data Dimensions Orientation Pit Length (m) Pit Width (m) Orientation (deg Pit Stability Shoring Used Remarks Date Rate Remarks Stable Not required 3.00 0.60 135 Weather: Dry and sunny

#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.60 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation


GI\_DZLV1\_TP2046

Project ID:

GTS-19-250









BH2046\_5.60 m\_side\_D\_



Photograph	ic Report
------------	-----------

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2046


Project ID:

GTS-19-250



BH2046\_5.60 m\_sideB\_2





$\vdash$	Width (m)	П
	0.60	
Г	Length (m) 3.00	
	Depth (m) 5.60	7.
	Orientation (°) 135	ĺ

Remarks:

1. Location CAT scanned prior to excavation. 2. Trial pit backfilled with arisings compacted in 300 mm layers.



# Trial Pit Log

Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 03/03/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536004.30 N192120.20 Limited Project No.: GTS-19-250 Crew Name: DP Equipment: 140LC-7 Location Number Location Type Level Logged By Scale Page Number 14.56m AOD GI\_DZLV1\_TP2047 TP AB 1:25 Sheet 1 of 1 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Results Type 0.00 - 0.10 Yellowish brown slightly clayey very gravelly SAND 0.00 - 0.50 В with high cobble content. Sand is fine to coarse. 0.10 - 0.20 ES Gravel is subangular to subrounded fine to coarse flint 0.10 PID PID=0.00 brick and concrete. Cobbles are subangular brick and concrete. Car axle in pit and 30 mm dia. Steel cable. [MADE GROUND] 1.00 - 1.10 D 1.00 - 1.50 1.10 - 1.20 В ES 1.10 PID PID=0.00 2.00 - 2.10 D 2 2.00 - 2.40 2.10 - 2.20 В ES 2.10 PID PID=0.00 2.70 14.56 Dark grey slightly gravelly slightly sandy slightly silty CLAY. Sand is medium and coarse. Gravel is angular to subangular fine to coarse flint. [MADE GROUND] 3 3.10 - 3.20 В 3.10 - 3.20 D 3.10 - 3.20 ES 3.60 Firm grey with brown staining silty CLAY. [ALLUVIUM] 11.86 3.80 PP 50.00 4.00 - 4.50 В 4.10 D 4.10 m tree trunk obstruction. 4.10 - 4.20 ES 4.20 10.96 End of Trial Pit at 4.20m 5 Orientation Trench Support and Comment Pumping Data Dimensions Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Rate Remarks Stable Not required 1.00 150 3.80 Weather: Dry and sunny

#### Remarks

1. Position CAT scanned prior to digging. 2. Water encountered at 3.00 m bgl. 3. Trial pit terminated at 4.20 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2047

Project ID:

GTS-19-250



TP2047\_4.10 m\_Side\_A



TP2047\_4.10 m\_Side\_C



TP2047\_4.10 m\_Side\_B



TP2047\_4.10 m\_side\_D



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2047

Project ID:


GTS-19-250











1.00	
Length (m) 3.80	
Depth (m) 4.20	
Orientation (°) 150	

Remarks:

1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.



# Trial Pit Log

Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 07/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536000.26 N192094.68 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number GI\_DZLV1\_TP2048 TP 11.72m AOD AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Strong light grey CONCRETE. 40-50 % aggregate subrounded to rounded fine to coarse flint gravel. 10 % small voids. 0.25 - 0.40В [MADE GROUND] 0.32 11.72 0.35 - 0.45 D Orange brown slightly silty sandy GRAVEL. Sand is 0.35 - 0.45ES fine to coarse. Gravel is subrounded to rounded fine to 0.49 11.40 0.35 PID PID=0.00 coarse flint. 0.50 - 0.60 0.50 - 0.60 D [MADE GROUND] ES Brown slightly sandy gravelly CLAY with medium 0.71 11.23 0.50 - 0.70 В cobble and boulder content. Sand is fine and medium. 0.50 PID PID=0.00 Gravel is subrounded fine to coarse brick and flint. 0.72 - 1.20 0.75 - 0.80 В Cobbles and boulders are angular to subangular brick ES and concrete PID PID=0.00 0.75 [MADE GROUND] 0.80 - 0.90 D Soft grey slightly sandy slightly gravelly CLAY with 10.00 1.00 occasional pockets of grey sand and rare roots (<10 mm diameter). Sand is fine. Gravel is subrounded fine and medium flint. [ALLUVIUM] 1.70 - 1.80 D 1.70 - 1.80 ES 1.70 - 2.20 1.70 В PID PID=0.00 1.90 10.00 2 2.70 - 2.80 D 2.70 - 2.80 ES 2.70 - 3.00 В 2.70 PID PID=0.00 3.00 PP 15.00 3.00 11.01 End of Trial Pit at 3.00m 5 Orientation Trench Support and Comment Pumping Data Dimensions Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Rate Remarks Stable Not required 1.10 194 3.60 Weather: Dry and sunny

#### Remarks

1. Position CAT scanned prior to digging. 2. Water encountered at 2.50 m bgl. 3. Trial pit terminated at 3.00 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers and reinstated with concrete.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2048

Project ID:

GTS-19-250





TP2048\_ (21) m\_Side D TP2048\_ (23) m\_Spoil







Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2048

Project ID:

GTS-19-250





TP2048\_0.49 m\_Spoil TP2048\_1.30 m\_Side\_D





TP2048\_1.30 m\_Spoil TP2048\_3.00 m Base



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2048

Project ID:


GTS-19-250





TP2048\_3.00 m\_Side D TP2048\_3.00\_Spoil





Width (m) 1.10	Remarks:
Length (m) 3.60	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 3.00	
Orientation (°) 194	



# Trial Pit Log

Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 10/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536022.42 N192046.43 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number GI\_DZLV1\_TP2051 TP 11.84m AOD AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Results Depth (m) Type Strong light grey CONCRETE. 40-50 % aggregate subangular to subrounded fine to coarse flint gravel. 0.15 - 0.300.15 11.84 10 % small voids. 0.20 - 0.30 0.20 - 0.30 D [MADE GROUND] FS 11.69 0.31 Orangish brown sandy GRAVEL. Sand is fine to PID=0.00 0.20 PID coarse. Gravel is subangular to subrounded fine to 0.35 - 0.45 В 0.45 11.53 coarse flint brick and concrete. 0.35 - 0.45 0.35 - 0.45 D [MADE GROUND] FS Dark grey sandy GRAVEL with medium cobble content PID=0.60 PID 0.35 and frequent soft clay pockets. Sand is fine to coarse. 0.50 - 0.60 D Gravel is angular to subangular fine to coarse flint and 0.50 - 0.60 0.50 - 1.00 0.50 ES brick. Cobbles are angular brick. R [MADE GROUND] PĪD PID=0.00 Soft to firm dark grey slightly gravelly sandy CLAY. Sand is light grey fine to coarse and occurs in pockets and streaks. Gravel is subrounded fine to coarse flint. [ALLUVIUM] PP 75.00 1.60 1.80 - 1.90 D 1.80 - 1.90 1.80 - 2.00 ES В 1.80 PID=0.00 PID 2.80 - 3.00 В 2.80 - 3.00 D 2.80 - 3.00 ES 3.00 11.39 PID=0.00 2.80 PID End of Trial Pit at 3.00m 3 00 141.67 5 Trench Support and Comment Pumping Data Dimensions Orientation Pit Stability Orientation (deg Shoring Used Date Rate Remarks Pit Length (m) Pit Width (m) Stable Not required 1.10 54 3.50 Weather: Fair and dry

#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 3.00 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers and reinstated with concrete.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2051

Project ID:

GTS-19-250





TP2051\_0.15 m\_Base

TP2051\_0.30 m\_Spoil







Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2051

Project ID:

GTS-19-250





TP2051\_0.90 m\_Side B

TP2051\_0.90 m\_Side\_D





TP2051\_0.90 m\_Spoil

TP2051\_1.80 m\_Side\_B



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2051

Project ID:

GTS-19-250





TP2051\_1.80 m\_Side\_D TP2051\_1.80 m\_Spoil







Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TP2051

Project ID:

GTS-19-250






TP2051\_3.00 m\_Side D

TP2051\_3.00 m\_Side\_B







	William Committee of the Committee of th				
	Width (m) 1.10	Remarks:			
Ī	Length (m) 3.50	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.			
Ī	Depth (m) 3.00				
Ī	Orientation (°)				

#### Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 24/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Location: Meridian Water, Enfield Co-ords: E536023.48 N192264.08 Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Logged By Location Number Location Type Level Scale Page Number 10.76m AOD GI\_DZLV1\_TT2001 TP AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Brown slightly sandy gravelly CLAY with frequent fragments of wire and plastic. Sand is fine to coarse. Gravel is angular fine to coarse brick and concrete. [MADE GROUND] 0.50 - 0.60 0.50 - 0.60 ES ES 0.60 ES 0.60 - 1.00 В PID 0.60 PID=0.00 1.20 - 2.00 ES 1.30 ES PID PID=0.10 1.30 1.40 - 2.00 2.00 10.76 Pale yellow to orange SAND and GRAVEL. Sand is fine to coarse. Gravel is subrounded to round fine to coarse flint brick and concrete. [KEMPTON PARK GRAVEL FORMATION] 2.20 - 3.20 ES PID PID=0.00 2.20 2.30 - 2.80 3.00 8.76 End of Trial Pit at 3.00m

Trench Support and Comment Pumping Data Orientation Dimensions Pit Stability Shoring Used Date Pit Length (m) Pit Width (m) Orientation (deg Remarks Rate Remarks Unstable Not required 3.00 1.00 330 Weather: Dry and sunny

5 -

#### Remarks

1. Position CAT scanned prior to digging. 2. Water encountered at 2.00 m bgl. 3. Trial pit terminated at 3.00 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2001

Project ID:

GTS-19-250



TT2001\_3.00 m\_Side\_A\_B




TT2001\_3.00 m\_Side\_D




TT2001\_3.00 m\_Side\_B\_C





Width (m) 1.10	Remarks:
Length (m) 3.00	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 3.00	
Orientation (°) 330	



Trench Support and Comment Pumping Data Orientation Dimensions Pit Stability Shoring Used Date Pit Length (m) Pit Width (m) Orientation (deg Remarks Rate Remarks Stable Not required 10.00 1.40 82 Weather: Fair and dry

5 -

#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 1.70 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2002

Project ID:

GTS-19-250





TT2002\_1.40 m\_Side\_C

TT2002\_1.40 m\_Side\_D





TT2002\_1.40 m\_Spoil

TT2002\_3.00 m\_Side\_B



Photographic	Report
--------------	--------

Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2002

Project ID:

GTS-19-250




TT2002\_3.00 m\_Spoil



## **Trial Trench Section**

Project Name: Meridian Infrastructure Ground In		Client: London Borou	gh of Enfield	Date: 19/02/2020	
Location: Meridian Wate	er, Enfield	Engineer: Ground Techn	ology Services Limited	Co-ords: E536041.49 N192220.94	
Project No.: GTS-19-250		Crew Name: PH		Equipment: 140LC-7	
Location Number GI_DZLV1_TT2002	Location Type TT	Level 10.61m aOD	Drawn By AB	Scale 1:50	Page Number Sheet 2 of 2



	Width (m) 1.40	Remarks:
	l ength (m) 10.00	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
	Depth (m) 3.00	
Ī	Orientation (°) 082	

#### Trial Pit Log Project Name: Meridian Water HIF and Date: 05/03/2020 Client: London Borough of Enfield Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536056.54 N192169.57 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: DP Equipment: 140LC-7 Location Number Location Type Level Logged By Scale Page Number GI\_DZLV1\_TT2003 TP 11.20m AOD JT 1:25 Sheet 1 of 2 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Results Depth (m) Type 0.00 - 0.10 Greyish brown silty very gravelly SAND with medium cobble content and medium boulder content and fragments of wood metal plastic glass pottery and sheet ACM. Sand is fine to coarse. Gravel is angular fine to coarse brick concrete and flint. Cobbles and 0.40 - 0.58В boulders are angular brick and concrete. 0.40 - 0.58D [MADE GROUND] 0.40 - 0.58 ES 1.40 - 1.50 В 1.40 - 1.50 1.40 - 1.50 D ES 1.50 m to 1.90 m yellowish brown sandy gravel. Sand is fine to coarse. Gravel is angular to subrounded fine to coarse flint 2 2.20 - 2.40 2.20 11.20 В Brownish grey clayey gravelly SAND with frequent 2.20 - 2.40 D lenses of grey sandy gravelly clay. Sand is fine to 2.20 - 2.40 FS coarse. Gravel is angular to subrounded fine to coarse flint. (Reworked alluvium?) [MADE GROUND] 2.70 9.00 Brownish grey and greyish brown sandy slightly gravelly CLAY. Sand is fine to coarse. Gravel is subangular to rounded fine to coarse flint. [MADE GROUND] 3.00 - 3.10 В 3.00 - 3.10 D 3.00 - 3.10 ES 4.20 8.50 Firm to stiff mottled grey and blueish grey CLAY, with a 4.30 - 4.40 В very few very fine roots and root channels, rare fine 4.30 - 4.40 D

Trench Support and Comment Pumping Data Dimensions Orientation Pit Stability Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Date Rate Remarks Stable Not required 1.00 35 5.50 Weather: Light showers

subangular flint gravel and coarse sand sized fresh

4.70 m to 5.20 m stiff mottled grey and yellowish

5

water shells [ALLUVIUM]

grey

#### Remarks

4.30 - 4.40

5.00 - 5.10

ES

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.20 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.

	<b>U</b> II			Trial Pit Log								
Projec	t Name	: Meridiai	l n Water F nvestigat	HIF and	Client: London	Borough	of Enfield		Date: 05/03/2020			
f			ter, Enfiel			Engineer: Ground Technology Services Limited			Co-ords: E536056.54 N192169.57			
Projec	ct No. : C	GTS-19-2	:50		Crew Name: DP			Equipment: 140LC-7				
Location Number Location Type			Level		Logg	ged By	Scale		ge Numb	er		
GI_I	DZLV1_			TP	11.20m A	DD		JT	1:25	SI	neet 2 of	2
Well	Water Strikes	Sam Depth	Militaria contrata	In Situ Testin	()	Level (m)	Legend		Stratum Descript	on		
Pit Length		5.00 - 5	entation tation (deg)	Pit Stability	Trenct Shoring Used	7.00	and Comm	very few v subangula water she [ALLUVIU		Pumpii	e fine	6   7   10   10   Irks
5.50			35	Stable	Not required				Jak			
Weath	er: ligh	t showers										
Rema	arks										1	
1. Pos	ition CA	T scanne	d prior to	digging. 2. No	ground water e	encounte	red. 3. Tria	al pit termir	nated at 5.20 m bgl. 4.	Trial		

pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2003

Project ID:

GTS-19-250











GROUND TECHNOLOGY Victory Park, Attleborough Norfolk, NR17 1ZA Tel: 01953 459462

### **Photographic Report**

GI\_DZLV1\_TT2003

Project:

Meridian Water HIF and Infrastructure Ground Investigation

Project ID:

GTS-19-250








TT2003\_5.20m\_Side\_D1

TT2003\_5.20m\_Side\_D2



## **Trial Trench Section**

Project Name: Meridian Infrastructure Ground In		Client: London Borou	gh of Enfield	Date: 05/03/2020	
Location: Meridian Wate	er, Enfield	Engineer: Ground Techn	ology Services Limited	Co-ords: E536054.33 N192178.13	
Project No.: GTS-19-250		Crew Name: PH		Equipment: 140LC-7	
Location Number	Location Type	Level	Drawn By	Scale 1.50	Page Number



Width (m) 1.00	Remarks:
l ength (m) 5.50	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 5.20	7
Orientation (°) 035	7

#### Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 06/03/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E535962.82 N192145.03 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: DP Equipment: 140LC-7 Page Number Location Number Location Type Level Logged By Scale GI\_DZLV1\_TT2004 TP 12.51m AOD JT 1:25 Sheet 1 of 2 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Dark brown slightly clayey gravelly SAND with low cobble content and occasional fragments of metal and glass. Sand is fine to coarse. Gravel is angular fine to coarse flint brick and concrete. Cobbles are brick and 0.30 - 0.50 В concrete. D 0.30 - 0.50[MADE GROUND] 0.30 - 0.50 ES 1.50 - 1.60 1.50 - 1.60 1.50 - 1.60 B D ES 2.20 - 2.40 2.20 12.51 В Brown silty gravelly fine to coarse SAND. Frequent 2.20 - 2.40 D gravel is angular to rounded fine to coarse flint. 2.20 - 2.40 ES [MADE GROUND] 2.20 m to 3.20 m sandy slightly gravelly pockets. Sand is fine to coarse. Gravel is fine and medium 3 3.40 10.31 Grey and brown CLAY. Clay is closely fissured with 3.50 - 3.70 B D very few very fine roots. [MADE GROUND] 3.50 - 3.70 3.50 - 3.70 ES 3.40 m to 4.00 m moderate organic odour 3.60 2.67

5.00 PP 70.00 Trench Support and Comment Pumping Data Dimensions Orientation Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Rate Remarks Stable Not required 4.50 1.30 45 Weather: Light showers

#### Remarks

4.90 - 5.00

4.90 - 5.00

В

D

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.30 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.

4.00

4.70

9.11


8.51

Firm to stiff grey and yellowish grey CLAY.

5

[ALLUVIUM]

Firm to stiff grey CLAY. [ALLUVIUM]



# 4.50 1.30 45 Stable Not required Weather: Light showers

#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 5.30 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers.



Project:

Meridian Water HIF and Infrastructure Ground Investigation


GI\_DZLV1\_TT2004

Project ID:

GTS-19-250









TT2004\_Side B




Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2004

Project ID:

GTS-19-250












TT2004\_Side D

TT2004\_Reinstatement



## **Trial Trench Section**

Project Name: Meridian Infrastructure Ground In		Client: London Borou	gh of Enfield	Date: 06/03/2020		
Location: Meridian Wate	er, Enfield	Engineer: Ground Techn	ology Services Limited	Co-ords: E535981.16 N192133.63		
Project No.: GTS-19-250		Crew Name: PH		Equipment: 140LC-7		
Location Number GI DZLV1 TT2004	Location Type TT	Level 12.51m aOD	Drawn By AB	Scale 1:50	Page Number Sheet 2 of 2	



Width (m) 1.30	Remarks:
l ength (m) 4.50	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 5.30	
Orientation (°) 045	



## Trial Pit Log

Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 07/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536030.69 N192089.98 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number GI\_DZLV1\_TT2005 TP 11.78m AOD AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Depth Water Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Strong light grey CONCRETE. 40-50 % aggregate subrounded to rounded fine to coarse flint gravel. 15 % small voids. [MADE GROUND] 0.30 - 0.40 11.78 D 0.30 Brown slightly clayey sandy GRAVEL with medium 0.30 - 0.40ES cobble content and medium boulder content. Sand is 0.30 - 0.45 В fine to coarse. Gravel is angular to subangular fine to 0.30 PID PID=0.00 0.56 11.48 coarse concrete and brick. Cobbles and boulders are 0.60 - 0.70 D angular concrete and brick. 0.60 - 0.70 ES [MADE GROUND] 0.60 - 0.80В 0.4 m metal pipe (6 mm x 1000 mm) and wooden 0.60 PP 10.00 plank (80 mm x 600 mm) 0.60 PID PID=0.00 0.45 m becoming very clayey Soft to firm grey and dark grey slightly sandy slightly gravelly silty CLAY with occasional peat clumps and occasional pockets of grey sand. Sand is fine to coarse. Gravel is subrounded fine to coarse flint. [ALLUVIUM] 1.33 m becoming sandy. Sand is fine to coarse 1.60 - 1.70 D 1.60 - 1.70 ES 1.60 - 1.80 В 1.60 20.00 1.60 PID PID=0.00 2 2.50 - 2.60 ES PP 2.50 2.50 40.00 PID PID=0.00 3 3.20 PP 80.00 3.20 11.22 End of Trial Pit at 3.20m 5 Orientation Trench Support and Comment Pumping Data Dimensions Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Rate Remarks Stable Not required 4.00 1.00 60 Weather: Dry and sunny

#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 3.30 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers and reinstated with concrete.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2005

Project ID:

GTS-19-250





TT2005\_0.30 m\_Base\_side\_D\_A

TT2005\_0.30 m\_Spoil







Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2005

Project ID:

GTS-19-250





TT2005\_1.50 m\_Side\_C

TT2005\_1.50 m\_Side\_D\_Base







Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2005

Project ID:

GTS-19-250






TT2005\_3.20 m Spoil TT2005\_3.20 m\_Base





TT2005\_3.20 m\_Side\_D TT2005\_Location





Width (m) 1.00	Remarks:
Length (m) 4.00	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 3.20	
Orientation (°) 060	

#### Trial Pit Log Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 12/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536058.90 N192065.85 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Page Number Location Number Location Type Level Logged By Scale GI\_DZLV1\_TT2006 TP 11.84m AOD AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Depth (m) Type Results Strong light grey CONCRETE. 50-60 % aggregate subrounded to subangular fine and medium flint gravel. 10-20 % small voids. 0.25 - 0.35В 0.25 11.84 [MADE GROUND] 0.30 - 0.35D Yellowish brown sandy GRAVEL. Sand is medium and 0.35 11.59 0.30 - 0.35ES coarse. Gravel is subrounded to rounded fine to 0.30 PID PID=0.00 coarse flint. Distinct hydrocarbon odour. 0.40 - 0.50 D [MADE GROUND] 0.60 11.49 0.40 - 0.50 0.40 - 0.60 ES Dark grey slightly sandy gravelly CLAY with high R cobble content and medium boulder content with rare PID PID=3.80 0.40 fragments of metal rebar and occasional fragments of 0.70 - 1.70 wood. Sand is fine to coarse. Gravel is angular to subangular fine to coarse concrete flint and brick. Cobble and boulders are angular of concrete and brick. [MADE GROUND] Grey and light grey sandy gravelly CLAY with low cobble and boulder content. Sand is fine to coarse. Gravel is subangular to rounded fine to coarse flint concrete and brick. Cobble and boulder are angular and subrounded concrete and brick. 1.60 - 1.70 [MADE GROUND] D 1.60 - 1.70 ES 1.60 PID PID=0.00 2 2.60 - 2.70 2.60 - 2.70 2.60 - 2.70 B ES PID=0.00 PID 2.60 3 3.30 11.24 End of Trial Pit at 3.30m

Orientation Trench Support and Comment Pumping Data Dimensions Pit Stability Date Pit Length (m) Pit Width (m) Orientation (deg Shoring Used Remarks Rate Remarks Stable Not required 1.00 1.50 65 Weather: Overcast

5

#### Remarks

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 3.30 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers and reinstated with concrete.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2006

Project ID:

GTS-19-250





TT2006\_0.35 m\_Base







GROUND TECHNOLOGY Victory Park, Attleborough Norfolk, NR17 1ZA Tel: 01953 459462

### **Photographic Report**

GI\_DZLV1\_TT2006


Project:

Meridian Water HIF and Infrastructure Ground Investigation

Project ID:

GTS-19-250









TT2006\_3.30 m Side\_C\_D

TT2006\_0.60 m\_Base




Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2006

Project ID:


GTS-19-250





TT2006\_3.30 m\_Side\_D





Width (m) 1.00	Remarks:
Length (m) 1.50	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 3.30	
Orientation (°) 065	



## Trial Pit Log

	Ground Inve	stigation	)	Client: London	1000			Date: 09/03/202	0				
Location: Mer	idian Water,			Engineer: Crou									
Project No. : 0	OTC 40 250		Location: Meridian Water Enfield				Engineer: Ground Technology Services				Co-ords: E536037.81 N192053.46		
	Project No. : GTS-19-250				Crew Name: PH				Equipment: JCB 3CX				
Location Number Location Type GI_DZLV1_TT2006A TP		Level 11.82m AOD		Logged By JT				Page Number					
Well Water Strikes			Situ Testing	(100)	Level	Legend	Legend Stratum Description						
Strikes	Depth (m)	Туре	Results	(m)	(m)	14 N. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14 1. 14	Strong lie	ght grey CONCRETE.	0.000	gregate			
	0.20 - 0.40 0.20 - 0.40 0.20 - 0.40 0.20 0.50 - 0.70 0.50 - 0.70	B D ES PID B D	PID=0.00	0.16 0.32 0.45	11.82 11.66 11.50		angular t quartzite into the a [MADE O Reddish medium fine to co	o subrounded fine to . 8 mm re-bar mesh a adjacent slab. 10 % sr SROUND] brown silty SAND and and coarse. Gravel is arrse flint brick and co	coarse flint a t 70 mm. 30 mall voids. d Gravel. Sa angular to s	and mm tie bars nd is			
	0.50 - 0.70 0.50 0.50 0.70	ES PP PID PP	81.67 PID=0.00 46.80	0.90	11.37		Grey and medium Gravel is flint maca and cond mm x 10	MADE GROUND] Grey and dark grey silty SAND and GRAVEL with medium cobble content. Sand is medium and coarse. Gravel is angular to subangular fine to coarse brick lint macadam and concrete. Cobbles are angular brick and concrete. Low wood fragment content up to 100 mm x 100 mm x 500 mm.  MADE GROUND] Greenish grey locally sandy CLAY with low cobble content and frequent dark brown organic silt pockets up to 150m mm x 150 mm x 200 mm. Cobbles are angular brick and concrete.  MADE CROUND] Greenish grey and grey slightly gravelly CLAY with requent dark brown organic silt pockets up to 20 mm (400 mm x 100 mm. Gravel is angular to subangular			1 -		
	1.30 - 1.40 1.30 - 1.40 1.30 - 1.40 1.30 - 1.40 1.40	B D ES PID PP	PID=0.00 23.33	1.70	10.92		Greenish content a up to 150 angular b [MADE C Greenish frequent						
	1.80	PP	75.00				fine to co	arse flint and brick. F	requent yello	owish grey			
	2.00 - 2.20 2.00 - 2.20 2.00 - 2.20 2.00 - 2.20	B D ES PID	PID=0.00				thick. [MADE Control of the control	ium and coarse sand  GROUND] y slightly gravelly CLA plant debris. Gravel is ded fine to coarse flint	Y with rare s	semi	2 -		
	2.40	PP	128.63				[MADE 0	GROUND]					
	2.90 - 3.10 2.90 - 3.10 2.90 - 3.10 2.90 2.90	B D ES PP PID	138.33 PID=0.00		10.12	Stiff greenish grey slift CLAY with roots. Slight organic odour.  [ALLUVIUM]		with a very fe	ew very fine	3 -			
	3.60 - 3.70 3.60 - 3.70	B D	71.67	3.30	9.12	xx_x xx_x xx_x	Firm to s [ALLUVII	tiff grey and brownish UM]	grey silty C	LAY.			
				3.75	8.52	x		End of Trial Pit	at 3.75m		4 -		
											5 -		
Dimensions Pit Length (m) Pit Wid 5.00 0.0			Pit Stability Stable	Trench Shoring Used Not required	Support	and Comme	ent Remarks		Date Ra	mping Data ate Rema	rks		
Weather: Dry	and sunny												

1. Position CAT scanned prior to digging. 2. No ground water encountered. 3. Trial pit terminated at 3.75 m bgl. 4. Trial pit back filled with arisings and compacted in 300 mm layers and reinstated with concrete.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2006A

Project ID:

GTS-19-250



TT2006A\_3.75 m\_Side\_A



TT2006A\_3.75 m\_Side\_D



TT2006A\_3.75 m\_Side\_B\_C



TT2006A\_3.75 m\_Stockpile\_1 - Copy



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2006A

Project ID:

GTS-19-250






TT2006A\_3.75 m\_Stockpile\_1

TT2006A\_Stockpile\_2 - Copy



## **Trial Trench Section**

Project Name: Meridian Infrastructure Ground In		Client: London Boroug	gh of Enfield	Date: 09/03/2020		
Location: Meridian Wate	er, Enfield	Engineer: Ground Techn	ology Services Limited	Co-ords: E536065.53 N192069.04		
Project No.: GTS-19-250		Crew Name: PH		Equipment: JCB 3CX		
Location Number GI_DZLV1_TT2006A	Location Type TT	Level 10.82m aOD	Drawn By AB	Scale 1:50	Page Number Sheet 2 of 2	



Width (m) 0.60	Remarks:
l ength (m) 5.00	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
Depth (m) 3.75	
Orientation (°) 060	



### Trial Pit Log

Project Name: Meridian Water HIF and Client: London Borough of Enfield Date: 17/02/2020 Infrastructure Ground Investigation Engineer: Ground Technology Services Co-ords: E536031.92 N191995.39 Location: Meridian Water, Enfield Limited Project No.: GTS-19-250 Crew Name: PH Equipment: JCB 3CX Location Number Location Type Level Logged By Scale Page Number GI\_DZLV1\_TT2007 TP 11.90m AOD AW 1:25 Sheet 1 of 1 Sample and In Situ Testing Water Depth Level Well Legend Stratum Description Strikes (m) (m) Results Depth (m) Type Very strong light grey CONCRETE. 40-50 % aggregate angular to subangular fine to coarse flint 0.18 - 0.30 0.18 11.90 gravel. 20 % small voids. 0.20 - 0.30 D [MADE GROUND] 11.72 0.31 0.20 - 0.30ES Orange brown sandy GRAVEL with medium cobble 0.20 PID PID=0.00 content. Sand is fine to coarse. Gravel is subangular 0.40 - 0.50 to subrounded fine to coarse brick concrete and flint. 0.40 - 0.50 ES Cobbles are angular brick and concrete. 0.40 - 0.60B [MADE GROUND] 0.66 11.59 0.40 PID PID=0.70 Dark grey slightly sandy gravelly clayey COBBLES 0.70 - 0.80D with medium boulder content and rare fragments of 0.70 - 0.80 ES wood. Sand is fine to coarse. Gravel is angular to 0.70 PID PID=0.00 subangular fine to coarse flint brick and concrete. 1.00 - 1.60 В Cobbles are angular concrete and brick. Boulders are angular concrete. [MADE GROUND] 0.61 m 10 mm dia. black alkathene pipe Soft to firm dark grey and grey slightly sandy slightly silty gravelly CLAY with occasional pockets of grey very sandy clay and rare pockets of organics. Sand is fine and medium. Gravel is subrounded to rounded fine to coarse flint. [ALLUVIUM] 2 2.50 - 3.00 В 2.70 - 2.80 2.70 - 2.80 D FS PID PID=0.00 2.70 3.00 11.24 End of Trial Pit at 3.00m 5 Orientation Trench Support and Comment Pumping Data Dimensions Pit Stability Orientation (des Shoring Used Remarks Date Rate Remarks Pit Length (m) Pit Width (m) Stable Not required 1.10 4.70 61 Weather: Fair and dry

#### Remarks

 Position CAT scanned prior to digging.
 Water encountered at 0.60 m bgl.
 Trial pit terminated at 3.00 m bgl. Trial pit back filled with arisings and compacted in 300 mm layers and reinstated with concrete.



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2007

Project ID:

GTS-19-250









TT2007\_0.30 m\_Spoil

TT2007\_0.90 m\_Base\_Side\_D



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2007

Project ID:

GTS-19-250





TT2007\_0.90 m\_Side\_B

TT2007\_0.90 m\_Spoil





TT2007\_1.60 m\_Side\_B TT2007\_1.60 m\_Spoil



Project:

Meridian Water HIF and Infrastructure Ground Investigation

GI\_DZLV1\_TT2007

Project ID:

GTS-19-250





TT2007\_3.00 m\_Side B

TT2007\_3.00 m\_Side\_D






TT2007\_3.00 m\_Spoil\_A



## **Trial Trench Section**

Project Name: Meridian Infrastructure Ground In		Client: London Borou	gh of Enfield	Date: 17/02/2020		
Location: Meridian Wate	er, Enfield	Engineer: Ground Techn	ology Services Limited	Co-ords: E536040.24 N191997.82		
Project No.: GTS-19-250		Crew Name: PH		Equipment: JCB 3CX		
Location Number GI DZLV1 TT2007	Location Type TT	Level 11.90m aOD	Drawn By AB	Scale 1:50	Page Number Sheet 2 of 2	



	Width (m) 1.10	Remarks:
	l ength (m) 4.70	1. Position scanned using a CAT prior to digging. 2. Trial pit back filled with arising and compacted in 300 mm layers.
	Depth (m) 3.00	
İ	Orientation (°) 061	1