

**A REPORT ON A GROUND INVESTIGATION AT  
MURROW AD PLANT  
(FACTUAL)**

CLIENT: Murrow AD Plant Limited

ENGINEER: Plandescil Limited

Date: 8 September 2021

Reference: ADB/21.237

A F Howland Associates  
The Old Exchange  
Newmarket Road  
Cringleford  
Norwich  
NR4 6UF

Tel: 01603 250754  
Email: [admin@howland.co.uk](mailto:admin@howland.co.uk)  
Web: [www.howland.co.uk](http://www.howland.co.uk)

# **CONTENTS**

<b>1. INTRODUCTION</b>	<b>1</b>
<b>2. FIELDWORK</b>	<b>2</b>
<b>3. LABORATORY TESTING</b>	<b>4</b>
<b>3.1 GENERAL</b>	<b>4</b>
<b>3.2 TEST PROCEDURES</b>	<b>4</b>
<b>4. COPYRIGHT</b>	<b>8</b>

## **APPENDICES**

**APPENDIX A: REFERENCES**

**APPENDIX B: WINDOWLESS SAMPLE HOLE RECORDS**

**APPENDIX C: TRIAL PIT RECORDS**

**APPENDIX D: LABORATORY TESTING**

**APPENDIX E: DRAWINGS**



**CLIENT:** Murrow AD Plant Limited

**ENGINEER:** Plandescil Limited

# **A REPORT ON A GROUND INVESTIGATION AT MURROW AD PLANT (FACTUAL)**

**Reference:** ADB/21.237

**Date:** 8 September 2021

## **1. INTRODUCTION**

It is proposed to carry out construction work at Murrow AD Plant near Wisbech in Norfolk (Drawing 21.237/01).

At the instruction of Murrow AD Plant Limited, an investigation was carried out to provide information on the subsoil conditions and relevant geotechnical parameters associated with the proposed construction and of embankments that formed two existing lagoons.

This report provides the factual details of the fieldwork and laboratory testing undertaken during the investigation.

## 2. FIELDWORK

Fieldwork was carried out on 5 and 6 August 2021 and comprised three windowless dynamic sample holes and two machine excavated trial pits in the area of proposed construction. Four hand dug trial pits were also carried out in the lagoon embankments.

The exploratory hole positions were set out in general accordance with the requirements of the Client, as shown on Drawing 21.237/02. The National Grid references, and elevation of the hole locations relative to Ordnance Datum, were measured using a Hemisphere S320 VRS GPS (RTK) system. A cable avoidance tool was used to sweep the positions and the immediate surrounding area to locate any potential services with the position adjusted as necessary. A starter pit was also excavated by hand to a depth of 1.2 m at the windowless dynamic sample hole positions to provide direct inspection for services.

The **windowless dynamic sample holes**, referenced WS01 to WS03 were advanced with a tracked dynamic sampling rig and taken to a depth of 4.00 m below ground level (bgl). The sampling system utilises a 63.5 kg weight falling a distance of 750 mm to drive rods and sampling tubes into the ground, these are then extracted and the continuous samples described. During advance, sampling and *in situ* testing were carried out in general accordance with BS EN1997-2:2007 Eurocode 7 and its UK National Annex supported by BS 5930:2015+A1:2020.

Hand vane tests (HV) were carried out in cohesive material within the starter inspection pits using a Pilcon hand vane to estimate the undrained shear strength. This is achieved using a four-bladed cruciform stainless steel vane which is pushed into the ground. The torque head is attached to the 19 or 33 mm diameter vane and is rotated at the rate of one revolution per minute until the material fails. The equipment includes a direct reading scale to give the undrained shear strength

Open tube (U70) drive samples were taken in cohesive materials to allow laboratory testing of undisturbed material, as appropriate. Standard penetration tests (SPT) were carried out in cohesionless soils or materials where undisturbed samples could not be obtained, using a split barrel sampler or a solid cone as appropriate. The SPT N-value was taken as the number of blows for 300 mm of penetration, following a seating drive of 150 mm or 25 blows.

The **Hand dug trial pits**, referenced HDTP01 to HDTP04 were excavated using hand-held insulated digging tools and taken to a depth of 1.2 m within the existing lagoon embankments.

The **machine dug trial pits**, referenced TP01 and TP02 were excavated by a mechanical excavator equipped with a 1.5 m wide bucket and were taken to a maximum depth of 3.0 m. Hand vane tests (HV) were again carried out in cohesive material using the same Pilcon hand vane to estimate the undrained shear strength.

The exploratory holes were monitored for **groundwater** ingress during advance. However in this instance none was encountered

Details of the strata encountered, the sampling, *in situ* and laboratory testing are shown on records appended to this report.

### **3. LABORATORY TESTING**

#### **3.1 GENERAL**

Subsequent to the fieldwork, a programme of laboratory testing was carried out to provide additional quantitative data on the materials encountered. The tests were completed in accordance with the procedures laid down in BS EN ISO 17892 and BS1377: 1990, unless stated otherwise, and consisted of:

- Natural moisture content
- Atterberg limits
- Particle size distribution
- Unconsolidated undrained triaxial testing
- Sulphate content and pH value
- Total sulphur content
- Loss on ignition

#### **3.2 TEST PROCEDURES**

##### **3.2.1 NATURAL MOISTURE CONTENT**

The natural moisture content (also known as water content) is determined according to BS EN ISO 17892: Part 1: 2014: clause 5.2. This represents the mass of moisture content retained by the soil in its natural state as a percentage of its dry mass. For organic soils and peats care should be taken to avoid heating the sample above 50°C to prevent irreversible physical changes to the material.

##### **3.2.2 ATTERBERG LIMITS**

The Atterberg limits are determined in the laboratory by the procedures given in BS EN ISO 17892: Part 12: 2018. The liquid limit (LL) is the moisture content of the soil at the point that its behaviour passes from that of a plastic solid to that of a liquid. The test procedure given as clause 5.3 was used based on the cone penetrometer in which the penetration of a free-fall cone into moistened and cured samples of the soil is measured. The plastic limit (PL) is the moisture content of the soil at the point that its behaviour passes from a plastic solid to a brittle solid. This point is measured according to clause 5.5 and is the point at which a thread of the soil rolled to 3 mm diameter begins to crumble.

Together the Atterberg limits can be used to define the plastic range of the soil. The plasticity index (PI) is the difference between the liquid and plastic limit and is broadly correlated to the engineering behaviour of the soil. When used with the natural moisture content of the soil they can also give an indication of its *in situ* condition.

### **3.2.3 PARTICLE SIZE DISTRIBUTION**

A quantitative assessment of the particle size distribution of the soil down to the fine grained sand size is made according to BS EN ISO 17892: Part 4: 2016: clause 5.2. In this the percentage of certain sized fractions of the soil are found by determining the weight retained on a variety of sieve sizes through which the material is allowed to pass. The combined silt and clay fraction is determined by the difference between the sum of the retained weights and the original sample weight. Variations of the test procedure allow the silt and clay fraction to be removed from the coarser fraction by wet sieving during which the fine material is washed from the surface of the coarser material.

The quantitative determination of the particle size distribution for fine soils, from coarse silt to clay size, is made according to BS EN ISO 17892: Part 4: 2016: clause 5.3 or 5.4, using either the sedimentation by hydrometer method or pipette method. These tests are generally carried out if greater than 10% of the material passes the BS test sieve size of 63  $\mu\text{m}$ . The percentages of the constituents of the fine soil can be linked to the curve obtained by sieving to provide a single curve for the whole material.

### **3.2.4 UNCONSOLIDATED UNDRAINED TRIAXIAL TESTING**

The undrained shear strength of the soil was measured, as stated in BS EN ISO 17892: Part 8: 2018 or BS 1377: Part 7: 1990: clause 8, by axial compression of 70 mm diameter cylindrical specimens cut from the U70 undisturbed samples. The nature of the test is such that no change in moisture content of the specimen is allowed during shear.

The theory of behaviour of saturated clay materials in undrained shear failure gives that the strength will not be influenced by the confining pressure such that the measured angle of internal friction for the material will apparently be equal to zero. Experience has shown that this is true only for samples of unweathered heavily overconsolidated pure clays. Where the material is weathered or it contains a significant granular content a plastic rather than a brittle failure develops which produces a strain hardening during shear. In this

situation measurable apparent undrained angle of internal friction is produced. A similar situation develops in partially saturated materials. The test results are also influenced by sample variation, and in particular the presence of natural fissures or inclusions within the sample.

The use of large diameter specimens is preferred as this compensates for the scale effects of random features in smaller specimens. One of two tests are carried out according to the soil characteristic. Unweathered specimens of heavily overconsolidated clays which have a brittle failure in shear are tested in a single stage according to BS EN ISO 17892: Part 8: 2018. The confining pressure is taken as the total overburden pressure of the sample *in situ*. It is then failed by axial compression and the measured deviator stress reported as the apparent undrained cohesion. Specimens of weathered clay or the clays with granular contents are tested in a multistage manner according to BS 1377: Part 7: 1990: clause 9.

The test procedure is similar to the single stage but at the point that failure begins the confining pressure is increased and the specimen compressed for a further 2% of vertical strain at which point the confining pressure is again increased and held for a further 2% strain. The deviator stresses at each of the confining pressures are used to plot the Mohr envelope and the apparent undrained cohesion and if appropriate the undrained angle of internal friction.

### **3.2.5 SULPHATE CONTENT AND pH VALUE**

In order to aid the evaluation of any aggressive tendency of the subsoil or groundwater to buried concrete, the pH, water soluble and total sulphate concentrations in a number of samples were determined using in-house procedures based on other methodologies.

The pH of a groundwater sample or a soil filtrate was established electrometrically according to BS 1377: Part 3: 1990: clause 9.5, while water soluble sulphate and groundwater sulphate were determined using procedures based on Standard Methods for the Examination of Water and Wastewater Part 3120 B – 21st Edition (AWWA & WEF, 2005). This requires the preparation of a soil extract using deionised water at a 2:1 ratio. The filtered extract of the soil, or a water sample, are then injected into an ion exchange chromatograph with a conductivity detector. The samples are compared against commercially available standards to evaluate the sulphate concentration.



The total sulphate content of a soil was measured on a filtrate following digestion of the soil by 10% hydrochloric acid, as shown by BS 1377: Part 3: 1990: clause 5.5 and TRL 447 (Reid *et al* 2005). Subsequently the soil filtrate is introduced into ICP-OES equipment to determine sulphate concentration.

### **3.2.6 TOTAL SULPHUR CONTENT**

To aid the evaluation of aggressive tendency of the subsoil to buried concrete as a result of its pyritic potential, the total potential sulphate content can be determined from the relationship between the total (acid soluble) sulphate content and the amount of total sulphur present. The total sulphur content is determined by a laboratory in-house methodology based on Standard Methods for the Examination of Water and Wastewater Part 3120 B – 21st Edition (AWWA & WEF, 2005).

A dried portion of the soil is extracted at 115 °C for 75 minutes using 100% aqua regia. The digest solution is filtered and analysed by ICP-OES. The results are expressed as % S, and include water soluble and acid soluble sulphates and total reduced sulphur, as well as insoluble sulphates and organic sulphur.

### **3.2.7 LOSS ON IGNITION**

The organic content of peats or organic clays containing more than about 10% organic matter or sandy soils containing only limited quantities of clay or chalk can be related to the loss in the mass of the soil on ignition. This is carried out according to a laboratory in-house method based on BS 1377: Part 3: 1990: Clause 4. The test involves a previously dried and weighed sample being burned at a temperature of 450°C, the result is then reported as the ratio (%) of mass before and after burning.

#### **4. COPYRIGHT**

The copyright of any proposal or any data presented in the report, including without exclusion all text and all procedures and methods developed by A F Howland Associates Limited is held by A F Howland Associates Limited and all rights to such are reserved.

Outside of the use of the report by the Client and its advisors outside of the immediate context for which the work was commissioned, no part of the content of, procedures described, or other facets of the report will be copied or used by others without the express and specific request and approval to do so in writing.

A D Barks  
BSc (Hons) FGS

Eur Ing Dr A F Howland  
MSc PhD DIC CEng FIMMM CGeol FGS GMICE

A F HOWLAND ASSOCIATES  
8 September 2021



## **APPENDIX A: REFERENCES**

AMERICAN WATER WORKS ASSOCIATION & WATER ENVIRONMENT FEDERATION. 2005. Standard Methods for the Examination of Water and Wastewater Part 3120 B – 21st Edition. American Public Health Association, Washington D.C.

BRITISH STANDARDS INSTITUTION. 1990. BS 1377: Methods of test for Soils for engineering purposes. British Standards Institution, London.

BRITISH STANDARDS INSTITUTION. 2007. BS EN ISO 1997-2:2007 Geotechnical Design - Part 2 Ground investigation and testing. British Standards Institution, London.

BRITISH STANDARDS INSTITUTION. 2020. BS 5930:2015+A1:2020 Code of practice for ground investigations. British Standards Institution, London.

BRITISH STANDARDS INSTITUTION. BS EN ISO 17892-1:2014 Geotechnical investigation and testing - Laboratory testing of soil. Part 1: Determination of water content. British Standards Institution, London.

BRITISH STANDARDS INSTITUTION. BS EN ISO 17892-4:2016 Geotechnical investigation and testing - Laboratory testing of soil. Part 4: Determination of particle size distribution. British Standards Institution, London.

BRITISH STANDARDS INSTITUTION. BS EN ISO 17892-8:2018 Geotechnical investigation and testing - Laboratory testing of soil. Part 8: Unconsolidated undrained triaxial test. British Standards Institution, London.

BRITISH STANDARDS INSTITUTION. BS EN ISO 17892-12:2018 Geotechnical investigation and testing - Laboratory testing of soil. Part 12: Determination of liquid and plastic limits. British Standards Institution, London

REID, J. M, CZEREWKO, M. A. and CRIPPS, J.C. Sulphate specification for structural backfills. TRL Report 447, 2005. Transport Research Laboratory, Crowthorne, UK



## APPENDIX B: WINDOWLESS SAMPLE HOLE RECORDS

<b>B</b>	Bulk disturbed sample
<b>D</b>	Small disturbed sample
<b>L</b>	Liner sample
<b>HV</b>	Hand shear vane
<b>U</b>	70 mm diameter undisturbed open tube drive sample
<b>X blows</b>	The associated figure 'X' is the number of blows to drive the sample tube over the given depth range
<b>SPT(C)</b>	Standard penetration test using a solid cone. N Value is uncorrected, but the hammer energy ratio is provided (in remarks)
<b>SPT</b>	Standard penetration test using a split spoon sampler. N Value is uncorrected, but the hammer energy ratio is provided (in remarks)
<b>IP</b>	Initial penetration of SPT equipment under its own weight
<b>X,X/X,X,X,X</b>	Blows per increment during the standard penetration test. The initial value relates to the seating drive (150 mm) and the remaining four to the 75 mm increments of the test length
<b>N=X</b>	SPT blow count 'N' given by the summation of the blows 'X' required to drive the full test length (300 mm)
<b>X*/Y</b>	Incomplete standard penetration test where the seating drive could not be completed. The blows 'X' represent the total blows for the given length of seating drive 'Y' (mm)
<b>X/Z</b>	Incomplete standard penetration test where the seating drive was achieved but the full test length was not. The blows 'X' represent the total blows for the given test length 'Z' (mm)
<b>dd/mm/yy:1.0</b> <b>dd/mm/yy: dry</b>	Date, water level at the borehole depth at the end of shift and the start of the following shift

Each sample type is numbered sequentially with depth and relates to the depth range quoted

All depths and measurements are given in metres, except as noted

Strata descriptions compiled by visual examination of samples obtained during boring, after BS 5930:2015+A1:2020 and modified in accordance with laboratory test results where applicable



# A F Howland Associates Geotechnical Engineers

Site  
Murrow AD Plant

Number  
**WS01**

<b>Machine</b> : Dando Terrier 2002 <b>Method</b> : Windowless Dynamic Sampling	<b>Dimensions</b> 102mm to 2.00m 87mm to 3.00m 75mm to 4.00m	<b>Ground Level (mOD)</b> -0.06	<b>Client</b> Murrow AD Plant Limited	<b>Job Number</b> 21.237
	<b>Location</b> 537510 E 304685 N	<b>Dates</b> 05/08/2021	<b>Engineer</b> Plandescil Limited	<b>Sheet</b> 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.00-0.30	D1				(0.30)	TOPSOIL (Brown desiccated silty slightly sandy clay)		
0.40-0.50	D2			-0.36	0.30	Soft grey brown silty slightly sandy organic CLAY		
0.80-1.00	B1				(0.90)			
1.00	HV 27kPa		26,28,27/Av. 27.00					
1.20-1.65	SPT N=0	DRY	IP 450 Test Failed	-1.26	1.20	Very soft grey brown silty slightly sandy CLAY		
1.20-1.65	D3							
1.20-2.00	L1							
2.00-2.45	U1	DRY	0 blows		(1.50)			
2.00-3.00	L2							
2.50-2.60	D4							
2.80-3.00	D5			-2.76	2.70	Very soft dark grey silty slightly sandy organic CLAY with occasional pockets of semi-decayed organic matter		
3.00-3.45	SPT N=0	DRY	IP 450 Test Failed		(1.30)			
3.00-3.45	D6							
3.00-4.00	L3							
3.80-4.00	D7			-4.06	4.00	Complete at 4.00m		

<b>Remarks</b> 1. Location CAT scanned prior to excavation 2. Hand dug inspection pit to 1.20 m 3. No groundwater encountered 4. SPT Hammer Energy Ratio = 63% 5. Hand vane serial number = 2032	<b>Scale (approx)</b> 1:25	<b>Logged By</b> SW
	<b>Figure No.</b> 21.237.WS01	



# A F Howland Associates Geotechnical Engineers

Site  
Murrow AD Plant

Number  
**WS02**

<b>Machine :</b> Dando Terrier 2002 <b>Method :</b> Windowless Dynamic Sampling	<b>Dimensions</b> 102mm to 2.00m 87mm to 3.00m 75mm to 4.00m	<b>Ground Level (mOD)</b> -0.53	<b>Client</b> Murrow AD Plant Limited	<b>Job Number</b> 21.237
	<b>Location</b> 537649 E 304667 N	<b>Dates</b> 05/08/2021	<b>Engineer</b> Plandescil Limited	<b>Sheet</b> 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.00-0.30	D1				(0.40)	TOPSOIL (brown desiccated silty slightly sandy clay)		
0.60-0.80	D2				0.40	Soft brown silty slightly sandy organic CLAY		
0.90	HV 44.33kPa		36,48,49/Av. 44.33					
1.00-1.20	D3				(1.30)			
1.20-1.65	U1	DRY	0 blows			... becoming very soft		
1.20-2.00	L1							
1.70-1.90	D4				1.70	Very soft grey silty organic CLAY with wood fragments and pockets of black semi decayed organic matter		
2.00-2.45	SPT N=0	DRY	IP 450 Test Failed					
2.00-2.45	D5							
2.00-3.00	L2							
2.80-3.00	D6				(2.30)	.... pockets of brown peat from 1.70 m		
3.00-3.45	U2	DRY	0 blows					
3.00-4.00	L3							
3.20-3.40	D7							
3.80-4.00	D8				4.00	.... shell fragments (Bivalves) from 3.70 m		
						Complete at 4.00m		

<b>Remarks</b> 1. Location CAT scanned prior to excavation 2. Hand dug inspection pit to 1.20 m 3. No groundwater encountered 4. SPT Hammer Energy Ratio = 63% 5. Hand vane serial number = 2032	<b>Scale (approx)</b> 1:25	<b>Logged By</b> SW
	<b>Figure No.</b> 21.237.WS01	



# A F Howland Associates Geotechnical Engineers

**Site**  
Murrow AD Plant

**Number**  
**WS03**

<b>Machine</b> : Dando Terrier 2002	<b>Dimensions</b> 102mm to 2.00m 87mm to 3.00m 75mm to 4.00m	<b>Ground Level (mOD)</b> -0.34	<b>Client</b> Murrow AD Plant Limited	<b>Job Number</b> 21.237
<b>Method</b> : Windowless Dynamic Sampling	<b>Location</b> 537788 E 304631 N	<b>Dates</b> 05/08/2021	<b>Engineer</b> Plandescil Limited	<b>Sheet</b> 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.00-0.30	D1				(0.50)	TOPSOIL (Brown desiccated silty slightly sandy clay with rare angular to subrounded fine to coarse limestone gravel)		
0.40-0.50	D2			-0.84	0.50	Soft brown, orange and grey mottled silty CLAY with occasional pockets of black organic matter		
0.80-1.00 0.90	D3 HV 95.33kPa		99,91,96/Av. 95.33		(1.10)	.... desiccated layer		
1.20-1.65 1.20-1.50 1.20-2.00	SPT N=0 D4 L1	DRY	IP 450 Test Failed	-1.94	1.60	Very soft grey silty organic CLAY with frequent pockets of black organic matter		
1.80-2.00	D5							
2.00-2.45 2.00-3.00	U1 L2	DRY	0 blows					
2.45-2.95 2.50-2.95	D6 SPT N=0	DRY	IP 450 Test Failed		(2.40)			
3.00-3.45 3.00-3.45 3.00-4.00	SPT N=0 D7 L3	DRY	IP 450 Test Failed			.... band of peat from 3.50 m to 3.60 m		
3.80-4.00	D8			-4.34	4.00	Complete at 4.00m		

<b>Remarks</b> 1. Location CAT scanned prior to excavation 2. Hand dug inspection pit to 1.20 m 3. No groundwater encountered 4. SPT Hammer Energy Ratio = 63% 5. Hand vane serial number = 2032	<b>Scale (approx)</b>	<b>Logged By</b>
	1:25	SW
	<b>Figure No.</b> 21.237.WS01	

## APPENDIX C: TRIAL PIT RECORDS

<b>B</b>	Bulk disturbed sample
<b>D</b>	Small disturbed sample
<b>HV</b>	Hand shear vane
<b>dd/mm/yy:1.0</b>	Date, water level at the borehole depth at the end of shift
<b>dd/mm/yy: dry</b>	and the start of the following shift

Each sample type is numbered sequentially with depth and relates to the depth range quoted

All depths and measurements are given in metres, except as noted

Strata descriptions compiled by visual examination of samples obtained during boring, after BS 5930:2015+A1:2020 and modified in accordance with laboratory test results where applicable







# A F Howland Associates Geotechnical Engineers

Site  
Murrow AD Plant

Trial Pit  
Number  
**HDT P01**

Excavation Method Hand dug	Dimensions 0.3 L x 0.3 W x 1.2 D	Ground Level (mOD) 1.61	Client Murrow AD Plant Limited	Job Number 21.237
	Location (dGPS) 537467 E 304563 N	Dates 06/08/2021	Engineer Plandescil Limited	Sheet 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.80	D1			0.41	1.20	EMBANKMENT (Stiff brown silty clay)  ... frequent rootlets           ... becoming light brown           Complete at 1.20m		



**Remarks**

1. Location CAT scanned prior to excavation
2. No groundwater encountered
3. Trial pit remained open and sidewalls stable during excavation.
4. Trial pit backfilled with arisings upon completion.

Scale (approx) 1:10	Logged By ZRH	Figure No. 21.237.HDTP01
------------------------	------------------	-----------------------------





**A F Howland Associates**  
**Geotechnical Engineers**

Site  
 Murrow AD Plant

Trial Pit Number  
**HDTPO3**

Excavation Method Hand dug	Dimensions 0.3 L x 0.3 W x 1.2 D	Ground Level (mOD) 2.62	Client Murrow AD Plant Limited	Job Number 21.237
	Location (dGPS) 537754 E 304518 N	Dates 06/08/2021	Engineer Plandescil Limited	Sheet 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.80	D1			1.42	(1.20)	EMBANKMENT (Soft brown greyish mottled silty clay)  ... occasional rootlets		
					1.20	Complete at 1.20m		

**Remarks**

1. Location CAT scanned prior to excavation
2. No groundwater encountered
3. Trial pit remained open and sidewalls stable during excavation.
4. Trial pit backfilled with arisings upon completion.



Scale (approx) 1:10	Logged By ZRH	Figure No. 21.237.HDTPO3
------------------------	------------------	-----------------------------



# A F Howland Associates Geotechnical Engineers

Site  
Murrow AD Plant

Trial Pit  
Number  
**HOTP04**

Excavation Method Hand dug	Dimensions 0.3 L x 0.3 W x 1.2 D	Ground Level (mOD) 0.93	Client Murrow AD Plant Limited	Job Number 21.237
	Location (dGPS) 537822 E 304564 N	Dates 06/08/2021	Engineer Plandescil Limited	Sheet 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.80	D1			-0.27	(1.20) 1.20	EMBANKMENT (Stiff light brown silty clay)  ... frequent rootlets		
						Complete at 1.20m		



**Remarks**

1. Location CAT scanned prior to excavation
2. No groundwater encountered
3. Trial pit remained open and sidewalls stable during excavation.
4. Trial pit backfilled with arisings upon completion.

Scale (approx) 1:10	Logged By ZRH	Figure No. 21.237.HOTP04
------------------------	------------------	-----------------------------



# A F Howland Associates

## Geotechnical Engineers

**Site**  
Murrow AD Plant

**Trial Pit Number**  
**TP01**

<b>Excavation Method</b> Machine Excavated	<b>Dimensions</b> 3.40 m x 1.50 x 3.00 m	<b>Ground Level (mOD)</b> 0.01	<b>Client</b> Murrow AD Plant Limited	<b>Job Number</b> 21.237
	<b>Location</b> 537496 E 304686 N	<b>Dates</b> 06/08/2021	<b>Engineer</b> Plandescil Limited	<b>Sheet</b> 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.00-0.30	D1				(0.30)	TOPSOIL (Brown desiccated very slightly slightly sandy clay)		
0.30-0.70	D2			-0.29	0.30 (0.40)	Soft to firm occasionally desiccated grey brown very silty slightly sandy organic CLAY with rare shell fragments.		
0.60	HV 74.33kPa		69,83,71/Av. 74.33	-0.69	0.70	Soft brown, grey and orange mottled very silty slightly peaty CLAY with occasional black organic matter and rare shell fragments		
1.10 1.10	HV 32.33kPa D3		34,38,25/Av. 32.33		(1.40)			
1.60	D4					Very soft dark grey very silty slightly sandy CLAY with occasional organic matter		
2.00 2.10	HV 15.67kPa D5		18,15,14/Av. 15.67	-2.09	2.10			
2.50	D6				(0.90)	Complete at 3.00m		
3.00 3.00	HV 10kPa D7		12,8,10/Av. 10.00	-2.99	3.00			

No image available

**Remarks**

1. Location CAT scanned prior to excavation
2. No groundwater encountered
3. Trial pit remained open and sidewalls stable during excavation.
4. Trial pit backfilled with arisings upon completion.
5. Hand vane serial number = 2032

<b>Scale (approx)</b> 1:20	<b>Logged By</b> SW	<b>Figure No.</b> 21.237.TP01
-------------------------------	------------------------	----------------------------------











# A F Howland Associates

## Geotechnical Engineers

**Site**  
Murrow AD Plant

**Trial Pit Number**  
**TP02**

<b>Excavation Method</b> Machine Excavated	<b>Dimensions</b> 3.40 m x 1.50 x 3.00 m	<b>Ground Level (mOD)</b> -0.56	<b>Client</b> Murrow AD Plant Limited	<b>Job Number</b> 21.237
	<b>Location</b> 537776 E 304635 N	<b>Dates</b> 06/08/2021	<b>Engineer</b> Plandescil Limited	<b>Sheet</b> 1/1

Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
0.00-0.40	D1					TOPSOIL (Brown desiccated very silty slightly sandy clay)		
0.50 0.60	D2 HV 54kPa		55,49,58/Av. 54.00	-0.96	0.40	Soft grey brown with occasional orange mottling very silty slightly sandy organic CLAY  .... desiccated 0.60 m to 0.90 m		
1.00 1.00	HV 24kPa D3		22,26,24/Av. 24.00		(1.20)			
1.50	D4			-2.16	1.60	Very soft grey very silty organic peaty CLAY with frequent fragments of wood, reeds and black organic matter		
2.00 2.00	HV 7.67kPa D5		8,6,9/Av. 7.67		(1.40)			
2.50	D6							
2.80	D7					.... 2.70 m to 2.80 m band of fibrous peat and plant matter with a strong organic odour		
3.00 3.00	HV 9.33kPa D8		9,9,10/Av. 9.33	-3.56	3.00	Complete at 3.00m		

No image available

**Remarks**

1. Location CAT scanned prior to excavation
2. No groundwater encountered
3. Trial pit remained open and sidewalls stable during excavation.
4. Trial pit backfilled with arisings upon completion.
5. Hand vane serial number = 2032

<b>Scale (approx)</b> 1:20	<b>Logged By</b> SW	<b>Figure No.</b> 21.237.TP02
-------------------------------	------------------------	----------------------------------

## **APPENDIX D: LABORATORY TESTING**

Natural moisture content

Atterberg limits

Particle size distribution

Unconsolidated undrained triaxial testing

Sulphate, sulphur and pH values

Loss on ignition





**Site** : Murrow AD Plant  
**Client** : Murrow AD Plant Limited  
**Engineer** : Plandescil Limited

**Job Number**  
21.237  
**Sheet**  
1 / 1

**DETERMINATION OF MOISTURE CONTENT, LIQUID LIMIT AND PLASTIC LIMIT  
AND DERIVATION OF PLASTICITY AND LIQUIDITY INDEX**

Borehole/ Trial Pit	Depth (m)	Sample	Natural Moisture Content %	Sample Passing 425µm Sieve		Liquid Limit %	Plastic Limit %	Plasticity Index %	Liquidity Index	Group Symbol	Laboratory Description
				Percentage %	Moisture Content %						
TP02	2.50	D6	53.8	100	53.8	67	27	40	0.68	CH	Grey mottled black CLAY.
WS01	0.80	B1	28.1	100	28.1	41	20	21	0.38	CI	Dark brown sandy CLAY. Sand is fine.
WS03	1.80	D5	70.7	100	70.7	95	34	61	0.61	CE	Dark brown and dark grey CLAY.

**Method of Preparation** : BS EN ISO 17892:PART 1:2014:5.1 Test specimen preparation (moisture content). BS EN ISO 17892:PART 1:2018:5.2 Preparation of samples for classification tests  
**Method of Test** : BS EN ISO 17892:PART 1:2014:5.2 Test execution (moisture content) BS EN ISO 17892: PART 12:5.3 & 6.2 Determination of the liquid limit BS EN ISO 17892:PART 5.5, 6.4 & 6.5 Determination of the plastic limit and plasticity index  
**Remarks** :








**Site** : Murrow AD Plant  
**Client** : Murrow AD Plant Limited  
**Engineer** : Plandescil Limited

**Job Number**  
21.237  
**Sheet**  
2/2

**DETERMINATION OF PARTICLE SIZE DISTRIBUTION**

Borehole / Trial Pit	Depth (m)	Sample	Laboratory Description
WS01	2.50	D4	Brownish grey slightly sandy silty CLAY.



CLAY	Fine	Medium	Coarse	Fine	Medium	Coarse	Fine	Medium	Coarse	COBBLES	BOULDERS
	SILT			SAND			GRAVEL				

Grading Analysis	
D85	90.5 µm
D60	14.6 µm
D10	<2.0 µm
Uniformity Coefficient	-

Particle Proportions	
Cobbles + Boulders	-
Gravel	-
Sand	21.5%
Silt	45.5%
Clay	33.0%

**Method of Preparation** : BS EN ISO 17892:2016 Part 4. Determination of particle size distribution

**Method of Test** : BS EN ISO 17892: Part 4: 2016: Clause 5.2 Wet or dry sieve. Clause 5.4 Sedimentation by pipette

**Remarks** :



**Site** : Murrow AD Plant  
**Client** : Murrow AD Plant Limited  
**Engineer** : Plandescil Limited

**Job Number**  
21.237  
**Sheet**  
1 / 1

**DETERMINATION OF DENSITY, MOISTURE CONTENT AND UNDRAINED SHEAR STRENGTH  
IN TRIAXIAL COMPRESSION WITHOUT MEASUREMENT OF PORE PRESSURE**

Borehole/ Trial Pit	Depth (m)	Sample	Moisture Content %	Bulk Density (Mg/m <sup>3</sup> )	Dry Density (Mg/m <sup>3</sup> )	Cell Pressure (kN/m <sup>2</sup> )	Deviator Stress (kN/m <sup>2</sup> )	Apparent Cohesion (kN/m <sup>2</sup> )	Angle of Shearing Resistance (degrees)	Laboratory Description
WS01	2.00	U1	37.7	1.69	1.23	40	47	23		Firm brown sandy CLAY.
WS02	1.20	U1	57.4	1.62	1.03	24	30	15		Soft to firm brownish grey CLAY.
WS02	3.00	U2	77.9	1.39	0.78	60	14	7		Very soft dark grey CLAY.

**Method of Preparation** : BS EN ISO 17892:PART 1:2014:5.1 Test specimen preparation (moisture content). BS EN ISO 17892:PART 8:2018: 6.2 Preparation of undisturbed samples for testing  
**Method of Test** : BS EN ISO 17892:PART 1:2014:5.2 Test execution (moisture content) and PART 2:2014 Determination of density. BS EN ISO 17892: PART 8: 2018: 6,7 + 8 Undrained shear strength (Single stage). BS 1377:PART 7:1990:9 Multistage loading  
**Remarks** :



**Site** : Murrow AD Plant  
**Client** : Murrow AD Plant Limited  
**Engineer** : Plandescil Limited

**Job Number**  
21.237  
**Sheet**  
1 / 1

**DETERMINATION OF pH, SULPHATE CONTENT AND TOTAL SULPHUR OF SOIL AND GROUNDWATER**

Borehole/ Trial Pit	Depth (m)	Sample	Concentration of Soluble Sulphate			Total Sulphur %	Percentage of sample passing 2mm Sieve %	pH	Laboratory Description
			Soil		Groundwater g / l				
			Total S04 %	S03 in 2:1 water:soil g / l					
WS01	0.40	D2	0.64	1.48		1.13		7.7	Grey loamy clay
WS01	2.80	D5	0.08	0.12		0.08		7.9	Brown sandy clay
WS03	2.50	D6	0.31	0.58		0.55		7.7	Grey loamy clay

**Method of Preparation** : BS 1377:PART 1:1990:7.5 Preparation of soil for chemical tests

**Method of Test** : Laboratory in-house methods based on BS1377: Part 3 for ph and total sulphate and TRL 447 (2005) for total sulphate, Standard Methods for the Examination of Water and Wastewater Part 3120 B – 21st Edition (2005) for water soluble sulphate and total sulphur.

**Remarks** :



**Site** : Murrow AD Plant  
**Client** : Murrow AD Plant Limited  
**Engineer** : Plandescil Limited

**Job Number**  
21.237

**Sheet**  
1 / 1

**DETERMINATION OF CHLORIDE CONTENT, ORGANIC MATTER CONTENT AND LOSS ON IGNITION**

Borehole/ Trial Pit	Depth (m)	Sample	Concentration of Chloride			Percentage of sample passing 2mm Sieve %	Organic Matter Content %	Mass Loss on Ignition %	Laboratory Description
			Soil		Groundwater mg/l				
			Acid Soluble %	Water Soluble mg/l					
WS03	2.50	D6					6.80	Grey loamy clay	

**Method of Preparation** : BS 1377:PART 1:1990:7.5 Preparation of soil for chemical tests

**Method of Test** : Lab in-house method based on Standard Methods for the Examination of Water and Wastewater Part 3120 B – 21st Edition (2005) for Determination of chloride content, BS 1377:PART 3:1990:4 for Determination of loss on ignition

**Remarks** :

## **APPENDIX E: DRAWINGS**

Drawing 21.237/01 Site Location Plan

Drawing 21.237/02 Exploratory Hole Location Plan





North



Circle indicates approximate location of site



**A F Howland Associates**  
Geotechnical Engineers

**Site:** Murrow AD Plant

SITE LOCATION PLAN


**Client :** Murrow AD Plant Limited

**Date :** September 2021


**Dwg :** 21.237/01

Scale 1: 50,000 @ A4




Reproduced by permission of Ordnance Survey on behalf of the Controller of Her Majesty's Stationery Office © Crown Copyright Licence No. AL 100002157  
Copyright © A F Howland Associates Limited 2021



Wisbech High Fen

North 

Key:

-  Windowless dynamic sampling location and reference
-  Trial pit location and reference
-  Hand dug trial pit location and reference

Reproduced by permission of Ordnance Survey on behalf of the  
 Controller of Her Majesty's Stationery Office © Crown  
 Copyright Licence No. AL 100002157  
 Copyright © A F Howland Associates Limited 2020

Rev	Date	Revision Description	Drwn	Chkd


 **A F Howland Associates**  
 Geotechnical Engineers

A F Howland Associates Ltd  
 The Old Exchange  
 Newmarket Road  
 Cringleford  
 Norwich  
 NR4 6UF

Tel: 01603 250754 Fax: 01603 250749  
 web: www.howland.co.uk  
 mail: admin@howland.co.uk

<b>Client:</b> Murrow AD Plant Limited
<b>Site:</b> Murrow AD Plant
<b>Job No.:</b> 21.237
<b>Drawing Title:</b> EXPLORATORY HOLE LOCATION PLAN
<b>Date:</b> September 2021
<b>Drawing No.:</b> 21.237/02
<b>Scale:</b> 1:1250 @ A3





**A F Howland Associates**

The Old Exchange  
Newmarket Road  
Cringleford  
Norwich  
NR4 6UF

Tel: 01603 250754

Fax: 01603 250749

Email: [admin@howland.co.uk](mailto:admin@howland.co.uk)

www: <http://www.howland.co.uk>