



Crimplesham Inert Landfill Site

Environmental Permit Application

Environmental Management and Monitoring Plan

September 2020

Prepared on behalf of Mick George Limited





Document Control

Document:	Environmental Management and Monitoring Plan	
Project:	Crimplesham Quarry Permit	
Client:	Mick George Limited	
Job Number:	A110260	
File Origin:	\\southampton14\Data\Projects\Mick George (G05059)\A110260 (Crimplesham Quarry Permit)\Reports	
Revision:	Draft	
Date:	September 2020	
Prepared by: Alice Shaw	Checked by: Michael Jones	Approved By:
Description of revision:		



Contents

1.0 Introduction 3

2.0 Groundwater Management and Monitoring 4

3.0 Surface Water Management and Monitoring 7

4.0 Landfill Gas Management and Monitoring 9

5.0 Meteorological Monitoring.....10

6.0 Landfill Body Monitoring11

7.0 Amenity Management and Monitoring12

8.0 Health Impact Monitoring13

9.0 Aftercare Monitoring14

Drawings

MGL-A110260-HYD-02 – Monitoring network and inferred groundwater flow direction



1.0 Introduction

1.1 Report Context

- 1.1.1 This section of the Environmental Permit application corresponds to Part B4 of the application forms, specifically detailing the environmental management and monitoring plan for the importation of suitable inert waste at Crimplesham.
- 1.1.2 The Environmental Permit application has been prepared by WYG on behalf of the Operator, Mick George Limited (Mick George).
- 1.1.3 This report has been prepared in accordance with the Environment Agency's (EA) Guidance for the Landfill Sector and LFTGN 02: Guidance on Monitoring of Landfill Leachate, Groundwater and Surface Water and with reference to the Hydrogeological Risk Assessment (HRA) and the Environmental Risk Assessment (ERA).



2.0 Groundwater Management and Monitoring

2.0.1 Adherence to the Waste Acceptance Criteria will ensure that the waste deposited at the site complies with the inert classification, thereby mitigating any risk to groundwater.

2.0.2 A HRA has been prepared for the inert landfill application (Appendix F of the Environmental Permit Application). The objective of the HRA is to assess the potential risk of significant impacts on groundwater quality as a result of the proposed development, to derive control and compliance limits for groundwater and surface water and to provide recommendations for contingency actions on the event of exceedances of those levels.

2.1 Groundwater Monitoring Schedule

2.1.1 The parameters to be sampled and monitoring frequency to be included in the Environmental Permit are presented in Table 1 below. These requirements are considered adequate in providing an ongoing characterisation of the groundwater conditions.

Table 1: Proposed Groundwater Monitoring Determinands and Sampling Frequency

Monitoring Location	Monthly	Quarterly	Annually
BHA, BHB, BHC, BHD, BHE, BHF and BHG (as shown on Drawing Number MGL-A110260-HYD-02)		Levels, pH, Chloride, Alkalinity Amm N, Sulphate, Sodium, Potassium, Iron, Manganese, Cadmium Chromium, Copper, Calcium, Nickel, Lead, Zinc, Electrical conductivity, Magnesium	<i>To include quarterly suites plus: Hazardous substances</i>

Compliance Levels

2.1.2 The HRA provides proposed compliance levels for Ammoniacal Nitrogen, Chloride, Sulphate, Nickel and Mercury. Table 2 below provides the Compliance Limit for each parameter at each of the boreholes.

Table 2: Proposed Groundwater Compliance Limits

Determinands	Compliance limits
Ammoniacal Nitrogen (mg/l)	4.38
Chloride (mg/l)	223
Sulphate (mg/l)	316



Nickel (µg/l)	3.5
Mercury (µg/l)	0.01

Contingency Plan

2.1.3 Once compliance levels have been agreed, should site monitoring identify an increase in the concentration of the selected determinands then a series of contingency actions will be required. Suggested contingency actions, which require agreement with the EA, are presented in Table 3.

Table 3: Suggested Contingency Actions for Exceeding Groundwater Compliance Limits

Appropriate Contingency Action	Timescale
Advise Site Management	Immediately
Advise Environmental Manager of PQL	1 Week
Advise Environment Agency	1 Week
Confirm by repeat sampling and analysis	1 Month
Review existing monitoring information	1 Month
Review site management/operations, implement actions to prevent future failure of a compliance level	3 Months
Review assumptions in conceptual site model	3 Months
Review existing HRA Compliance Levels	6 Months
Consult EA about need for corrective action	6 Months

2.2 Quality Control Procedures

Monitoring Personnel

2.2.1 Monitoring will be undertaken by suitably trained person(s) by the site management, who are familiar with the monitoring procedures. The monitoring personnel will have access to the Environmental Permit and any relevant accompanying application documents to gain an understanding of the conditions applicable to groundwater monitoring (levels and quality). Personnel will also be familiar with the assessment criteria to identify compliance and assessment levels.

Monitoring Procedures

2.2.2 The groundwater levels will be measured prior to sampling using an electronic dip tape.

2.2.3 The groundwater samples will be collected using a portable electric submersible pump or other suitable sampling equipment. In order to obtain a sample of the groundwater, each monitoring



borehole will be purged to at least three times the well volume to prevent sampling non-representative, stagnant samples.

2.2.4 All groundwater samples will be collected in 1 litre polyethylene or glass containers. Unless the containers already contain a preservative, they will be flushed three times with the sample prior to filling.

2.2.5 Filled sample bottles will be stored upright in cool boxes with ice packs. Sample bottles will be pre-labelled in accordance with laboratory requirements and will be submitted to a UKAS accredited laboratory within 24 hours of collection, together with the sample details, tests and suites required. If samples have to be kept overnight, they will be stored in a fridge/cool box and maintained at approximately 4°C.

Recording and Reporting

2.2.6 A hard copy of the sampling results will be stored on site for the duration of the site operations.

2.2.7 The site management will ensure that copies of the sampling results are sent to the EA in an agreed format and at quarterly frequencies.



3.0 Surface Water Management and Monitoring

3.0.1 The nearest surface water feature to the site is an unnamed pond which is located approximately 415m south from the application site.

3.0.2 According to the Flood Map for Planning Service (FMPS), the application site is not situated in an area at risk of flooding.

3.1 Surface Water Management

3.1.1 Drainage from the site occurs to two local surface water catchments, the Wissey operational catchment to the north and South Level and Cut Off Channel operational catchment to the south. The surface water divide between the two catchments crosses the centre of the site from west to east and this will remain after site restoration.

3.2 Surface Water Monitoring Schedule (if required)

3.2.1 The parameters to be sampled and monitoring frequency to be included in the Environmental Permit are presented in 4 below. These requirements are considered adequate in providing an ongoing characterisation of the groundwater conditions.

Table 4: Proposed Surface Water Monitoring Determinands and Sampling Frequency

Quarterly
pH, Chloride, Amm N, Sulphate, Nickel, Electrical conductivity

3.3 Contingency Plan

3.3.1 In the unlikely event of a pollution incident caused by a direct discharge of contamination e.g. leaking pipework, fuel spillage, the following emergency procedures will be implemented:-

- Immediately report incident to the Site Manager; and
- Identify source and prevent further leak/spillage.

3.3.2 For major fuel/oil spillage the following procedures will be implemented:-

- i) Clear the area immediately and extinguish any naked flames. Attempt to make a bund



- to contain the fuel/oil in order to limit the extent of the spillage;
- ii) If possible, try and contain the spill using absorbent materials available on site;
 - iii) Phone 999, ask for the Fire and Rescue Service and request assistance;
 - iv) Ring the EA the explain what has happened so they can take appropriate action;
 - v) At no time put staff, customers or the public at risk;
 - vi) If appropriate close the site, wait at the gate for emergency services and explain the situation prior to allowing access to site;
 - vii) Do not allow staff or the public to go back into the site until authorised to do so;
 - viii) Keep customers, and if appropriate public, informed about what is going on at all times;
 - ix) Once it is safe to enter the site, re-open to customers and update the EA;
 - x) Complete the site diary and any other paperwork about the incident; and
 - xi) The resultant spillage material should be disposed of in accordance with Environmental Permitting requirements. Specialist advice must be sought in the event of any doubt.

3.3.3 For minor fuel/spillage implement the following procedure: -

- i) Clear the area immediately and extinguish any naked flames;
- ii) Lay absorbent material over the spill to soak up the spillage and if any drains are nearby place the absorbent material around the drain to stop any liquid going into any surface water gullies; and
- iii) Once the liquid has all been absorbed use a shovel to clear up the waste, put it in a plastic sack and then place it in the fullest container for non-recyclable waste for disposal via the normal route.

3.3.4 In the event of the pollution reaching a surface water course, implement remedial measures in accordance with the EA guidance. Undertake additional monitoring to ensure water quality does not exceed assessment criteria.



4.0 Landfill Gas Management and Monitoring

- 4.0.1 A Landfill Gas Risk Assessment (GRA) has not been prepared for Crimplesham Inert Landfill Site, as Environment Agency Guidance Note H1 Annex I indicates that it is not a requirement for inert landfill sites. However, a screening report has been carried out in accordance with the requirements of Landfill Technical Guidance Note 03 (LFTGN03).
- 4.0.2 This Landfill Gas Screening Report indicates that there is unlikely to be a significant risk posed by the development. However, monitoring of the perimeter boreholes for landfill gas will be carried out in accordance with the Landfill Gas Screening Report as detailed within Appendix G of the Environmental Permit Application. The perimeter gas monitoring proposals including frequencies of monitoring are outlined in Table 5 below.

Table 5: Monitoring Programme

Monitoring Location	Parameter	Monitoring Frequency
BHA, BHB, BHC, BHD, BHE and BHF, BHG (as shown on MGL-A110260-HYD-02)	Methane, carbon dioxide, oxygen, meteorological data, atmospheric pressure, differential pressure, temperature.	Quarterly

- 4.0.3 Furthermore, in accordance with the EA’s guidance note on inert landfills, in-waste landfill gas monitoring infrastructure will be installed within each completed cell at a frequency of not less than 2 borehole per hectare. These boreholes will be monitored quarterly after restoration.



5.0 Meteorological Monitoring

- 5.0.1 The proposed landfill will only accept inert waste and with reference to the HRA and EA guidance, it is not considered necessary to manage and monitor leachate. This negates the need to monitor meteorological conditions for the purpose of using water balance calculations as a tool for evaluating leachate production.
- 5.0.2 Atmospheric pressure, temperature and ground conditions will be monitored and recorded during all monitoring visits.
- 5.0.3 Weather conditions that may be unfavourable to landfilling particularly dry loads will be used to determine the acceptability of such wastes on a particular day, for example strong winds given as severe weather warnings from the Meteorological Office.
- 5.0.4 Details on weather conditions will be recorded in the Site Diary on a daily basis.



6.0 Landfill Body Monitoring

6.0.1 Procedures will be in place to undertake routine surveys in order to record the following:-

- Surface area of waste;
- Volume of waste;
- Remaining capacity; and
- Settling behaviour.

6.0.2 Monitoring will be undertaken on an annual basis, or at a greater frequency determined by the site owner.



7.0 Amenity Management and Monitoring

7.0.1 An Environmental Risk Assessment (ERA) has been prepared in accordance with the EA's Risk Assessment guidance. It specifically deals with the following:-

- Particulate Matter Management and Monitoring;
- Noise Management and Monitoring;
- Odour Management and Monitoring;
- Mud Management and Monitoring;
- Litter Management and Monitoring; and
- Birds, Vermin and Insect Management and Monitoring.

7.0.2 Due to the inert nature of the waste, the site will not produce odour or litter nor will it attract birds, vermin and insects.

7.0.3 The ERA concluded that the risk of particulate matter and noise annoyance was not significant and therefore it is not proposed to implement monitoring regimes for these potential hazards.

7.0.4 The ERA also considered the risk of mud being transferred to the local highways as not significant. A wheel washing facility will be employed on site which will be used by HGVs before they leave the site. Water sprays will also be employed to dampen the access road. However, in the unlikely event that mud is deposited on the road then a road sweeper will be utilised as necessary.

7.0.5 The site is covered by planning permission C/2/2015/2038. This consent has planning conditions covering noise and dust.



8.0 Health Impact Monitoring

8.0.1 Due to the inert nature of the waste, it is considered unnecessary to undertake health impact monitoring on the surrounding population.



9.0 Aftercare Monitoring

- 9.0.1 It is proposed to continue the monitoring of groundwater and landfill gas during the aftercare period. At this stage it is proposed to monitor on the same basis as during the operational phase. Any changes to the monitoring frequency and analysis will be subject to agreement with the EA.



Drawings

MGL-A110260-HYD-02 – Monitoring network and inferred groundwater flow direction