

Biffa Waste Service Ltd

Eye Landfill, Eastern Extension

Nuisance and Health Management Plan

Submitted to:

Biffa Waste Services Ltd

Coronation Road Cressex High Wycombe HP12 3TZ

Submitted by:

Golder WSP

Attenborough House, Browns Lane Business Park, Stanton-on-the-Wolds, Nottingham, NG12 5BL, UK

+44 0 115 937 1111

21453458.636/A.0



Distribution List

Biffa Waste Services Ltd - 1 copy (pdf)

Golder, member of WSP in UK - 1 copy (pdf)

Peterborough City Council - 1 copy (pdf)



i

Table of Contents

1.0	INTRO	DDUCTION1
2.0	ENVIR	RONMENTAL RISK ASSESSMENT1
3.0	NUISA	ANCE AND HEALTH MANAGEMENT PLAN1
	3.1	Particulate Matter1
	3.1.1	
		Dust Generating Activities1
	3.1.2	Sensitive Receptors2
	3.1.3	Control Measures
	3.1.3.1	Weather Conditions
	3.1.3.2	Dust Control Actions
	3.1.3.3	Vehicle Speeds2
	3.1.3.4	Waste Placement2
	3.2	Odour
	3.2.1	Odour Generating Activities
	3.2.2	Sensitive Receptors
	3.2.3	Control Measures
	3.2.3.1	
	3.2.3.2	
	3.2.3.3	
	3.3	Dirt and Mud
	3.4	Litter
	3.5	Birds
	3.6	Vermin and Insects
	3.7	Noise and Vibration

APPENDICES

APPENDIX NHMP1

Environmental Risk Assessment (ERA)



1.0 INTRODUCTION

Biffa has requested Golder, member of WSP in UK (Golder), to prepare an Environmental Permit variation application for the landfilling of non-hazardous and inert waste in an extension to Eye Landfill.

Biffa proposes to develop parts of neighbouring Willow Hall Farm Quarry and Inert Landfill as a non-hazardous landfill (to be called the Eastern Extension) for continuous and uninterrupted landfilling operations after the current Southern Extension at Eye Landfill is completed. The Southern Extension is regulated under Environmental Permit EPR/BP3537PP/V010.

The Nuisance and Health Management Plan is updated here to reflect this proposed development. Following submission with the planning application, this Nuisance and Health Management Plan will also accompany an Environmental Permit variation application (EPR/BP3537PP/V011) to reflect the same development proposal.

The permitted waste list for the Eastern Extension will be the same as that currently approved for the Southern Extension *excluding* stable non-reactive hazardous waste. Wastes may also be received at the landfill for use in restoration, in accordance with the Environmental Permit.

2.0 ENVIRONMENTAL RISK ASSESSMENT

The Nuisance and Health Management Plan is based on current operational practice and the findings of the Environmental Risk Assessment (ERA) provided as **Appendix NHMP1**. The ERA identifies potential hazards, pathways and receptors. It refers to the control measures implemented at the Site to manage nuisance and health issues and therefore assesses the residual significance of each. It is noted that the landfill operational processes and procedures have been well established and satisfactorily implemented at the Site since 1982, as follows:

- The Central Area (~24 ha) was filled with putrescible waste from 1982 to 2000 and has been restored to agriculture.
- The Northern Extension (~7 ha) was filled with non-hazardous waste and with some asbestos between approximately 2000 and 2005 and has been restored to agriculture.
- The Northeastern Extension (~11 ha) was filled with non-hazardous waste between approximately 2005 and 2011 and has been restored to agriculture.
- The Southern Extension (~15 ha) is the current operational landfill area for non-hazardous and stable non-reactive hazardous (i.e. asbestos) wastes.

3.0 NUISANCE AND HEALTH MANAGEMENT PLAN

3.1 Particulate Matter

3.1.1 Dust Generating Activities

These may include the reception of waste delivery vehicles at the Site, exit of vehicles following deposit of wastes, traffic movements on internal site haul roads, landscaping/reprofiling works, raising of dust from bare areas by wind, deposit of non-hazardous wastes, excavation of inert wastes, handling of wastes at the operational area, compaction and covering of wastes, site preparation and engineering works, and site restoration works.



1

3.1.2 Sensitive Receptors

The ERA identifies residential and commercial properties on Willow Hall Lane as high sensitivity receptors to particulate matter from the Site; the specific receptors are down or crosswind from the Site and the closest (Cells 10, 11) are 150 m from the landfill cells or 50 m from restoration work activities. The ERA also identifies that the internal haul road crosses the Green Wheel path and runs parallel to it over a section of some 400 m.

3.1.3 Control Measures

3.1.3.1 Weather Conditions

Meteorological monitoring will be undertaken and includes monitoring for wind direction and wind speed to identify adverse weather conditions and significant wind speeds where particulate matter has the potential to leave the Site.

3.1.3.2 Dust Control Actions

To prevent the release of dust created by operations at the Site, water will be sprayed over the operational areas and site roads to affect control as necessary. Internal access roads and reception areas will be cleaned and maintained on a regular basis using an on-site, or hired, road sweeper.

Where ground conditions are damp, or there is precipitation, no further action may be necessary in relation to site engineering works, restoration works on completed phases, waste handling operations, or site haul roads in relation to damping of areas.

During dry weather conditions and irrespective of wind direction, measures may be implemented to dampen (subject to moisture content requirements of materials being placed) any areas being engineered, restoration works involving soils placement, operational areas being trafficked and site haul roads, to minimise release of dusts. This will be undertaken with a tractor and bowser or similar plant.

In adverse weather conditions where the raising of airborne dust from waste disposal or engineering operations cannot be prevented and dust cannot be prevented from leaving the Site, the offending operation will not occur.

3.1.3.3 Vehicle Speeds

Vehicle speeds will be limited to 15 mph on all Site roads and landfill areas. Appropriate signs are in place and will be maintained at the site entrance and along the haul road to indicate the maximum permissible site speed.

3.1.3.4 Waste Placement

To control dust from the landfill surface, specified waste types will be subject to handling measures detailed in the site waste acceptance procedures, to minimise releases of dust during deposit, handling and covering.

When necessary, high-risk particulate matter waste streams will be accepted in bagged or treated forms only. Waste will be thoroughly compacted and covered with a suitable amount of daily cover material. Upon any cell reaching permanent filling levels a temporary capping system will be installed after six months if permanent capping systems have not been installed.

3.2 Odour

3.2.1 Odour Generating Activities

These comprise waste reception, deposit and handling, removal of intermediate cover, landfill gas control and maintenance of landfill gas control infrastructure, and leachate re-circulation.



3.2.2 Sensitive Receptors

The ERA identifies residential and commercial properties on Willow Hall Lane as high sensitivity receptors to odour from the Site; the specific receptors are down or crosswind from the Site and the closest are 150 m from the landfill cells.

3.2.3 Control Measures

3.2.3.1 General

Control measures will include:

- Restricting materials that are likely to cause odour, like putrescible or already putrid biodegradable waste;
- Minimising quantities and storage times for odorous or potentially odorous materials;
- Managing materials and processes in ways which minimise the production of odours;
- Working within the effective operational capacity of the site, and
- Providing effective containment and abatement for odorous materials and activities.

3.2.3.2 Weather Conditions

Meteorological monitoring will be undertaken and includes monitoring for wind direction and wind speed to identify adverse weather conditions and significant wind speeds where odour has the potential to leave the Site. Periods of low wind speed towards receptors will also be considered, as odours are least likely to be dispersed during these conditions. Details of weather condition monitoring and remedial actions undertaken will be recorded in the site diary.

3.2.3.3 Odour Monitoring

An olfactory assessment shall be made by the Site Manager or designated member of staff at a minimum frequency of once per week at Environmental Monitoring Points 5 to 9 (EMP5 to EMP9) as shown on **Drawing ESID4.** Assessment may also be made by a suitably qualified member of staff during the monitoring round of the leachate and gas monitoring points. If an odour problem is detected, then the landfill gas and leachate management procedures and other relevant operational procedures including a site-specific odour management plan will be reviewed, and appropriate action taken.

Other sources of potential odour problems are the active tipping face, which will be assessed during site operations by a designated member of staff. If an odour problem is detected, then the waste deposition and cover procedures will be reviewed, and appropriate action taken. If odour from wastes deposited at the active tipping face cannot be adequately controlled, then further monitoring shall be undertaken at the site boundary. If required, the site shall cease to accept high odour risk waste streams when odour cannot be adequately controlled at the site boundary and the prevalent wind direction is towards sensitive receptors.

The assessment shall be recorded in terms of odour intensity and extent in accordance with the following:

Intensity:

- 1) No detectable odour;
- 2) Faint odour (barely detectable, need to stand still and inhale facing into the wind);
- 3) Moderate odour (odour easily detected while walking and breathing normally, possibly offensive);
- 4) Strong odour (bearable, but offensive odour will my clothes/hair smell); and
- 5) Very strong odour (this is when you really wish you were somewhere else).



Extent:

- 1) No detectable odour;
- 2) Local and impersistent (only detected during brief periods when wind drops or blows);
- 3) Impersistent as above, but detected away from site boundary;
- 4) Persistent, but fairly localised;
- 5) Persistent and pervasive up to 50 m from site boundary; and
- 6) Persistent and widespread (odour detected >50 m from site boundary).

The location, date, time and duration of the assessment shall be recorded, together with a description of the odour.

Odour nuisance from the importation of malodorous wastes will be controlled by the application of daily cover as detailed in the site waste acceptance procedures.

Odour nuisance arising from landfill gas emission will be controlled by extraction of the gas and utilisation or flaring as described in the Gas Management and Monitoring Plan for the Site.

3.3 Dirt and Mud

The dispersal of dirt and mud originating on the landfill onto public roads will be controlled. Unless properly controlled, mud and dirt has the potential to adhere to the tyres and chassis of vehicles and then be deposited beyond the site.

In the event of mud or debris being deposited onto the public highway, or fouling or discoloration of the public highway, then immediate arrangements will be made for the use or hire of a mechanical road sweeper in order to cleanse the affected areas as soon as practicably possible to the best standard that the available plant and prevailing conditions allow.

The following operational procedures will be implemented to ensure that dirt and mud do not reach the public highway and surrounding land:

- The Site Entrance Road will be cleaned and maintained on a regular basis using a hired or on-site road sweeper to remove dust, mud, and other debris;
- Waste compacting machinery and other plant will be thoroughly cleaned before being allowed off the site;
 and
- A wheel wash is available at the Site Reception.

The Site Entrance Road will be monitored twice daily but inspection will occur more frequently during adverse weather conditions. If any dirt or mud is found on the road, measures will be made immediately for the debris to be swept up with a road sweeper or tractor and brush, and for this to be cleared by the end of the working day. The cause will be identified and any appropriate measures to reduce the probability of this nuisance reoccurring will be taken. If a marked elevation in mud and debris is noted during the daily inspection, then the mitigating measures employed on-site will be reviewed.

During adverse weather conditions, should failure of road cleaning facilities occur in conjunction with excessive trafficking of mud onto external public highways, the installation will cease to accept waste until measures can be implemented to clean and maintain the cleanliness of the highway.



3.4 Litter

All vehicles delivering waste to the site will be required to ensure that loads carried in open vehicles or containers are secured with a net or tarpaulin to prevent items falling or being blown from the load.

Operations at the site will be conducted in a manner that minimises the incidence of windblown litter. During adverse weather conditions, waste containing paper and other materials likely to be windblown from the site will be deposited at lower levels within a phase and/or at the toe of the landfill face or, when necessary, will be refused access to the site until weather conditions become acceptable. Whenever possible, the filling of the upper levels in each phase will be undertaken during favourable weather conditions when the wind speed is low.

Litter netting (as used to date in the Southern Extension) will be installed inside the site boundary downwind of the operational cells and towards sensitive receptors and Willow Hall Lane. In addition, when necessary, the current tipping area and completed areas awaiting final capping will be protected by a >2.0 m high mobile fence, erected within the operational phase with due regard to wind direction. The fencing is of a quality and design such that it will be sufficient to catch most of the litter blown from the disposal area.

The litter netting and fence will be regularly inspected, maintained and repaired.

EMPs downwind of the active tipping area will be inspected daily and any loose waste material will be collected and disposed of within the landfill. If windblown materials leave the site the landfill will stop accepting light wastes, for example paper, polythene and dry powders.

Litter collecting on the litter nets and screens will be removed at intervals consistent with maintaining the efficiency and appearance of the screens and amenity of the area. The netting and fences described above will be walked regularly not less than once a week, more often if required, to retrieve any windblown litter caught by the fence or which has blown over it without delay. Litter accumulations near footpaths, screening bunds, soil bunds, drains, fields or residential areas shall be cleared first.

During very adverse weather conditions, Biffa reserves the right to cease waste acceptance until satisfactory weather conditions return.

3.5 Birds

The site is located in an area remote from any airport, and reservoirs used for public water supply, but lies adjacent to areas of agricultural land and close to the Green Wheel path and residential and commercial properties. Accordingly, the site will be operated in a manner designed to minimise the opportunity for birds to feed on waste deposited at the site.

During the day, the placed waste will be progressively covered with daily cover or other wastes to bury any biodegradable/putrescible materials, such that, at the end of the working day all biodegradable/putrescible waste will be covered by a thickness of selected cover material sufficient to prevent birds scavenging from the surface.

Site staff will report increased incidences of scavenging birds to the Site Manager during the day and immediately when they have the potential to impact upon sensitive receptors. Incidences of increased numbers of scavenging birds will be recorded in the site diary. In the event that the incidence of scavenging birds is unacceptable, methods will be used to control the birds. Such methods may include a combination of the measures detailed below:

- Use of additional daily cover to deter scavenging;
- Bird scaring cartridges;



- Crow scaring ropes;
- Amplified distress calls;
- Birds of prey or decoys; and
- Restrictions on acceptance of putrescible materials, closure of the site to high-risk waste streams or implementation of procedures to cover immediately such wastes during periods of high incidences of scavenging birds.

Selection of the appropriate method to be employed will take account of both effectiveness of the method to be used and its additional impact on the immediate environment, to ensure, subject to the need, effective control of any environmental risk resulting from scavenging birds and that the measures do not themselves cause pollution of the environment or harm to human health.

Particular attention will be made to ensure that deterrent methods do not generate excessive noise levels, by virtue of not siting these on areas of the site in proximity to sensitive receptors. Where wastes have been sufficiently covered at the end of the working day, so as to deter scavenging by birds, use of bird-scarers and amplified distress calls may be ceased until re-commencement of operations.

Use of measures implemented at the site, in response to incidences of increased numbers of scavenging birds, will be recorded in the site diary, along with details of date and time of deployment and location chosen to reduce off-site impacts arising from the use of the measures.

3.6 Vermin and Insects

The proposed method of operation and appropriate use of daily and intermediate cover, waste compaction techniques and handling procedures will ensure the minimisation of flies and rats at the site. The use of intermediate cover will minimise the risk of rats being attracted to, and feeding from, the waste mass and will ensure that fly eggs laid on or in the waste will not have the opportunity to hatch and emerge.

Site staff will be aware of the importance to control flies and to report to Site Manager in the event that an infestation becomes evident. An assessment will be made for the presence of flies weekly between the months of May and October and monthly at all other times.

In the event that flies are introduced to the site with incoming waste, or an infestation is observed, then insecticides offering rapid knockdown and long-term treatment will be applied, as appropriate.

A specialist pest control inspector will inspect the site for the presence of rats. Site staff will also be made aware of the need to report any instances of evidence of rats to site management. In the event that evidence of rats is found, a specialist contractor will administer appropriate poisons.

Where preparations are used to control rats or flies, as above, the pest control contractor will be required to submit relevant health and safety data sheets and risk assessment for the activities being undertaken. Materials to be used will be selected, based upon risk to environment for residues and active ingredients, and need to maintain effective control.

If required by the Weeds Act 1959, action will be taken to control or prevent the spread of injurious weeds. Following the establishment of pasture at the site, inspections will be carried out at intervals for the presence of ragwort, which will, if necessary, be controlled.

The types of materials that will be used in the control of pests and weeds will be selected in accordance with the provisions above prior to their use.



Details of all site inspections for pests by the Site Manager, nominated deputy or specialist contractor will be recorded in the site diary. In addition, any incidences reported by site staff will also be recorded. Where remedial, or preventative, pest control measures are implemented at the site; full details will be recorded in the site diary, including materials used, date and effectiveness, or planned date for the next follow up visit.

3.7 Noise and Vibration

Noise pollution will be aurally monitored (qualitatively) by the Site Manager and effective noise reduction measures shall be introduced and noted in the site diary. Noise reduction measures will typically include:

- Careful selection of the plant to be operated at the site, e.g. selecting plant with lower sound power levels.
- Careful management of plant such that it is not all operated at the same time where that it not necessary.
- Undertaking ongoing site works behind raised cell boundaries / working faces, such that it is acoustically screened from receptors.
- Storing stripped soil such that it forms acoustic screens/bunds between receptors and ongoing working operations.
- Controlled use of reversing bleepers.
- Turning off idling plant engines.
- Acoustic containers for gas engines.
- Selection of bird scaring devices.

No quantitative noise monitoring shall be routinely carried out at the site. Should noise be identified as a primary concern, for example following substantiated complaints, this will be undertaken as appropriate.



Signature Page

Golder WSP

Chris McDonald Project Director Nicola White Project Manager

31 March 2022

IC/NW/CM/ab

Company Registered in England No. 01383511 At WSP House, 70 Chancery Lane, London, WC2A 1AF VAT No. 905054942



APPENDIX NHMP1

Environmental Risk Assessment (ERA)



Hazard	Receptor	Harm	Pathway	Probability of Exposure	Consequence	Magnitude of Risk	Justification of Magnitude	Control Measures	Residual Risk
Releases of particulate matter (dusts)	Local human population/ presence. Closest residential/ commercial receptor is 150 m to the east of Cells 10, 11 down- wind of the operational site. Green Wheel path is parallel to section of internal haul road for a length of 400 m	Harm to human health - respiratory irritation and illness.	Air transport then inhalation of dust.	High	Medium	Medium	(vehicle movements) and placement of waste, and from the operational face/waste flanks.	Waste is delivered in accordance with approved acceptance procedures; vehicles delivering waste to the site are appropriately covered; during dry weather conditions, dampening of roads, engineering area, restoration work areas and operational areas will be undertaken if required; in adverse weather conditions where release of airborne dust cannot be prevented from leaving the site, waste disposal will be stopped; vehicle speeds are limited on all site roads and landfill areas; waste is thoroughly compacted and covered with suitable daily cover materials. Probability of exposure is greatest for Cells 10, 11.	Medium
Releases of particulate matter (dusts)	Local human population/ presence. Closest residential/ commercial receptor is 150 m to the east of Cells 10, 11 down- wind of the operational site. Green Wheel path is parallel to section of internal haul road for a length of 400 m	Nuisance - dust on cars, clothing etc.	Air transport then deposition	High	Medium	Medium	Permitted waste types are inert or non-hazardous but could be dusty. Dust could be raised from the delivery (vehicle movements) and placement of waste, and from the operational face/waste flanks. Probability of exposure is greatest for Cells 9, 10, 11. Proximity of houses, although screened by vegetation. Transient users of Green Wheel path.	Waste is delivered in accordance with approved acceptance procedures; vehicles delivering waste to the site are appropriately covered; during dry weather conditions, dampening of roads, engineering area, restoration work areas and operational areas will be undertaken if required; in adverse weather conditions where release of airborne dust cannot be prevented from leaving the site, waste disposal will be stopped; vehicle speeds are limited on all site roads and landfill areas; waste is thoroughly compacted and covered with suitable daily cover materials.	Medium
Litter	Inoniliation/presence	Nuisance, loss of amenity and harm to animal health.	Air transport then deposition	Medium	Medium	Medium	Houses and commercial properties	Waste is delivered in accordance with approved acceptance procedures - vehicles delivering waste to the site are appropriately covered (loads in open vehicles will be secured with a net or tarpaulin); during adverse weather conditions, waste containing materials that could be easily windblown will be deposited at lower levels within the landfill; a perimeter (fixed or mobile) fence will be used where required, erected within the operational phase and with due regard to wind direction; daily inspections will be undertaken and any loose material collected and disposed of in the landfill; litter collected on litter fences will be regularly removed; where release of litter cannot be prevented from leaving the site, waste disposal will be stopped.	Low
Dirt and mud on local roads.	Eyebury Road south of Site Entrance.	Nuisance, loss of amenity, road traffic accidents.	Vehicles entering and leaving site.	Medium	Medium	Medium	Road safety, local residents often sensitive to mud on roads. Traffic routing restricted to south along Eyebury Road. No HGV through	A twice daily inspection will identify if there are any areas of build up of mud on Site Entrance Road and local roads and any issues will be cleared as soon as practicable. The entrance road is surfaced in concrete with signage and traffic calming measures. Entrance road will be cleaned and maintained on a regular basis using suitable road sweeping equipment. Wheel wash is available at the Site Reception. If the operator and/or EA perceives that mud is an issue, then a management plan will be implemented as required by the permit.	Low

Odour	Local human population/ presence. Closest residential/ commercial receptor is 150 m to the east of Cells 10, 11 down- wind of the operational site. Green Wheel path is parallel to section of internal haul road for a length of 400 m.	Nuisance, loss of amenity.	Air transport then inhalation.	Medium	Medium	Medium	Probability of exposure is greatest for Cells 9, 10, 11.	Waste is delivered in accordance with approved acceptance procedures; the leachate holding tanks is fully enclosed, management of landfill gas is via extraction and flaring; daily cover is applied over the waste materials; meteorological monitoring assesses wind speed and direction - where this identifies low wind speed towards receptors, actions may be taken; olfactory monitoring is carried out at least once per week at defined locations.	Low
Noise and vibration.	Local human population/ presence. Closest residential/ commercial receptor is 150 m to the east of Cells 10, 11.	Nuisance, loss of amenity	Noise through the air and vibration through the ground.	Medium	High	High	vibration; the site is in an open rural area.	Qualitative noise monitoring will be carried out and effective noise reduction measures introduced and noted in the site diary; white noise reversing beepers utilised on site plant; idling plant engines are turned off; bird scaring devices are chosen based on their noise impact; any complaints will be recorded within the Site diary and an investigation will be undertaken and finding acted upon.	Medium
Scavenging animals and scavenging bird, and pests.	Local human population/ presence. Closest residential/ commercial receptor is 150 m to the east of Cells 10, 11.	Harm to human health - from waste carried off site and faeces. Nuisance and loss of amenity.	Air transport and over land.	Medium	Medium	Medium	Permitted wastes are biodegradable and have the potential to attract scavenging animals and birds, and pests; site is close to agricultural land and close to recreational areas and commercial/light industrial properties.	Daily cover will be applied to cover wastes at the end of the day; other wastes will be used to bury any biodegradable/putrescible materials during the days; waste is compacted; assessment is made monthly of flies apart from between May and October where it is weekly; regular monitoring of the site will be undertaken and any increase in incidents of scavenging birds reported to the Site Manager for action and recording in the site diary; use of bird scarers to control birds; use of pest control measures where required.	Low



golder.com