

APPENDIX 4

STABILITY ANALYSES – WASTE MASS

1. WASTE MASS MODEL

The site will receive inert waste as part of the deposit for recovery activity within the western extension area.

The waste associated with the deposit for recovery activity in the western excavation area will be placed in layers *c.* 1m thick in lifts *c.* 5m thick. The maximum total thickness of waste will be *c.* 15m. Active advancing slopes in waste material will be formed no steeper than 1v : 2h. Temporary inter-phase slopes in waste material will be formed no steeper than 1v : 3h. An intermediate bench with a minimum width of 10m will be maintained between lifts. The final restoration surface of the waste mass will be formed at gradients shallower than *c.* 1v : 25h.

No daily cover material will be placed.

2. SLOPE STABILITY – WASTE MASS

- **Aim**

To assess the potential for instability of the waste mass.

- **Analytical approach**

Use of SLIDE computer software to investigate the potential for slope failure.

- **Slope geometry**

See Analysis C.

- **Analysis input parameters**

- Shear strength and bulk density parameters

Material Type	Drained Shear Strength [c' (kPa)]	Angle of Shearing Resistance (°)	Bulk Density (Mg/m ³)
Artificial Geological Barrier (AGB)	4	23	1.8
Waste Mass	4	23	1.8
Groundwater	Quarry Floor Level		
Leachate	None		

- **Results (Analysis C)**

Advancing waste slope


Using the input parameters detailed above, a minimum FoS value of 1.34 is indicated by the analysis results for a circular failure involving an advancing waste slope.

Temporary inter-phase waste slope

Temporary inter-phase slopes in waste material will be formed at a shallower gradient than active advancing waste slopes. FoS values for circular slope failure involving the waste mass will be higher for temporary inter-phase waste slopes than for advancing waste slopes.

3. CONCLUSIONS

The calculated FoS value of 1.34 for an advancing waste slope is considered satisfactory. Accordingly, it is considered that the stability and integrity of an advancing or temporary inter-phase waste slope will not be compromised by slope instability.




Project		Shellingford Quarry - Stability Risk Assessment	
Group	Waste Mass Stability - Analysis C	Scenario	Master Scenario
Drawn By	GWP Consultants LLP	Company	Multi-Agg Limited
Date	25/09/2025, 16:19:56	File Name	Shellingford Quarry SRA 2025.slmd

GWP consultants
Upton House, Market Street, Charlbury, Oxfordshire OX7 3PJ, United Kingdom
tel +44 (0)1608 810374 fax +44 (0)1608 810093 e-mail info@gwp.uk.com web www.gwp.uk.com

earth & water resources GWP Consultants LLP, Registered No. OC326183, Registered Office: Upton House, Market Street, Charlbury, Oxfordshire OX7 3PJ, UK

SLIDEINTERPRET 9.038



Project

Shellingford Quarry - Stability Risk Assessment

Group Waste Mass Stability Layer 2 - Analysis C **Scenario** Master Scenario


Drawn By GWP Consultants LLP **Company** Multi-Agg Limited

Date 25/09/2025, 16:19:56 **File Name** Shellingford Quarry SRA 2025.slmd

GWP consultants
Upton House, Market Street, Charlbury, Oxfordshire OX7 3PJ, United Kingdom
tel +44 (0)1608 810374 fax +44 (0)1608 810093
e-mail: info@gwp.uk.com web: www.gwp.uk.com

earth & water resources

SLIDEINTERPRET 9.038



Project		Shellingford Quarry - Stability Risk Assessment		
Group	Waste Mass Stability Layer 3 - Analysis C	Scenario	Master Scenario	
Drawn By	GWP Consultants LLP	Company	Multi-Agg Limited	
Date	25/09/2025, 16:19:56	File Name	Shellingford Quarry SRA 2025.slmd	
	GWP consultants Upton House, Market Street, Charlbury, Oxfordshire OX7 3PJ, United Kingdom tel +44 (0)1608 810374 fax +44 (0)1608 810093 e-mail info@gwp.uk.com web www.gwp.uk.com earth & water resources GWP Consultants LLP, Registered No. OC326183 Registered Office: Upton House, Market Street, Charlbury, Oxfordshire OX7 3PJ, UK SLIDEINTERPRET 9.038			