

Odour Assessment

IPPC NEW PERMIT
Erection of 1 no. Pullet raising unit

Prepared for DA and LJ Woollam

Roger Parry & Partners **Reviewed: April 2025**

Roger Parry & Partners LLP www.rogerparry.net oswestry@rogerparry.net

Tel: 01691 655334

Odour Management Plan

Introduction

This Plan has been prepared as part of the Environmental Permit application as there are sensitive receptors (neighbouring dwelling houses) within 400m of the installation (Bryn y Plentyn Farm)

The following table sets out:

The likely sources of odour arising from a typical poultry unit The procedures to be followed at Bryn y Plentyn Farm in order to prevent or minimise odour levels

Typical Odour Sources and Actions to be Taken to Minimise Odours

Odour Related Issue	Potential Risks and Problems	Actions taken to minimise odour and odour risks at Bryn y Plentyn Farm	Completion date
Manufacture and selection of feed	Milling and mixing of compound feeds The use of poor quality and odorous ingredients Feeds which are 'unbalanced' in nutrients, leading to increased excretion and litter moisture and emissions of ammonia and other odorous compounds to air	No on-site milling. Feed specifications are prepared by the feed compounder's nutrition specialist Feed is supplied only from UKASTA accredited feed mills, so that only approved raw materials are used	In place
Feed delivery and storage	Spillage of feed during delivery and storage Creation of dust during feed delivery	•Feed delivery systems are sealed to minimise atmospheric dust •Any spillage of feed around the bin is immediately swept up •The condition of feed bins is checked frequently so that any damage or leaks can be identified	In place

Ventilation system	•Inadequate air movement in the house, leading to high humidity and wet litter •Inadequate system design, causing poor dispersal of odours	•The ventilation system is regularly adjusted according to the age and requirements of the flock •The ventilation system is designed to efficiently remove moisture from the house	In place
Litter management	Odours arising from wet litter (see above) •The use of insufficient or poor quality litter •Spillage of water from drinking systems •Disease outbreaks, leading to wet litter	Controls on feed and ventilation (see above) help to maintain litter quality. Additional controls include: Use of cupped nipple drinking systems which minimise spillage Insulated walls and ceilings to prevent condensation Concrete floors to prevent water ingress Stocking density at optimal levels to prevent overcrowding Use of a health plan, with specialist veterinary input used as necessary. The litter used would be sawdust as this is proved to have the best effect of reducing ammonia production	In place
Carcass disposal	 Inadequate storage of carcasses on site On-site disposal of carcasses by incineration 	•Carcasses are placed in the storage containers immediately after they are removed from the house before being removed from site by a specialist contractor under the National Fallen Stock Scheme	In place
House Clean Out	Creation of dust associated with litter removal from houses •Use of odorous products to clean houses	Litter is carefully placed into trailers positioned at the entrance to each house. When full, the trailer is covered Only approved and suitable products are used	In place
Used litter	•Storage of used litter on site •Transport of litter and applications to land	•There is no storage of used litter outside the houses at any time •Litter is transported in covered trailers	In place

Dirty water	•'Standing' dirty water during the production cycle or at	•Areas around the front of the houses are concreted and remain	In place	İ
management	clean out	clean during the production cycle		İ
	Applications of dirty water to land	•At clean-out, dirty water is directed to underground tanks for		1
		storage. It is then exported off site.		1
				1
				İ