



Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Expert Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1 Product identifier

Substance name: Hydrated lime, Calcium dihydroxide
Synonyms: Slaked lime, Air slaked lime, Building lime, Fat lime, Chemical lime, Finishing lime, Mason's lime, Calcium dihydroxide, Calcium hydroxide, Calcium hydrate, Lime, Lime water
Chemical name and formula: Calcium dihydroxide - $\text{Ca}(\text{OH})_2$
Trade name: Ultralime® Hydrated Lime
CAS: 1305-62-0
EINECS: 215-137-3
Molecular Weight: 74.09 g/mol
REACH Registration number: 01-2119475151-45-0019

1.2 Relevant identified uses of the substance or mixture and uses advised against

Please check the identified uses in table 1 of the Appendix of this SDS.

Uses advise against: There are no uses advised against.

1.3 Details of the supplier of the safety data sheet

Name: Singleton Birch Limited
Address: Melton Ross Quarries, Barnetby,
North Lincolnshire DN38 6AE
Phone N°: +44(0)1652 686000
Fax N°: +44(0)1652 686081
E-mail of competent person responsible for SDS in the MS or in the EU: kb@singletonbirch.co.uk; jt@singletonbirch.co.uk

1.4 Emergency telephone number

European Emergency N°: 112
National centre for Prevention & Treatment of Intoxications N°: National Chemicals Emergency Centre (NCEC) +44 (0) 870 190 6621
Emergency telephone at the company: +44(0)1652 686000 (24 hours)
Available outside office hours: Yes

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance

2.1.1 Classification according to Regulation (EC) 1272/2008

STOT Single Exp. 3, Route of exposure: Inhalation

Skin Irritation 2

Eye Damage 1



2.1.2 Classification according to Directive 67/548/EEC

Xi – irritant

2.2 Label elements

2.2.1 Labelling according to Regulation (EC) 1272/2008

Signal word:

Danger

Hazard pictogram:



Hazard statements:

H315:

Causes skin irritation

H318:

Causes serious eye damage

H335:

May cause respiratory irritation

Precautionary statements:

P102:

Keep out of reach of children

P280:

Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P310:

IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTRE or doctor/physician

P302+P352:

IF ON SKIN: Wash with plenty of water

P261:

Avoid breathing dust/spray

P304+P340:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P501:

Dispose of contents/container in accordance with local, regional, national and international regulation – use a registered hazardous waste carrier/licence holder, and/or contact the manufacturer

2.2.2 Labelling according to Directive 67/548/EEC

Indication of danger:

Xi irritant

Hazard pictogram:



Risk phrases:

R37: Irritating to respiratory system

R38: Irritating to skin

R41: Risk of serious damage to eyes



Your complimentary
use period has ended.
Thank you for using
PDF Complete.



Click Here to upgrade to
Unlimited Pages and Export Capabilities

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

Safety phrases:

- S2: Keep out of the reach of children
- S25: Avoid contact with eyes
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- S37: Wear suitable gloves
- S39: Wear eye/face protection

2.3 Other hazards

The substance does not meet the criteria for PBT or vPvB substance.
No other hazards identified.

3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Main constituent

Name: Calcium dihydroxide
CAS: 1305-62-0
EINECS: 215-137-3

Impurities

No impurities relevant for classification and labelling.

4 FIRST AID MEASURES

4.1 Description of first aid measures

General advice

No known delayed effects. Consult a physician for all exposures except for minor instances.

Following inhalation

Move source of dust or move person to fresh air. Obtain medical attention immediately.

Following skin contact

Carefully and gently brush the contaminated body surfaces in order to remove all traces of product. Wash affected area immediately with plenty of water. Remove contaminated clothing. If necessary seek medical advice.

Following eye contact

Rinse eyes immediately with plenty of water and seek medical advice.

Following ingestion

Clean mouth with water and drink afterwards plenty of water. Do **NOT** induce vomiting. Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Calcium dihydroxide is not acutely toxic via the oral, dermal, or inhalation route. The substance is classified as irritating to skin and the respiratory tract, and entails a risk of serious damage to the eye. There is no concern for adverse systemic effects because local effects (pH-effect) are the major health hazard.





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Expanded Features



Change

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

4.3 Indication of any immediate medical attention and special treatment needed

Follow the advises given in section 4.1

5 FIREFIGHTING MEASURES

5.1 Extinguishing media

5.1.1 Suitable extinguishing media

Suitable extinguishing media: The product is not combustible. Use a dry powder, foam or CO₂ fire extinguisher to extinguish the surrounding fire. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.1.2 Unsuitable extinguishing media

Do not use water

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for fire fighters

Avoid generation of dust. Use breathing apparatus. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation.

Keep dust levels to a minimum.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8)

6.1.2 For emergency responders

Keep dust levels to a minimum.

Ensure adequate ventilation.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8)

6.2 Environmental precautions

Contain the spillage. Keep the material dry if possible. Cover area if possible to avoid unnecessary dust hazard. Avoid uncontrolled spills to watercourses and drains (pH increase). Any large spillage into watercourses must be alerted to the Environment Agency or other regulatory body.





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Expanded Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

6.3 Methods and material for containment and cleaning up

In all cases avoid dust formation.

Keep the material dry if possible.

Pick up the product mechanically in a dry way.

Use vacuum suction unit, or shovel into bags.

6.4 Reference to other sections

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13 and the Annex of this safety data sheet.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

7.1.1 Protective measures

Avoid contact with skin and eyes. Wear protective equipment (refer to section 8 of this safety data sheet). Do not wear contact lenses when handling this product. It is also advisable to have individual pocket eyewash. Keep dust levels to a minimum. Minimize dust generation. Enclose dust sources, use exhaust ventilation (dust collector at handling points). Handling systems should preferably be enclosed. When handling bags usual precautions should be paid to the risks outlined in the Council Directive 90/269/EEC.

7.1.2 Advice on general occupational hygiene

Avoid inhalation or ingestion and contact with skin and eyes. General occupational hygiene measures are required to ensure safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no drinking, eating and smoking at the workplace. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home.

7.2 Conditions for safe storage, including any incompatibilities

The substance should be stored under dry conditions. Any contact with air and moisture should be avoided. Bulk storage should be in purpose – designed silos. Keep away from acids, significant quantities of paper, straw, and nitro compounds. Keep out of reach of children. Do not use aluminium for transport or storage if there is a risk of contact with water.

7.3 Specific end use(s)

Please check the identified uses in table 1 of the Appendix of this SDS.

For more information please see the relevant exposure scenario, available via your supplier/given in the Appendix, and check section 2.1: Control of worker exposure.





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Expanded Features



Change

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

SCOEL recommendation (SCOEL/SUM/137 February 2008; see Section 16.6):

Workplace Exposure Limit (WEL), 8 h TWA: 5 mg/m³

Occupational Exposure Limit (OEL), 8h TWA: 1 mg/m³ respirable dust of calcium oxide

Short-term exposure limit (STEL), 15 min: 4 mg/m³ respirable dust of calcium oxide

PNEC aqua = 490 µg/l

PNEC soil/groundwater = 1080 mg/l

8.2 Exposure controls

To control potential exposures, generation of dust should be avoided. Further, appropriate protective equipment is recommended. Eye protection equipment (e.g. goggles or visors) must be worn, unless potential contact with the eye can be excluded by the nature and type of application (i.e. closed process). Additionally, face protection, protective clothing and safety shoes are required to be worn as appropriate.

Please check the relevant exposure scenario, given in the Appendix/available via your supplier.

8.2.1 Appropriate engineering controls

If user operations generate dust, use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne dust levels below recommended exposure limits.

8.2.2 Individual protection measures, such as personal protective equipment

8.2.2.1 Eye/face protection

Do not wear contact lenses. For powders, tight fitting goggles with side shields, or wide vision full goggles. It is also advisable to have individual pocket eyewash.

8.2.2.2 Skin protection

Since calcium dihydroxide is classified as irritating to skin, dermal exposure has to be minimised as far as technically feasible. The use of protective gloves (nitrile), protective standard working clothes fully covering skin, full length trousers, long sleeved overalls, with close fittings at openings and shoes resistant to caustics and avoiding dust penetration are required to be worn.

8.2.2.3 Respiratory protection

Local ventilation to keep levels below established threshold values is recommended. A suitable particle filter mask is recommended, depending on the expected exposure levels - please check the relevant exposure scenario, given in the Appendix/available via your supplier.

8.2.2.4 Thermal hazards

The substance does not represent a thermal hazard, thus special consideration is not required.





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Expanded Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

8.2.3 Environmental exposure controls

All ventilation systems should be filtered before discharge to atmosphere.

Avoid releasing to the environment.

Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority responsible for environmental protection or other regulatory body.

For detailed explanations of the risk management measures that adequately control exposure of the environment to the substance please check the relevant exposure scenario, available via your supplier.

For further detailed information, please check the Appendix of this SDS.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	White or off white (beige) fine powder
Odour:	odourless
Odour threshold:	not applicable
pH:	12.4 (saturated solution at 20 °C)
Melting point:	> 450 °C (study result, EU A.1 method)
Boiling point:	not applicable (solid with a melting point > 450 °C)
Flash point:	not applicable (solid with a melting point > 450 °C)
Evaporation rate:	not applicable (solid with a melting point > 450 °C)
Flammability:	non flammable (study result, EU A.10 method)
Explosive limits:	non explosive (void of any chemical structures commonly associated with explosive properties)
Vapour pressure:	not applicable (solid with a melting point > 450 °C)
Vapour density:	not applicable
Relative density:	2.24 (study result, EU A.3 method)
Solubility in water:	1844.9 mg/L (study results, EU A.6 method)
Partition coefficient:	not applicable (inorganic substance)
Auto ignition temperature:	no relative self-ignition temperature below 400 °C (study result, EU A.16 method)
Decomposition temperature:	When heated above 580°C, calcium dihydroxide decomposes to produce calcium oxide (CaO) and water (H ₂ O)
Viscosity:	not applicable (solid with a melting point > 450 °C)
Oxidising properties:	no oxidising properties (Based on the chemical structure, the substance does not contain a surplus of oxygen or any structural groups known to be correlated with a tendency to react exothermally with combustible material)

9.2 Other information

Not available





Your complimentary
use period has ended.
Thank you for using
PDF Complete.



Click Here to upgrade to
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

10 STABILITY AND REACTIVITY

10.1 Reactivity

In aqueous media $\text{Ca}(\text{OH})_2$ dissociates resulting in the formation of calcium cations and hydroxyl anions (when below the limit of water solubility).

10.2 Chemical stability

Under normal conditions of use and storage, calcium dihydroxide is stable.

10.3 Possibility of hazardous reactions


Calcium dihydroxide reacts exothermically with acids. When heated above 580 °C, calcium dihydroxide decomposes to produce calcium oxide (CaO) and water (H₂O): $\text{Ca}(\text{OH})_2 \rightarrow \text{CaO} + \text{H}_2\text{O}$. Calcium oxide reacts with water and generates heat. This may cause risk to flammable material.

10.4 Conditions to avoid

Minimise exposure to air and moisture to avoid degradation.

10.5 Incompatible materials

Calcium dihydroxide reacts exothermically with acids to form salts. Calcium dihydroxide reacts with aluminium and brass in the presence of moisture leading to the production of hydrogen.



10.6 Hazardous decomposition products

None

Further information: calcium dihydroxide reacts with carbon dioxide to form calcium carbonate, which is a common material in nature.

11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Calcium dihydroxide is classified as irritating to skin and the respiratory tract and it entails a risk of serious damage to the eye. The occupational exposure limit for the prevention of local sensory irritation and decrease of lung function parameters as critical effects is OEL (8 h) = 1 mg/m³ respirable dust.

Toxicity endpoints	Outcome of the effects assessment
Absorption	The primary health effect of calcium dihydroxide is local irritation due to a pH shift. Therefore, absorption is not a relevant parameter for the effects assessment.





Your complimentary
use period has ended.
Thank you for using
PDF Complete.



Click Here to upgrade to
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

Toxicity endpoints	Outcome of the effects assessment
Acute toxicity	<p>Calcium dihydroxide is not acutely toxic.</p> <p>Oral LD₅₀ > 2000 mg/kg bw (OECD 425, rat)</p> <p>Dermal LD₅₀ > 2500 mg/kg bw (calcium dihydroxide, OECD 402, rabbit)</p> <p>Inhalation no data available</p> <p>Classification for acute toxicity is not warranted.</p> <p>For irritating effects to the respiratory tract see below.</p>
Irritation / corrosion	<p>Eye Irritation: Calcium dihydroxide entails a risk of serious damage to the eye (eye irritation studies (<i>in vivo</i>, rabbit).</p> <p>Skin Irritation: Calcium dihydroxide is irritating to skin (<i>in vivo</i>, rabbit).</p> <p>Respiratory Irritation: From human data it is concluded that Ca(OH)₂ is irritating to the respiratory tract.</p> <p>Based on experimental results, calcium dihydroxide requires classification as irritating to skin [R38, irritating to skin; Skin Irrit 2 (H315 - Causes skin irritation)] and as severely irritating to the eye [R41, Risk of serious damage to eye; Eye Damage 1 (H318 - Causes serious eye damage)].</p> <p>As summarised and evaluated in the SCOEL recommendation (Anonymous, 2008), based on human data calcium dihydroxide is classified as irritating to the respiratory system [R37, Irritating to respiratory system; STOT SE 3 (H335 - May cause respiratory irritation)].</p>
Sensitisation	<p>No data available. Calcium dihydroxide is considered not to be a skin sensitiser, based on the nature of the effect (pH shift) and the essential requirement of calcium for human nutrition.</p> <p>Classification for sensitisation is not warranted.</p>
Repeated dose toxicity	<p>Toxicity of calcium via the oral route is addressed by upper intake levels (UL) for adults determined by the Scientific Committee on Food (SCF), being UL = 2500 mg/d, corresponding to 36 mg/kg bw/d (70 kg person) for calcium.</p> <p>Toxicity of Ca(OH)₂ via the dermal route is not considered as relevant in view of the anticipated insignificant absorption through skin and due to local irritation as the primary health effect (pH shift).</p> <p>Toxicity of Ca(OH)₂ via inhalation (local effect, irritation of mucous membranes) is addressed by an 8-h TWA determined by the Scientific Committee on Occupational Exposure Limits (SCOEL) of 1 mg/m³ respirable dust (see Section 8.1).</p> <p>Therefore, classification of Ca(OH)₂ for toxicity upon prolonged exposure is not required.</p>
Mutagenicity	<p>Bacterial reverse mutation assay (Ames test, OECD 471): Negative</p> <p>In view of the omnipresence and essentiality of Ca and of the physiological non-relevance of any pH shift induced by lime in aqueous media, lime is obviously void of any genotoxic potential.</p> <p>Classification for genotoxicity is not warranted.</p>





Your complimentary
use period has ended.
Thank you for using
PDF Complete.



Click Here to upgrade to
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

Toxicity endpoints	Outcome of the effects assessment
Carcinogenicity	Calcium (administered as Ca-lactate) is not carcinogenic (experimental result, rat). The pH effect of calcium oxide does not give rise to a carcinogenic risk. Human epidemiological data support lack of any carcinogenic potential of calcium oxide. Classification for carcinogenicity is not warranted.
Toxicity for reproduction	Calcium (administered as Ca-carbonate) is not toxic to reproduction (experimental result, mouse). The pH effect does not give rise to a reproductive risk. Human epidemiological data support lack of any potential for reproductive toxicity of calcium dihydroxide. Both in animal studies and human clinical studies on various calcium salts no reproductive or developmental effects were detected. Also see the Scientific Committee on Food (Section 16.6). Thus, calcium dihydroxide is not toxic for reproduction and/or development. Classification for reproductive toxicity according to regulation (EC) 1272/2008 is not required.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

12.1.1 Acute/Prolonged toxicity to fish

LC₅₀ (96h) for freshwater fish: 50.6 mg/l

LC₅₀ (96h) for marine water fish: 457 mg/l

12.1.2 Acute/Prolonged toxicity to aquatic invertebrates

EC₅₀ (48h) for freshwater invertebrates: 49.1 mg/l

LC₅₀ (96h) for marine water invertebrates: 158 mg/l

12.1.3 Acute/Prolonged toxicity to aquatic plants

EC₅₀ (72h) for freshwater algae: 184.57 mg/l

NOEC (72h) for freshwater algae: 48 mg/l

12.1.4 Toxicity to micro-organisms e.g. bacteria

At high concentration, through the rise of temperature and pH, calcium dihydroxide is used for disinfection of sewage sludges

12.1.5 Chronic toxicity to aquatic organisms

NOEC (14d) for marine water invertebrates: 32 mg/l





Your complimentary
use period has ended.
Thank you for using
PDF Complete.



Click Here to upgrade to
Unlimited Pages and Expanded Features

ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

12.1.6 Toxicity to soil dwelling organisms

EC₁₀/LC₁₀ or NOEC for soil macro organisms: 2000 mg/kg soil dw

EC₁₀/LC₁₀ or NOEC for soil micro organisms: 12000 mg/kg soil dw

12.1.7 Toxicity to terrestrial plants

NOEC (21d) for terrestrial plants: 1080 mg/kg

12.1.8 General effect

Acute pH-effect. Although this product is useful to correct water acidity, an excess of more than 1 g/l may be harmful to aquatic life. pH-value of > 12 will rapidly decrease as result of dilution and carbonation

12.2 Persistence and degradability

Not relevant for inorganic substances

12.3 Bioaccumulative potential

Not relevant for inorganic substances

12.4 Mobility in soil

Calcium dihydroxide which is sparingly soluble, and present a low mobility in most soils

12.5 Results of PBT and vPvB assessment

Not relevant for inorganic substances

12.6 Other adverse effects

No other adverse effects are identified

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal of calcium dihydroxide should be in accordance with local and national legislation.

Processing, use or contamination of this product may change the waste management options.

Dispose of container and unused contents in accordance with applicable member state and local requirements.

The used packing is only meant for packing this product; it should not be reused for other purposes.

After usage, empty the packing completely.

14 TRANSPORT INFORMATION

Calcium dihydroxide is not classified as hazardous for transport (ADR (Road), RID (Rail), IMDG / GGVSea (Sea)).

14.1 UN-Number

Not regulated





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Export Capabilities



Change

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

14.2 UN proper shipping name

Not regulated

14.3 Transport hazard class

Not regulated

14.4 Packing group

Not regulated

14.5 Environmental hazards

None

14.6 Special precautions for user

Avoid any release of dust during transportation, by using air-tight tanks

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not regulated.

15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance

Authorisations: Not required

Restrictions on use: None

Other EU regulations: Calcium dihydroxide is not a SEVESO substance, not an ozone depleting substance and not a persistent organic pollutant.

National regulations: Water endangering class 1 (Germany)

15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.

16 OTHER INFORMATION

Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.

16.1 Hazard Statements

H315: Causes skin irritation

H318: Causes serious eye damage

H335: May cause respiratory irritation

16.2 Precautionary Statements

P102: Keep out of reach of children

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+P351: IF IN EYES: Rinse cautiously with water for several minutes

P310: Immediately call a POISON CENTRE or doctor/physician





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

Click Here to upgrade to
Unlimited Pages and Expanded Features



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

- P302+P352: **IF ON SKIN:** Wash with plenty of soap and water
P261: Avoid breathing dust/fume/gas/mist/vapours/spray
P304+P340: **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing
P501: Dispose of contents/container in accordance with local/regional/national/international regulation - use a registered hazardous waste carrier/licence holder, and/or contact the manufacturer

16.3 Risk Phrases

- R37: Irritating to respiratory system
R38: Irritating to skin
R41: Risk of serious damage to eyes

16.4 Safety Phrases

- S2: Keep out of the reach of children
S25: Avoid contact with eyes
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S37: Wear suitable gloves
S39: Wear eye/face protection

16.5 Abbreviations

- EC₅₀: median effective concentration
LC₅₀: median lethal concentration
LD₅₀: median lethal dose
NOEC: no observable effect concentration
WEL: workplace exposure limit
OEL: occupational exposure limit
PBT: persistent, bioaccumulative, toxic chemical
PNEC: predicted no-effect concentration
STEL: short-term exposure limit
TWA: time weighted average
vPvB: very persistent, very bioaccumulative chemical
EULA: European Lime Association

16.6 Key literature references

- Anonymous, 2006: Tolerable upper intake levels for vitamins and minerals Scientific Committee on Food, European Food Safety Authority, ISBN: 92-9199-014-0 [SCF document]
Anonymous, 2008: Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL) for calcium oxide (CaO) and calcium dihydroxide (Ca(OH)₂), European Commission, DG Employment, Social Affairs and Equal Opportunities, SCOEL/SUM/137 February 2008





Your complimentary
use period has ended.
Thank you for using
PDF Complete.

[Click Here to upgrade to
Unlimited Pages and Expanded Features](#)



ange

REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Revision date: December 2010

Printing Date: January 20, 2011

16.7 Revision

SDS revised in accordance with EULA SDS format

Disclaimer

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.

ANNEX

Addition of exposure Scenarios as applicable - Please see Appendix SD30A SDS - Hydrate Lime Range.



SAFETY DATA SHEET

According to 1907/2006/EC, Article 31

Sodium Chloride - Rock Salt

Section 1: Identification of the substance/mixture and of the company / undertaking

1.1 Product Identifier	
Product Name	Sodium Chloride - Rock Salt
Other Names	Sodium Chloride Technical
CAS No.	7647-17-5
Index No.	Not listed
EC No.	231-598-3
Product Code	S0001296

1.2 Relevant identified uses of the substances or mixture and uses advised against	
Product Use	Laboratory chemicals, manufacture of substances, Scientific R&D

1.3 Details of the supplier of the safety data sheet	
Company	Breckland Scientific Supplies Ltd
Address	Antom Court, Tollgate Drive, Stafford, ST16 3AF
Web	www.brecklandscientific.co.uk
Telephone	01785 227 227
Fax	01785 227 444
Email	msds@brecklandscientific.co.uk
Emergency Telephone	08:30-17:00: 01785 227227 24hrs: 112

Section 2: Hazard Identification

2.1 Classification of the substance mixture	
Classification - (EC) No 1272/2008	Not considered hazardous

2.2 Label Elements	
Hazard Pictograms	
Signal Word	N/A
Hazard Statement	Not considered hazardous
Precautionary Statement	No additional precautions required No additional precautions required

Section 3: Composition/information on ingredients

3.1 Substances - 67/548/EEC/1999/45/EC

Chemical Name & Code	CAS No.	Classification	Concentration

All percentages are by weight.

If above table is empty - no components need to be disclosed according to the applicable regulations

Section 4: First Aid Measures

4.1 Description of first aid measures

Inhalation	Move the exposed person to fresh air. If breathing stops, provide artificial respiration.
Eye Contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin Contact	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash off immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly. Seek medical attention.
General Information	If you feel unwell, seek medical advice (show the label where possible).

Section 5: Firefighting Measures

5.1 Extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment
5.2 Special hazards arising from substances or mixture	No data available
5.3 Advice for firefighters	Wear suitable respiratory equipment when necessary

Section 6: Accidental Release Measures

6.1 Personal precaution, protective equipment and emergency procedures	Wear suitable protective clothing. Avoid breathing vapours, mist or gas. Avoid formation of dust. Ensure adequate ventilation of the working area. Evacuate personnel to a safe area.
6.2 Environmental precautions	If safe to do so, prevent further leakage or spillage. Do not let product enter drains.
6.3 Methods and materials for containments and cleaning up	Avoid raising dust. Sweep up. Transfer to suitable, labelled containers for disposal.

Section 7: Handling and Storage

7.1 Precautions for safe handling	Handle in accordance with good industrial hygiene and safety practice. Never carry a bottle by its top. Avoid formation of dust. Ensure adequate ventilation of the working area.
-----------------------------------	---

7.2 Conditions for safe storage including any incompatibilities.	<p>Keep container tightly closed in a cool, dry and well-ventilated area. Keep in properly labeled containers.</p> <p>General principles of chemical storage: Store the minimum stock levels of hazardous chemicals, always disposing of chemicals that are no longer required. Store large breakable containers, particularly of liquids, below shoulder height. Ensure containers and bottle tops are sealed properly to avoid unnecessary leakage of vapours. Ensure hazard labels are clear and never store in direct sunlight.</p>
--	---

Section 8: Exposure controls/ personal protection

8.1 Control parameters

8.1.1 Exposure limit values

Sodium Chloride - Rock Salt CAS No: 7647-17-5	Long Term (8hr TWA)	Short Term (15 min period STEL)
ppm	N/A	N/A
mg/m ³	N/A	N/A

Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used.

Figures are based upon UK EH40 WEL (Workplace Exposure Limits)

8.2 Exposure Controls

Engineering Measures	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of the working day. Ensure adequate ventilation of the working area. Ensure quickly accessible eye-wash stations are available.
Eye / face protection	Wear appropriate well-fitting protective eyeglasses or chemical safety goggles as described by EN166 (EU Standard)
Skin / hand protection	Wear appropriate protective gloves and clothing to prevent skin exposure. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact.
Respiratory protection	Use a EN149 (EU Standard) approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Section 9: Physical and chemical properties

State:	Solid
Colour:	Colourless
Melting point:	801
Boiling point:	1413
Relative density: (g/cm ³)	2.1650
Chemical formula:	N/A
Molecular weight: (g/mol)	

Section 10: Stability & Reactivity

10.1 Reactivity	No data available
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	No data available
10.4 Conditions to avoid	No data available
10.5 Incompatible materials	No data available

10.6 Hazardous decomposition products	No data available
---------------------------------------	-------------------

Section 11: Toxicological information

11.1 Information on toxicological effects:	
Acute toxicity	No data available
Germ cell mutagenicity	No data available
Carcinogenicity	No data available
Reproductive toxicity	No data available
11.4 Toxicological information	
Sodium Chloride - Rock Salt	Oral Rat LD50 (mg/kg): 3550

Section 12: Ecological information

12.1 Toxicity: Toxicity to daphnia and other aquatic vertebrates	
Sodium Chloride - Rock Salt	EC50 Daphnia magna (Water flea) (mg/l - 48hr): 1661

Section 13: Disposal considerations

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. Dispose of this material and its container to hazardous or special waste collection point

Section 14: Transport information

14.1 UN Number		
ADR/RID: N/A	IMDG: N/A	IATA: N/A
14.2 UN Proper shipping name:	Sodium Chloride - Rock Salt	
14.3 Transport hazard class(es):	N/A	
14.4 Packing group:	N/A	
14.5 Environmental Hazards		
ADR/RID: No	IMDG Marine Pollutant: No	IATA: No

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	Labelling according to Regulation (EC) No 1272/2008.

Section 16: Other information

16.1 Other information: Text of hazard statements in Section 3	

If above table is empty - no components need to be disclosed according to the applicable regulations

16.2 Further information	
Further information	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials. Breckland Scientific Supplies Limited will not be held liable for any damage or injury caused by this product and does not obviate the requirement for end users to carry out their own workplace and specific use risk assessment.</p>

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl₂, technical

article number: **6846**
Version: **4.0 en**
Replaces version of: 2019-07-25
Version: (3)

date of compilation: 2016-07-14
Revision: 2020-06-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Sodium hypochlorite solution
Article number	6846
Registration number (REACH)	01-2119488154-34-xxxx
Index No	017-011-00-1
EC number	231-668-3
CAS number	7681-52-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: laboratory chemical
laboratory and analytical use

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

Emergency information service **+49/(0)89 19240**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

Classification acc. to GHS			
Section	Hazard class	Hazard class and category	Hazard statement
2.16	substance or mixture corrosive to metals	(Met. Corr. 1)	H290
3.2	skin corrosion/irritation	(Skin Corr. 1B)	H314
3.3	serious eye damage/eye irritation	(Eye Dam. 1)	H318
4.1A	hazardous to the aquatic environment - acute hazard	(Aquatic Acute 1)	H400
4.1C	hazardous to the aquatic environment - chronic hazard	(Aquatic Chronic 2)	H411

Supplemental hazard information

Code	Supplemental hazard information
EUH031	contact with acids liberates toxic gas

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS05, GHS09



Hazard statements

H290 May be corrosive to metals
H314 Causes severe skin burns and eye damage
H410 Very toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - response

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

Supplemental hazard information

EUH031 Contact with acids liberates toxic gas.

Hazardous ingredients for labelling:

Sodium hypochlorite, solution ... % Cl active, Sodium hydroxide

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



H314 Causes severe skin burns and eye damage.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
EUH031 Contact with acids liberates toxic gas.
contains: Sodium hypochlorite, solution ... % Cl active, Sodium hydroxide

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description of the mixture

Composition/information on ingredients.

Name of substance	Identifier	wt %	Classification acc. to 1272/2008/EC	Pictograms	Specific Conc. Limits	M-Factors
Sodium hypochlorite, solution ... % Cl active	CAS No 7681-52-9 EC No 231-668-3 Index No 017-011-00-1 REACH Reg. No 01- 2119488154- 34-xxxx	5 – 15	Skin Corr. 1B / H314 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410 EUH031			M-factor (acute) = 10.0
Sodium hydroxide	CAS No 1310-73-2 EC No 215-185-5 Index No 011-002-00-6 REACH Reg. No 01- 2119457892- 27-xxxx	1 – <2	Met. Corr. 1 / H290 Skin Corr. 1A / H314 Eye Dam. 1 / H318		Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0,5 % ≤ C < 2 % Eye Dam. 1; H318: C ≥ 2 % Eye Irrit. 2; H319: 0,5 % ≤ C < 2 %	

Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Cough, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings
water spray, foam, dry extinguishing powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: hydrogen chloride (HCl), chlorine (Cl₂), May produce toxic fumes of carbon monoxide if burning.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

5.3 Advice for firefighters

Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Provision of sufficient ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handle and open container with care. Provide adequate ventilation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Protect from sunlight. Keep only in the original container. Due to gaseous decomposition products, overpressure can occur in tightly sealed containers.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

• Ventilation requirements

Use local and general ventilation.

• Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Source
GB	sodium hydroxide	1310-73-2		WEL				2			EH40/2005

Notation

- Ceiling-C Ceiling value is a limit value above which exposure should not occur
- STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium hypochlorite, solution ... % Cl active	7681-52-9	DNEL	1,55 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Sodium hypochlorite, solution ... % Cl active	7681-52-9	DNEL	3,1 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Sodium hypochlorite, solution ... % Cl active	7681-52-9	DNEL	1,55 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Sodium hypochlorite, solution ... % Cl active	7681-52-9	DNEL	3,1 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Sodium hydroxide	1310-73-2	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Sodium hydroxide	1310-73-2	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects

• relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Environmental compartment	Exposure time
Sodium hypochlorite, solution ... % Cl active	7681-52-9	PNEC	0,21 µg/l	freshwater	short-term (single instance)
Sodium hypochlorite, solution ... % Cl active	7681-52-9	PNEC	0,042 µg/l	marine water	short-term (single instance)
Sodium hypochlorite, solution ... % Cl active	7681-52-9	PNEC	4,69 mg/l	sewage treatment plant (STP)	short-term (single instance)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

• material thickness

0,5 mm.

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection

Respiratory protection necessary at: Aerosol or mist formation. Type: B-P2 (combined filters for acidic gases and particles, colour code: Grey/White).

Respiratory protection necessary at: Aerosol or mist formation.

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (fluid)
Colour	light yellow - light green
Odour	like: chlorine

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

Odour threshold	No data available
Other physical and chemical parameters	
pH (value)	12 – 13 (20 °C)
Melting point/freezing point	-25 °C
Initial boiling point and boiling range	98 °C
Flash point	not determined
Evaporation rate	no data available
Flammability (solid, gas)	not relevant (fluid)
<u>Explosive limits</u>	
• lower explosion limit (LEL)	this information is not available
• upper explosion limit (UEL)	this information is not available
Explosion limits of dust clouds	not relevant
Vapour pressure	23 hPa
Density	1,22 – 1,26 g/cm ³ at 20 °C
Vapour density	This information is not available.
Bulk density	Not applicable
Relative density	Information on this property is not available.
<u>Solubility(ies)</u>	
Water solubility	miscible in any proportion
<u>Partition coefficient</u>	
n-octanol/water (log KOW)	-3,42 (20 °C)
Auto-ignition temperature	Information on this property is not available.
Decomposition temperature	>111 °C
Viscosity	
• kinematic viscosity	2,222 mm ² /s at 20 °C
• dynamic viscosity	2,8 mPa s at 20 °C
Explosive properties	Shall not be classified as explosive
Oxidising properties	none

9.2 Other information

There is no additional information.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

Reactivity if exposed to light. Slow decomposition of the material.

10.3 Possibility of hazardous reactions

Violent reaction with: Amines, Ammonia (NH₃), Ammonia (NH₃), Organic substances, Oxidisers, Reducing agents, Formic acid, Acetic anhydride, Methanol, Cyanide, Dangerous/dangerous reactions with: Acids,

=>

Release of an acute toxic gas: Chlorine

10.4 Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: >111 °C.

10.5 Incompatible materials

different metals

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Shall not be classified as acutely toxic.

• Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Sodium hypochlorite, solution ... % Cl active	7681-52-9	oral	1.100 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant

• Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: 6846

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds

Other information

None

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Very toxic to aquatic organisms.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium hypochlorite, solution ... % Cl active	7681-52-9	EC50	35 µg/l	aquatic invertebrates	48 h
Sodium hypochlorite, solution ... % Cl active	7681-52-9	ErC50	0,036 mg/l	algae	72 h
Sodium hydroxide	1310-73-2	EC50	40,4 mg/l	water flea (Daphnia)	48 h

Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

12.2 Process of degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW) -3,42 (20 °C)

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Sodium hypochlorite, solution ... % Cl active	7681-52-9		-3,42 (pH value: 12,5, 20 °C)	

12.4 Mobility in soil

Data are not available.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.


13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number	1791
14.2	UN proper shipping name	HYPOCHLORITE SOLUTION
	Hazardous ingredients	Sodium hypochlorite, solution ... % Cl active, Sodium hydroxide
14.3	Transport hazard class(es)	
	Class	8 (corrosive substances)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	hazardous to the aquatic environment (Sodium hypochlorite, solution ... % Cl active)
14.6	Special precautions for user	
	Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	
14.8	Information for each of the UN Model Regulations	

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU




Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)


UN number	1791
Proper shipping name	HYPOCHLORITE SOLUTION
Particulars in the transport document	UN1791, HYPOCHLORITE SOLUTION, 8, II, (E), environmentally hazardous
Class	8
Classification code	C9
Packing group	II
Danger label(s)	8 + "fish and tree"



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	521
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	E
Hazard identification No	80
Emergency Action Code	2X

• International Maritime Dangerous Goods Code (IMDG)

UN number	1791
Proper shipping name	HYPOCHLORITE SOLUTION
Particulars in the shipper's declaration	UN1791, HYPOCHLORITE SOLUTION, (contains: Sodium hypochlorite, solution ... % Cl active, Sodium hydroxide), 8, II, MARINE POLLUTANT
Class	8
Marine pollutant	yes (P) (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	8 + "fish and tree"



Special provisions (SP)	274, 900
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Stowage category	B

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

Segregation group	8 - Hypochlorites
• International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	1791
Proper shipping name	Hypochlorite solution
Particulars in the shipper's declaration	UN1791, Hypochlorite solution, 8, II
Class	8
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	8
Special provisions (SP)	A3
Exempted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

- **Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)**

None of the ingredients are listed.

- **Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)**

None of the ingredients are listed.

- **Regulation 850/2004/EC on persistent organic pollutants (POP)**

None of the ingredients are listed.

- **Restrictions according to REACH, Annex XVII**

Name of substance	CAS No	Wt%	Type of registration	Conditions of restriction	No
Sodium hypochlorite solution		100	1907/2006/EC annex XVII	R3	3

Legend

R3

1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and,
 - present an aspiration hazard and are labelled with R65 or H304,
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

Legend

marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
(b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
(c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.
7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.

Name acc. to inventory	CAS No	Wt%	Listed in	Remarks
Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		12,5	A)	
Biocides and plant protection products		12,5	A)	

Legend

A) Indicative list of the main pollutants

• Restrictions according to REACH, Title VIII

None.

• List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

none of the ingredients are listed

• Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100	200	56)

Notation

56) Hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

• Directive 75/324/EEC relating to aerosol dispensers

Filling batch

Deco-PAINT Directive (2004/42/EC)

VOC content	0 % -0 g/l
-------------	---------------

Directive on industrial emissions (VOCs, 2010/75/EU)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl₂, technical

article number: 6846

VOC content	0 %
VOC content Water content was discounted	-0.9/1

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

None of the ingredients are listed.

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

Name acc. to inventory	CAS No	Listed in	Remarks
Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		A)	
Biocides and plant protection products		A)	

Legend

A) Indicative list of the main pollutants

Regulation 98/2013/EU on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation 111/2005/EC laying down rules for the monitoring of trade between the Community and third countries in drug precursors

none of the ingredients are listed

National inventories

Country	National inventories	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	hazardous to the aquatic environment - acute hazard
Aquatic Chronic	hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
BCF	bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

Abbr.	Descriptions of used abbreviations
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	substance or mixture corrosive to metals
M-factor	means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
STEL	short-term exposure limit
SVHC	Substance of Very High Concern
TWA	time-weighted average
VOC	Volatile Organic Compounds
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- Dangerous Goods Regulations (DGR) for the air transport (IATA)
- International Maritime Dangerous Goods Code (IMDG)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Sodium hypochlorite solution 5-10 % Cl, technical

article number: **6846**

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	may be corrosive to metals
H314	causes severe skin burns and eye damage
H318	causes serious eye damage
H400	very toxic to aquatic life
H410	very toxic to aquatic life with long lasting effects
H411	toxic to aquatic life with long lasting effects

Disclaimer

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Ref. 2.1/GB/EN

SUPERFLOC C-498HMW

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Commercial Product Name
SUPERFLOC C-498HMW

1.2 Relevant identified uses of the substance or mixture and uses advised against
Use of the Substance/Mixture

Water treatment chemical

Recommended restrictions on use

-

1.3 Details of the supplier of the safety data sheet

Kemira Oyj
 P.O. Box 33000101 HELSINKI FINLAND
 Telephone+358108611, Telefax. +358108621124
 ProductSafety.FI.Helsinki@kemira.com

1.4 Emergency telephone number

Carechem 24 International: +44 (0) 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EU) 1272/2008(CLP)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.;

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements

:

EUH210

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Safety data sheet available on request.

2.3 Other hazards

Advice; Forms slippery/greasy layers with water.

Potential environmental effects; This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Chemical nature of the mixture	Cationic polyacrylamide.		
CAS/EU number/REACH Registration Number	Chemical name of the substance	Concentration	Classification according to Regulation (EU) 1272/2008(CLP)
77-92-9 201-069-1 01-2119457026-42	Citric acid	0 - 9.9 %	Eye Irrit. Category 2,H319
124-04-9 204-673-3 01-2119457561-38	Adipic acid	0 - 5 %	Eye Irrit. Category 2,H319

The total combined concentration of Adipic acid and Citric acid does not exceed 9.9%.

Further information

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Ingestion

Rinse mouth with water. Call a physician immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Symptomatic treatment.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Extinguishing media : Water spray
Dry chemical
Carbon dioxide (CO₂)

Unsuitable extinguishing media : none

5.2 Special hazards arising from the substance or mixture

Dust may form explosive mixture in air.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Specific methods

Avoid dust accumulation.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

For personal protection see section 8.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and materials for containment and cleaning up

Product becomes slippery when it is wet. Sweep up and shovel into suitable containers for disposal.
Flush with water. Prevent product from entering drains.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Ref. 2.1/GB/EN

SUPERFLOC C-498HMW

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

The product is hygroscopic. Protect from moisture. Avoid dust formation.

7.2 Conditions for safe storage, including any incompatibilities

Store at room temperature in the original container.

Materials for packaging

Unsuitable material: To avoid product degradation and equipment corrosion, do not use iron, copper or aluminium containers or equipment.

Materials to avoid:

Strong oxidizing agents

Storage stability:

Storage temperature 4 - 27 °C

Other data Stable under recommended storage conditions.

7.3 Specific end use(s)

Not listed

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters**

Contains no substances with occupational exposure limit values.

PNEC : No data available

8.2 Exposure controls**8.2.1 Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes and clothing. Do not breathe dust. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation.

8.2.2 Individual protection measures, such as personal protective equipment**Hand protection**

Glove material: Nitrile rubber, Protective gloves complying with EN 374. Permeability tests are not available for this product. Please observe the instructions regarding permeability and breakthrough time

Ref. 2.1/GB/EN

SUPERFLOC C-498HMW

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection

Safety glasses with side-shields conforming to EN166

Skin and body protection

Protective clothing.

Respiratory protection

Dust safety masks are recommended when the dust concentration is more than 10 mg/m³. Half mask with a particle filter P2 (EN 143)

8.2.3 Environmental exposure controls

No data available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information (appearance, odour)

Physical state	solid, crystalline, powder
Colour	off-white
Odour	odourless
Odour Threshold	Not relevant

Important health safety and environmental information

pH	3 - 5 (0.5 %) (as aqueous solution)
Melting point/range	No data available
Boiling point/boiling range	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability (solid, gas) :	No data available
Explosive properties:	
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapour pressure	Not applicable

SUPERFLOC C-498HMW

Ref. 2.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

Relative vapour density	Not applicable
Bulk density	750 kg/m ³
Solubility(ies):	
Water solubility	Limited by viscosity.
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	> 150 °C
Thermal decomposition	> 150 °C
Viscosity:	
Viscosity, dynamic	Not applicable
Oxidizing	The substance or mixture is not classified as oxidizing.
Saturation in air (% vol.)	Not applicable

9.2 Other data

Surface tension	Not applicable
------------------------	----------------

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Conditions to avoid : Avoid contact with alkaline materials which will degrade the polymer.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : Ammonia
Carbon oxides (CO_x)
Nitrogen oxides (NO_x)
hydrogen chloride (HCl)

Ref. 2.1/GB/EN

SUPERFLOC C-498HMW

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

Thermal decomposition : > 150 °C

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects****Acute toxicity**

The acute toxicological results displayed may not be the results of actual testing of this material but based on a similar tested material.

LD50/Oral/Rat: > 5,000 mg/kg

Remarks:estimated

LC50/Inhalation/4 h/Rat: 20 mg/l

Remarks: estimated

LD50/Dermal/Rabbit: > 2,000 mg/kg

Remarks: estimated

Irritation and corrosion

Skin:

No skin irritation

Eyes:

No eye irritation

Sensitisation

Not sensitizing.

Long term toxicity

Repeated dose toxicity

Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Ref. 2.1/GB/EN

SUPERFLOC C-498HMW

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity

No aspiration toxicity classification

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity****Aquatic toxicity**

Ecotoxicological information provided is based on a structurally or compositionally similar product. This material is not classified as dangerous for the environment. The effects on aquatic organisms are due to an external (non-systemic) mode of action and are significantly reduced (by a factor of 7-20) within 30 minutes due to the binding of the product to dissolved organic carbon and inorganic sorbents such as clays and silts.

LC50/96 h/Branchydanio rerio (zebra fish)/Acute toxicity/OECD Test Guideline 203: > 1 - 10 mg/l
EC50/48 h/Daphnia magna (Water flea)/Immobilization/OECD Test Guideline 202: > 10 - 100 mg/l
IC50/algae/Growth inhibition/OECD Test Guideline 201:
Due to the cationicity of the polymer, test is not appropriate.

Toxicity to other organisms

No data available

12.2 Persistence and degradability

Biological degradability:
CO2 Evolution Test/OECD Test Guideline 301B/28 d:

The polymeric ingredient is not readily biodegradable, but degradable by hydrolysis.

12.3 Bioaccumulative potential

Bioaccumulation is unlikely. Because of the high molecular weight of the polymer diffusion through biological membranes is very small.

Partition coefficient: n-octanol/water: Not applicable

12.4. Mobility in soil**Mobility**

Water solubility: Limited by viscosity.

Surface tension: Not applicable

12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No information available.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods****Product**

Recycling, recovery and reuse of materials is recommended if permitted by regulations. If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Dirty package must be disposed of in the same way as the product itself.

SECTION 14: TRANSPORT INFORMATION**14.1 UN number****Land transport**

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not classified as dangerous in the meaning of transport regulations.

SUPERFLOC C-498HMW

Ref. 2.1/GB/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Revision Date: 21.02.2019

Previous date: 13.02.2015

Print Date:22.03.2019

14.8 Special precautions for user

None known.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Notification status

TSCA : All components of this product are included in the United States TSCA Chemical Inventory or are not required to be listed on the United States TSCA Chemical Inventory.

DSL : All components of this product are included in the Canada Domestic Substance List (DSL) or are not required to be listed on the Canada Domestic Substance List (DSL).

EINECS : All components of this product are included in the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.

AICS : All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on the Australian Inventory of Chemical Substances (AICS).

IECSC : All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

ENCS : All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese (ENCS) inventory.

KECI : All components of this product are included in the Korean (ECL) inventory or are not required to be listed on the Korean (ECL) inventory.

PICCS : All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine (PICCS) inventory.

NZIoC : All components of this product are included in the New Zealand inventory (NZIoC) or are not required to be listed on the New Zealand inventory(NZIoC).

TCSI : All components of this product are included on the Taiwan Toxic Chemical Substances Control Act Inventory.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: OTHER INFORMATION**Full text of H-Statements referred to under section 3.**

H319	Causes serious eye irritation.
H319	Causes serious eye irritation.

Training advice

Read the safety data sheet before using the product.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Sources of key data used to compile the Safety Data Sheet

Regulations, databases, literature, own tests.

Additions, Deletions, Revisions

Relevant changes have been marked with vertical lines.

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No.
1907/2006 (REACH)



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Substance name:	Fuels, diesel
Code:	817652
Unique Formula Identifier (UFI):	X4MS-CM5S-AK77-AVAX
MARPOL Annex I Category:	Fuels, Including Ship's Bunkers
REACH Registration Number:	01-2119484664-27-0221
Issue date:	18-Nov-2020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Fuel
Uses advised against:	Uses other than those covered by the exposure scenarios appended to this Safety Data Sheet are not supported.

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier:	Phillips 66 CS Limited 7th Floor 200-202 Aldersgate Street London EC1A 4HD UK
------------------------	--

SDS Information:	URL: www.Phillips66.com/SDS Email: ESDS@P66.com CHEMTREC Global +1 703 527 3887 CHEMTREC Germany 0800-181-7059 CHEMTREC France +(33)-975181407 CHEMTREC Spain 900-868538 CHEMTREC UK +(44)-870-8200418 CHEMTREC Denmark +(45)-69918573 CHEMTREC Sweden (Stockholm) +(46)-852503403 CHEMTREC Netherlands +(31)-858880596
------------------	--

1.4. Emergency telephone number

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP Classification (EC No 1272/2008)

H226 - Flammable liquids -- Category 3
H304 -- Aspiration Hazard -- Category 1
H315 -- Skin corrosion/irritation -- Category 2
H332 -- Acute toxicity, Inhalation -- Category 4
H351 -- Carcinogenicity -- Category 2
H373 -- Specific target organ toxicity (repeated exposure) -- Category 2 (Immune system/Liver/bone)
H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2

2.2. Label elements



DANGER

- H226 - Flammable liquid and vapour**
- H304 - May be fatal if swallowed and enters airways**
- H315 - Causes skin irritation**
- H332 - Harmful if inhaled**
- H351 - Suspected of causing cancer**
- H373 - May cause damage to organs through prolonged or repeated exposure**
- H411 - Toxic to aquatic life with long lasting effects**
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray
- P273 - Avoid release to the environment
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P331 - Do NOT induce vomiting

2.3. Other hazards

Electrostatic charge may be generated during pumping and other operations
 Does not meet the criteria for persistent, bioaccumulative and toxic (PBT) or very persistent, very bioaccumulative (vPvB) substances.

SECTION 3: Composition/information on ingredients

3.1. Substances

Chemical Name	CASRN	EINECS	REACH Registration No	Concentration ¹	Classification ²
Fuels, diesel	68334-30-5	269-822-7	01-2119484664-27	0-100	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Acute Tox. 4, H332 Carc. 2, H351 STOT RE 2, H373 Aquatic Chronic 2, H411
Kerosine, petroleum	8008-20-6	232-366-4	01-2119485517-27	0-18	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Aromatic hydrocarbons, distillation residues, naphthalene-rich	98072-36-7	308-487-4	01-2119480164-41	<10	Acute Tox. 4, H302 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 Muta. 1B, H340 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Naphthalene, 1,2,3,4-tetrahydro-	119-64-2	204-340-2	Not applicable	<5	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
Naphthalene	91-20-3	202-049-5	-	<2.5	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

¹ All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
² Regulation EC 1272/2008.
 See Section 11 for more information.

Total Sulphur: < 0.1 wt%

SECTION 4: First aid measures

4.1. Description of first aid measures

Eye Contact: If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

Skin Contact: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician. (see Note to Physician)

Inhalation: If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If symptoms persist, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

While significant vapour concentrations are not likely, high concentrations can cause minor respiratory irritation, headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Ingestion can cause irritation of the digestive tract, nausea, diarrhea, and vomiting. Prolonged or repeated contact may dry skin and cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician: When using high-pressure equipment, injection of product under the skin can occur. In this case, the casualty should be sent immediately to the hospital. Do not wait for symptoms to develop. High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. These injuries often require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury. Early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Dry chemical, carbon dioxide, or foam is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards: Flammable. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe) Vapours may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapour/air explosion hazard indoors, in confined spaces, outdoors, or in sewers. This product will float and can be reignited on surface water. Vapours are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulphur may also be formed.

5.3. Special protective actions for fire-fighters

For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When

the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapours and to protect personnel. Avoid spreading burning liquid with water used for cooling purposes. Cool equipment exposed to fire with water, if it can be done safely.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. The use of explosion-proof electrical equipment is recommended. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorised personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

6.2. Environmental precautions

Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorised drainage systems, and natural waterways. Use foam on spills to minimise vapours Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard.

6.3. Methods and material for containment and cleaning up

Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use non-sparking tools. Do not breathe vapour or mist. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8).

Flammable. May vaporize easily at ambient temperatures. The vapour is heavier than air and may create an explosive mixture of vapor and air. Beware of accumulation in confined spaces and low lying areas. Open container slowly to relieve any pressure. Electrostatic charge may accumulate and create a hazardous condition when handling or processing this material. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes for specific bonding/grounding requirements). Do not enter confined spaces such as tanks or pits without following proper entry procedures. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames.

High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing of high pressure hydraulic oil equipment.

For use as a motor fuel only. Do not use as a solvent due to its flammable and potentially toxic properties. Siphoning by mouth can result in lung aspiration which can be harmful or fatal.

The use of hydrocarbon fuel in an area without adequate ventilation may result in hazardous levels of incomplete combustion products (e.g. carbon monoxide, oxides of sulphur and nitrogen, benzene and other hydrocarbons) and/or dangerously low

oxygen levels.

Diesel engine exhaust contains hazardous combustion products and has been identified as a cancer hazard. Exposure should be minimized to reduce potential risk.

7.2. Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Post area "No Smoking or Open Flame." Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to appropriate guidance pertaining to cleaning, repairing, welding, or other contemplated operations. Outdoor or detached storage is preferred. Indoor storage should meet Country or Committee standards and appropriate fire codes.

7.3. Specific end use(s)

Refer to supplemental exposure scenarios if attached.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits:

Chemical Name	ACGIH	Ireland	United Kingdom	Phillips 66
Fuels, diesel	TWA-8hr: 100 mg/m ³ inhalable fraction and vapor Skin	TWA-8hr: 100 mg/m ³ STEL: 300 mg/m ³	---	TWA-8hr: 100 mg/m ³ Skin
Kerosine, petroleum	TWA-8hr: 200 mg/m ³ total hydrocarbon vapor Kerosene/Jet fuels Skin	Skin	---	TWA-8hr: 200 mg/m ³ TWA-8hr: 28 ppm Skin
Naphthalene	TWA-8hr: 10 ppm Skin	TWA-8hr: 10 ppm TWA-8hr: 50 mg/m ³ STEL: 30 ppm STEL: 150 mg/m ³	---	TWA-8hr: 10 ppm Skin

STEL = Short Term Exposure Limit (15 minutes); TWA = Time Weighted Average (8 hours); --- = No Occupational Exposure Limit. Local regulations may be more stringent than regional or national requirements.

Biological Limit Values:

Chemical Name	ACGIH	European Union	United Kingdom
Naphthalene	1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis in : , end of shift (nonquantitative, nonspecific)	---	---

--- = No Biological Limit Value. Local regulations may be more stringent than regional or national requirements

Relevant DNEL and PNEC:

Worker Derived No-Effect Level (DNEL)
Inhalation: 68.3 mg/m³
Dermal: 2.9 mg/kgbw/day

Consumer Derived No-Effect Level (DNEL)
Inhalation: 20 mg/m³
Dermal: 1.3 mg/kgbw/day
Ingestion: Not applicable

Environmental Predicted No-Effect Concentration (PNEC): No information available

8.2. Exposure controls

Engineering controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

Eye/Face Protection: The use of eye protection that meets or exceeds EN 166 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, close fitting eye protection and a face shield may be necessary.

Skin/Hand Protection: The use of gloves impervious to the specific material handled that comply with EN 374 is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical resistant boots, aprons, arm covers, hoods, coveralls, or encapsulated suits. Suggested protective materials: Nitrile rubber

Respiratory Protection: Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type A, organic gases and vapour filters (as specified by the manufacturer) may be used.

A respiratory protection programme that follows recommendations for the selection, use, care and maintenance of respiratory protective devices in EN 529:2005 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health.

Other Protective Equipment: Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before reuse.

Environmental Exposure Controls: Refer to Sections 6, 7, 12 and 13.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Data represent typical values and are not intended to be specifications. N/A = Not Applicable; N/D = Not Determined

Appearance:	Clear to amber
Physical form of product:	Liquid
Odour:	Diesel fuel
Odour threshold:	N/D
pH:	N/A
Melting / freezing point:	N/D
Initial boiling point and boiling range:	356 - 734 °F / 180 - 390 °C
Flash point:	> 131 °F / > 55 °C
Method:	CC (closed cup)
Evaporation Rate (nBuAc=1):	N/D
Flammability (solid, gas):	N/A
Upper Explosive Limits (vol % in air):	5.0
Lower Explosive Limits (vol % in air):	0.5
Vapour pressure:	<0.3 kPa @20°C
Vapour density:	>1 (air = 1)
Relative density:	0.85 @ 60°F (15.6°C) (water = 1)
Solubility(ies):	Negligible
Partition coefficient n-octanol /water (log KOW):	N/D
Autoignition temperature:	250 °C
Decomposition temperature:	N/D
Viscosity:	4.8 mm ² /s @ 20°C; 1.5-5.5 mm ² /s @ 40°C
Explosive properties:	N/D
Oxidising properties:	N/D

9.2. Other information

Other information

Pour point: -11.2 °F / -24 °C
Bulk Density:: N/D

SECTION 10: Stability and reactivity

- 10.1. Reactivity** Not chemically reactive.
- 10.2. Chemical stability** Stable under normal ambient and anticipated conditions of use.
- 10.3. Possibility of hazardous reactions** Hazardous reactions not anticipated.
- 10.4. Conditions to avoid** Avoid high temperatures and all sources of ignition. Prevent vapour accumulation.
- 10.5. Incompatible materials** Avoid contact with strong oxidizing agents and strong reducing agents.
- 10.6. Hazardous decomposition products** Not anticipated under normal conditions of use.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Substance / Mixture

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Harmful if inhaled		> 4.1 mg/L (mist, estimated) (rat)
Dermal	Unlikely to be harmful		>2 g/kg (Estimated) (rabbit)
Oral	Unlikely to be harmful		>5 g/kg (Estimated) (rat)

Likely Routes of Exposure: Inhalation, eye contact, skin contact

Aspiration Hazard: May be fatal if swallowed and enters airways.

Skin Corrosion/Irritation: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Serious Eye Damage/Irritation: Causes mild eye irritation.

Skin Sensitisation: Not expected to be a skin sensitizer.

Respiratory Sensitisation: No information available on the mixture, however none of the components have been classified for respiratory sensitisation (or are below the concentration threshold for classification).

Specific Target Organ Toxicity (Single Exposure): No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity: Suspected of causing cancer. Based on component information.

Germ Cell Mutagenicity: No information available on the mixture, however none of the components have been classified for germ cell mutagenicity (or are below the concentration threshold for classification). Based on component information.

Reproductive Toxicity: Not expected to cause reproductive toxicity.

Other Comments: Diesel engine exhaust has been classified by the International Agency for Research on Cancer (IARC) and National Toxicology Programme (NTP) as a carcinogen.

11.2 Information on Hazardous Components

Fuels, diesel

Carcinogenicity: Repeated application of residual aromatic extracts to mouse skin resulted in an increased incidence of skin tumours. They have been identified as a carcinogen by IARC.

Target Organ(s): Repeated dermal application of petroleum gas oils for 90 days resulted in decreased liver, thymus, and spleen weights, and altered bone marrow function. Microscopic alterations included liver hypertrophy and necrosis, decreased hematopoiesis and lymphocyte depletion.

Target organs, tissues and biological systems: Immune system, Liver, bone

Kerosine, petroleum

Target organs, tissues and biological systems: Central Nervous System (CNS)

Reproductive Toxicity: Hydrodesulphurized kerosene applied to the skin of female rats at 494, 330, or 165 mg/kg daily for 7 consecutive weeks (pre-mating, mating, and gestation), or for 8 consecutive weeks in males did not result in systemic, reproductive, or developmental toxicity.

Naphthalene

Carcinogenicity: Naphthalene has been evaluated in two year inhalation studies in both rats and mice. The US National Toxicology Programme (NTP) concluded that there is clear evidence of carcinogenicity in male and female rats based on increased incidences of respiratory epithelial adenomas and olfactory epithelial neuroblastomas of the nose. NTP found some evidence of carcinogenicity in female mice (alveolar adenomas) and no evidence of carcinogenicity in male mice.

Naphthalene has been identified as a carcinogen by IARC and NTP.

SECTION 12: Ecological information

12.1. Toxicity

Experimental studies of gas oils show that acute aquatic toxicity values are typically in the range 2-20 mg/L. These values are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions. They should be regarded as toxic to aquatic organisms, with the potential to cause long term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Gas oils are complex combinations of individual hydrocarbon species. Based on the known or expected properties of individual constituents, category members are not predicted to be readily biodegradable. Some hydrocarbon constituents of gas oils are predicted to meet the criteria for persistence; on the other hand, some components can be easily degraded by microorganisms under aerobic conditions.

Persistence per IOPC Fund definition: Non-Persistent

12.3. Bioaccumulative potential

Gas oil components have measured or calculated Log Kow values in the range of 3.9 to 6 which indicates a high potential to bioaccumulate. Lower molecular weight compounds are readily metabolized and the actual bioaccumulation potential of higher molecular weight compounds is limited by the low water solubility and large molecular size.

12.4. Mobility in soil

Releases to water will result in a hydrocarbon film floating and spreading on the surface. For the lighter components, volatilisation is an important loss process and reduces the hazard to aquatic organisms. In air, the hydrocarbon vapours react readily with hydroxyl radicals with half-lives of less than one day. Photooxidation on the water surface is also a significant loss process particularly for polycyclic aromatic compounds. In water, the majority of components will be adsorbed on sediment. Adsorption is the most predominant physical process on release to soil. Adsorbed hydrocarbons will slowly degrade in both water and soil.

12.5. Results of PBT and vPvB assessment

Not a PBT or vPvB substance.

12.6. Other adverse effects

None anticipated.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

European Waste Code: 13 07 01* fuel oil and diesel

This material, if discarded as produced, would be considered as hazardous waste pursuant to Directive 2008/98/EC on

hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies. This code has been assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste generators/producers are responsible for assessing the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code.

Disposal must be in accordance with Directive 2008/98/EC and other applicable national or regional provisions, and based upon material characteristics at time of disposal. For incineration of waste, follow Directive 2000/76/EC. For landfill of waste, follow Directive 1999/31/EC. Product is suitable for burning in an enclosed controlled burner for fuel value if >5000 BTU, or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Follow Directive 2000/76/EC.

Empty Containers: Container contents should be completely used and containers emptied prior to discard. Empty drums should be properly sealed and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with applicable regulations.

SECTION 14: Transport information

14.1. UN number

UN1202

14.2. UN proper shipping name

Diesel fuel

14.3. Transport hazard class(es)

3; (N2, F)

14.4. Packing group

III

14.5. Environmental hazards

Marine pollutant - Environmentally Hazardous

14.6. Special precautions for user

If transported in bulk by marine vessel in international waters, product is being carried under the scope of MARPOL Annex I.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EC 1272/2008 - Classification, labelling and packaging of substances and mixtures
EN166:2002 Eye Protection
EN 529:2005 Respiratory Protective devices
BS EN 374-1:2003 Protective gloves against chemicals and micro-organisms
Occupational Exposure Limits, Technical Rules for Dangerous Substances
Occupational Exposure Limits, Health and Safety Authority
Workplace Exposure Limits, EH40/2005, Control of Substances Hazardous to Health
Federal Water Act on the Classification of Substances Hazardous to Waters
Directive 2008/98/EC (Waste Framework Directive)
Directive 2000/76/EC on incineration of waste
Directive 1999/31/EC on landfill of waste

Export Rating: NLR (No Licence Required)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out for the substance/mixture.

SECTION 16: Other information

Issue date 18-Nov-2020
Status: FINAL
Previous Issue Date: 19-Aug-2020
Revised Sections or Basis for Revision: Unique Formula Identifier (UFI)
Toxicological (Section 11)
Format change
Safety Data Sheet Number: 817652
Language: BE

List of Relevant Hazard Statements:

- H226 - Flammable liquid and vapour
- H302 - Harmful if swallowed
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H336 - May cause drowsiness or dizziness
- H340 - May cause genetic defects
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects
- H411 - Toxic to aquatic life with long lasting effects

Regulatory Basis of Classification

	Regulatory Basis
CLP Classification (EC No 1272/2008)	Regulatory Basis
H226 - Flammable liquids -- Category 3	Based on component information.
H304 -- Aspiration Hazard -- Category 1	Based on component information.
H315 -- Skin corrosion/irritation -- Category 2	Based on component information.
H332 -- Acute toxicity, Inhalation -- Category 4	Based on component information.
H351 -- Carcinogenicity -- Category 2	Based on component information.
H373 -- Specific target organ toxicity (repeated exposure) -- Category 2 (Immune system/Liver/bone)	Based on component information.
H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2	Based on component information.

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; ADR = Agreement on Dangerous Goods by Road; BMGV = Biological Monitoring Guidance Value; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA = [US] Environmental Protection Agency; Germany-TRGS = Technical Rules for Dangerous Substances; IARC = International Agency for Research on Cancer; ICAO/IATA = International Civil Aviation Organisation / International Air Transport Association; INSHT = National Institute for Health and Safety at Work; IMDG = International Maritime Dangerous Goods; Irland-HSA = Ireland's National Health and Safety Authority; LEL = Lower Explosive Limit; MARPOL = Marine Pollution; N/A = Not Applicable; N/D = Not Determined; NTP = [US] National Toxicology Programme; PBT = Persistent, Bioaccumulative and Toxic; RID = Regulations Concerning the International Transport of Dangerous Goods by Rail; STEL = Short Term Exposure Limit; TLV = Threshold Limit Value; TRGS 903 = Technical rules for hazardous substances; TWA = Time Weighted Average; UEL = Upper Explosive Limit; UK-EH40 = United Kingdom EH40/2005 OEL; vPvB = very Persistent, very Bioaccumulative

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorisation is given nor implied to practice any patented invention without a licence.



1. Manufacture of substance - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Manufacture of substance
Use Descriptor	
Sector(s) of use	3, 8, 9
Process category(ies)	1, 2, 3, 4, 8a, 8b, 15
Environmental release category(ies)	1, 4
Specific Environmental Release Category	ESVOC SpERC 1.1.v1
Processes, tasks, activities covered	
Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Operation is carried out at elevated temperature (>20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
Specific Risk Management Measures & Operating Conditions	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
bulk closed loading and unloading	Handle substance within a closed system Wear suitable gloves tested to EN374.
bulk open loading and unloading	Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or

	maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Laboratory activities	No other specific measures identified
Bulk product storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.8e7
Fraction of regional tonnage used locally	0.021
Frequency and duration of use	
Continuous release.	
Emission days (days/year)	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Release fraction to air from process (initial release prior to RMM)	1.0e-2
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-5
Release fraction to soil from process (initial release prior to RMM)	0.0001
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	90.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	3.3e6
Assumed domestic sewage treatment plant flow (m ³ /d):	10000
Conditions and measures related to external treatment of waste for disposal	
During manufacturing no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	
During manufacturing no waste of the substance is generated.	
Section 3 Exposure Estimation	
3.1 Health	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
3.2 Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.
Section 4 Guidance to check compliance with the Exposure Scenario
4.1 Health
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.
4.2 Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf). Scaled local assessments for EU refineries have been performed using site-specific data and are attached in PETRORISK file – “Site-Specific Production” worksheet.

2. Use of substance as an intermediate - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Use as an intermediate
Use Descriptor	
Sector(s) of use	3, 8, 9
Process category(ies)	1, 2, 3, 4, 8a, 8b, 15
Environmental release category(ies)	6a
Specific Environmental Release Category	ESVOC SpERC 6.1a.v1
Processes, tasks, activities covered	
Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Operation is carried out at elevated temperature (>20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to

	EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
bulk closed loading and unloading	Handle substance within a closed system Wear suitable gloves tested to EN374.
bulk open loading and unloading	Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	No other specific measures identified
Laboratory activities	No other specific measures identified
Bulk product storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	3.5e5
Fraction of regional tonnage used locally	0.043
Frequency and duration of use	
Continuous release.	
Emission days (days/year)	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Release fraction to air from process (initial release prior to RMM)	1.0e-3
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-5
Release fraction to soil from process (initial release prior to RMM)	0.001
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	51.7
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment)	94.1

plant) RMMs (%):	
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	4.1e5
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
This substance is consumed during use and no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of the substance is generated.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
Section 4 Guidance to check compliance with the Exposure Scenario	
4.1 Health	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
4.2 Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHimpl-ES-CSA-CSR.pdf).	

3. Distribution of substance - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Distribution of substance
Use Descriptor	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 4, 8a, 8b, 9, 15
Environmental release category(ies)	1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7
Specific Environmental Release Category	ESVOC SpERC 1.1b.v1
Processes, tasks, activities covered	
Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
General measures applicable to all activities	Specific Risk Management Measures & Operating Conditions Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to

	minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
Laboratory activities	No other specific measures identified
bulk closed loading and unloading	Handle substance within a closed system Wear suitable gloves tested to EN374.
bulk open loading and unloading	Wear suitable gloves tested to EN374.
Drum and small package filling	Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.8e7
Fraction of regional tonnage used locally	0.002
Frequency and duration of use	
Continuous release.	
Emission days (days/year)	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Release fraction to air from process (initial release prior to RMM)	1.0e-3
Release fraction to wastewater from process (initial release prior to RMM)	1.0e-6
Release fraction to soil from process (initial release prior to RMM)	0.00001
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	9.6

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	4.1e5
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
This substance is consumed during use and no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of the substance is generated.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
Section 4 Guidance to check compliance with the Exposure Scenario	
4.1 Health	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
4.2 Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHimpl-ES-CSA-CSR.pdf).	

4. Formulation & (Re)packing of substance - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Formulation & (re)packing of substances and mixtures
Use Descriptor	
Sector(s) of use	3, 10
Process category(ies)	1, 2, 3, 4, 5, 8a, 8b, 9, 14, 15
Environmental release category(ies)	2
Specific Environmental Release Category	ESVOC SpERC 2.2.v1
Processes, tasks, activities covered	
Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios / Product Category	Specific Risk Management Measures & Operating Conditions
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
Drum/batch transfers	Use drum pumps or carefully pour from container. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Bulk transfers	Handle substance within a closed system. Wear suitable gloves tested to EN374.
Mixing operations (open systems)	Provide extract ventilation to points where emissions occur. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Production or preparation of articles by tableting, compression, extrusion or pelletisation	Wear suitable gloves tested to EN374.
Drum/batch transfers	Wear suitable gloves tested to EN374.
Laboratory activities	No other specific measures identified
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear suitable gloves tested to EN374.
Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.8e7
Fraction of regional tonnage used locally	0.0011
Frequency and duration of use	

Continuous release.	
Emission days (days/year)	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Release fraction to air from process (initial release prior to RMM)	1.0e-2
Release fraction to wastewater from process (initial release prior to RMM)	2.0e-5
Release fraction to soil from process (initial release prior to RMM)	0.0001
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%):	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	60.0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	91.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	6.8e5
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or national regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
Section 4 Guidance to check compliance with the Exposure Scenario	
4.1 Health	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
4.2 Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf).	

5. Use of substance in Metal working fluids / rolling oils - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Metal working fluids / rolling oils
Use Descriptor	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 17

Environmental release category(ies)	4
Specific Environmental Release Category	ESVOC SpERC 4.7a.v1
Processes, tasks, activities covered	
Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
Specific Risk Management Measures & Operating Conditions	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system
General exposures (open systems)	Provide extract ventilation to points where emissions occur
Bulk transfers	Handle substance within a closed system Wear suitable gloves tested to EN374.
Filling / preparation of equipment from drums or containers	Wear suitable gloves tested to EN374.
Process sampling	No other specific measures identified
Metal machining operations	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Treatment by dipping and pouring	Wear suitable gloves tested to EN374.
Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) Wear suitable gloves (tested to EN374), coverall and eye protection.
Manual Roller, spreader, flow application	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Automated metal rolling/forming	Handle substance within a predominantly closed system provided with extract ventilation
Semi-automated metal rolling/forming	Provide extract ventilation to points where emissions occur
Equipment cleaning and maintenance	Drain down and flush system prior to equipment break-in or maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system

Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.

2.2 Control of environmental exposure

Product characteristics
 Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	1.0e4
Fraction of regional tonnage used locally	0.01

Frequency and duration of use

Continuous release.
 Emission days (days/year) 20

Environmental factors not influenced by risk management

Local freshwater dilution factor	10
Local marine water dilution factor	100

Other operational conditions of use affecting environmental exposure

Release fraction to air from process (initial release prior to RMM)	0.02
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-6
Release fraction to soil from process (initial release prior to RMM)	0

Technical conditions and measures at process level (source) to prevent release
 Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil
 Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Treat air emission to provide a typical removal efficiency of (%):	70
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0

Organisation measures to prevent/limit release from site
 Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	7.8e4
Assumed domestic sewage treatment plant flow (m³/d):	2000

Conditions and measures related to external treatment of waste for disposal
 External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste
 External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3 Exposure Estimation

3.1 Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

3.2 Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Section 4 Guidance to check compliance with the Exposure Scenario

4.1 Health
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.
4.2 Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf).

6. Use of substance as Release agents or binders - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Use as binders and release agents
Use Descriptor	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 4, 6, 7, 8b, 10, 13, 14
Environmental release category(ies)	4
Specific Environmental Release Category	ESVOC SpERC 4.10a.v1
Processes, tasks, activities covered	
Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mold forming and casting, and handling of waste.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
Specific Risk Management Measures & Operating Conditions	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are

	likely to lead to substantial aerosol release, e.g. spraying
Bulk transfers	Handle substance within a closed system
Drum/batch transfers	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Mixing operations (closed systems)	No other specific measures identified
Mixing operations (open systems)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Mould forming	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Casting operations (open systems)	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Wear suitable gloves tested to EN374.
Machine Spraying	Minimise exposure by extracted full enclosure for the operation or equipment. Wear suitable gloves tested to EN374.
Manual Spraying	Wear a full face respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable gloves (tested to EN374), coverall and eye protection. Ensure operatives are trained to minimise exposures.
Manual Roller, spreader, flow application	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system

Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.

2.2 Control of environmental exposure

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	1.4e4
Fraction of regional tonnage used locally	0.18

Frequency and duration of use

Continuous release.

Emission days (days/year)	100
---------------------------	-----

Environmental factors not influenced by risk management

Local freshwater dilution factor	10
Local marine water dilution factor	100

Other operational conditions of use affecting environmental exposure

Release fraction to air from process (initial release prior to RMM)	1.0
Release fraction to wastewater from process (initial release prior to RMM)	3.0e-7
Release fraction to soil from process (initial release prior to RMM)	0

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Treat air emission to provide a typical removal efficiency of (%):	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal	59.2

efficiency >= (%):	
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	1.7e5
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or national regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
Section 4 Guidance to check compliance with the Exposure Scenario	
4.1 Health	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
4.2 Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf).	

7. Use of substance as Release agents or binders - Professional

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Use as binders and release agents
Use Descriptor	
Sector(s) of use	22
Process category(ies)	1, 2, 3, 4, 6, 8a, 8b, 10, 11, 14
Environmental release category(ies)	8a, 8d
Specific Environmental Release Category	ESVOC SpERC 8.10b.v1
Processes, tasks, activities covered	
Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios / Product Category	Specific Risk Management Measures & Operating Conditions
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying
Material transfers (closed systems)	No other specific measures identified
Drum/batch transfers	Wear suitable gloves tested to EN374.
Mixing operations (closed systems)	No other specific measures identified
Mixing operations (open systems)	Wear suitable gloves tested to EN374.
Mould forming	Provide extract ventilation to points where emissions occur Wear suitable gloves tested to EN374.
Casting operations with local exhaust ventilation	Provide extract ventilation to points where emissions occur Wear suitable gloves tested to EN374.
Casting operations without local exhaust ventilation	Wear a respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable gloves (tested to EN374), coverall and eye protection.
Spraying Manual without local exhaust ventilation	Carry out in a vented booth or extracted enclosure Wear suitable gloves (tested to EN374), coverall and eye protection. Ensure operatives are trained to minimise exposures.
Spraying Manual without local exhaust ventilation	Wear a full face respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable gloves (tested to EN374), coverall and eye protection. Ensure operatives are trained to minimise exposures.
Manual Roller, spreader, flow application	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to</p>	

protect from these adverse effects.	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	2.9e3
Fraction of regional tonnage used locally	0.0005
Frequency and duration of use	
Continuous release.	
Emission days (days/year)	365
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Release fraction to air from process (initial release prior to RMM)	0.95
Release fraction to wastewater from process (initial release prior to RMM)	0.025
Release fraction to soil from process (initial release prior to RMM)	0.025
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%):	N/A
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	6.2e1
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or national regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
Section 4 Guidance to check compliance with the Exposure Scenario	
4.1 Health	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.	
4.2 Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf).	

8. Use of substance as a Fuel - Industrial

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Use as a fuel
Use Descriptor	
Sector(s) of use	3
Process category(ies)	1, 2, 3, 8a, 8b, 16
Environmental release category(ies)	7
Specific Environmental Release Category	ESVOC SpERC 7.12a.v1
Processes, tasks, activities covered	
Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
Specific Risk Management Measures & Operating Conditions	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up any contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Bulk transfers	Wear suitable gloves tested to EN374.
Drum/batch transfers	Wear suitable gloves tested to EN374.
Use as a fuel (closed systems)	No other specific measures identified
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system
Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived.	

Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.

2.2 Control of environmental exposure

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	4.5e6
Fraction of regional tonnage used locally	0.34

Frequency and duration of use

Continuous release.

Emission days (days/year)	300
---------------------------	-----

Environmental factors not influenced by risk management

Local freshwater dilution factor	10
Local marine water dilution factor	100

Other operational conditions of use affecting environmental exposure

Release fraction to air from process (initial release prior to RMM)	5.0e-3
Release fraction to wastewater from process (initial release prior to RMM)	0.00001
Release fraction to soil from process (initial release prior to RMM)	0

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Treat air emission to provide a typical removal efficiency of (%):	95
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	97.7
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	60.4

Organisation measures to prevent/limit release from site

Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	97.7
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	5.5e6
Assumed domestic sewage treatment plant flow (m³/d):	2000

Conditions and measures related to external treatment of waste for disposal

Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3 Exposure Estimation

3.1 Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

3.2 Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Section 4 Guidance to check compliance with the Exposure Scenario

4.1 Health

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.

4.2 Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to

define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf>).

9. Use of substance as a Fuel - Professional

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Use as a fuel
Use Descriptor	
Sector(s) of use	22
Process category(ies)	1, 2, 3, 8a, 8b, 16
Environmental release category(ies)	9a, 9b
Specific Environmental Release Category	ESVOC SpERC 9.12b.v1
Processes, tasks, activities covered	
Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.	
Section 2 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently)
Other operational conditions affecting exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.
Contributing Scenarios / Product Category	
Specific Risk Management Measures & Operating Conditions	
General measures applicable to all activities	Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Bulk transfers	Wear suitable gloves tested to EN374.
Drum/batch transfers	Use drum pumps or carefully pour from container Wear suitable gloves tested to EN374.
Refuelling	Wear suitable gloves tested to EN374.
Use as a fuel (closed systems)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) or Ensure operation is undertaken outdoors
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

Storage	Store substance within a closed system
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	6.7e6
Fraction of regional tonnage used locally	0.0005
Frequency and duration of use	
Continuous release.	
Emission days (days/year)	365
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Release fraction to air from process (initial release prior to RMM)	1.0e-4
Release fraction to wastewater from process (initial release prior to RMM)	0.00001
Release fraction to soil from process (initial release prior to RMM)	0.00001
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%):	N/A
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency >= (%):	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of >= (%):	0
Organisation measures to prevent/limit release from site	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	1.4e5
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

Section 4 Guidance to check compliance with the Exposure Scenario
4.1 Health
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data does not enable the derivation of a DNEL for dermal irritant effects. Available hazard data does not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterization.
4.2 Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf).

10. Use of substance as a Fuel - Consumer

Section 1 Exposure Scenario	
Vacuum or Hydrocracked Gas Oils and Distillate Fuels	
Title	Use as a fuel
Use Descriptor	
Sector(s) of use	21
Product category(ies)	13
Environmental release category(ies)	9a, 9b
Specific Environmental Release Category	ESVOC SpERC 9.12c.v1
Processes, tasks, activities covered	
Covers consumer uses in liquid fuels.	
Section 2 Operational conditions and risk management measures	
2.1 Control of consumer exposure	
Product characteristics	
Physical form of product	Liquid, vapour pressure > 10 Pa at STP
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).
Frequency and duration of use	For each use event, covers use amounts up to (g): 37500 Covers skin contact area up to (cm ²): 420
Other operational conditions affecting exposure	Covers use up to (times/day of use): 0.143. Covers exposure up to (hours/event): 2 hours per event.
Contributing Scenarios / Product Category	
Specific Risk Management Measures & Operating Conditions	
Liquid: Automotive Refuelling	Covers concentrations up to (%): 100%. Covers use up to (days/year): 52. Covers use up to (times/day of use): 1. Covers skin contact area up to (cm ²): 210.00. For each use event, covers use amounts up to (g): 37500. Covers use in room size of (m ³): 100. Covers exposure up to (hours/event): 0.05. Covers outdoor use No specific risk management measure identified beyond those operational conditions stated
Liquid Garden Equipment - Use	Covers concentrations up to (%): 100%. Covers use up to (days/year): 26. Covers use up to (times/day of use): 1. For each use event, covers use amounts up to (g): 750. Covers outdoor use Covers use in room size of (m ³): 100. Covers exposure up to (hours/event): 2.00. No specific risk management measure identified beyond those operational conditions stated
Liquid: garden equipment - refuelling	Covers concentrations up to (%): 100%. Covers use up to (days/year): 26. Covers use up to (times/day of use): 1. Covers skin contact area up to (cm ²): 420.00. For each use event, covers use amounts up to (g): 750. Covers use in a one car garage (34 m ³) under typical ventilation. Covers use in room size of (m ³): 34. Covers exposure up to (hours/event): 0.03. No specific risk management measure identified beyond those operational conditions

stated	
<p>Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits acute inhalation toxicity and is classified R20 (Harmful by inhalation) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary / additional RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels exhibits irritation to the skin and is classified R38 (Irritating to skin) accordingly. The available data for this adverse effect do not provide quantitative dose-response information, but there exists toxicity data appropriate to allow a qualitative risk characterisation; please see section 2 of the SDS for the necessary RMMs. Vacuum or Hydrocracked Gas Oils and Distillate Fuels is classified R65 (Harmful: may cause lung damage if swallowed). The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aims to define the appropriate RMMs necessary to protect from this adverse effect. There is limited evidence of carcinogenic effects in Vacuum or Hydrocracked Gas Oils and Distillate Fuels and it is classified R40 (May cause cancer) accordingly. The available data for this adverse effect do not provide quantitative dose-response information for a D(M)NEL to be derived. Instead, the toxicity data triggers a qualitative risk characterisation and the RMMs in section 2 of the SDS aim to define the appropriate RMMs necessary to protect from these adverse effects.</p>	
2.2 Control of environmental exposure	
Product characteristics	
Substance is complex UVCB. Predominantly hydrophobic.	
Amounts used	
Fraction of EU tonnage used in region	0.1
Regional use tonnage (tonnes/year)	1.6e7
Fraction of regional tonnage used locally	0.0005
Frequency and duration of use	
Continuous release.	
Emission days (days/year)	365
Environmental factors not influenced by risk management	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other operational conditions of use affecting environmental exposure	
Conditions and measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.1
Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal (kg/d):	3.5e5
Assumed domestic sewage treatment plant flow (m ³ /d):	2000
Conditions and measures related to external treatment of waste for disposal	
Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or national regulations.	
Section 3 Exposure Estimation	
3.1 Health	
The ECETOC TRA tool has been used to estimate consumer exposures, consistent with the content of ECETOC report #107 and the Chapter R15 of the IR&CSA TGD. Where exposure determinants differ to these sources, then they are indicated.	
3.2 Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
Section 4 Guidance to check compliance with the Exposure Scenario	
4.1 Health	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
4.2 Environment	
Further details on scaling and control technologies are provided in SpERC factsheet (https://cefic.org/app/uploads/2019/01/SPERCs-Specific-Environmental-Release-Classes-REACHImpl-ES-CSA-CSR.pdf).	

SUPERFLOC C-496

Ref. 2.0/GB/EN

Revision Date: 13.02.2015

Previous date: 04.12.2013

Print Date: 17.03.2015

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Commercial Product Name
SUPERFLOC C-496

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture

Flocculating agent.

Recommended restrictions on use

-

1.3 Details of the supplier of the safety data sheet

Kemira Oyj
P.O. Box 33000101 HELSINKI FINLAND
Telephone +358108611, Telefax. +358108621124
ProductSafety.FI.Helsinki@kemira.com

1.4 Emergency telephone number

Carechem 24 International: +44 (0) 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EU) 1272/2008 (CLP)

|| Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.;

Classification according to EU Directives 67/548/EEC or 1999/45/EC

Not a hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

|| Hazard statements

:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.



EUH210

Safety data sheet available on request.

2.3 Other hazards

Advice; Forms slippery/greasy layers with water.

Potential environmental effects; This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Chemical nature of the mixture

Cationic polyacrylamide.

CAS/EU number/REACH Registration Number	Chemical name of the substance	Concentration	Classification according to Regulation (EU) 1272/2008(CLP)	Classification according to EU Directives 67/548/EEC or 1999/45/EC
77-92-9 201-069-1 01-2119457026-42	Citric acid	0 - 9.9 %	Eye Irrit. Category 2,H319	Xi ,R36
124-04-9 204-673-3 01-2119457561-38	Adipic acid	0 - 5 %	Eye Irrit. Category 2,H319	Xi ,R36

The total combined concentration of Adipic acid and Citric acid does not exceed 9.9%.

Further information

For the full text of the H-Statements mentioned in this Section, see Section 16.

For the full text of the R-phrases mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance.

Inhalation

Move to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water.

Eye contact

Rinse immediately with plenty of water for at least 15 minutes.

Ingestion

Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Symptomatic treatment.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical

Unsuitable : none
extinguishing media

5.2 Special hazards arising from the substance or mixture

Dust can form an explosive mixture in air.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Specific methods

Avoid dust accumulation.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and materials for containment and cleaning up

Product becomes slippery when it is wet. Sweep up and shovel into suitable containers for disposal. Flush with plenty of water. Prevent product from entering drains. Dispose of as hazardous waste in compliance with local and national regulations.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid dust formation.

7.2 Conditions for safe storage, including any incompatibilities

The product is hygroscopic. Protect from moisture.

Materials for packaging

Unsuitable material: To avoid product degradation and equipment corrosion, do not use iron, copper or aluminium containers or equipment.

Materials to avoid:

Strong oxidizing agents

Storage stability:

Storage temperature 4 - 27 °C

Other data Stable under recommended storage conditions.

Other data Reason:
integrity

7.3 Specific end use(s)

Not listed

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Contains no substances with occupational exposure limit values.

PNEC : No data available

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. Do not breathe vapours/dust. Avoid contact with skin and eyes.

Ensure that eyewash stations and safety showers are close to the workstation location.
Ensure adequate ventilation.

8.2.2 Individual protection measures, such as personal protective equipment

Hand protection

Glove material: Nitrile rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection

Safety glasses or Face-shield

Skin and body protection

Wear suitable protective equipment.

Respiratory protection

Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

8.2.3 Environmental exposure controls

No data available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information (appearance, odour)

Physical state	solid, powder
Colour	off-white
Odour	odourless

Important health safety and environmental information

pH	3 - 5 (0.5 %) (as aqueous solution)
Melting point/range	No data available
Boiling point/boiling range	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable

Explosive properties:

SUPERFLOC C-496

Ref. 2.0/GB/EN

Revision Date: 13.02.2015

Previous date: 04.12.2013

Print Date: 17.03.2015

Lower explosion limit	No data available
Upper explosion limit	No data available
Vapour pressure	Not applicable
Relative vapour density	Not applicable
Bulk density	750 kg/m ³
Solubility(ies):	
Water solubility	Limited by viscosity.
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	> 150 °C
Thermal decomposition	> 150 °C
Oxidising	The substance or mixture is not classified as oxidizing.
Saturation in air (% vol.)	Not applicable
Volatile organic content (VOC)	Not applicable

9.2 Other data

Surface tension	Not applicable
Corrosion	

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Conditions to avoid : Avoid contact with alkaline materials which will degrade the polymer.
Protect from moisture.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : Ammonia
Carbon oxides (COx)
Nitrogen oxides (NOx)
hydrogen chloride (HCl)

Thermal decomposition : > 150 °C

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

The acute toxicological results displayed may not be the results of actual testing of this material but based on a similar tested material.

LD50/Oral/Rat: > 2,500 mg/kg

Remarks: estimated

LC50/Inhalation/4 h/Rat: > 20 mg/l

Remarks: estimated

LD50/Dermal/Rabbit: > 10,000 mg/kg

Remarks: estimated

Citric acid:

LD50/Oral/Rat: 11,700 mg/kg

Adipic acid:

LD50/Oral/Rat: > 5,000 mg/kg

LD50/Dermal/Rabbit: > 5,000 mg/kg

Irritation and corrosion

Skin:

No skin irritation

Eyes:

No eye irritation

Adipic acid:

Skin: No skin irritation

Eyes: Irritating to eyes.

Sensitisation

Not sensitizing.

Long term toxicity

Repeated dose toxicity

Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Citric acid:

Carcinogenicity

Oral/Rat/2 years:

Animal testing did not show any carcinogenic effects.

Reproductive toxicity

Oral/Rat:

Result: No impairment of fertility has been observed.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity

—

This material is not classified as dangerous for the environment. The effects on aquatic organisms are due to an external (non-systemic) mode of action and are significantly reduced (by a factor of 7-20) within

SUPERFLOC C-496

Ref. 2.0/GB/EN

Revision Date: 13.02.2015

Previous date: 04.12.2013

Print Date: 17.03.2015

30 minutes due to the binding of the product to dissolved organic carbon and inorganic sorbents such as clays and silts. Ecotoxicological information provided is based on a structurally or compositionally similar product.

LC50/96 h/Branchydanio rerio (zebra fish)/Acute toxicity/OECD Test Guideline 203: > 1 - 10 mg/l
EC50/48 h/Daphnia magna (Water flea)/Immobilization/OECD Test Guideline 202: > 10 - 100 mg/l
/algae/Growth inhibition/OECD Test Guideline 201:

Remarks: Due to the cationicity of the polymer, test is not appropriate.

Citric acid:

LC50/96 h/Carassius auratus (goldfish)/DIN 38412: 440 - 706 mg/l

Adipic acid:

LC50/96 h/Fish: > 100 mg/l

EC50/48 h/Daphnia (water flea): 85.6 mg/l

EC50/72 h/algae: 31.3 mg/l

Toxicity to other organisms

No data available

No data available

Citric acid:

/Bacteria/DIN 38412, part 5: > 10,000 mg/l

12.2 Persistence and degradability

Biological degradability:

Modified Sturm Test/OECD Test Guideline 301B/28 d: < 70 %

The polymeric ingredient is not readily biodegradable, but degradable by hydrolysis.

Biological degradability:

Citric acid:

/DIN 38412/2 d: 98 %

Readily biodegradable

Biochemical Oxygen Demand (BOD): 575 - 675 mg/g (5 d)

Chemical Oxygen Demand (COD): 700 - 800 mg/g

Adipic acid:

Not readily biodegradable.

12.3 Bioaccumulative potential

Bioaccumulation is unlikely. Because of the high molecular weight of the polymer diffusion through biological membranes is very small.

Partition coefficient: n-octanol/water: Not applicable

Citric acid:

Does not bioaccumulate.

Adipic acid:

Does not bioaccumulate.

Partition coefficient: n-octanol/water: log Pow: 0.093

12.4. Mobility in soil

Mobility

Water solubility: Limited by viscosity.

Surface tension: Not applicable

12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

If recycling is not practicable, dispose of in compliance with local regulations. Incineration is recommended.

Contaminated packaging

Dirty package must be disposed of in the same way as the product itself.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

Land transport

SUPERFLOC C-496

Ref. 2.0/GB/EN

Revision Date: 13.02.2015

Previous date: 04.12.2013

Print Date: 17.03.2015

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

14.6 Special precautions for user

None known.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : None.

Notification status

- :
- : All components of this product are included in the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.
- : All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on the Australian Inventory of Chemical Substances (AICS).
- : All components of this product are included in the Canada Domestic Substance List (DSL) or are not required to be listed on the Canada Domestic Substance List (DSL).
- : All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.
- : All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese (ENCS) inventory.
- : All components of this product are included in the Korean (ECL) inventory or are not required to be listed on the Korean (ECL) inventory.
- : All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine (PICCS) inventory.
- : All components of this product are included in the United

SUPERFLOC C-496

Ref. 2.0/GB/EN

Revision Date: 13.02.2015

Previous date: 04.12.2013

Print Date: 17.03.2015

- States TSCA Chemical Inventory or are not required to be listed on the United States TSCA Chemical Inventory.
- : All components of this product are NOT included on the New Zealand Inventory of Chemical Substances.
- : This product's Taiwan Toxic Chemical Substances Control Act Inventory status has NOT been determined.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under section 3.

H319 Causes serious eye irritation.
H319 Causes serious eye irritation.

Text of R-phrases mentioned in Section 3

R36 Irritating to eyes.
R36 Irritating to eyes.

Training advice

Read the safety data sheet before using the product.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Sources of key data used to compile the Safety Data Sheet

Regulations, databases, literature, own tests.

Additions, Deletions, Revisions

Relevant changes have been marked with vertical lines.

Material Safety Data Sheet – Cut Grass Deodoriser

1. Identification of the Substance & Company

Company: Cobra Hydro Limited
Product: Cut Grass Deodoriser
Product Type: Deodoriser

2. Composition/Information on ingredients

Hazardous component:	Cas No.	Index	Risk Phrases:	Concentration:
Non Ionic Surfactant		Xi	R36/38	<5%
Amyl acetate		F+	R11	<10%

3. Hazard Identification

Not classified as Hazardous under CHIP regulations.

4. First-aid measures

Eye Contact: Flush with plenty of clean water for at least 15 minutes. If irritation persists, obtain medical attention.

Skin Contact: Wash off with Water. The application of skin reconditioning (emollient) cream, can be beneficial.

Inhalation: N/a.

Ingestion: Milk or water to drink may be beneficial. Do not induce vomiting without medical advice.

5. Fire-fighting measures

Flammability: Not classed as flammable.

Extinguishing Media: Foam, Dry Powder, Co2, Halon, fine water spray suitable.

Protective Equipment: Standard protective equipment.

6. Accidental release measures

Wear gloves/eye protection. Do not allow product to soak into drains or water courses. Soak liquid in absorbent material and collect solids in a container. Wash down floor area as spillages can be slippery.

Material Safety Data Sheet – Cut Grass Deodoriser

7. Handling and Storage

Storage Precautions: Store between 0-35°C. Keep in tightly closed containers. Protect from frost.
Handling: Avoid contact with skin and eyes. Observe good standards of industrial hygiene.

8. Exposure controls/personal protection

Respiratory Protection: Unlikely to be necessary where adequate ventilation is provided.
Eyes: Chemical eye goggles should be worn.
Hand: PVC or rubber gloves are recommended.
Skin: Use protective clothing. Remove contaminated clothing and wash with soap and water.

9. Physical and chemical properties

Appearance: Blue/Green Fluid
Specific Gravity @ 20°C: 1.00 typical
Odour: Perfumed
pH Neat: 8.5 typical
pH @ 5% in tap water: 7.50 typical
Boiling Point: 100°C
Freezing Point: 0°C
Vapour Pressure: Water=18mm Hg
Water Solubility: Totally soluble

10. Stability and reactivity

Stability: Stable under normal conditions.
Hazardous Decomposition: Oxides of carbon, nitrogen, water vapour and unidentified compounds, some of which could be toxic may be evolved.
Conditions to Avoid: Naked flames, hot surfaces, other high temperature sources.

11. Toxicological information

Eyes: Not classified as an eye irritant. However contact with the undiluted product is likely to cause irritation and stinging.
Skin: Not classified as a skin irritant. Brief or occasional contact is unlikely to cause any significant reaction. Prolonged or repeated contact with the undiluted product may lead to de-fatting of the skin and/or slight irritation.
Inhalation: Unlikely to present any significant hazard at ambient temperature. Excessive exposure to mists caused by atomising systems may cause irritation to eyes and respiratory tract.
Ingestion: Low order of acute toxicity. Ingestion of this product is not regarded as a significant health hazard, likely to arise in normal use.

12. Ecological information

There is no data available on the product itself.
The components of the product exhibit good to moderate biodegradability and readily broken down by sewage treatment plants. They are not expected to bio-accumulate.

13. Disposal considerations

Product should be disposed of via an authorised waste disposal contractor in accordance with all local and national regulations.

Material Safety Data Sheet – Cut Grass Deodoriser

Wash out containers with water, running the washings to sewage treatment plant system. Dispose of empty containers in accordance with local and national regulations.

Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product.

14. Transport Information

Not classified as dangerous goods

15. Regulatory Information

Label for Supply:	Not Classified.
Risk Phrases:	Non
Safety Phrases:	S2: Keep out of reach of children.
	S24/25: Avoid contact with skin and eyes.

16. Other information

Do not mix with other chemicals.

The information provided in this data sheet has been compiled in accordance with the requirements of the Chemicals (Hazard information and packaging) Regulations, Directive 93/112/EC.

This data sheet does not constitute an assessment of the workplace risks as required under the provisions of the Health & Safety at Work act and the Control of Substances Hazardous to Health (COSHH).

Legal Disclaimer:

The information supplied above is based upon the present state of our knowledge of the product at the time of publication. It is given in good faith and no warranty is implied with respect to the specification or quality of the product. The user must satisfy himself that the product is entirely suitable for his purpose.

Date 23.11.15

Revision Date 24/05/13
 Revision 9
 Supersedes date March 2011



SAFETY DATA SHEET

Sodium hydroxide solution, 5 - 51%

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	Sodium hydroxide solution, 5 - 51%
REACH Registration number	01-2119457892-27
CAS-No.	1310-73-2
EC No.	215-185-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Treatment of drinking water, has received approval by the European Committee for Standardisation. Treatment of waste water. Raw material. Neutralising agent. pH regulating agent Manufacture of substances. Absorbant for gases and liquids Manufacturing soaps Washing and cleaning products
------------------------	---

1.3. Details of the supplier of the safety data sheet

Supplier	Industrial Chemicals Limited Hogg Lane Grays Essex RM17 5DU United Kingdom T:+44 (0)1375 389000 F:+44 (0)1375 389110 sds@icgl.co.uk
-----------------	---

1.4. Emergency telephone number

+44 (0)1865 407333 (24-hour)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Met. Corr. 1 - H290
Human health	Skin Corr. 1A - H314; Eye Dam. 1 - H318
Environment	Not classified.

Classification (1999/45/EEC)

C;R35.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

Corrosive. Prolonged contact causes serious eye and tissue damage.

Environment

Substantial amounts of the product may lead to a local change in acidity in small water systems which may have adverse effects on aquatic organisms.

2.2. Label elements

EC No.	215-185-5
Contains	SODIUM HYDROXIDE
Label In Accordance With (EC) No. 1272/2008	

Sodium hydroxide solution, 5 - 51%



Signal Word Danger

Hazard Statements

H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H318 Causes serious eye damage.

Supplementary Precautionary Statements

P234 Keep only in original container.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P260 Do not breathe vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P321 Specific treatment (see medical advice on this label).
 P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
 P310 Wash contaminated clothing before reuse.
 P363 Absorb spillage to prevent material damage.
 P390 Store locked up.
 P405 Store in corrosive resistant/... container with a resistant inner liner.
 P501 Dispose of contents/container to ...

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SODIUM HYDROXIDE		40-60%
CAS-No.: 1310-73-2	EC No.: 215-185-5	
Classification (EC 1272/2008) Met. Corr. 1 - H290 Skin Corr. 1A - H314 Eye Dam. 1 - H318	Classification (67/548/EEC) C;R35	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

REACH Registration number 01-2119457892-27
CAS-No. 1310-73-2
EC No. 215-185-5

Composition Comments

Mercury (Rayon) grade contains a low level of mercury, typically less than 0.1 ppm. Diaphragm grade contains up to 1.3% sodium chloride, which increases the density of the solution.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Get medical attention immediately! CAUTION! First aid personnel must be aware of own risk during rescue!

Sodium hydroxide solution, 5 - 51%

Inhalation

Rinse nose, mouth, and throat with running water.

Ingestion

Do not induce vomiting. If confined to the mouth, rinse mouth thoroughly and ensure water is not swallowed. If swallowed, drink plenty of water. If substance has been swallowed, give water or milk to drink immediately. Get medical attention immediately!

Skin contact

Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention immediately!

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes.

4.2. Most important symptoms and effects, both acute and delayed

General information

Strong corrosive action on all body tissue, causing burns and frequently deep ulceration, and ultimately scarring.

Inhalation

Mist/droplets are irritating to the respiratory tract, and will cause a burning sensation in the throat, coughing, and breathing difficulties. Pulmonary oedema (excessive liquid in the lungs) can occur after inhalation of higher amounts.

Ingestion

Causes severe damage to gastrointestinal tract. Can cause perforation and scarring.

Skin contact

Burning pain and severe corrosive skin damage. Causes burns, deep ulceration, and scarring. Frequent contact with lower concentrations may cause eczema.

Eye contact

Corrosive to eyes. May cause severe corneal damage, reduced vision, or even blindness.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

The product is non-combustible. Use fire-extinguishing media appropriate for surrounding materials.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Contact with some metals can liberate flammable hydrogen gas.

5.3. Advice for firefighters

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material. Release to rivers will cause a strong increase in pH, resulting in death to aquatic organisms. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Small Spillages: Neutralise with weak acid and wash away with water. Alternately, drench spill with water and wash away. Large Spillages: Isolate and pump into a tank. Dispose of via a licensed hazardous waste contractor. Keep people and animals away from contaminated areas.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Sodium hydroxide solution, 5 - 51%

Following prolonged storage in metal tanks, a black sludge will collect at the bottom of the tank. This will contain iron, sodium carbonate, and when Mercury (Rayon) grade is stored, mercury. Test the atmosphere in the tank for oxygen and mercury vapour before entering. Appropriate care must be taken when removing and handling this sludge, including control of atmospheric levels. Handle with care as an alkaline material. Take care when diluting with water (heat generation). Avoid contact with skin and eyes. Avoid generation of sprays or mists.

7.2. Conditions for safe storage, including any incompatibilities

Store in vessels of mild steel. Keep away from acids and other chemicals that react with this product. Build-up of white metal carbonate crystals may occur if tank is open to air.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
SODIUM HYDROXIDE	WEL				2 mg/m ³	

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection

Wear protective gloves. Rubber or plastic.

Eye protection

Goggles/face shield are recommended.

Other Protection

Chemical suit and boots if handling large quantities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Colourless liquid.
Odour	Odourless.
Solubility	Miscible with water
Initial boiling point and boiling range (°C)	142
Melting point (°C)	For 50% Membrane grade 12
Relative density	For 50% Membrane grade 1525 20
Viscosity	For 50% Membrane grade 78 cP 20
	For 50% Membrane grade

9.2. Other information

Sodium hydroxide solution, 5 - 51%

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Vessels should not be open to air; substance absorbs water and carbon dioxide. In extreme cases, the carbonate can form white floating crystals. Do not store adjacent to incompatible materials, such as acids and amphoteric metals eg aluminium, magnesium, zinc, tin and bronze - may release hydrogen gas.

10.5. Incompatible materials

Materials To Avoid

Reaction with ammonium compounds releases ammonia. May react violently with acrolein, acrylnitrile, and allyl alcohol. Heating with trichloroethylene will form explosive mixtures of dichloroacetylene. Some plastics, leather and textiles are destroyed on contact. Mixture with water or acids will release large quantities of heat.

10.6. Hazardous decomposition products

Thermally stable to boiling point; does not decompose. Precipitation of metal hydroxide crystals can occur below 12C.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General information

Strong corrosive action on all body tissue, causing burns and frequently deep ulceration, with ultimate scarring.

Inhalation

Mist/droplets are corrosive to the respiratory tract, and will cause a burning sensation in the throat, coughing and breathing difficulties. Pulmonary oedema (excessive liquid in lungs) can occur after inhalation of higher amounts.

Ingestion

If ingested will cause severe damage to gastrointestinal tract. Can cause perforation and scarring.

Skin contact

Corrosive to body tissue, causing burns, deep ulceration, and scarring. Frequent contact with lower concentrations may cause eczema.

Eye contact

Vapour or spray may cause eye damage, impaired sight or blindness.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Spillage will cause localised damage to animals and plants on the ground. Do not allow release into controlled waters; resulting high pH will affect aquatic life forms. If allowed to enter drains will damage effluent treatment organisms. Neutralisation and dilution will greatly reduce these effects. Product is chemically degradable into sodium carbonate.

12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l 45.4

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Sodium hydroxide solution, 5 - 51%

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Neutralise with dilute acid and wash away with large amounts of water. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1824

14.2. UN proper shipping name

Proper Shipping Name SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es)

ADR/RID/ADN Class Class 8: Corrosive substances.

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group II

IMDG Packing group II

ICAO Packing group II

14.5. Environmental hazards

14.6. Special precautions for user

Hazard No. (ADR) 80

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

General information

The material must only be loaded and unloaded from tankers by trained personnel, such as those with a Hazchem certificate.

Sodium hydroxide solution is used as a chemical for the treatment of drinking water, as approved by the European Committee for Standardisation under EN 896:2005.

This data sheet was prepared in accordance with EC 1907/2006 concerning REACH.

Issued By D.Kelly
 Revision Date 24/05/13
 Revision 9

Sodium hydroxide solution, 5 - 51%

Supersedes date

March 2011

Risk Phrases In Full

R35 Causes severe burns.

Hazard Statements In Full

H318 Causes serious eye damage.

H314 Causes severe skin burns and eye damage.

H290 May be corrosive to metals.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.